

# PRODUCT CATALOGUE 2024

## AIR CONDITIONERS LINEUP

FUJITSU

### PRODUCT CATALOGUE 2024 AIR CONDITIONERS LINEUP

FUJITSU GENERAL LIMITED



**FUJITSU GENERAL LIMITED**

3-3-17, Suenaga, Takaatsu-ku, Kawasaki, Kanagawa, 213-8502, Japan  
www.fujitsu-general.com



Copyright© 2008-2024 Fujitsu General Limited. All rights reserved. 3EF037-2401E

### Notice regarding specifications

I.U. = Indoor Unit O.U. = Outdoor Unit Qu = Quiet \* = Not decided yet


- Specifications and design are subject to change without notice for future improvement.
- For further details, check with our authorized dealers.
- Cooling and heating capacities are based on the following conditions:

Cooling	Indoor temp. : 27°C DB/19°C WB Outdoor temp.: 35°C DB/24°C WB	Heating	Indoor temp. : 20°C DB Outdoor temp.: 7°C DB/6°C WB
---------	--	---------	--

- Performance tests are conducted in accordance with EN14511.
- Seasonal efficiency tests are conducted in accordance with EN14825.
- Sound power tests are conducted in accordance with EN12102.



Fujitsu General (Thailand) Co., Ltd.



ISO 9001 Certification number: 01 100 075229  
ISO 14001 Certification number: 01 104 9245

Fujitsu General (Shanghai) Co., Ltd.



ISO 9001 Certification number: 01 100 79269  
ISO 14001 Certification number: CNB312244-UK

Fujitsu General Central Air-conditioner (Wuxi) Co., Ltd.



ISO 9001 Certification number: 15917020073RSM  
ISO 14001 Certification number: 15918E20021RSM

- The products and equipment listed in this catalog contain fluorinated greenhouse gases.
- "AIRSTAGE" is a worldwide trademark of Fujitsu General Limited, and a registered trademark in Japan and other countries and regions.
- iPhone and iPod touch are trademarks of Apple Inc., registered in the United States and other countries.
- "Microsoft," "Windows," and "DirectX" are trademarks of Microsoft Corporation in the United States and other countries.
- "Inesis" is a registered trademark of HMS Industrial Networks in the European Union and is trademarked in the rest of the world.
- "BACnet" is a trademark and registered trademark of the American Society of Heating, Refrigerating and Air-Conditioning Engineers, Inc.
- "MODBUS" is a registered trademark of Schneider Electric.
- "LONWORKS" and "Echelon" are trademarks of Echelon Corporation registered in the United States and other countries.
- "Adobe" and "Acrobat Reader" are either registered trademarks or trademarks of Adobe in the United States and/or other countries.
- "Android" is a trademark of Google LLC.
- Other company and product names mentioned in this document may be the registered trademarks, trademarks or trade names of their respective owners.
- "Pcalat" is a worldwide trademark of Fujitsu General Limited.
- "Bluetooth" is a registered trademark of Bluetooth SIG, inc.

Distributed by:

## Our mission

# Living together for our future

Through innovation and technology, we deliver a brighter future with peace of mind to our customers and societies around the world.

## Our philosophy

### Act spontaneously

We embrace new challenges by investing in ourselves for personal growth, and through continuous creativity with a spontaneous attitude.

### Develop our team

We respect and value our people, and optimize their abilities through fostering culture and diversity, and utilizing a collaborative effort focused on communication.

### Value integrity

To achieve our goals, we always act with integrity and shared ethics.



## CONTENTS

### 004 OUR MESSAGE

- 006 Sustainable
- 008 Cleanliness
- 010 Future
- 012 Comfort
- 014 Control
- 016 Design
- 018 History
- 020 Worldwide locations
- 022 Global business activities
- 024 Project references
- 026 Global development & Production bases
- 028 High-quality development & Production Facilities
- 030 2024 New Products

### 034 SOLUTIONS

- 036 For Light Commercial Use
- 044 For Commercial Use
- 046 For Apartments & Houses

## SUPPORT

- Sp-002 VRF Support
- Sp-004 HVAC System design Support Tool
- Sp-006 Air To Water Support Tool
- Sp-008 Quick Service & Maintenance
- Sp-010 AIRSTAGE Service Monitor Tool
- Sp-012 Service Tool
- Sp-013 Web monitoring tool

## PRODUCT LINEUP

### SPLIT & MULTI-SPLIT

### VRF

### VENTILATION

### CONTROL SYSTEM & OPTIONAL PARTS

### AIR TO WATER

# OUR MESSAGE



for Sustainable



for Cleanliness



for Future

Innovation  
and  
Globalization



for Comfort



for Control



for Design

We create comfortable lives for people around the world with "made-in-Japan quality" and innovative manufacturing.



History



Worldwide locations



Global business activities



Project references



Global development &amp; Production bases



High-quality development &amp; Production facilities



# Sustainable

## Sustainable management

We see the challenge of expanding our business by contributing to the realization of a sustainable society as a core element of our growth strategy, and we are working on "sustainable management," based on the three pillars of "harmonious coexistence with our planet," "social contribution," and "care for employees."




## Basic policy on sustainable management

The sustainable development goals (SDGs) of the UN will drive business creation in the coming years. The key principle of the SDGs, "Leave no one behind," is synonymous with our own corporate philosophy of "Living together for our future." The promotion of sustainable management is carried out from a medium- to long-term perspective, with a promise to shape a sustainable society for the children and society of the future. We will pursue business growth by accelerating this transformation.



### Key Initiatives





# Cleanliness

## Think about air quality

Fresh air is essential for comfortable air conditioning. Fujitsu General offers a wide range of air conditioning products with air purification functions, such as ventilation systems equipped with high-performance filters and heat exchangers.





## Collecting dust particles to clean the air



### Silver Ion Filter

The Silver ion filter helps to keep indoor air free from viruses, bacteria and molds.  
Notice: Not a result of experiments in an actual use environment. Silver ion filter inhibits activity or growth of microorganism, but do not prevent infection.




## Different filters are used on each side



### Ion Deodorization Filter

Deodorizes the air by decomposing absorbed odors using the oxidizing and odor-reducing effects of ions generated by ultra-fine particle ceramic.




### Apple-catechin Filter

The Apple-catechin filter uses static electricity to remove fine particles and dust from the air.

## Ventilation with adequate airflow with reduced temperature changes

### Heat Exchange Ventilation

When a room is cooled or heated, the exhausted cooling or heating energy is recovered by heat exchange ventilation.





# Future



## The green refrigerant


Throughout our research and development process, we are constantly striving to create products that we can be proud of in the future. The technologies we have cultivated through these efforts are incorporated into our environmentally friendly products, and are recognized in the European market, which has extremely strict environmental regulations.

### R32 refrigerant with reduced global warming potential

- **Zero** Ozone Depletion Potential (ODP<sup>\*1</sup>)
- High environmental properties
- High performance
- Economically efficient

<sup>\*1</sup> ODP (Ozone Depleting Potential): a relative value that indicates the impact per unit weight of ozone-depleting substances released into the atmosphere when CFC-11 (trichlorofluoromethane, CC13F) is fixed at 1.0

<sup>\*2</sup> GWP (Global Warming Potential): a measurement that indicates how much other greenhouse gases are capable of warming the Earth based on carbon dioxide. This is the integrated value of radiant energy given to the Earth (i.e., the estimated impact on global warming) expressed as a ratio to CO<sub>2</sub>.



### Low GWP to a wide range of projects

We are continuously working to develop products that use R32 refrigerant and have R32 products in all product categories in our lineup (Split, Multi-Split, VRF, and ATW). This allows us to realize environmentally and regulatory friendly system designs for a wide range of projects from residential to light commercial.



### New energy labelling requirement 626/2011/EU

Our air conditioners have reached the "Class A+++" ranking, the highest energy efficiency level that is now shown on energy labels in Europe.

		SEER (Cooling operation)	SCOP (Heating operation)
A++	SEER ≥ 8.50	SCOP ≥ 5.10	
A+	6.10 ≤ SEER < 8.50	4.60 ≤ SCOP < 5.10	
A	5.60 ≤ SEER < 6.10	4.00 ≤ SCOP < 4.60	
B	4.60 ≤ SEER < 5.10	3.10 ≤ SCOP < 3.40	
C	4.10 ≤ SEER < 4.60	2.80 ≤ SCOP < 3.10	
D	3.60 ≤ SEER < 4.10	2.50 ≤ SCOP < 2.80	
E	3.10 ≤ SEER < 3.60	2.20 ≤ SCOP < 2.50	
F	2.60 ≤ SEER < 3.10	1.90 ≤ SCOP < 2.20	
G	SEER < 2.60	SCOP < 1.90	

### Fujitsu General's Environmental Vision

#### Medium-Term Environmental Plan: Target and Measure

	Target	Measure
Reduction of Our Own Environmental Impact Achieve	<b>Achieve carbon neutrality by FY2025</b> ▲ <b>[Old Target]</b> Greenhouse gas emissions from our Group's business activities: Completely eliminate by FY2030	1. Renewable energy conversion: Existing plants (by FY2023) 2. Renewable energy conversion: All Group companies (by FY2025) → Achieved 1 and 2 ahead of schedule (April 2022) 3. Shift to use of renewable energy for all other energy used (by FY2025)
Through Our Supply Network	<b>Reduction of 30%</b> for total greenhouse gas emissions through our supply Network by FY2035 (vs. FY2018)	• Promotion of green electricity use by our suppliers • Reduction of material consumption and product weight
For our Customers and Society	Reduce greenhouse gas emissions from the use of our products. <b>Reduction of 30% by FY2030 (vs. FY2013)</b>	• Replace constant-speed A/C with inverter A/C (India and Middle East) • Enhance energy efficiency



# Comfort



## Cassette type 3D flow Series

### 3 individually controlled air outlet ports

The Comfortable airflow setting enables the right and left air outlet ports as well as the wide center port to work together to provide a comfortable room environment.



## Cassette type One-way flow Series

### Wide airflow range created by triangle design and large flap

A large flap with a wide range of movements, equipped with louvers arranged triangularly, sends air into every corner of the room.

## Cassette type Circular flow Series

### Unique circular flow design

This Series realizes a Circular Flow to blow a large airflow in a 360° direction by using a high-performance DC fan motor, turbo fan, and a unique seamless airflow louver design.



## Auto louver grille kit for Mini duct and Slim duct

### Flexible Control

The optional clean-looking flat Auto louver grille kit blends into any interior and provides a comfortable airflow.





# Control

## Operation from anywhere

Using the Internet of Things (IoT), Fujitsu General is actively providing services that allow users to control their air conditioners from their smartphones. We are also expanding our open co-creation activities with external partners to deepen the development of new functions and services using IoT and artificial intelligence (AI) to develop safe and convenient air conditioners.



### Software application for WLAN Adapter

"AIRSTAGE Mobile" is a software application that allows users to control Fujitsu General air conditioners from anywhere with a mobile device while out or on the move.



### AIRSTAGE Mobile

Download Free



### Compact wired remote controller

#### Large screen and simple display

- Large screen, yet compact in size
- Large, easy-to-read letters are used.
- The controls are simple and easy to understand.



### Central remote controller for VRF system

The central remote controller uses a touch panel screen to display multiple menus on the top screen. Just touch the menu you want to operate, and the necessary window will pop up, and allow intuitive operation.



#### Remote monitoring and operation

The central remote controller enables monitoring and control of a tenant's air conditioner anytime, anywhere.



# Design



**Harmonizes with the installation space**


Fujitsu General offers a wide range of products for the European market, including models with unique textural designs, award-winning models that integrate with room interiors, and Cassette type models with different designs that match office spaces. We also have a lineup of models with elegant designs, such as the Ceiling type models with its beautiful curved surface.



## Light Elegant Design

### New Ceiling type design

The light, elegant and three-dimensional expression achieved by the curved surface gives a sense of comfort and well-being.



**NEW** KN Series

## New "Elegant & Smart" Square Design

### New Wall-mounted type design

Smart design with ridges and subtle shade

\*Image is KN Series

**NEW**

## Sleek and Stylish Design

### New designed wired remote controller

When not in use, the controller is a part of the interior decor. This is achieved by using mirrors, glass, and clear panel, and it appears to be on with the wall.



**NEW**

## Stylish design

### New outdoor unit for Air to Water Future Release

A design that offers a sophisticated style that is quiet and blends in with the outdoor landscape.





# History

Yaou Shoten Ltd. established in 1936

## Overseas air conditioning business since 1971

Starts air conditioning business in Japan in 1960

**1971** Air conditioner exports to the Middle East.

**1977** "Super Power, Super Quiet" Series released

**1982** Window type 3 Super Series released



**1985** Large wall-mounted type and multi-split air conditioner released.

**\*1,\*2 1991** World's first air conditioner equipped with lambda-shaped heat exchanger

**1994** World's first air conditioner with power diffuser

**1950 ~**

**2001** AIRSTAGE Series released VRF air conditioners for large buildings



**2004** Standalone Compact VRF AIRSTAGE J Series released



**2006** VRF Heat Pump type Maximum 42 HP AIRSTAGE V Series released



**2009** VRF Heat Pump Modular type Maximum 48 HP AIRSTAGE V-II Series released

**2009** Air to water system released



**1970 ~**

**2000 ~**

## Manufacturing Company Establishment

**1955** Head Office established in Kawasaki

**1964** Electronic components factory in Ichinoseki



**1977** Air conditioner manufacturing company in Hamamatsu (now Hamamatsu business office)

**1991** Air conditioner manufacturing company in Thailand

**1994** Air conditioner manufacturing company in Shanghai, China

**1998** Air conditioner motor manufacturing company in Thailand

**2006** VRF air conditioner manufacturing, sale, and service company in China

**2007** Air Conditioner Technology Building becomes operational on the premises of the Kawasaki Headquarters. Air conditioner R&D Center in Kawasaki

**2009** Compressor Factory begins operation in Thailand

**For Light commercial use**

**2011** Compact 2 Fan type VRF AIRSTAGE J-II Series released

**2014** Compact 1 Fan type VRF AIRSTAGE J-IIS Series released

**2016** Compact 2 Fan type VRF AIRSTAGE J-III Series released

**2017-19** Compact VRF AIRSTAGE J-III Series for light commercial use released

**2020** Compact & lightweight outdoor unit AIRSTAGE J-IVL, J-IV, J-IVS Series released



**2019**

New cassette style released  
3D Flow Cassette

**For Commercial use**

**2012** VRF AIRSTAGE VR-II Series released



**2014-15** VRF AIRSTAGE VR-III Series released

**2020** Heat Recovery Modular type VRF AIRSTAGE VR-IV Series & AIRSTAGE Air handling unit released

**2022** Energy-saving operation model VRF V-IV Series released



**For Residential use**

**2011** Hi-spec Design model LT Series & LU Series released



**2017** Flagship Wall-mounted type "nocria X" released



**2017-19** Added to this lineup recently are the environment-friendly R32 refrigerant models. (Split & Multi-split type)

**2022** Harmonizes beautifully design model KE Series released



**2010 ~**

**2012** Joint venture in Thailand to manufacture compressors



**2016** Commercial use air conditioner R&D Center in Thailand

**2019** New building constructed at Kawasaki Head Office to strengthen development capabilities



**2020** Building IoT-based manufacturing in Thailand



**2024 What's New**

**2023 FGAI R&D New Office:**  
FGAI Research & Development office moved to the new office in New Jersey, USA



## Sales & service maintenance company established

**1976** North America sales company

**1977** Europe sales company (UK)

**1978** Australia sales company and Europe sales company (Germany)

**1980** Brazil sales company

**1997** Asia sales company (Singapore)


**1998** Middle East sales company (UAE) and New Zealand sales company

**2000** Air conditioner manufacturing and sale technical partnership in India

**2002** Taiwan sales company

**2006** China sales company

**2016** THE AIRSTAGE on Broadway in New York



**2023 Communication Lounge EURO:**  
New lounge in Dusseldorf, Germany



\*1: Announced 1991. In room air conditioner for the home (Our company's investigation) \*2: Announced 1994. In the category of room air conditioners for the home (Our company's investigation).

\*3: Announced 2002. In the category of room air conditioners for the home (Our company's investigation).




# Worldwide locations

Under a system of five bases in Europe, the Middle East, Asia and Oceania, North and South America, and Japan, the company promotes Globalization from a worldwide perspective while emphasizing the actual conditions in each region.




JAPAN Head Office



Technology research building (Japan)

**18** Overseas Sales Companies



Fujitsu General Sales & Trading (Shanghai) Co., Ltd.




Fujitsu General (EURO) GmbH (Germany)



Fujitsu General Air Conditioning (UK) Ltd. (U.K.)




Fujitsu General (Italia) S.p.A. (Italy)




Fujitsu General Private Ltd. (India)



Fujitsu General (Aust.) Pty Ltd. (Australia)



Precise Air Group (Holding) Pty Ltd. (Australia)



Fujitsu General New Zealand Ltd. (New Zealand)



Fujitsu General (Middle East) FZE (U.A.E.)




FUJITSU GENERAL SOLUTION CENTER "THE AIRSTAGE" (U.S.A.)



- Fujitsu General Air Conditioning (UK) Ltd.
  - Kløver Vest Holdings AS
  - Fujitsu General (Euro) GmbH
  - Fujitsu General (Italia) S.p.A.
  - Fujitsu General South East Europe S.A.
- Fujitsu General EMC Laboratory Ltd.
- Fujitsu General Limited
- Fujitsu General (Taiwan) Co., Ltd.
- Fujitsu General (Aust.) Pty Limited
- Precise Air Group (Holding) Pty Ltd.
- Fujitsu General New Zealand Ltd.



# Global business activities



We have been recognized for our activities in advertising, human resource development and customer service, as well as for our community-based social contribution activities in each region, winning numerous awards and achieving a high level of customer satisfaction.

## North and South Americas



AHR Expo



HVAC trade shows in Brazil



Distributor conference in USA



Call center

## Middle East



Exhibition



Training in Kuwait



Launch event in Oman



New product seminar in UAE

## Europe



HVAC trade show in Germany



HVAC trade show in Germany



Event in the United Kingdom

## Oceania



HVAC trade show in Australia



Launch event in New Zealand



Launch event in New Zealand

## Asia



Thanksgiving party in Taiwan



Exhibition in India



Opening ceremony in India



New product presentation seminar in Singapore



Service training in Vietnam

## International authoritative design awards

The NEWS  
Dealer Design AwardsGold Award (Category:  
HVAC & PLUMBING) in  
Reader's Choice AwardsTOP OF MIND 2016 First prize in  
"MARCA DE EQUIPAMENTO DE  
AR-CONDICIONADO" category of  
"CLIMATIZACAO" division

Superbrands is the world's largest independent arbiter of branding.



The iF Product Design Award is given annually by iF International Forum Design GmbH for industrial products from around the world.



The Plus X Award is the world's largest innovation award for technology, sports and lifestyle.



reddot winner 2020



A product design competition that has been held since 1955. Products that win the award are given the "Red Dot" seal, a sign of international recognition of quality.



ProductReview.com.au's annual awards are selected from products and services that have been well-rated by the ProductReview community.



Voted by Australians as the 'Most Trusted Brand - Air Conditioning Category 5 Years Running'



China State Construction Engineering Luban Prize




The Good Design Award is an award sponsored by the Japan Institute of Design Promotion, and is given once a year to items of outstanding design.



# Project references



Introduced in over 50 countries worldwide

Highly popular for their excellent quality, energy efficiency, and ease of installation, Fujitsu General's products are installed in a wide range of buildings around the world, including high-rise office buildings, stores, hotels, public facilities, schools, hospitals, and residences.



For Light commercial use

- 1 Shop in Europe
- 2 Factory in Europe
- 3 School in Asia
- 4 Hospital in Asia
- 5 Office in Asia
- 6 Shop in Oceania
- 7 Office in Oceania
- 8 School in the Middle East
- 9 Public facility in the United States



For Commercial use

- 10 Public Square in Asia
- 11 Hotel in Asia
- 12 Hotel in Asia
- 13 Public facility in Asia
- 14 Apartment in Oceania
- 15 Apartment in Oceania
- 16 Hotel in the Middle East
- 17 Hotel in the Middle East



For Residential use


- 18 Villa in Africa
- 19 Residence in Oceania
- 20 Residence in the United States
- 21 Villa in the Middle East



# Global development & Production bases

We have established R&D bases in five countries from Japan, Europe, Asia, China, and North America to pursue environmental properties and comfort according to the needs of each region.

- • Head office
- ■ R&D center
- ■ ■ Manufacturing companies



## R&D center & Technology Research Building



R&D center in Fujitsu General (EURO) GmbH (Germany)



North America R&D Center (USA)



Fujitsu General Air Conditioning R&D (Thailand) Co., Ltd. (Thailand)



R&D center in Fujitsu General (Shanghai)



JAPAN Head office, R&D center and 60 m height difference testing tower (Japan)

Technology research building in Japan Head office



**Constructing IoT-based manufacturing**  
We are implementing a real-time IoT-enabled system to immediately visualize and analyze various information such as facility operating status, assembly line production progress, and parts inventory and transportation status. This will further enhance the accuracy of production and shipping forecasts in the Head Office and factory management departments. The system will also help improve activities by employees at production sites, with the aim of improving the efficiency of the production process, the efficiency of parts distribution operations, and the utilization rates of the facilities.



Fujitsu General (Thailand) Co., Ltd. (Thailand) Factory-2



Fujitsu General (Thailand) Co., Ltd. (Thailand)



Fujitsu General Air Conditioning R&D (Thailand) Co., Ltd. (Thailand)



FGA (Thailand) Co., Ltd. (Thailand)



TCFG Compressor (Thailand) Co., Ltd. (Thailand)

## Overseas manufacturing companies



Fujitsu General (Shanghai) Co., Ltd. (China)



F.G.L.S. Electric Co., Ltd. (China)




Fujitsu General Central Air-conditioner (Wuxi) Co., Ltd. (China)



Fujitsu General Electronics Ltd. (Japan)



# 2024 New Products



Split, Wall-mounted type  
Built-in W-LAN adapter models

ECO Range  
Compact Size (Cooling-enhanced type)

S-032-033

- 7-12 classes, 3 models
- Elegant & smart square design
- High energy saving
- Comfortable airflow & Quiet operation
- Smart device control
- Easy access to the flare pipe connection

SPLIT MULTI-SPLIT



## Wall-mounted type Built-in W-LAN adapter models

Designer Range, Standard Range

S-016, 020 M-006, 022


- Improved energy efficiency from the current products
- 7-14 classes, 8 models
- High energy saving
- Built-in WLAN adapter
- Comfortable airflow & Quiet operation
- Easy access to the flare pipe connection



Designer Range  
High Spec & Design



Standard Range  
High-Efficiency & Comfort



**Smart Device control**  
You need to install the "AIRSTAGE Mobile" app on your smart device in order to control the air conditioner.

## ECO Range

S-022-023 M-006, 023

- 5-12 classes, 4 models \*5 class only for multi-split
- Elegant & smart square design
- High energy saving
- Comfortable airflow & Quiet operation
- Built-in WLAN adapter
- Easy access to the flare pipe connection



ECO Range  
Compact Size



## Medium static pressure duct

High-efficiency & Comfort

S-040-043 M-007, 025

- 12-54 classes \*Multi-split is only 12-22 classes
- Slim & Compact design
- High energy saving
- Easy maintenance
- Drain hose as standard
- Wide range of static pressures



12-18 class



22 /24 class



30-54 class

\*Multi-split is only 12-22 classes



## VRF J-VS

### Heat Pump for Small-capacity type

Outdoor unit

**V-020-025**

- **Sustainable:** R32 refrigerant with reduced global warming potential
- **Saving CO<sub>2</sub>:** Top class high energy saving
- **Small Body:** Easy carriage and installation
- **Situational Piping Design:** Long pipe length, Up to 13 indoor units\* can be connected
- **Sightlessness installation:** External static pressure, cooling piping system

\*: 6 HP model



Indoor unit

**V-058-065**

- 4 - 24 classes, 3 type, 34 models
- Compact & Slim design
- Flexible installation



Compact Cassette



Low Static Pressure Duct  
Slim Duct/Slim Concealed Floor



Wall-mounted type



## New Monobloc system

Comfort series

**Future Release**

- 5-10 kW classes, 3 Models
- High energy efficiency
- Quiet operation
- Easy installation & maintenance



## CONTROL SYSTEM

### Wired remote controller

Design type

**C-010-011**

- Harmonizes with the Installation Space
- Intuitive operation
- Status LED Colors
- Refrigerant cycle monitor
- Logo Display
- AIRSTAGE Remo Set application (free download)
- Initial Settings / Indoor Unit Function



## SUPPORT

### AIRSTAGE Service Monitor Tool

for Single-split, Multi-split, Air to water

**Sp-010-011**


- Improved work efficiency
- Bluetooth communication
- Compact and lightweight design
- New application with simple design
- Refrigerant cycle graph display

UTY-ASSXZ1




#### AIRSTAGE Service Monitor Tool

\*Android only.  
You need to install the "AIRSTAGE Service Monitor Tool" app on your smart device.



## From Business to private spaces SOLUTIONS




### Key solution points

Fujitsu General's total solutions are tailored to each property's unique needs.



Fujitsu General provides the best control solutions for buildings.



### Target buildings



#### For Light commercial use

Comfortable and economical air conditioning systems, ideal for small and midsize commercial buildings

- 036** Restaurants, Shops
- 038** Small offices
- 040** Hotels
- 042** Schools



#### For Commercial use

Single and modular VRF systems for high efficiency, comfort, design flexibility, ease of installation, and high reliability

- 044** Large Buildings



#### For Residences

Smart air conditioning systems with extensive control options for comfort and convenience of use


- 046** Residences



# Restaurant, shops


For Light commercial use

Fujitsu General provides perfect total air conditioning systems that offer seamless support by tenant, by purpose, and by customer visit frequency in shops and restaurants with multiple lighting and a high density of customers.



REFRIGERANT  
**R32**

## Single split For Restaurants



### R32 large model lineup expanded


Expanded lineup of ceiling, cassette, and duct types suitable for large spaces using environmentally friendly R32 refrigerant



### Two panel colors


Both black and white panels are available for Cassette type. Black panels are suitable for dark places such as atmospheric restaurants. White panels, by contrast, are more appropriate for use in brightly lit spaces such as offices. (Available for Single split and VRF indoor units)

## Simultaneous multi-split For Shops



### Various indoor unit lineup

You can choose from 3 types of indoor units to suit the atmosphere and layout of your shop.




### Small, lightweight outdoor unit

Models equipped with the new R32 refrigerant Compared to current models, the outdoor unit is more compact and easier to install. (45/54 models)  
 Compact cassette Series for grid ceiling were added to the lineup of indoor units to improve ease of installation.

# Small offices

For Light commercial use


Fujitsu General offers a perfect total air conditioning system for small office buildings with multiple small rooms, taking into consideration energy savings, low noise, comfortable air volume, usage and purpose, and centralized control.



J-IV Series



J-IVL Series



Compact outdoor unit with low noise design

Takes up little space even when installed in a machine room or on the roof. Sufficient static pressure can be maintained even with louvers. Low-noise mode suffices even for nighttime operations at low noise levels.

## VRF J Series compact outdoor units with up to 18 HP

Suitable for the buildings with multiple small rooms. Up to 42 indoor units\* can be connected.

\*Only J-IVL Series 18 HP model

## Breakthrough 3D flow cassette with innovative pursuit of comfort

The left and right air outlet ports with a maximum rotation angle of 100° and the wide central air outlet port create a comfortable space with less uneven temperature.



## Wide lineup of indoor units of low-capacity class

Various low-capacity 1.1 kW indoor units are available for small rooms and spaces.




Wall-mounted type

Compact floor type



Compact cassette Series for grid ceiling



## Control and monitoring

You can operate the main unit from your desk. Non-administrators can also operate the air conditioners with a computer, smartphone or tablet PC.



\*Wireless LAN will be supported in the future.

## Compact wired remote controller


Compact size with a large screen for easy operation. The stylish design harmonizes with the interior.



# Hotels

For Light commercial use

Fujitsu General offers total air conditioning systems perfect for low-rise, small hotels that take into account energy savings, external appearance, safety, and ease of installation.



Select the product best suited to the characteristics of the property.

	Split	VRF J-VS	VRF VR-IV
Project size	Small	Middle	Large
Individual Air conditioning	Great	Good	Great
Reduction of installation space	Fair	Great	Great
Landscape (hide outdoor unit)	Fair*	Great	Fair
Maintenance (individualized)	Great	Good	Fair

\*Depends on pipe length constraints

## Guest room air conditioning with superior comfort, energy efficiency, and ease of installation

### Space saving

Mini duct type with a height of 198 mm and a depth of 450 mm. Easily installed in a narrow ceiling space.



Mini duct

- Card key switch available
- Linked to a card key to prevent people from forgetting to turn off the air conditioner.



External connection switch


- Comfortable airflow by switching the up/down airflow direction
- The Auto louver grille kit creates comfortable airflow by adjusting the air direction.



Auto louver grille kit




Ventilation of each room can be achieved relatively inexpensively by combining an appropriate duct fan (locally procured) through a hole for Fresh air in the indoor unit. If the airflow required to ventilate the room is not sufficient, use ERV (Energy Recovery Ventilator).



## Centralized control of air conditioning for shared spaces

Centralized control of air conditioning for shared spaces Lobbies, hallways, and other common spaces are centrally controlled for air conditioning. Central Remote Controller can manage VRF products, but Split products can also be managed together via Network converter.



\*Some functions will not be available.

- Wired remote controller (design type) with sophisticated design. The touch panel can be easily operated by swiping vertically and horizontally.



NEW



NEW




- Large space air conditioning for the reception area and lobby

Duct type Big duct Series suitable for large spaces with high ceilings

# Schools


For Light commercial use

Fujitsu General offers indoor units that allow multiple connections with a compact design that reduces the installation area and increases the flexibility for selecting installation locations, making them perfect for midsize educational institutions. One single outdoor unit is able to cover an entire school building.



## Centralized control of both air conditioning and ventilation equipment

Centralized control is also possible to stop the operation of not only air conditioners but also lighting and ventilation equipment. These features are useful for managing the energy efficiency of the entire building.



One-way flow cassette Series



Mini duct



Ceiling type



Wall-mounted type




Circular flow cassette Series

**Comfortable room air conditioning without airflow sensation**

Circular flow cassette blows air in all directions at a uniform temperature.




**Individual airflow direction control to prevent people from being exposed to airflow**



**Energy-saving operation when unattended, in conjunction with a Human sensor.**



Energy recovery ventilator





# Large buildings

For Commercial use

Fujitsu General offers modular VRF systems that pursue high efficiency, comfort, design flexibility, ease of installation, and reliability for high-rise buildings.



## Abundant lineup optimized for the operating environment

The VRF system meets a variety of needs, including energy-saving models and models with compatibility to outdoor temperatures of up to 46°C.



## VRF VR-IV

Smart, cutting-edge design Extensive lineup from 8 HP to 48 HP with the capacity ratio of indoor units connectable up to 150%.


### 34 models with 8 to 48 HP

- Space saving combination: 21 models from 8 to 48 HP
- Energy efficient combination: 13 models from 16 to 44 HP

## VRF V-IV

### 34 models from 8 to 48 HP

- Space saving combination: 21 models from 10 to 48 HP
- Energy efficient combination: 13 models from 16 to 46 HP



## Height difference up to 110 m



The height difference between the outdoor unit and the indoor unit is normally 50 m for the V-IV Series, but can be extended to 110 m by installing the Pressure sensor kit.

\* Can only be connected to the V-IV Series




## Centralized control

Not only indoor units in the building, but also facilities such as ventilation can be controlled easily by anyone



## Linkage with various BMS

Linking with MODBUS®, BACnet®, KNX® and other interfaces allows centralized control of equipment other than air conditioning.





## High system flexibility

The industry-leading high static pressure, long pipe design, and connection capacity enable flexible installation on each floor and installation of various indoor units.


82\* Pa

\*: V-IV Series, 80Pa for VR-IV Series



## Prompt service support

Web monitoring tool and System controller remotely monitor the air conditioning of the entire building. Self-diagnosis in cooperation with the management company enables quick response in case of an emergency.





# Residences

For Apartments & Houses

From the living room, where the whole family relaxes, to bedrooms, children's rooms and other small rooms, Fujitsu General has designed systems suited to spaces that reflect the rhythm of life.



REFRIGERANT  
**R32**



## A variety of indoor units to suit the characteristics of each room



### For Living & Dining room

**KE**  
Series

#### Cool beauty design model

This series features a special European-style design. The light, elegant and three-dimensional expression achieved by the curved surface is beautiful from all angles.



### For Large rooms

**KM**  
Series

#### Standard & Comfort model

The basic functions and powerful, comfortable airflow volume controls are optimal for large spaces.



**KG**  
Series  
GOOD DESIGN

### For Primary bedrooms or Living rooms



**KM**  
Series  
GOOD DESIGN

**Award winning design, Quiet models**  
High performance, low noise with emphasis on design

**KN**  
Series  
NEW



### For Bedrooms or Home offices

**ECO Range, Compact size**  
High performance and compact design suitable for bedrooms, home offices and other small spaces




## Outdoor units suitable for residential environments




### R32 Multi-split type released

Models are now available with environment-friendly R32 refrigerant. A number of products with improved external design have been added to the indoor unit lineup.



### Operated by smart speaker

Simply talk to the smart speaker to operate the air conditioner and check its operating status while doing other things.



With the WLAN adapter and the AIRSTAGE Mobile app, you can control the heating and cooling of your home anytime, anywhere.



# Light Commercial & Residential SPLIT & MULTI-SPLIT

Energy saving design to provide a comfortable indoor environment while being environment-friendly.

These are air conditioners that are both user-friendly and environment-friendly. Fujitsu General air conditioners cater to a wide range of needs, from living rooms, bedrooms, stores, small offices, through to hotels.

## SPLIT

- Refrigerant R32 models
  - Wall-mounted type
  - Cassette
  - Duct
  - Floor
  - Ceiling
- Refrigerant R410A models
  - Duct



## MULTI-SPLIT

- Refrigerant R32 models
  - 2-unit to 5-unit Multi-split
  - Simultaneous Multi-split Twin/Triple
- Refrigerant R410A models
  - 6-unit Multi-split
  - Simultaneous Multi-split Twin/Triple/Double Twin



## SPLIT & MULTI-SPLIT

Light Commercial &  
Residential



## Light Commercial & Residential SPLIT

- S-004 Split Overview
- S-006 Indoor Units Lineup
- S-010 Features
- S-015 Features Explanation
- S-060 Wall-mounted Specifications
- S-063 ECO Series Lineup Specifications
- S-068 Feature Summary



### Refrigerant R32 models

- Wall-mounted type** – Built in W-LAN adapter model
- S-016 Designer Range
  - High Spec & Design
  - Cool Beauty Design
- S-020 Standard Range – High-Efficiency & Comfort
- S-022 ECO Range – Compact Size

### Wall-mounted type

- S-024 Standard Range
  - High-Efficiency & Large Rooms
- S-028 ECO Range
  - Compact Size
  - Comfort for Large Rooms
  - Cooling-enhanced type

### Cassette

- S-034 Compact 4-way Flow Range – Compact Size
- S-036 Circular Flow Range – Comfort for Large Rooms

### Duct

- S-038 Slim Duct – Slim Design
- S-040 Medium Static Pressure Duct
  - High-Efficiency & Comfort
  - Compact Size
  - Standard
- S-050 High Static Pressure Duct



### Floor, Ceiling

- S-056 Floor – Compact Size
- S-058 Ceiling



### Refrigerant R410A models

- Duct**
- S-052 High Static Pressure Duct
- S-054 Big Duct



# Split Overview

Fujitsu General provides its customers with 5 types and 149 models of air conditioning systems perfect for various customer applications and layouts. Added to this lineup recently are the environment-friendly R32 refrigerant models.



## Existing pipes can be reused if they meet our guidelines

Please consult with our regional sales subsidiaries for details.


### Cautions when reusing the existing pipes

- The thickness of the pipes must be 0.8 mm or thicker in accordance with the pipe diameter.
- Use flares that have been reworked to be compatible with the new refrigerant, and are compliant with ISO 14903.
- Select suitable wiring in accordance with the installation manual of the new air conditioning unit.
- When pump-down is not possible or when the inner pipe walls are dirty, make sure to clean the pipes before connecting new ones.
- When using different diameters pipes from the standard sizes,
  - The performance may not reach the published specification value.
  - Dedicated flare nuts compliant with ISO 14903 should be procured locally.
  - Restrictions apply to pipe lengths, refrigerant volumes, and room sizes.



### Wall-mounted type

Simple and easy to install, all models, are expertly designed to control airflow and save energy. The design, with its flat and simple appeal, perfectly matches room interiors. Many of the models in the lineup adopt the new environmentally friendly R32 refrigerant.



### Cassette

The Cassette type, which blends in perfectly with the interior design, blows air in all four directions to create an even air-conditioning for the entire space. We have a variety of series including Compact models with a uniquely designed panel to match grid ceilings, and Circular Flow models that send airflow in a 360° direction.



### Floor

The compact and slim design makes this model suitable for installation in commercial as well as residential buildings. This model is also recommended as a heating device because it delivers a warm airflow from both the top and bottom outlets.



### Duct

The main unit is hidden in the wall, making the room look neat and tidy. Mini Duct and Slim Duct models are also available for installation in narrow spaces between beams or above the ceiling. Large models, suitable for air conditioning vast spaces, allow multiple outlets to be installed in just one unit, and are perfect for atypical room layouts.



### Ceiling

As with the wall-mounted unit, ceiling installation is very easy, and the unit's thin structure with a height of just 240 mm allows neat installation. The powerful airflow that can reach far away from the wide outlet is perfect for large meeting rooms, audiovisual rooms, and other rectangular spaces with a lot of depth.

# Indoor Units Lineup



FUJITSU GENERAL (Euro) GmbH participates in the ECP program for AC.  
Check ongoing validity of certificate:  
[www.eurovent-certification.com](http://www.eurovent-certification.com)

Type	Range	Refrigerant	Model	Class								Class							
				7	9	12	14	18	22	24	30	36	45	54	60	72	90		
Wall-mounted type Built in WLAN adapter model	Designer Range High Spec & Design	Cooling & Heating	NEW	<b>KG</b> Series	ASEH07KGTG	ASEH09KGTG	ASEH12KGTG	ASEH14KGTG											
	Designer Range Cool Beauty Design	Cooling & Heating		<b>KE</b> Series	ASEG07KETF ASEG07KETF-B	ASEG09KETF ASEG09KETF-B	ASEG12KETF ASEG12KETF-B	ASEG14KETF ASEG14KETF-B											
	Standard Range High-Efficiency & Comfort	Cooling & Heating	NEW	<b>KM</b> Series	ASEH07KMCG	ASEH09KMCG	ASEH12KMCG	ASEH14KMCG											
	ECO Range Compact Size	Cooling & Heating	NEW	<b>KN</b> Series	ASEH07KNCA	ASEH09KNCA	ASEH12KNCA												
Wall-mounted type	Standard Range High-Efficiency & Large Rooms	Cooling & Heating		<b>KM</b> Series				ASEG18KMTE		ASEG24KMTE									
	Standard Range High-Efficiency & Large Rooms	Cooling & Heating		<b>KM</b> Series							ASEH30KMTB	ASEH36KMTB							
	ECO Range Compact Size	Cooling & Heating		<b>KP</b> Series	ASEG07KPCE	ASEG09KPCE	ASEG12KPCE												
	ECO Range Comfort for Large Rooms	Cooling & Heating		<b>KL</b> Series				ASEG18KLCA		ASEG24KLCA									
	ECO Range Cooling-enhanced	Cooling & Heating	NEW	<b>KL</b> Series	ASEH07KLTA	ASEH09KLTA	ASEH12KLTA												

# Indoor Units Lineup



FUJITSU GENERAL (Euro) GmbH participates in the ECP program for AC.  
Check ongoing validity of certificate:  
[www.eurovent-certification.com](http://www.eurovent-certification.com)

Type	Range	Refrigerant	Model	Class									Class									
				7	9	12	14	18	22	24	30	36	45	54	60	72	90					
Cassette	Compact 4-way Flow Range Compact Size	Cooling & Heating				AUXG09KVLA	AUXG12KVLA	AUXG14KVLA	AUXG18KVLA	AUXG22KVLA	AUXG24KVLA											
	Circular Flow Range Comfort for Large Rooms	Cooling & Heating	 18/22/24    30/36/45/54						AUXG18KRLB	AUXG22KRLB	AUXG24KRLB	AUXG30KRLB	AUXG36KRLB	AUXG45KRLB	AUXG54KRLB							
Duct	Slim Duct	Cooling & Heating	 09/12/14    18		ARXG09KLLAP	ARXG12KLLAP	ARXG14KLLAP	ARXG18KLLAP														
	Medium Static Pressure Duct High-Efficiency & Comfort	Cooling & Heating	 12/14/18    22/24    30/36/45/54			ARXH12KMTAP		ARXH14KMTAP	ARXH18KMTAP	ARXH22KMTAP	ARXH24KMTAP	ARXH30KMTAP	ARXH36KMTAP	ARXH45KMTAP	ARXH54KMTAP							
	Medium Static Pressure Duct Compact Size	Cooling & Heating	 12/14    18/22/24/30    36/45/54			ARXG12KHTAP		ARXG14KHTAP	ARXG18KHTAP	ARXG22KHTAP	ARXG24KHTAP	ARXG30KHTAP	ARXG36KHTAP	ARXG45KHTAP	ARXG54KHTAP							
	Medium Static Pressure Duct Standard	Cooling & Heating							ARXG22KMLB	ARXG24KMLA	ARXG30KMLA	ARXG36KMLA	ARXG45KMLA									
	High Static Pressure Duct	Cooling & Heating														ARXG45KHTB	ARXG54KHTB					
		Cooling & Heating																ARYG60LHTA				
	Big Duct	Cooling & Heating																	ARYG72LHTA	ARYG90LHTA		
	Floor Compact & Comfort	Cooling & Heating			AGEG09KVCA	AGEG12KVCA	AGEG14KVCA															
	Ceiling	Cooling & Heating	 18/22    24/30    36/45/54						ABEG18KRTA	ABEG22KRTA	ABEG24KRTA	ABEG30KRTA	ABEG36KRTA	ABEG45KRTA	ABEG54KRTA							

# Features


## High-Efficiency

### **ALL DC** All DC Inverter Technology



#### DC twin-rotary compressor

A high-efficiency 2-cylinder rotary compressor with a DC inverter optimizes the internal structure of the compressor to achieve higher energy efficiency compared to similar compressors.




#### DC fan motor

The DC fan motor produces high power, a wide operating range, and high-efficiency.



#### Sine-wave DC inverter control

High-efficiency operation is realized by using sine-wave DC inverter control.




## Heat Exchanger for Wall-mounted type

### High-density multipath heat exchanger

Thinner and denser heat exchangers and multipath efficiency technology have substantially improved heat exchange performance.

### High-performance sub-cool heat exchanger


A counter-type bypass circuit has been incorporated to achieve a higher performance. (Large multi-split type, VRF)



## High Energy Saving


### **Save-Stop** Human sensor control

The Human sensor monitors the movements of people in a room and operates the air conditioner at a lower capacity when people leave the room. When people come back to the room, it automatically returns to the previous operating mode.




### **Economy** Economy operation

Limits maximum operation, reducing the power consumption, and thereby suppressing the maximum load.




### **Set Temp.** Setting temperature range limitation

The minimum and maximum temperature range can be set giving further energy savings while considering the comfort of the occupants.




### **Return** Set temperature auto return

- The set temperature automatically returns to the previously set temperature.
- The time range in which the set temperature can be changed is from 10 to 120 minutes.



### **OFF** Auto-off timer

- The indoor unit is automatically turned off when it reaches a preset operating time frame.
- The time frame of the Auto-off timer can be flexibly scheduled.
- Auto-off times can be set from 30 to 240 minutes.




## More Comfort




### Power diffuser

These three technologies enable precise wind direction control and improve ventilation efficiency; our airflow control offers a more comfortable environment.




### Wireless LAN control

Users can control their air conditioners from anywhere with their mobile devices while out or on the move.





### Powerful operation

Maximum airflow and maximum compressor speed are maintained for the period necessary to reach the set temperature quickly.



### 10°C heat

After a person has left the room, the system switches to minimum heating operation to maintain the room temperature. (Maintained at 10°C)



### Uniform air conditioning

Circular airflow to achieve uniform air conditioning without temperature unevenness in workspaces




## Quiet and Comfort Control



## Low Noise Technology


### Outdoor unit fan

Outdoor unit fan design with a small separation vortex, minimized air volume by fan control, and top-class low noise




### Air stabilizer in Duct

Low-noise duct structure with a built-in air stabilizer




### Outdoor unit low noise operation

Users can choose low noise levels, depending on the installation environment. Operation time can be set by timer.



### Auto changeover

In an auto setting, the system automatically switches between cooling and heating modes according to the set temperature and room temperature.



### Fresh air intake

Fresh air is taken in by a fan connected to an external control unit.



## Feature Explanation

### Energy-Saving Features



#### Save Human sensor

The Human sensor detects the movement of people in the room and determines whether to switch to energy saving operation.



#### Setting temperature range limitation

Sets the minimum and maximum limits on room temperature to establish the right balance between energy saving and a comfortable environment.



#### Human sensor control

The Human sensor (option) detects movement of people in the room and decides whether to save energy or stop the unit.



#### Set temperature auto return

The setting temperature automatically returns to the previously set temperature.



#### Economy operation

The thermostat setting is adjusted automatically according to the room temperature to avoid unnecessary cooling or heating.

### Features for Comfort



#### Power diffuser

An additional louver that opens based on input from monitoring sensors to quickly enhance immediate comfort needs.



#### Outdoor unit low noise operation

The noise level of the outdoor unit can be selected.



#### Double swing automatic

Complex swing action of the louver enables automatic swing in both the left/right and up/down directions.



#### Connectable fresh air duct

Outside air can be introduced by attaching a locally purchased duct to the fresh air knockout and an optional part.



#### Individual airflow direction control

Each louver of a 4-way Cassette type can be controlled individually to provide comfortable airflow.



#### Powerful operation

Operation at maximum air flow and compressor speed, that quickly makes the room comfortable.



#### Auto changeover

The unit automatically switches between heating and cooling modes based on the temperature setting and the room temperature.



#### Automatic fan speed

A micro-computer automatically adjusts the airflow to follow the changes in room temperature.



#### Fresh air intake

Fresh air can be taken in by a fan connected to an external control unit.



#### 10°C Heat

The room temperature can be set to go no lower than 10°C, thus ensuring that the room does not get too cold when not occupied.



#### UP/DOWN swing louver

The vertical louver automatically swings up and down.



#### Auto restart

In the event of a temporary power failure, the air conditioner will automatically restart in the same operating mode as before, once the power supply is restored.



#### Connectable distributing duct

Locally purchased branch ducts can be attached to the systems to distribute the airflow.

### Convenience Features



#### Auto-off timer

Automatically stops operation when a fixed time has elapsed from the start of operation.



#### Sleep timer

A micro-computer gradually changes the room temperature automatically to promote a comfortable night's sleep.



#### Weekly timer

Different ON-OFF times can be set for each day.



#### External error output

External ON/OFF input



#### Multi System Control

Operation using "Lead Lag Operation", "Back up operation", "Lag Operation" is possible. (Page C-011)



#### Special Cooling

"Special Cooling" is a function that supports the operation of "Multi System Control".



#### Program timer

This digital timer allows selection of one of four options: ON, OFF, ON > OFF, or OFF > ON.



#### Filter sign

Indicates the filter cleaning period by blinking.



#### Wireless LAN control

The optional WLAN adapter enables the air conditioner to be operated by smartphone or tablet PC from outside the home.

### Clean Features



#### Ion deodorization filter

The filter deodorizes by powerfully decomposing absorbed odors using the oxidizing and reducing effects of ions generated by an ultra-fine-particle ceramic.



#### Apple-catechin filter

The Apple-catechin filter uses static electricity to clean fine particles and dust from the air.



#### Washable panel

Since the front panel is easy to remove, maintenance is also easy.



#### Silver Ion Filter

The Silver ion filter helps to keep indoor air free from viruses, bacteria and molds.



#### Long-life filter

### Installation / Support



#### Automatic airflow adjustment

Automatically detects required airflow in each application case and adjusts the volume.



#### Drain pump as standard



#### Blue fin

### Refrigerant cycle monitor

The values of each sensor and actuator can be displayed, and the status of the refrigeration cycle can be checked.



#### All DC models

NEW

## Wall-mounted type

Built-in WLAN adapter model  
Designer Range  
High Spec & Design



ALL DC




### High energy saving

Top class high efficiency is achieved by high efficient lambda-shaped heat exchanger, large cross flow fan and new refrigerant.




**SEER**  
**9.80\***  
\*07 model

**SCOP**  
**5.20\***  
\*07/09/12 models



#### Hybrid-heat exchanger

The large hybrid heat exchanger has greatly improved the heat exchange efficiency to achieve top-level SEER and SCOP.



#### Ø107 Large cross-flow fan

The large-diameter fan generates air volume efficiently even at reduced power.



#### Human sensor

The Human sensor monitors the movements of people in a room and operates the air conditioner at a lower capacity when people leave the room. When people come back to the room, it automatically returns to the previous operating mode.



### Comfortable airflow & Quiet operation

The large louver and the new air-blowing structure create a comfortable air flow that spreads all the way down to the user's feet with quiet operation.



### Smart device control


A WLAN adapter is included as standard equipment. By installing the AIRSTAGE mobile app on your smart device, you can check and control the operating status of the air conditioner from anywhere indoors or outdoors.  
\* See page C-020 for details on smart device control.



### Refrigerant cycle monitor (Option)

Wired Remote Controller (Touch Panel) will support to display some sensor values for maintenance and service support.

\*Wired remote controller (UTY-RNRYZ5 or UTY-RVRY) is required.



Model: ASEH07KGTG / ASEH09KGTG / ASEH12KGTG / ASEH14KGTG



### Specifications

Model name	Indoor unit		ASEH07KGTG	ASEH09KGTG	ASEH12KGTG	ASEH14KGTG
	Outdoor unit					
Power Source						
Capacity	Cooling	Rated Min.-Max.	kW	2.0	2.5	3.4
	Heating	Rated Min.-Max.		0.9-3.3	0.9-4.1	0.9-4.5
				2.5	2.8	4.0
Input Power	Cooling/Heating	kW	kW	0.400 / 0.500	0.550 / 0.600	0.870 / 0.910
	Cooling	W/W		5.00	4.55	3.91
	Heating	W/W		5.00	4.67	4.40
Pdesign	Cooling/Heating (-10°C)	kW	W/W	2.0 / 2.3	2.5 / 2.4	3.4 / 2.5
SEER	Cooling			9.80	9.40	8.80
SCOP	Heating (Average)			5.20	5.20	4.60
Energy Efficiency Class	Cooling		A+++	A+++	A+++	A++
	Heating (Average)			A+++	A+++	A++
Max. Operating Current	Cooling/Heating	A	kWh/a	6.5 / 9.0	6.5 / 9.0	9.0 / 10.5
Annual Energy Consumption	Cooling			71	93	135
	Heating			618	646	673
Moisture Removal		l/h	l/h	1.1	1.3	1.6
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q		36 / 32 / 29 / 19	38 / 34 / 29 / 19	40 / 35 / 30 / 19
	Indoor (Heating)	H/M/L/Q		38 / 34 / 31 / 20	39 / 34 / 31 / 20	42 / 38 / 33 / 21
Sound Power Level	Outdoor (Cooling/Heating)	High	dB(A)	42 / 43	44 / 45	50 / 50
	Indoor (Cooling/Heating)	High		49 / 51	52 / 52	56 / 58
Airflow Rate	Outdoor (Cooling/Heating)	High	m³/h	56 / 56	58 / 58	65 / 66
	Indoor/Outdoor (Cooling)	High		570 / 1,390	640 / 1,480	680 / 1,800
Net Dimensions H x W x D	Indoor	mm		270 × 834 × 215	270 × 834 × 215	270 × 834 × 215
	Outdoor	mm		542 × 799 × 290	542 × 799 × 290	542 × 799 × 290
Weight	Indoor	kg		10	10	10
	Outdoor	kg		30	30	31
Connection Pipe Diameter (Liquid/Gas)		mm		6.35 / 9.52	6.35 / 9.52	6.35 / 9.52
Drain Hose Diameter (I.D./O.D.)		mm		13.8 / 15 to 16.8	13.8 / 15 to 16.8	13.8 / 15 to 16.8
Max. Pipe Length (Pre-Charge)		m		20 (15)	20 (15)	20 (15)
Max. Height Difference				15	15	15
Operating Range	Cooling	°CDB		-10 to 50	-10 to 50	-10 to 50
	Heating			-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		kg (CO <sub>2</sub> eq-T)	R32 (675)	R32 (675)	R32 (675)
	Charge			0.75 (0.506)	0.75 (0.506)	0.85 (0.574)

### Optional parts


\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Wired Remote Controller (Design type):	UTY-RVRY	Simple remote controller: UTY-RSRY	Network Convertor for single split (DC power supply type): UTY-VTGX
Compact wired remote controller:	UTY-RCRYZ1	External switch controller: UTY-TERX	Network Convertor for single split (AC power supply type): UTY-VTGV
Wired remote controller (touch panel):	UTY-RNRYZ5	Communication kit: UTY-TWRXZ2	Silver Ion filter: UTR-FA16-5
Wired remote controller:	UTY-RRLY	External connect kit: UTY-XWZX	External input and output PCB*: UTY-XCSXZ2
Simple remote controller (without operation mode):	UTY-RHRY	UTY-XWZXZ5	

\*1 It is required when 2 or more external input and output ports are used.

### Dimensions

(Unit: mm)



## Wall-mounted type

Built-in WLAN adapter model  
Designer Range  
Cool Beauty Design



ALL DC



### Cool beauty design

We have designed this series exclusively for the European market. The exterior design harmonizes beautifully with any decor and adds comfortable elegance to the room. The light, elegant and three-dimensional expression achieved by the curved surface is beautiful from any angle.




CMF: COLOR MATERIAL FINISH

The texture of the front panel expresses the craftsmanship of Europe, and changes its expression with the changing light of the day.


### High energy saving

Top class high efficiency is achieved by high efficient lambda-shaped heat exchanger, large cross flow fan and new refrigerant.



### Smart device control


A WLAN adapter is included as standard equipment. By installing the AIRSTAGE mobile app on your smart device, you can check and control the operating status of the air conditioner from anywhere indoors or outdoors.



\* See page C-020 for details on smart device control.

### Comfortable airflow & Quiet operation

The large louver and the new air-blowing structure create a comfortable air flow that spreads all the way down to the user's feet with quiet operation.



**Model: ASEG07KETF / ASEG09KETF / ASEG12KETF / ASEG14KETF (Pearl white X White)  
ASEG07KETF-B / ASEG09KETF-B / ASEG12KETF-B / ASEG14KETF-B (Silver X Dark gray)**



Pearl white X White



Silver X Dark gray



WLAN adapter (Built-in)



Wireless RC

For ASEG07/09/12KETF  
ASEG07/09/12KETF-BFor ASEG14KETF  
ASEG14KETF-B

### Specifications

Model name	Indoor unit		ASEG07KETF ASEG07KETF-B	ASEG09KETF ASEG09KETF-B	ASEG12KETF ASEG12KETF-B	ASEG14KETF ASEG14KETF-B
	Outdoor unit		AOEG07KETA	AOEG09KETA	AOE12KETA	AOE14KETA
Power Source					Single phase, ~230 V, 50 Hz	
Capacity	Cooling	Rated	2.0	2.5	3.4	4.2
		Min.-Max.	0.9 - 3.0	0.9 - 3.2	0.9 - 3.9	0.9 - 4.4
	Heating	Rated	2.5	2.8	4.0	5.4
		Min.-Max.	0.9 - 3.4	0.9 - 4.0	0.9 - 5.3	0.9 - 6.0
Input Power	Cooling/Heating	kW	0.450/0.555	0.630/0.620	0.935/0.960	1.220/1.410
EER	Cooling	W/W	4.43	3.97	3.65	3.44
COP	Heating		4.52	4.52	4.17	3.83
Pdesign	Cooling/Heating (-10°C)	kW	2.0/2.3	2.5/2.4	3.4/2.5	4.2/4.0
SEER	Cooling	W/W	7.40	7.40	7.30	6.90
SCOP	Heating (Average)		4.10	4.10	4.40	4.10
Energy Efficiency Class	Cooling		A++	A++	A++	A++
	Heating (Average)		A+	A+	A+	A+
Max. Operating Current	Cooling/Heating	A	6.5/9.0	6.5/9.0	6.5/9.0	6.5/9.0
Annual Energy Consumption	Cooling	kWh/a	95	118	163	213
	Heating		785	819	795	1,367
Moisture Removal		l/h	1.0	1.3	1.8	2.1
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	38/33/29/20	40/34/29/20	40/35/30/20	43/36/30/20
	Indoor (Heating)	H/M/L/Q	41/35/31/22	42/36/31/22	42/38/33/22	44/39/33/24
	Outdoor (Cooling/Heating)	High	46/46	46/46	50/50	50/50
Sound Power Level	Indoor (Cooling/Heating)	High	54/56	55/57	55/58	57/59
	Outdoor (Cooling/Heating)	High	61/61	61/62	65/65	65/66
Airflow Rate	Indoor/Outdoor (Cooling)	High	650/1,650	700/1,650	700/1,700	770/1,680
	Indoor/Outdoor (Heating)	High	720/1,450	750/1,450	770/1,470	800/1,580
Net Dimensions	Indoor	mm			295 × 950 (wall side: 840) × 230	
	Outdoor	mm	541 × 663 × 290	541 × 663 × 290	541 × 663 × 290	542 × 799 × 290
Weight	Indoor	kg	11	11	11	11.5
	Outdoor	kg	23	23	25	31
Connection Pipe Diameter (Liquid/Gas)		mm	6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52
Drain Hose Diameter (I.D./O.D.)		mm	13.8/15.0 to 16.8	13.8/15.0 to 16.8	13.8/15.0 to 16.8	13.8/15.0 to 16.8
Max. Pipe Length (Pre-Charge)		m	20 (15)	20 (15)	20 (15)	20 (15)
Max. Height Difference			15	15	15	15
Operating Range	Cooling	°CDB	-10 to 46	-10 to 46	-10 to 46	-10 to 46
	Heating		-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge	kg (CO2eq-T)	0.6 (0.405)	0.6 (0.405)	0.7 (0.473)	0.85 (0.574)


### Optional parts

Wired Remote Controller (Design type):	UTY-RVRY	Simple remote controller: UTY-RSRY	* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.
Compact wired remote controller:	UTY-RCRYZ1	Communication kit: UTY-TWRXZ2	
Wired remote controller (touch panel):	UTY-RNRYZ5	External connect kit: UTY-XWZX	
Wired remote controller:	UTY-RLRY	Silver Ion filter: UTR-FA16-5	
Simple remote controller (without operation mode):	UTY-RHRY	External switch controller: UTY-TERX	Network Convertor for single split (DC power supply type): UTY-VTGX
			Network Convertor for single split (AC power supply type): UTY-VTGXV

\*1 It is required when 2 or more external input and output ports are used.

### Dimensions

(Unit: mm)



NEW

## Wall-mounted type

Built-in WLAN adapter model  
Standard Range  
High-Efficiency & Comfort





ALL DC



### Slim & stylish square design


The slim and stylish square design of this indoor unit is realized by using a high-density, multipath heat exchanger and a high-efficiency wind blower.

#### Hybrid-heat exchanger



### High energy saving

High-efficiency has been achieved by the lambda-shaped heat exchanger, large cross-flow fan, and the new refrigerant.



### Comfortable airflow & Quiet operation

The large louver and the new air-blowing structure create a comfortable air flow that spreads all the way down to the user's feet with quiet operation.



### Smart device control

A WLAN adapter is included as standard equipment. By installing the AIRSTAGE mobile app on your smart device, you can check and control the operating status of the air conditioner from anywhere indoors or outdoors.


\* See page C-020 for details on smart device control.



### Refrigerant cycle monitor (Option)

Wired Remote Controller (Touch Panel) will support to display some sensor values for maintenance and service support.

\*Wired remote controller (UTY-RNRYZ5 or UTY-RVRY) is required.



Model: ASEH07KMCG / ASEH09KMCG / ASEH12KMCG / ASEH14KMCG



WLAN adapter (Built-in)



Wireless RC



For ASEH07/09/12KMCG



For ASEH14KMCG

### Specifications

Model name	Indoor unit		ASEH07KMCG	ASEH09KMCG	ASEH12KMCG	ASEH14KMCG
	Outdoor unit	kW				
Power Source			2.0	2.5	3.4	4.2
Capacity	Cooling	Rated Min.-Max.	0.9-3.0	0.9-3.2	0.9-3.9	0.9-4.4
	Heating	Rated Min.-Max.	2.5	2.8	4.0	5.4
			0.9-3.4	0.9-4.0	0.9-5.3	0.9-6.0
Input Power	Cooling/Heating	kW	0.450 / 0.555	0.650 / 0.620	0.960 / 1.020	1.220 / 1.410
EER	Cooling	W/W	4.43	3.85	3.54	3.44
COP	Heating		4.52	4.52	3.92	3.83
Pdesign	Cooling/Heating (-10°C)	kW	2.0 / 2.3	2.5 / 2.4	3.4 / 2.5	4.2 / 4.0
SEER	Cooling	W/W	8.40	8.40	7.70	7.10
SCOP	Heating (Average)		4.60	4.60	4.60	4.10
Energy Efficiency Class	Cooling		A++	A++	A++	A++
	Heating (Average)		A++	A++	A++	A+
Max. Operating Current	Cooling/Heating	A	6.5 / 9.0	6.5 / 9.0	6.5 / 9.0	6.5 / 9.0
Annual Energy Consumption	Cooling	kWh/a	83	104	155	207
	Heating		700	730	761	1,366
Moisture Removal		l/h	1.0	1.3	1.8	2.1
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	38 / 33 / 29 / 20	40 / 34 / 29 / 20	40 / 35 / 30 / 20	43 / 36 / 30 / 20
	Indoor (Heating)	H/M/L/Q	41 / 35 / 31 / 22	42 / 36 / 31 / 22	42 / 38 / 33 / 22	44 / 39 / 33 / 24
Sound Power Level	Outdoor (Cooling/Heating)	High	46 / 46	46 / 46	50 / 50	50 / 50
	Indoor (Cooling/Heating)	High	54 / 56	55 / 57	55 / 58	57 / 59
Airflow Rate	Outdoor (Cooling/Heating)	High	61 / 61	61 / 62	65 / 65	65 / 66
	Indoor/Outdoor (Cooling)	High	650 / 1,650	700 / 1,650	700 / 1,700	770 / 1,680
Net Dimensions H x W x D	Indoor	m³/h	720 / 1,450	750 / 1,450	780 / 1,470	820 / 1,580
	Outdoor	mm	270 x 834 x 222			
Weight	Indoor	mm	541 x 663 x 290	541 x 663 x 290	541 x 663 x 290	542 x 799 x 290
	Outdoor	kg	10	10	10	10
Connection Pipe Diameter (Liquid/Gas)		mm	6.35 / 9.52	6.35 / 9.52	6.35 / 9.52	6.35 / 9.52
Drain Hose Diameter (I.D./O.D.)			13.8 / 15 to 16.8			
Max. Pipe Length (Pre-Charge)		m	20 (15)	20 (15)	20 (15)	20 (15)
Max. Height Difference			15	15	15	15
Operating Range	Cooling	°CDB	-10 to 50	-10 to 50	-10 to 50	-10 to 50
	Heating		-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge	kg (CO <sub>2</sub> eq-T)	0.60 (0.405)	0.60 (0.405)	0.70 (0.473)	0.85 (0.574)

### Optional parts


\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Wired Remote Controller (Design type):	UTY-RVRY	Simple remote controller: UTY-RSRY	Network Convertor for single split (DC power supply type): UTY-VTGX
Compact wired remote controller:	UTY-RCRYZ1	Communication kit: UTY-TWRXZ2	Network Convertor for single split (AC power supply type): UTY-VTGXV
Wired remote controller (touch panel):	UTY-RNRYZ5	External connect kit: UTY-XWZX	Silver Ion filter: UTR-FA16-5
Wired remote controller:	UTY-RLRY	UTY-XWZXZ5	External input and output PCB <sup>1</sup> : UTY-XCSXZ2
Simple remote controller (without operation mode):	UTY-RHRY	External switch controller: UTY-TERX	

<sup>1</sup> It is required when 2 or more external input and output ports are used.

### Dimensions

(Unit: mm)



## Wall-mounted type

Built-in WLAN adapter model  
ECO Range  
Compact Size



ALL DC



### Elegant & smart square design

An elegant and smart type in the eco range.  
The delicate shading of the ridge line makes the unit an accessory for the room.



### High energy saving

The size of the heat exchanger has increased to improve performance, making it more powerful despite its compact size.



### Comfortable airflow & Quiet operation

The large louver and the new air-blowing structure create a comfortable air flow that spreads all the way down to the user's feet with quiet operation.



### Smart device control

A WLAN adapter is included as standard equipment. By installing the AIRSTAGE mobile app on your smart device, you can check and control the operating status of the air conditioner from anywhere indoors or outdoors.



\* See page C-020 for details on smart device control.

### Highly efficient operation even at high outdoor temperatures

Even when installed in areas with high outdoor air temperatures (Max. 50°C\*), it is comfortable because it can cool the interior well.

\* suction temperature of the outdoor unit

Operation Range  
MAX 50 °C  
(Cooling operation)



Model: ASEH07KNCA / ASEH09KNCA / ASEH12KNCA



AR-RPF4E

WLAN adapter (Built-in)

Wireless RC



### Specifications

Model name	Indoor unit		AOEH07KNCA	AOEH09KNCA	AOEH12KNCA		
	Outdoor unit						
Power Source							
Capacity	Cooling	Rated Min.-Max.	kW	2.0	2.5		
	Heating	Rated Min.-Max.		0.9-2.9	0.9-3.1		
				2.5	2.8		
Input Power	Cooling/Heating		kW	0.50 / 0.58	0.74 / 0.70		
	Cooling			4.00	3.38		
	Heating			4.31	4.00		
Pdesign	Cooling/Heating (-10°C)		kW	2.0 / 2.3	2.5 / 2.4		
	Cooling			7.8	7.4		
	Heating (Average)			4.4	4.4		
Energy Efficiency Class	Cooling		A++	A++	A++		
	Heating (Average)			A+	A+		
	Cooling/Heating	A		6.5 / 9.0	6.5 / 9.0		
Annual Energy Consumption	Cooling	kWh/a		90	118		
	Heating			731	763		
		I/h		1.0	1.0		
Moisture Removal	Indoor (Cooling)	H/M/L/Q	dB(A)	36 / 33 / 29 / 20	38 / 35 / 29 / 20		
	Indoor (Heating)	H/M/L/Q		38 / 33 / 30 / 22	39 / 35 / 31 / 22		
	Outdoor (Cooling/Heating)	High		43 / 44	44 / 45		
Sound Pressure Level	Indoor (Cooling/Heating)	High		51 / 52	53 / 52		
	Outdoor (Cooling/Heating)	High		53 / 54	56 / 56		
	Indoor/Outdoor (Cooling)	High		530 / 1,430	580 / 1,430		
Sound Power Level	Indoor/Outdoor (Heating)	High	m³/h	580 / 1,390	580 / 1,390		
	Indoor	mm		270 × 784 × 222	270 × 784 × 222		
	Outdoor	mm		541 × 663 × 290	541 × 663 × 290		
Airflow Rate	Indoor	kg		9	9		
	Outdoor	kg		22	22		
					24		
Net Dimensions H x W x D	Connection Pipe Diameter (Liquid/Gas)	mm		6.35 / 9.52	6.35 / 9.52		
	Drain Hose Diameter (I.D./O.D.)	mm		13.8 / 15 to 16.8	13.8 / 15 to 16.8		
	Max. Pipe Length (Pre-Charge)	m		20 (15)	20 (15)		
Max. Height Difference		m		15	15		
	Operating Range Cooling	°CDB		-10 to 50	-10 to 50		
	Heating			-15 to 24	-15 to 24		
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)		
	Charge	kg (CO <sub>2</sub> eq-T)		0.57 (0.385)	0.57 (0.385)		
					0.65 (0.439)		



### Optional parts

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Silver Ion Filter: UTR-FA16-5

### Dimensions

(Unit: mm)



## Wall-mounted type

### Standard Range

High-Efficiency & Large Rooms



ALL DC




### High energy saving

High-efficiency has been achieved by the lambda-shaped heat exchanger, large cross-flow fan, and the new refrigerant.

**SEER**  
7.8<sup>\*1</sup>    **SCOP**  
4.6<sup>\*1</sup>

\*1 Rank A++  
\*18 model



### Smart device control (option)

With the optional WLAN adapter installed in the air conditioner, you can control it from anywhere with your smart device.

\* For more information about smart device control, please refer to the page C-020.



You need to install the AIRSTAGE Mobile app on your smart device in order to control the air conditioner.



### Easy access to the flare pipe connection

Installation when left outlet piping is easier by removable under cover of the indoor unit chassis. Installation when center outlet piping is easier by design change of wall hook bracket.



Model: ASEG18KMTE / ASEG24KMTE



Wireless RC



For ASEG18KMTE



For ASEG24KMTE

### Specifications

Model name	Indoor unit		ASEG18KMTE		ASEG24KMTE	
	Outdoor unit		AOEG18KMTA		AOEG24KMTA	
Power Source						
Capacity	Cooling	Rated	kW	5.2	Single phase, ~230 V, 50 Hz	7.1
		Min.-Max.		0.9-6.0		0.9-8.3
	Heating	Rated		6.3		8.0
		Min.-Max.		0.9-8.7		0.9-10.1
Input Power	Cooling/Heating		kW	1.39/1.56	2.08/1.91	
EER	Cooling			3.74	3.41	
COP	Heating			4.04	4.19	
Pdesign	Cooling/Heating (-10°C)		kW	5.2/4.8	7.1/7.1	
SEER	Cooling			7.77	7.30	
SCOP	Heating (Average)			4.60	4.20	
Energy Efficiency Class	Cooling			A++	A++	
	Heating (Average)			A++	A+	
Max. Operating Current	Cooling/Heating		A	9.5/13.5	13.5/16.0	
Annual Energy Consumption	Cooling			234	340	
	Heating			1,460	2,362	
Moisture Removal	I/h			1.7	2.7	
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	dB(A)	45/40/35/29	49/40/35/29	
	Indoor (Heating)	H/M/L/Q		46/40/35/29	49/40/35/29	
Sound Power Level	Outdoor (Cooling/Heating)			50/50	54/52	
	Indoor (Cooling/Heating)	High		60/61	65/65	
Airflow Rate	Outdoor (Cooling/Heating)		m³/h	65/65	67/66	
	Indoor/Outdoor (Cooling)	High		980/2,350	1,170/3,240	
Net Dimensions H x W x D	Indoor		mm	1,020/2,100	1,170/2,820	
	Outdoor			280 × 980 × 240	280 × 980 × 240	
Weight	Indoor		kg	632 × 799 × 290	716 × 820 × 315	
	Outdoor			12.5	12.5	
Connection Pipe Diameter (Liquid/Gas)				36	42	
Drain Hose Diameter (I.D./O.D.)				6.35/12.70	6.35/12.70	
Max. Pipe Length (Pre-Charge)				13.8/15.8 to 16.7	13.8/15.8 to 16.7	
Max. Height Difference				25 (15)	30 (15)	
Operating Range	Cooling		°CDB	-10 to 46	-10 to 46	
	Heating			-15 to 24	-15 to 24	
Refrigerant	Type (Global Warming Potential)			R32 (675)	R32 (675)	
	Charge			1.02 (0.689)	1.32 (0.891)	

### Optional parts



\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Wired Remote Controller (Design type):	UTY-RVRY	External connect kit:	UTY-XWZX5	Network Converter for single split (DC power supply type):	UTY-VTGX
Compact wired remote controller:	UTY-RCRYZ1	Communication kit:	UTY-TWRXZ2	Network Converter for single split (AC power supply type):	UTY-VTGXV
Wired remote controller (touch panel):	UTY-RNRYZ5	External input and output PCB*1:	UTY-XCSXZ2	Silver Ion filter:	UTR-FA16-5
Wired remote controller:	UTY-RLRY	WLAN adapter:	UTY-TFSXF2	External switch controller:	UTY-TERX
Simple remote controller (without operation mode):	UTY-RHRY		UTY-TFSXH3		
Simple remote controller:	UTY-RSRY		FG-AC-WIF1Z1		

\*1 It is required when 2 or more external input and output ports are used.

### Dimensions

(Unit: mm)



## Wall-mounted type

### Standard Range

High-Efficiency & Large Rooms



## Special Cooling

When it is necessary to be constantly cooled such as rooms with a high heat load, it is possible to operate the cooling with keeping performance even when the outside temperature is low.

\*Wired remote controller (UTY-RNRYZ5) is required.

\*Please note that we will not provide compensation for any damages suffered to your appliances or data as a result of using this function.

\*Please use it in low-humidity environments.

Condensation and other problems may be caused when used in high-humidity environments.



## Human sensor


The Human sensor monitors the movements of people in a room and operates the air conditioner at a lower capacity when people leave the room. When people come back to the room, it automatically returns to the previous operating mode.



## Refrigerant cycle monitor (Option)

Wired Remote Controller (Touch Panel) will support to display some sensor values for maintenance and service support.

\*Wired remote controller (UTY-RNRYZ5 or UTY-RVRY) is required.



## Smart device control (Option)

With the optional WLAN adapter installed in the air conditioner, you can control it from anywhere with your smart device.

\* For more information about smart device control, please refer to the page C-020.



Model: ASEH30KMTB / ASEH36KMTB



## Specifications

Model name	Indoor unit		ASEH30KMTB		ASEH36KMTB	
	Outdoor unit		AOEH30KMTB		AOEH36KMTB	
Power Source			Single phase, ~230V, 50Hz			
Capacity	Cooling	Rated	kW	8.0	9.4	2.9-10.0
		Min.-Max.		2.9-9.0		
	Heating	Rated		8.8		10.1
		Min.-Max.		2.2-11.8		2.7-12.6
Input Power	Cooling/Heating		kW	2.33/2.20	3.16/2.73	
EER	Cooling			3.43	2.97	
COP	Heating			4.00	3.70	
Pdesign	Cooling/Heating (-10°C)		kW	8.0/6.5	9.4/7.1	
SEER	Cooling			6.68	6.10	
SCOP	Heating (Average)			4.50	4.50	
Energy Efficiency Class	Cooling			A++	A++	
	Heating (Average)			A+	A+	
Max. Operating Current	Cooling/Heating		A	21.0/21.0	21.5/21.5	
Annual Energy Consumption	Cooling			419	534	
	Heating			1,994	2,189	
Moisture Removal			I/h	2.6	3.8	
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	dB(A)	50/44/40/33	50/44/40/33	
	Indoor (Heating)	H/M/L/Q		49/44/39/33	49/44/39/33	
Sound Power Level	Outdoor (Cooling/Heating)	High		53/55	55/55	
	Indoor (Cooling/Heating)	High		65/65	65/65	
Airflow Rate	Outdoor (Cooling/Heating)	High		68/69	70/70	
	Indoor/Outdoor (Cooling)	High		1,330/3,750	1,330/3,750	
Net Dimensions H x W x D	Indoor	mm		340 × 1,150 × 280	340 × 1,150 × 280	
	Outdoor	mm		788 × 940 × 320	788 × 940 × 320	
Weight	Indoor	kg		18.5	18.5	
	Outdoor	kg		52.0	52.0	
Connection Pipe Diameter (Liquid/Gas)			mm	9.52/15.88	9.52/15.88	
Drain Hose Diameter (I.D./O.D.)				13.8/15.8 to 16.7	13.8/15.8 to 16.7	
Max. Pipe Length (Pre-Charge)			m	50(30)	50(30)	
Max. Height Difference				30	30	
Operating Range	Cooling			-15 to 46	-15 to 46	
	Heating			-15 to 24	-15 to 24	
Refrigerant	Type (Global Warming Potential)			R32(675)	R32(675)	
	Charge	kg (CO <sub>2</sub> eq-T)		1.90(1.283)	1.90(1.283)	

## Optional parts



\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Wired Remote Controller (Design type):	UTY-RVRY	External connect kit:	UTY-XWZK5	Network Convertor for single split (DC power supply type):	UTY-VTGX
Compact wired remote controller:	UTY-RCRYZ1	Communication kit:	UTY-TWRX22	Network Convertor for single split (AC power supply type):	UTY-VTGKV
Wired remote controller (touch panel):	UTY-RNRYZ5	External input and output PCB*1:	UTY-XCSXZ2	Silver Ion Filter:	UTR-FA13-3
Wired remote controller:	UTY-RLRY	WLAN adapter:	UTY-TFSXF2	External switch controller:	UTY-TERX
Simple remote controller (without operation mode):	UTY-RHRY		UTY-TFSXH3		
Simple remote controller:	UTY-RSRY		FG-AC-WIF1Z1		

\*1 It is required when 2 or more external input and output ports are used.

## Dimensions

(Unit: mm)



## Wall-mounted type ECO Range Compact Size



ALL DC



### Slim & stylish square design

The slim and stylish square design of this indoor unit is realized by using a high-density, multipath heat exchanger and a high-efficiency wind blower.

### High energy saving

High-efficiency has been achieved by the lambda-shaped heat exchanger, large cross-flow fan, and the new refrigerant.



### Comfortable airflow & Quiet operation

The large louver and the new air-blowing structure create a comfortable air flow that spreads all the way down to the user's feet with quiet operation.



### Smart device control (option)


With the optional WLAN adapter installed in the air conditioner, you can control it from anywhere with your smart device.

\* For more information about smart device control, please refer to the page C-020.



### Easy access to the flare pipe connection

Installation when left outlet piping is easier by removable under cover of the indoor unit chassis. Installation when center outlet piping is easier by design change of wall hook bracket.



Model: ASEG07KPCE / ASEG09KPCE / ASEG12KPCE



### Specifications

Model name	Indoor unit		ASEG07KPCE	ASEG09KPCE	ASEG12KPCE
	Outdoor unit				
Power Source					Single phase, ~230 V, 50 Hz
Capacity	Cooling	Rated Min.-Max.	kW	2.0	2.5
	Heating	Rated Min.-Max.		0.9-2.8	0.9-3.0
				2.5	2.8
Input Power	Cooling/Heating		kW	0.48/0.63	0.71/0.79
EER	Cooling		W/W	4.17	3.52
COP	Heating			3.97	3.54
Pdesign	Cooling/Heating (-10°C)		kW	2.0/2.2	2.5/2.4
SEER	Cooling		W/W	6.70	6.70
SCOP	Heating (Average)			4.00	4.00
Energy Efficiency Class	Cooling			A++	A++
	Heating (Average)			A+	A+
Max. Operating Current	Cooling/Heating		A	6.5/9.0	6.5/9.0
Annual Energy Consumption	Cooling		kWh/a	104	131
	Heating			769	840
Moisture Removal	I/h			1.0	1.3
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	dB(A)	45/38/31/22	45/38/31/22
	Indoor (Heating)	H/M/L/Q		45/40/36/26	45/40/36/26
Sound Power Level	Outdoor (Cooling/Heating)	High		45/46	47/47
	Indoor (Cooling/Heating)	High		57/58	58/58
Airflow Rate	Outdoor (Cooling/Heating)	High	m³/h	57/58	59/59
	Indoor/Outdoor (Cooling)	High		580/1,650	580/1,650
Net Dimensions H x W x D	Indoor	270 × 784 × 224		270 × 784 × 224	270 × 784 × 224
	Outdoor	541 × 663 × 290		541 × 663 × 290	541 × 663 × 290
Weight	Indoor	kg		8	8
	Outdoor	kg		23	23
Connection Pipe Diameter (Liquid/Gas)		mm		6.35/9.52	6.35/9.52
Drain Hose Diameter (I.D./O.D.)		mm		11.8/15.0 to 16.8	11.8/15.0 to 16.8
Max. Pipe Length (Pre-Charge)		m		20 (15)	20 (15)
Max. Height Difference				15	15
Operating Range	Cooling	°CDB		-10 to 46	-10 to 46
	Heating			-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)
	Charge	kg (CO <sub>2</sub> eq-T)		0.55 (0.371)	0.55 (0.371)



### Optional parts

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

WLAN adapter: UTY-TFSXF2  
UTY-TFSXH3  
Silver Ion Filter: UTR-FA16-5

### Dimensions

(Unit: mm)



## Wall-mounted type ECO Range

Comfort for Large Rooms




ALL DC




### Narrow width & Compact design

Compact and versatile. Powerful airflow is realized despite the 790-mm width compact design for small spaces such as bedrooms or home offices.




### Economy operation

Set temperature automatically increases or decreases by 1°C. The thermostat setting is adjusted automatically according to the room temperature to avoid unnecessary cooling or heating.



### Powerful operation


In powerful operation mode, the compressor operates at maximum speed for 20 minutes to provide a powerful airflow. Rapid cooling and heating makes the room comfortable quickly.



### ON-OFF programmable timer

You can set ON/OFF or OFF/ON times depending on your lifestyle needs.  
(Setting time: 0.5, 1, 1.5, 2, 2.5, ----9.5, 10, 11, 12 hours)

### Low ambient operation



Model: ASEG18KLCA / ASEG24KLCA



Wireless RC



For ASEG18KLCA



For ASEG24KLCA

### Specifications

Model name	Indoor unit		ASEG18KLCA	ASEG24KLCA
	Outdoor unit	AOEG18KLCA		
Power Source				
Capacity	Cooling	Rated Min.-Max.	kW	5.2
	Heating	Rated Min.-Max.		0.9-5.5 6.3 0.6-7.6
				0.9-7.7 8.0 0.9-9.0
Input Power	Cooling/Heating	kW	1.685/1.80	2.42/2.225
EER	Cooling	W/W	3.09	2.93
COP	Heating		3.50	3.60
Pdesign	Cooling/Heating (-10°C)	kW	5.20/4.80	7.10/7.10
SEER	Cooling	W/W	7.20	7.10
SCOP	Heating (Average)		4.30	4.00
Energy Efficiency Class	Cooling		A++	A++
	Heating (Average)		A+	A+
Max. Operating Current	Cooling/Heating	A	9.5/13.5	13.5/17.5
Annual Energy Consumption	Cooling	kWh/a	253	350
	Heating		1563	2485
Moisture Removal		l/h	1.9	3.1
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	47/44/40/35	51/45/38/33
	Indoor (Heating)	H/M/L/Q	50/45/41/37	52/45/41/37
Sound Power Level	Outdoor (Cooling/Heating)	High	50/56	55/57
	Indoor (Cooling/Heating)	High	60/65	64/65
Airflow Rate	Indoor/Outdoor (Cooling)	High	61/66	65/67
	Indoor/Outdoor (Heating)	High	865/1,830	1,040/2,885
Net Dimensions H x W x D	Indoor	mm	995/2,265	1,040/3,030
	Outdoor	mm	293 x 790 x 249	293 x 790 x 249
Weight	Indoor	kg	542 x 799 x 290	632 x 799 x 290
	Outdoor	kg	9.5	10.0
Connection Pipe Diameter (Liquid/Gas)		mm	33	38
			6.35/9.52	6.35/12.70
Drain Hose Diameter (I.D./O.D.)		mm	13.8/15.8 to 16.7	13.8/15.8 to 16.7
			25 (15)	30 (15)
Max. Pipe Length (Pre-Charge)		m	20	25
			-10 to 46	-10 to 46
Max. Height Difference	Cooling	°CDB	-15 to 24	-15 to 24
	Heating		-10 to 46	-10 to 46
Operating Range	Type (Global Warming Potential)		R32 (675)	R32 (675)
	Charge	kg (CO <sub>2</sub> eq-T)	0.85 (0.574)	1.10 (0.743)



### Optional parts

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Silver Ion Filter: UTR-FA16-5

### Dimensions

(Unit: mm)



NEW

## Wall-mounted type

### ECO Range

Cooling-enhanced type



ALL DC



### Highly efficient operation even at high outdoor temperatures

Even when installed in areas with high outdoor air temperatures (Max. 52°C\*), it is comfortable because it can cool the interior well.

\*suction temperature of the outdoor unit

**SEER Rank A++**  
**7.1\***  
\*07 model  
Operation Range MAX 52 °C  
(Cooling operation)



### MINIMAL SMART design

The new smart design eliminates mechanical elements and offers a sophisticated, premium impression. Its compact size, with a width of 770 mm, allows for flexible installation in limited room space.



### Comfortable airflow & Quiet operation

The large louver and the new air-blowing structure create a comfortable air flow that spreads all the way down to the user's feet with quiet operation.




### Smart device control (Option)

With the optional WLAN adapter installed in the air conditioner, you can control it from anywhere with your smart device.

\* For more information about smart device control, please refer to the page C-020.



Model: ASEH07KLTA / ASEH09KLTA / ASEH12KLTA



### Specifications

Model name	Indoor unit		ASEH07KLTA	ASEH09KLTA	ASEH12KLTA
	Outdoor unit				
Power Source					Single phase, -230 V, 50 Hz
Capacity	Cooling	Rated Min.-Max.	kW	2.0	2.5
	Heating	Rated Min.-Max.		0.9-2.8	0.9-3.0
				2.4	2.5
Input Power	Cooling/Heating	kW	W/W	0.9-3.3	0.9-3.5
	Cooling	W/W		0.54 / 0.64	0.76 / 0.67
	Heating	W/W		3.70	3.29
Pdesign	Cooling/Heating (-10°C)	kW	2.0 / 2.2	2.5 / 2.3	3.4 / 2.5
SEER	Cooling	W/W	7.10	6.80	6.70
SCOP	Heating (Average)	W/W	4.10	4.10	4.10
Energy Efficiency Class	Cooling	A++	A++	A++	A++
	Heating (Average)	A+	A+	A+	A+
Max. Operating Current	Cooling/Heating	A	6.0 / 6.0	6.0 / 6.0	7.0 / 7.0
Annual Energy Consumption	Cooling	kWh/a	99	129	178
	Heating	kWh/a	752	786	854
Moisture Removal		l/h	0.18	0.55	1.26
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	41 / 36 / 29 / 21	43 / 36 / 29 / 21	43 / 37 / 30 / 21
	Indoor (Heating)	H/M/L/Q	41 / 37 / 32 / 23	43 / 37 / 32 / 23	43 / 37 / 32 / 23
Sound Power Level	Outdoor (Cooling/Heating)	High	47 / 47	47 / 47	50 / 50
	Indoor (Cooling/Heating)	High	54 / 55	55 / 55	55 / 56
Airflow Rate	Outdoor (Cooling/Heating)	High	56 / 57	58 / 57	60 / 61
	Indoor/Outdoor (Cooling)	High	600 / 1,650	620 / 1,650	620 / 1,700
Net Dimensions H x W x D	Indoor	m³/h	600 / 1,450	620 / 1,450	640 / 1,470
	Outdoor	mm	250 × 770 × 218	250 × 770 × 218	250 × 770 × 218
Weight	Indoor	mm	541 × 663 × 290	541 × 663 × 290	541 × 663 × 290
	Outdoor	kg	7.0	7.0	7.5
Connection Pipe Diameter (Liquid/Gas)		kg	19	19	22
		mm	6.35 / 9.52	6.35 / 9.52	6.35 / 9.52
Drain Hose Diameter (I.D./O.D.)		mm	13.8 / 15 to 16.8	13.8 / 15 to 16.8	13.8 / 15 to 16.8
		m	20 (15)	20 (15)	20 (15)
Max. Pipe Length (Pre-Charge)		m	15	15	15
		°CDB	10 to 52	10 to 52	10 to 52
Max. Height Difference	Cooling		-15 to 24	-15 to 24	-15 to 24
	Heating		-15 to 24	-15 to 24	-15 to 24
Operating Range	Type (Global Warming Potential)	R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge	kg (CO <sub>2</sub> eq-T)	0.53(0.358)	0.53(0.358)	0.60(0.405)



### Optional parts

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

WLAN adapter: UTY-TFSXF  
UTY-TFSXH  
Silver Ion Filter: UTR-FA16-5

### Dimensions

(Unit: mm)



## Compact Cassette

### Compact 4-way Flow Range

Compact Size




ALL DC




### Compact and stylish panel design

The compact and stylish panel fits nicely into a grid-type ceiling. Its linear design is a perfect fit into a grid of 620 mm × 620 mm in the ceiling.



### Easy maintenance

You can access the unit for maintenance simply by removing a ceiling panel next to the grille. As no inspection hole needs to be cut through the ceiling, no additional construction cost is incurred.



The air inlet grille can be installed to open in any direction for easy maintenance.



### Flexible installation

The unit fits nicely into the decor of a grid-type ceiling and can be installed near the lighting or a ventilation opening.



### Link up with a variety of central control system (Option)

Centralized control including facilities and equipment in addition to air conditioning is possible by linking up with MODBUS, KNX interfaces.



Model: AUXG09KVLA / AUXG12KVLA / AUXG14KVLA / AUXG18KVLA / AUXG22KVLA / AUXG24KVLA



For AUXG9/12/14KVLA

For AUXG18/22KVLA

For AUXG24KVLA

### Specifications


Model name	Indoor unit		AUXG09KVLA	AUXG12KVLA	AUXG14KVLA	AUXG18KVLA	AUXG22KVLA	AUXG24KVLA
	Outdoor unit		AOEG09KBTB	AOEG12KBTB	AOEG14KBTB	AOEG18KBTB	AOEG22KBTB	AOEG24KBTB
Power Source								
Capacity	Cooling	Rated	kW	2.5	3.5	4.3	5.2	6.0
		Min.-Max.		0.9-3.2	0.9-4.4	0.9-5.4	0.9-6.7	0.9-8.0
	Heating	Rated	kW	3.2	4.1	5.0	6.0	7.0
		Min.-Max.		0.9-4.7	0.9-5.7	0.9-6.5	0.9-7.5	0.9-9.1
Input Power								
Cooling/Heating		kW	0.55/0.79	0.93/1.08	1.28/1.32	1.60/1.66	1.82/1.87	2.21/2.03
EER	Cooling	W/W	4.57	3.76	3.36	3.25	3.30	3.08
COP	Heating	W/W	4.05	3.80	3.79	3.61	3.74	3.69
Pdesign	Cooling/Heating (-10°C)	kW	2.5/2.6	3.5/3.4	4.3/3.8	5.2/4.4	6.0/4.8	6.8/6.0
SEER	Cooling	W/W	6.70	6.60	6.50	6.60	6.60	6.10
SCOP	Heating (Average)	W/W	4.40	4.30	4.40	4.20	4.30	4.00
Energy Efficiency Class	Cooling		A++	A++	A++	A++	A++	A++
	Heating (Average)		A+	A+	A+	A+	A+	A+
Max. Operating Current		Cooling/Heating	A	7.9/7.9	9.7/9.7	10.2/10.2	12.1/12.1	12.6/12.6
Annual Energy Consumption		Cooling	kWh/a	131	186	231	275	318
		Heating		826	1,106	1,208	1,466	1,562
Moisture Removal		I/h	0.6	1.2	1.5	2.2	2.6	2.7
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	33/31/29/27	37/34/30/27	38/34/30/27	38/34/30/26	44/42/36/30	49/44/36/30
	Indoor (Heating)	H/M/L/Q	34/32/29/27	37/34/31/29	43/38/34/30	43/38/34/30	45/43/40/33	49/45/40/33
Sound Power Level	Outdoor (Cooling/Heating)	High	46/46	47/47	49/49	50/50	51/51	53/54
	Indoor (Cooling/Heating)	High	46/47	49/49	50/55	50/55	56/57	59/61
	Outdoor (Cooling/Heating)	High	59/59	61/61	62/62	63/63	65/66	65/66
Airflow Rate	Indoor/Outdoor (Cooling)	High	540/1,480	600/1,580	680/1,670	680/2,160	830/2,240	930/2,700
	Indoor/Outdoor (Heating)	High	540/1,410	600/1,520	800/1,580	800/1,830	860/1,960	930/2,700
Net Dimensions H x W x D	Indoor	mm	245 × 570 × 570	245 × 570 × 570	245 × 570 × 570	245 × 570 × 570	245 × 570 × 570	245 × 570 × 570
	Outdoor	mm	542 × 799 × 290	542 × 799 × 290	542 × 799 × 290	632 × 799 × 290	632 × 799 × 290	716 × 820 × 315
Weight	Indoor	kg	15	15	15	15	16	16
	Outdoor	kg	32	33	33	36	38	42
Connection Pipe Diameter (Liquid/Gas)		mm	6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.70	6.35/12.70	6.35/12.70
Drain Hose Diameter (I.D./O.D.)		mm	25/32	25/32	25/32	25/32	25/32	25/32
Max. Pipe Length (Pre-Charge)		m	20 (15)	25 (15)	25 (15)	30 (20)	30 (20)	30 (20)
Max. Height Difference			15	20	20	20	25	25
Operating Range	Cooling	°CDB	-15 to 46					
	Heating		-15 to 24					
Refrigerant	Type (Global Warming Potential)		R32 (675)					
	Charge	kg (CO <sub>2</sub> eq-T)	0.85 (0.574)	0.85 (0.574)	0.85 (0.574)	1.02 (0.689)	1.25 (0.844)	1.25 (0.844)
Model name			UTG-UFYF-W	UTG-UFYF-W	UTG-UFYF-W	UTG-UFYF-W	UTG-UFYF-W	UTG-UFYF-W
Cassette Grille		Dimensions (H × W × D)	mm	49 × 620 × 620	49 × 620 × 620	49 × 620 × 620	49 × 620 × 620	49 × 620 × 620
Weight		kg	2.3	2.3	2.3	2.3	2.3	2.3

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Wired Remote Controller (Design type):	UTY-RVRY	Wireless remote controller: UTY-LNTY	Network Convertor for single split (DC power supply type): UTY-VTGX
Compact wired remote controller:	UTY-RCRYZ1	External switch controller: UTY-TERX	Network Convertor for single split (AC power supply type): UTY-VTGXV
Wired remote controller (touch panel):	UTY-RNRYZ5	WLAN adapter: UTY-TFSXZ1	Insulation kit for high humidity: UTY-KXGC
Wired remote controller:	UTY-RRLY	FG-RC-WIFIZ2	External input and output PCB: UTY-XCSX
	UTY-RNNYM	UTY-TFSXJ3	External input and output PCB box: UTY-GXRA
	UTY-RVNYM	FG-AC-WIFIZ1	Silver Ion Filter: UTD-HFAA
Simple remote controller (without operation mode):	UTY-RHRY	Air Outlet Shutter Plate: UTR-YDZB	Fresh air intake kit: UTZ-VXA
Simple remote controller:	UTY-RSRY	Cassette Grille: UTG-UFYF-W	External connect kit: UTY-XWZXG

### Dimensions

(Unit: mm)



## Cassette Circular Flow Range

Comfort for Large Rooms



ALL DC



### Unique circular flow design

The Cassette model realizes a Circular Flow to blow a large airflow in a 360° direction by using a high-performance DC fan motor, turbo fan, and a unique seamless airflow louver design.



Airflows avoid blowing cool air directly at the occupants in the room, providing more comfortable air conditioning.


### Individual louver control

Each louver can be controlled individually with a wired remote controller equipped with a touch panel to provide different directional airflows according to the room layout.

\*Wired remote controller (touch panel) (UTY-RNRGZ3) only

### Compact and lightweight outdoor unit

The outdoor units for the 45,000 BTU and 54,000 BTU models have been completely redesigned. Easier installation is achieved for this compact and lightweight outdoor unit.



### Various cassette grilles

Both black and white grilles are available. Three types of grilles are available: a white grille with a remote controller; a white grille without a remote controller; and a black grille without a remote controller. Select to match the atmosphere and/or usage of the room.



**Model:** AUXG18KRLB / AUXG22KRLB / AUXG24KRLB / AUXG30KRLB / AUXG36KRLB / AUXG45KRLB / AUXG54KRLB  
AUXG36KRLB [3-phase] / AUXG45KRLB [3-phase] / AUXG54KRLB [3-phase]



### Specifications

Model name	Indoor unit		A0EG18KBTB	A0EG22KBTB	A0EG24KBTB	A0EG30KBTB	A0EG36KBTB	A0EG45KBTB	A0EG54KBTB	Outdoor unit			
	Cooling	Rated Min.-Max.								kW	5.2 0.9-5.9	6.0 0.9-6.7	6.8 0.9-8.0
Capacity	Heating	Rated Min.-Max.								6.0 0.9-7.5	7.0 0.9-8.0	7.5 0.9-9.1	10.0 2.7-11.2
Input Power	Cooling/Heating									kW	1.36/1.58	1.71/1.82	1.89/1.90
EER	Cooling									W/W	3.82	3.51	3.60
COP	Heating										3.80	3.85	3.95
Pdesign	Cooling/Heating (-10°C)									kW	5.2/4.4	6.0/4.8	6.8/6.0
SEER	Cooling										7.00	7.00	6.60
SCOP	Heating (Average)										4.30	4.40	4.20
Energy Efficiency Class	Cooling										A++	A++	A++
	Heating (Average)										A+	A+	A+
Max. Operating Current	Cooling/Heating									A	12.1/12.1	12.6/12.6	13.6/13.6
Annual Energy Consumption	Cooling										260	300	360
	Heating										1,431	1,527	1,999
Moisture Removal										I/h	1.5	2.2	2.7
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q									33/32/31/28	33/32/31/28	40/38/36/33
	Indoor (Heating)	H/M/L/Q									33/32/31/28	33/32/31/28	40/38/36/33
	Outdoor (Cooling/Heating)	High									50/50	51/51	53/54
Sound Power Level	Indoor (Cooling/Heating)	High									47/47	49/49	54/54
	Outdoor (Cooling/Heating)	High									62/62	63/63	65/66
Airflow Rate	Indoor/Outdoor (Cooling)	High								m³/h	1,050/2,160	1,050/2,400	1,150/2,700
	Indoor/Outdoor (Heating)	High									1,050/1,830	1,050/1,960	1,150/2,700
Net Dimensions H x W x D	Indoor	mm								mm	246 × 840 × 840	246 × 840 × 840	246 × 840 × 840
	Outdoor	mm									632 × 799 × 290	632 × 799 × 290	716 × 820 × 315
Weight	Indoor	kg								kg	23	23	24
	Outdoor	kg									36	38	42
Connection Pipe Diameter (Liquid/Gas)		mm									6.35/12.70	6.35/12.70	9.52/15.88
Drain Hose Diameter (I.D./O.D.)		mm									25/32	25/32	25/32
Max. Pipe Length (Pre-Charge)		m									30 (20)	30 (20)	50 (30)
Max. Height Difference											20	25	25
Operating Range	Cooling	°CDB									-15 to 46	-15 to 46	-15 to 46
	Heating										-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)										R32 (675)	R32 (675)	R32 (675)
	Charge	kg (CO2eq-T)									1.02 (0.689)	1.25 (0.844)	1.90 (1.283)
Cassette Grille	Variation												UTG-UKYA-W: White wired remote controller (touch panel) UTG-UKYC-W: White/UTG-UKYA-B*: Black
	Dimensions (H × W × D)	mm									53 × 950 × 950	53 × 950 × 950	53 × 950 × 950
	Weight	kg									6.0	6.0	6.0

\*1: IR Receiver kit and Human sensor kit cannot be connected.  
UTG-UKYA-W: White wired remote controller (touch panel)  
UTG-UKYC-W: White/UTG-UKYA-B\*: Black

UTG-UKYC-W: White/UTG-UKYA-B\*: Black


### Optional parts

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Wired Remote Controller (Design type):	UTY-RVRY	WLAN adapter:	UTY-TFSX1	Cassette Grille:	UTG-UKYA-B
Compact wired remote controller:	UTY-RCRYZ1	FG-RC-WIF1Z2		UTG-UKYA-W	UTG-UKYA-W
Wired remote controller (touch panel):	UTY-RNRYZ5	UTY-TFSX3		UTG-UKYC-W	UTG-UKYC-W
Wired remote controller:	UTY-RLRY	FG-AC-WIF1Z1		Network Converter for single split (DC power supply type):	UTY-VTGX
	UTY-RNNYM	UTY-XCSX		Network Converter for single split (AC power supply type):	UTY-VTGKV
	UTY-RVNYM	UTY-XVRA		Silver Ion Filter:	UTD-HFRA
Simple remote controller (without operation mode):	UTY-RHRY	UTZ-KXRA		External connect kit:	UTY-XWZXZG
Simple remote controller:	UTY-RSRY	UTZ-VXRA		(Outdoor unit 30/36/45/54)	
Human sensor kit:	UTY-SHZXC	UTZ-AKXA-W		External connect kit:	UTY-XWZXZ3
External switch controller:	UTY-TERX	UTG-BKXA-W			
IR receiver unit	UTY-LBTYC	UTR-YDZK		Air Outlet Shutter Plate:	

### Dimensions

(Unit: mm)




	AUXG 18/22/24KRLB	AUXG 30/36/45/54KRLB
a	256	298
b	56	98

## Slim Duct

Slim Design



ALL DC



### Slim design

The slim design fits nicely into narrow spaces under the ceiling.  
Drain hose as standard accessory



### Compact and lightweight outdoor unit

The compact and lightweight outdoor unit offers greater flexibility in the choice of installation location. This makes it easier to use this outdoor unit.



Static pressure range  
0 to 90 Pa

### Wide range of static pressures

The use of a DC fan motor makes it possible to adjust the static pressure between 0 and 90 Pa.

The static pressure range can be changed by a remote controller.

### Auto louver grille kit (Option)

The optional clean-looking flat Auto louver blends into any interior and provides a comfortable airflow.



### Link up with a variety of central control system (Option)

Centralized control including facilities and equipment in addition to air conditioning is possible by linking up with MODBUS, KNX interfaces.



Model: ARXG09KLLAP / ARXG12KLLAP / ARXG14KLLAP / ARXG18KLLAP



ARXG09/12/14KLLAP

ARXG18KLLAP



For ARXG09/12/14KLLAP



For ARXG18KLLAP

### Specifications

Model name	Indoor unit		ARXG09KLLAP	ARXG12KLLAP	ARXG14KLLAP	ARXG18KLLAP
	Outdoor unit		AOEG09KBTB	AOEG12KBTB	AOEG14KBTB	AOEG18KBTB
Power Source					Single phase, ~230 V, 50 Hz	
Capacity	Cooling	Rated Min.-Max.	2.5	3.5	4.3	5.2
	Heating	Rated Min.-Max.	0.9-3.2	0.9-4.4	0.9-5.4	0.9-5.9
		kW	3.2	4.1	5.0	6.0
			0.9-4.7	0.9-5.7	0.9-6.5	0.9-7.5
Input Power	Cooling/Heating	kW	0.60/0.79	0.93/1.08	1.28/1.32	1.55/1.62
EER	Cooling	W/W	4.17	3.76	3.36	3.35
COP	Heating		4.05	3.80	3.79	3.70
Pdesign	Cooling/Heating (-10°C)	kW	2.5/2.6	3.5/3.4	4.3/3.8	5.2/4.4
SEER	Cooling	W/W	6.20	6.10	5.80	6.20
SCOP	Heating		4.30	4.00	3.90	4.10
Energy Efficiency Class	Cooling		A++	A++	A+	A++
	Heating		A+	A+	A	A+
Max. Operating Current	Cooling/Heating	A	7.9/7.9	9.7/9.7	10.2/10.2	12.1/12.1
Annual Energy Consumption	Cooling	kWh/a	141	201	259	293
	Heating		845	1,189	1,362	1,501
Moisture Removal		l/h	0.7	1.3	1.5	2.0
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	28/27/26/25	29/28/26/25	32/30/28/26	32/30/29/27
	Indoor (Heating)	H/M/L/Q	28/26/25/24	29/28/26/24	32/30/28/25	32/30/29/27
	Outdoor (Cooling/Heating)	High	46/46	47/47	49/49	50/50
Sound Power Level	Indoor (Cooling/Heating)	High	57/57	58/58	60/60	58/58
	Outdoor (Cooling/Heating)	High	59/59	61/61	62/62	62/62
Airflow Rate	Indoor/Outdoor (Cooling)	High	600/1,480	650/1,580	800/1,670	940/2,160
	Indoor/Outdoor (Heating)	High	600/1,410	650/1,520	800/1,580	940/1,830
Static pressure range (Standard)		Pa	0 to 90 (25)	0 to 90 (25)	0 to 90 (25)	0 to 90 (25)
Net Dimensions	Indoor	mm	198 x 700 x 620	198 x 700 x 620	198 x 700 x 620	198 x 900 x 620
	Outdoor	mm	542 x 799 x 290	542 x 799 x 290	542 x 799 x 290	632 x 799 x 290
Weight	Indoor	kg	17	17	17	20
	Outdoor	kg	32	33	33	36
Connection Pipe Diameter (Liquid/Gas)		mm	6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.70
Drain Hose Diameter (I.D./O.D.)		mm	25/32	25/32	25/32	25/32
Max. Pipe Length (Pre-Charge)		m	20 (15)	25 (15)	25 (15)	30 (20)
Max. Height Difference			15	20	20	20
Operating Range	Cooling	°CDB	-15 to 46	-15 to 46	-15 to 46	-15 to 46
	Heating		-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge	kg (CO <sub>2</sub> eq-T)	0.85 (0.574)	0.85 (0.574)	0.85 (0.574)	1.02 (0.689)


### Optional parts

Wired Remote Controller (Design type):	UTY-RVRY	WLAN adapter:	UTY-TFSXZ1	Network Convertor for single split (DC power supply type):	UTY-VTGX
Compact wired remote controller:	UTY-RCRYZ1	FG-RC-WIFIZ2	FG-RC-WIFIZ2	Network Convertor for single split (AC power supply type):	UTY-VGXV
Wired remote controller (touch panel):	UTY-RNRYZ5	UTY-TFSXJ3	UTY-TFSXJ3	External connect kit:	UTY-XWZXG
Wired remote controller:	UTY-RRLY	FG-AC-WIFIZ1	FG-AC-WIFIZ1	External connect kit:	UTY-XSZXZ1
	UTY-RNNYM	UTD-HFTA (09-14)	UTD-HFTA (09-14)	Remote sensor unit:	UTD-GXTA-W (09-14)
	UTY-RVNYM	UTD-HFTB (18)	UTD-HFTB (18)	Auto Louver Grille Kit:	UTD-GXTB-W (18)
Simple remote controller (without operation mode):	UTY-RHRY	External switch controller: UTY-TERX	External switch controller: UTY-TERX		
	UTY-RSRY	IR receiver unit: UTY-LBTYM	IR receiver unit: UTY-LBTYM		


\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

### Dimensions

(Unit: mm)



ARXG 09 / 12 / 14KLLAP	ARXG18KLLAP
a = 574	774
b = P200x2=400	P200x3=600
c = 734	934
d = 700	900
e = 650	850
f = P100x6=600	P100x8=800



\*The design of the service access depends on the installation method. Refer to the installation manual for more information.

## Medium Static Pressure Duct

High-Efficiency & Comfort




ALL DC



### Slim & Compact design

The new product has reduced the height to 240 mm, making it more compact. The slim design fits nicely into narrow spaces under the ceiling.



### High energy saving

The new model has achieved high energy efficiency rank with a compact design.

Rank  
Cooling  
**A++**  
Heating  
**A+**

SEER  
**6.50**<sup>\*1</sup>

SCOP  
**4.20**<sup>\*2</sup>

\*1: 12/22 models

\*2: 12/22/24 models

### Easy maintenance

The indoor units have large panels on both sides providing easy maintenance in narrow spaces.



### Drain hose as standard

A drain hose is a standard accessory, making it easy to design drainage even in narrow spaces under the ceiling.



### Wide range of static pressures

Static pressures can be changed in the range of 30 to 150 Pa.

Static pressure range  
**30 to 150 Pa**

Model: ARXH12KMTAP / ARXH14KMTAP / ARXH18KMTAP / ARXH22KMTAP / ARXH24KMTAP



ARXH12/14/18KMTAP



ARXH22/24KMTAP



For ARXH12/14KMTAP



For ARXH18/22KMTAP



For ARXH24KMTAP

### Specifications

Model name	Indoor unit		ARXH12KMTAP	ARXH14KMTAP	ARXH18KMTAP	ARXH22KMTAP	ARXH24KMTAP
	Outdoor unit		AOEG12KBTB	AOEG14KBTB	AOEG18KBTB	AOEG22KBTB	AOEG24KBTB
Power Source							
Capacity	Cooling	Rated	kW	3.5	4.3	5.2	6.0
		Min.-Max.		0.9-4.4	0.9-5.4	0.9-5.9	0.9-6.7
	Heating	Rated	kW	4.1	5.0	6.0	7.0
		Min.-Max.		0.9-5.7	0.9-6.5	0.9-7.5	0.9-8.0
Input Power							
Cooling/Heating		kW	0.930 / 1.080	1.260 / 1.320	1.580 / 1.740	1.67 / 1.84	1.89 / 1.87
EER		W/W	3.76	3.40	3.30	3.60	3.60
COP		W/W	3.80	3.79	3.45	3.80	4.01
Pdesign		kW	3.5 / 3.4	4.3 / 3.8	5.2 / 4.4	6.0 / 4.8	6.8 / 6.0
SEER		W/W	6.50	6.10	6.20	6.50	6.40
SCOP		W/W	4.20	4.00	4.10	4.20	4.20
Energy Efficiency Class							
Cooling			A++	A++	A++	A++	A++
Heating (Average)			A+	A+	A+	A+	A+
Max. Operating Current		A	9.7 / 9.7	10.2 / 10.2	12.1 / 12.1	12.6 / 12.6	13.6 / 13.6
Annual Energy Consumption		kWh/a	196	255	301	331	380
Moisture Removal		I/h	1,133	1,330	1,501	1,598	1,999
Sound Pressure Level							
Indoor (Cooling)		H/M/L/Q	29 / 27 / 25 / 23	32 / 29 / 27 / 25	33 / 30 / 28 / 26	32 / 28 / 25 / 24	34 / 30 / 28 / 26
Indoor (Heating)		H/M/L/Q	29 / 27 / 25 / 23	32 / 29 / 27 / 25	33 / 30 / 28 / 26	32 / 28 / 25 / 24	34 / 30 / 28 / 26
Outdoor (Cooling/Heating)		High	47 / 47	49 / 49	50 / 50	51 / 51	53 / 54
Indoor (Cooling/Heating)		High	58 / 58	59 / 59	60 / 60	58 / 58	60 / 60
Outdoor (Cooling/Heating)		High	61 / 61	62 / 62	62 / 62	63 / 63	65 / 66
Airflow Rate		m³/h	650 / 1,580	800 / 1,670	840 / 2,160	1,150 / 2,240	1,230 / 2,700
Indoor/Outdoor (Cooling)		m³/h	650 / 1,520	800 / 1,580	840 / 1,830	1,150 / 1,960	1,230 / 2,700
Indoor/Outdoor (Heating)		m³/h	Pa	30 to 150 (40)	30 to 150 (40)	30 to 150 (40)	30 to 150 (50)
Static pressure range (Standard)		Pa	30 to 150 (40)	30 to 150 (50)			
Net Dimensions		mm	240 × 700 × 700	240 × 700 × 700	240 × 700 × 700	240 × 1,000 × 700	240 × 1,000 × 700
H × W × D		mm	542 × 799 × 290	542 × 799 × 290	632 × 799 × 290	632 × 799 × 290	716 × 820 × 315
Weight		kg	24	24	24	31	31
Indoor		kg	33	33	36	38	42
Outdoor		kg	24	24	24	31	31
Connection Pipe Diameter (Liquid/Gas)							
Indoor		mm	6.35 / 9.52	6.35 / 9.52	6.35 / 12.7	6.35 / 12.70	6.35 / 12.70
Outdoor		mm	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32
Max. Pipe Length (Pre-Charge)							
m		m	25 (15)	25 (15)	30 (20)	30 (20)	30 (20)
Max. Height Difference							
m		m	20	20	20	25	25
Operating Range		°CDB	-15 to 46				
Cooling			-15 to 24				
Heating			-15 to 24				
Refrigerant		Type (Global Warming Potential)	R32 (675)				
Charge		kg (CO <sub>2</sub> eq-t)	0.85 (0.574)	0.85 (0.574)	1.02 (0.689)	1.25 (0.844)	1.25 (0.844)


### Optional parts

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Wired Remote Controller (design type):	UTY-RVRY	Silver ion filter:	UTD-HFNC (12/14/18)	External input and output PCB:	UTY-XCSX
Compact wired remote controller:	UTY-RCRYZ1	Long-life filter:	UTD-LFDC (12/14/18)	External input and output PCB bracket:	UTZ-GXA
Wired remote controller (touch panel):	UTY-RNRYZ5	MODBUS converter:	UTY-VMSX	Network Convertor for single split (DC power supply type):	UTY-VTGX
Wired remote controller:	UTY-RLRY	KNX converter:	UTY-VKSX	Network Convertor for single split (AC power supply type):	UTY-VGXV
Simple remote controller (without operation mode):	UTY-RHRY	WLAN adapter:	UTY-TFSXZ1	External connect kit:	UTY-WXZXG
Simple remote controller:	UTY-RSRY		UTY-TFSXJ3	IR receiver unit:	UTY-LBTM
Remote sensor unit:	UTY-XSZX			External switch controller:	UTY-TERX
	UTY-XSZXZ1				

### Dimensions

(Unit: mm)



## Medium Static Pressure Duct

High-Efficiency & Comfort



ALL DC



### Slim & Compact design

The new product has reduced the height to 240 mm, making it more compact. The slim design fits nicely into narrow spaces under the ceiling.



### High energy saving

The new model has achieved high energy efficiency rank with a compact design.



SEER

6.23<sup>\*1</sup>

SCOP

4.10<sup>\*2</sup><sup>\*1: 30 model</sup><sup>\*2: 36 model</sup>

### Easy maintenance

The indoor units have large panels on both sides providing easy maintenance in narrow spaces.



### Drain hose as standard

A drain hose is a standard accessory, making it easy to design drainage even in narrow spaces under the ceiling.



### Wide range of static pressures

Static pressures can be changed in the range of 30 to 150 Pa.

Static pressure range  
**30 to 150 Pa**

**Model: ARXH30KMTAP / ARXH36KMTAP / ARXH45KMTAP / ARXH54KMTAP**  
**ARXH36KMTAP [3-phase] / ARXH45KMTAP [3-phase] / ARXH54KMTAP [3-phase]**



ARXH30/36/45/54KMTAP



For ARXH30/36KMTAP



For ARXH45/54KMTAP

### Specifications


Model name	Indoor unit		ARXH30KMTAP	ARXH36KMTAP	ARXH45KMTAP	ARXH36KMTAP	ARXH45KMTAP	ARXH54KMTAP
	Outdoor unit		AOEG30KBTB	AOEG36KBTB	AOEG45KBTB	AOEG36KRTA	AOEG45KRTA	AOEG54KRTA
Power Source								Single phase, ~230 V, 50 Hz
Capacity	Cooling	Rated	8.5	9.5	12.1	9.5	12.1	13.4
		Min.-Max.	2.8-10.0	2.8-11.2	4.0-13.5	2.8-11.2	4.0-13.5	4.5-14.5
	Heating	Rated	10.0	10.8	13.5	10.8	13.5	15.5
		Min.-Max.	2.7-11.2	2.7-12.7	4.2-16.2	2.7-12.7	4.2-16.2	4.7-16.5
Input Power								3-phase, ~400 V, 50 Hz
EER								3.87 / 2.70
COP								3.20
Pdesign								3.62
SEER								4.00
SCOP								3.62
Energy Efficiency Class								3.33
Max. Operating Current								-
Annual Energy Consumption								-
Moisture Removal								-
Sound Pressure Level								-
Sound Power Level								-
Airflow Rate								-
Static pressure range (Standard)								-
Net Dimensions								-
Weight								-
Connection Pipe Diameter (Liquid/Gas)								-
Drain Hose Diameter (I.D./O.D.)								-
Max. Pipe Length (Pre-Charge)								-
Max. Height Difference								-
Operating Range								-
Refrigerant								-

### Optional parts

Wired Remote Controller (Design type):	UTY-RVRY	IR receiver unit:	UTY-LBTYM	External input and output PCB:	UTY-XCSX
Compact wired remote controller:	UTY-RCRYZ1	Silver ion filter:	UTD-HFNA	External input and output PCB bracket:	UTZ-GXDA
Wired remote controller (touch panel):	UTY-RNRYZ5	Long-life filter:	UTD-LFDA	Network Convertor for single split (DC power supply type):	UTY-VTGX
Wired remote controller:	UTY-RLRY	MODBUS converter:	UTY-VMSX	Network Convertor for single split (AC power supply type):	UTY-VTGKV
Simple remote controller (without operation mode):	UTY-RHRY	KNX converter:	UTY-VKSX	External connect kit:	UTY-XWZXZG
Simple remote controller:	UTY-RSRY	WLAN adapter:	UTY-TFSXZ1	(Outdoor unit)	
Remote sensor unit:	UTY-XSZX	UTY-TFSXJ3	External switch controller: UTY-TERX	External connect kit:	UTY-XWZXZ3
	UTY-XSZXZ1				

### Dimensions

(Unit: mm)



\*The design of the service access depends on the installation method. Refer to the installation manual for more information.

## Medium Static Pressure Duct

Compact Size




ALL DC



### High-efficiency & Quiet operation

The combination of the V-shaped heat exchanger, air stabilizer, and the high-efficiency DC fan motor enable high-efficiency and quiet operation.



### Small, lightweight outdoor unit


The outdoor unit in this series is smaller and lighter than previous-generation outdoor units. It can be installed in a narrow space.



### Automatic airflow adjustment function

This unique and innovative function detects required air flow in each application case and automatically adjust the volume.

Automatically adjust !



### Link up with a variety of central control system (Option)

Centralized control including facilities and equipment in addition to air conditioning is possible by linking up with MODBUS, KNX interfaces.



Model: ARXG12KHTAP / ARXG14KHTAP / ARXG18KHTAP / ARXG22KHTAP / ARXG24KHTAP / ARXG30KHTAP



ARXG18/22/24/30KHTAP



### Specifications


Model name	Indoor unit		ARXG12KHTAP	ARXG14KHTAP	ARXG18KHTAP	ARXG22KHTAP	ARXG24KHTAP	ARXG30KHTAP
	Outdoor unit		AOEG12KBTB	AOEG14KBTB	AOEG18KBTB	AOEG22KBTB	AOEG24KBTB	AOEG30KBTB
Power Source								
Capacity	Cooling	Rated	3.5	4.3	5.2	6.0	6.8	8.5
		Min.-Max.	0.9-4.4	0.9-5.4	0.9-5.9	0.9-6.7	0.9-8.0	2.8-10.0
	Heating	Rated	4.1	5.0	6.0	7.0	7.5	10.0
Input Power	Cooling/Heating	kW	0.87/1.00	1.17/1.25	1.36/1.56	1.71/1.81	1.89/1.85	2.65/2.63
	Cooling	W/W	4.02	3.68	3.82	3.51	3.60	3.21
	Heating	W/W	4.10	4.00	3.85	3.87	4.06	3.80
Pdesign	Cooling/Heating (-10°C)	kW	3.5/3.4	4.3/3.8	5.2/4.4	6.0/4.8	6.8/6.0	8.5/8.0
	Cooling	W/W	6.30	6.20	6.50	6.50	6.50	6.23
	Heating (Average)	W/W	4.10	4.00	4.10	4.20	4.10	4.00
Energy Efficiency Class	Cooling	A++	A++	A++	A++	A++	A++	A++
	Heating (Average)	A+	A+	A+	A+	A+	A+	A+
	Max. Operating Current	A	9.7/9.7	10.2/10.2	12.1/12.1	12.6/12.6	13.6/13.6	22.6/22.6
Annual Energy Consumption	Cooling	kWh/a	194	243	280	323	366	477
	Heating	kWh/a	1,159	1,328	1,501	1,597	2,048	2,796
	Moisture Removal	I/h	0.7	0.9	1.2	1.5	1.8	2.3
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	32/27/26/24	33/28/27/25	28/25/22/20	28/25/22/20	32/28/24/21	36/33/30/29
	Indoor (Heating)	H/M/L/Q	32/27/26/24	33/28/27/25	28/25/22/20	28/25/22/20	32/28/24/21	36/33/30/29
	Outdoor (Cooling/Heating)	High	47/47	49/49	50/50	51/51	53/54	53/55
Sound Power Level	Indoor (Cooling/Heating)	High	57/58	59/60	54/54	57/57	63/65	63/65
	Outdoor (Cooling/Heating)	High	61/61	62/62	62/62	63/63	65/66	68/69
	Airflow Rate	m³/h	850/1,580	950/1,670	1,050/2,160	1,050/2,240	1,360/2,700	1,700/3,750
Airflow Rate	Indoor/Outdoor (Cooling)	m³/h	850/1,520	950/1,580	1,050/1,830	1,050/1,960	1,360/2,700	1,700/3,750
	Indoor/Outdoor (Heating)	m³/h	Pa	30 to 200 (35)	30 to 200 (35)	30 to 200 (35)	30 to 200 (35)	30 to 200 (47)
	Static pressure range (Standard)	Pa	mm	300 × 700 × 700	300 × 700 × 700	300 × 1,000 × 700	300 × 1,000 × 700	300 × 1,000 × 700
Net Dimensions	Indoor	mm	542 × 799 × 290	542 × 799 × 290	632 × 799 × 290	632 × 799 × 290	716 × 820 × 315	788 × 940 × 320
	Outdoor	mm	542 × 799 × 290	542 × 799 × 290	632 × 799 × 290	632 × 799 × 290	716 × 820 × 315	788 × 940 × 320
	Weight	kg	27	27	35	35	36	36
Connection Pipe Diameter (Liquid/Gas)	Indoor	mm	6.35/9.52	6.35/9.52	6.35/12.70	6.35/12.70	6.35/12.70	9.52/15.88
	Outdoor	mm	25/32	25/32	25/32	25/32	25/32	25/32
	Max. Pipe Length (Pre-Charge)	m	25 (15)	25 (15)	30 (20)	30 (20)	30 (20)	50 (30)
Max. Height Difference		m	20	20	20	25	25	30
	Operating Range	°CDB	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46
	Heating	°CDB	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge	kg (CO <sub>2</sub> eq-t)	0.85 (0.574)	0.85 (0.574)	1.02 (0.689)	1.25 (0.844)	1.90 (1.283)	

### Optional parts

Wired Remote Controller (Design type):	UTY-RVRY	Long-life filter: UTD-LFNB (18-30)	External input and output PCB: UTY-XCSX
Compact wired remote controller:	UTY-RCRYZ1	UTD-LFNC (12-14)	External connect kit: UTY-XWZXZG
Wired remote controller (touch panel):	UTY-RNRYZ5	Silver Ion Filter: UTD-HFNB (18-30)	External input and output PCB bracket: UTY-GXNA
Wired remote controller:	UTY-RLRY	UTD-HFNC (12/14)	Network Convertor for single split (DC power supply type): UTY-VTGX
	UTY-RNNYM	WLAN adapter: UTY-TFSXZ1	Network Convertor for single split (AC power supply type): UTY-VTGV
	UTY-RVNYM	FG-RC-WIFIZ2	External switch controller: UTY-TERX
Simple remote controller (without operation mode):	UTY-RHRY	UTY-TFSXJ3	
Simple remote controller:	UTY-RSRY	FG-AC-WIFIZ1	
Remote sensor unit:	UTY-XSZZ1	IR receiver unit: UTY-LBTYM	External connect kit: UTY-XWZXZ3


### Dimensions

(Unit: mm)



ARXG 12 / 14 KHTAP	ARXG 18 / 22 / 24 / 30 KHTAP
a 650	895
b P100×5=500	P100×8=800
c 740	1,040
d 700	1,000
e 462	762
f P100×4=400	P100×7=700

\*The design of the service access depends on the installation method. Refer to the installation manual for more information.



## Medium Static Pressure Duct

Compact Size




ALL DC




### High-efficiency & Quiet operation

The combination of the V-shaped heat exchanger, air stabilizer, and the high-efficiency DC fan motor enable high-efficiency and quiet operation.



### Small, lightweight outdoor unit


The outdoor unit in this series is smaller and lighter than previous-generation outdoor units. It can be installed in a narrow space.



### Automatic airflow adjustment function

This unique and innovative function detects required air flow in each application case and automatically adjust the volume.

Automatically adjust !



It was necessary to calculate

### Link up with a variety of central control system (Option)

Centralized control including facilities and equipment in addition to air conditioning is possible by linking up with MODBUS, KNX interfaces.



**Model:** ARXG36KHTAP / ARXG45KHTAP / ARXG54KHTAP  
ARXG36KHTAP [3-phase] / ARXG45KHTAP [3-phase] / ARXG54KHTAP [3-phase]



ARXG36/45/54KHTAP



For ARXG36KHTAP



For ARXG45/54KHTAP

### Specifications


Model name	Indoor unit		ARXG36KHTAP	ARXG45KHTAP	ARXG54KHTAP	ARXG36KHTAP	ARXG45KHTAP	ARXG54KHTAP
	Outdoor unit		AOEG36KBTB	AOEG45KBTB	AOEG54KBTB	AOEG36KRTA	AOEG45KRTA	AOEG54KRTA
Power Source								Single phase, ~230 V, 50 Hz
Capacity	Cooling	Rated	9.5	12.1	13.4	9.5	12.1	13.4
		Min.-Max.	2.8-11.2	4.0-14.0	4.5-14.5	2.8-11.2	4.0-14.0	4.5-14.5
	Heating	Rated	10.8	13.5	15.5	10.8	13.5	15.5
		Min.-Max.	2.7-12.7	4.2-16.2	4.7-16.5	2.7-12.7	4.2-16.2	4.7-16.5
Input Power								kW
EER								Cooling/Heating
COP								Cooling/Heating
Pdesign								Cooling/Heating (-10°C)
SEER								Cooling
SCOP								Heating (Average)
Energy Efficiency Class								Cooling
								Heating (Average)
Max. Operating Current								A
Annual Energy Consumption								Cooling
								Heating
Moisture Removal								i/h
Sound Pressure Level								Indoor (Cooling) H/M/L/Q
								Indoor (Heating) H/M/L/Q
								Outdoor (Cooling/Heating) High
Sound Power Level								Indoor (Cooling/Heating) High
								Outdoor (Cooling/Heating) High
Airflow Rate								m³/h
Static pressure range (Standard)								Pa
Net Dimensions								30 to 200 (47)
								30 to 200 (60)
H x W x D								300 x 1,400 x 700
								300 x 1,400 x 700
Weight								kg
								Indoor
								46
								Outdoor
Connection Pipe Diameter (Liquid/Gas)								mm
								9.5/215.88
Drain Hose Diameter (I.D./O.D.)								25/32
Max. Pipe Length (Pre-Charge)								m
Max. Height Difference								50 (30)
Operating Range								°CDB
								Cooling
								-15 to 46
								Heating
Refrigerant								Type (Global Warming Potential)
								R32 (675)
								Charge kg (CO <sub>2</sub> eq-t)
								1.90 (1.283)
								2.70 (1.823)
								1.90 (1.283)
								2.70 (1.823)

### Optional parts

Wired Remote Controller (Design type):	UTY-RVRY	Long-life filter:	UTD-LFNA	External input and output PCB:	UTY-XCSX
Compact wired remote controller:	UTY-RCRYZ1	Silver Ion Filter:	UTD-HFNA	External input and output PCB bracket:	UTZ-GXNA
Wired remote controller (touch panel):	UTY-RNRYZ5	UTY-TFSXZ1	FG-RC-WIFIZ2	Network Convertor for single split (DC power supply type):	UTY-VTGX
Wired remote controller:	UTY-RRLY	UTY-RNRYM	FG-RC-WIFIZ3	Network Convertor for single split (AC power supply type):	UTY-VTGXF
		UTY-RVNYM	FG-AC-WIFIZ1	(Outdoor unit 36/45/54)	UTY-XWZXZ3
Simple remote controller (without operation mode):	UTY-RHRY	UTY-RSRY	UTY-TERX	External connect kit:	UTY-XWZXZG
Simple remote controller:			UTY-LBTYM		
Remote sensor unit:		UTY-XSZXZ1	External connect kit:		

### Dimensions

(Unit: mm)



ARXG 36 / 45 / 54 KHTAP
a 1.295
b P100x12=1,200

## Medium Static Pressure Duct Standard




ALL DC



### Easy maintenance

Structural improvement is attained by making the bottom panel in two pieces—front and rear. The internal fan casing is also manufactured in two pieces—upper and lower. As a result, the motor and fan can be easily accessed and maintained by removing the rear panel and the lower casing while leaving the main chassis in place.




See below for case of rear-suction type

### Slim & Compact design


#### Indoor Unit

The slim and compact design of the indoor unit, with the control box mounted on the side, allows installation in narrow spaces.




#### Outdoor Unit

The outdoor units for the 45,000 BTU and 54,000 BTU models have been completely redesigned. Easier installation is achieved for this compact and lightweight outdoor unit.



### Two-direction drain piping



### Link up with a variety of central control system (Option)

Centralized control including facilities and equipment in addition to air conditioning is possible by linking up with MODBUS, KNX interfaces.



Model: ARXG22KMLB / ARXG24KMLA / ARXG30KMLA / ARXG36KMLA / ARXG45KMLA  
ARXG36KMLA [3-phase] / ARXG45KMLA [3-phase]



For ARXG22KMLB

For ARXG24KMLA

For ARXG30/36KMLA

For ARXG45KMLA

### Specifications

Model name	Indoor unit		ARXG22KMLB	ARXG24KMLA	ARXG30KMLA	ARXG36KMLA	ARXG45KMLA	ARXG36KMLA	ARXG45KMLA
	Outdoor unit		AOEG22KBTB	AOEG24KBTB	AOEG30KBTB	AOEG36KBTB	AOEG45KBTB	AOEG36KRTA	AOEG45KRTA
Power Source	Cooling	Rated	6.0	6.8	8.5	9.5	12.1	9.5	12.1
		Min.-Max.	0.9-6.7	0.9-8.0	2.8-10.0	2.8-11.2	4.0-13.0	2.8-11.2	4.0-13.0
	Heating	Rated	7.0	7.5	10.0	10.8	13.5	10.8	13.5
Capacity		Min.-Max.	0.9-8.0	0.9-9.1	2.7-11.2	2.7-12.7	4.2-15.2	2.7-12.7	4.2-15.2
	Cooling/Heating	kW	1.78/1.87	2.14/1.97	2.65/2.63	2.97/2.88	4.22/3.84	2.97/2.88	4.22/3.84
	Cooling	kW	3.37	3.18	3.21	3.20	2.87	3.20	2.87
Input Power	Heating	W/W	3.74	3.80	3.80	3.75	3.52	3.75	3.52
	Cooling/Heating	kW	6.0/4.8	6.8/6.0	8.5/8.0	9.5/8.7	-	9.5/8.7	-
	Cooling	W/W	6.10	6.20	6.23	6.10	-	6.10	-
Pdesign	Heating	W/W	4.10	4.10	4.00	4.00	-	4.00	-
	Cooling/Heating	A++	A++	A++	A++	-	A++	-	A++
	Cooling	A+	A+	A+	A+	-	A+	-	A+
SEER	Heating	A++	A++	A++	A++	-	A++	-	A++
	Cooling/Heating	A+	A+	A+	A+	-	A+	-	A+
	Cooling	A	12.6/12.6	13.6/13.6	22.6/22.6	22.6/22.6	28.5/28.5	10.5/10.5	14.0/14.0
SCOP	Heating	A	344	384	477	545	-	545	-
	Cooling/Heating	kWh/a	1,637	2,045	2,797	3,044	-	3,044	-
	Cooling	kWh/a	1,637	2,045	2,797	3,044	-	3,044	-
Energy Efficiency Class	Heating	I/h	2.1	2.5	2.5	3.0	4.0	3.0	4.0
	Cooling/Heating	Pa	30 to 150 (35)	30 to 150 (35)	30 to 150 (47)	30 to 150 (60)	30-150 (47)	30-150 (60)	30-150 (60)
	Cooling	mm	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700
Max. Operating Current	Heating	dB(A)	31/29/27/25	31/29/27/25	39/35/30/26	42/38/32/28	39/35/30/26	42/38/32/28	42/38/32/28
	Cooling/Heating	mm	31/29/27/25	31/29/27/25	42/35/30/26	42/38/32/28	42/35/30/26	42/38/32/28	42/38/32/28
	Cooling	mm	51/51	53/54	53/55	55/55	57/57	55/55	57/57
Annual Energy Consumption	Heating	m³/h	60/62	60/62	65/69	65/70	68/70	65/70	68/70
	Cooling/Heating	Pa	63/63	65/66	68/69	70/70	71/71	70/70	71/71
	Cooling	mm	1,100/2,240	1,100/2,700	1,900/3,750	2,100/4,450	1,900/3,750	2,100/4,450	2,100/4,450
Moisture Removal	Heating	mm	1,100/1,960	1,100/2,700	2,100/3,750	2,100/4,450	2,100/3,750	2,100/4,450	2,100/4,450
	Cooling/Heating	Pa	30 to 150 (35)	30 to 150 (35)	30 to 150 (47)	30 to 150 (60)	30-150 (47)	30-150 (60)	30-150 (60)
	Cooling	mm	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700
Sound Pressure Level	Heating	mm	31/29/27/25	31/29/27/25	39/35/30/26	42/38/32/28	39/35/30/26	42/38/32/28	42/38/32/28
	Cooling/Heating	mm	31/29/27/25	31/29/27/25	42/35/30/26	42/38/32/28	42/35/30/26	42/38/32/28	42/38/32/28
	Cooling	mm	51/51	53/54	53/55	55/55	57/57	55/55	57/57
Sound Power Level	Heating	m	60/62	60/62	65/69	65/70	68/70	65/70	68/70
	Cooling/Heating	m	63/63	65/66	68/69	70/70	71/71	70/70	71/71
	Cooling	m	1,100/2,240	1,100/2,700	1,900/3,750	2,100/4,450	1,900/3,750	2,100/4,450	2,100/4,450
Airflow Rate	Heating	m³/h	1,100/1,960	1,100/2,700	2,100/3,750	2,100/4,450	2,100/3,750	2,100/4,450	2,100/4,450
	Cooling/Heating	Pa	30 to 150 (35)	30 to 150 (35)	30 to 150 (47)	30 to 150 (60)	30-150 (47)	30-150 (60)	30-150 (60)
	Cooling	mm	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700
Static pressure range (Standard)	Heating	Pa	6.35/12.70	6.35/12.70	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88
	Cooling/Heating	mm	35.7/38.1	35.7/38.1	35.7/38.1	35.7/38.1	35.7/38.1	35.7/38.1	35.7/38.1
	Cooling	m	30 (20)	30 (20)	50 (30)	50 (30)	50 (30)	50 (30)	50 (30)
Net Dimensions	Heating	Pa	30 to 150 (35)	30 to 150 (35)	30 to 150 (47)	30 to 150 (60)	30-150 (47)	30-150 (60)	30-150 (60)
	Cooling/Heating	mm	632 × 799 × 290	716 × 820 × 315	788 × 940 × 320	788 × 940 × 320	998 × 940 × 320	788 × 940 × 320	998 × 940 × 320
	Cooling	mm	35	35	38	38	39	38	39
Weight	Heating	kg	38	42	52	52	67	53	67
	Cooling/Heating	kg	35	35	38	38	39	38	39
	Cooling	kg	35	35	38	38	39	38	39
Connection Pipe Diameter (Liquid/Gas)	Heating	mm							

## High Static Pressure Duct



### Easy installation (Compact & Lightweight)

The indoor and outdoor units are designed to be compact and light by reducing the basic chassis size and the overall material weight.




### Design also suits high static pressure



### Low noise

Slanted corners at the top help reduce turbulent airflow. Low noise is realized by adopting a plastic case and a plastic fan.



### Link up with a variety of central control system (Option)

Centralized control including facilities and equipment in addition to air conditioning is possible by linking up with MODBUS, KNX interfaces.



**Model: ARXG45KHTB / ARXG54KHTB**  
**ARXG45KHTB [3-phase] / ARXG54KHTB [3-phase]**



### Specifications


Model name	Indoor unit		ARXG45KHTB	ARXG54KHTB	ARXG45KHTB	ARXG54KHTB
	Outdoor unit		AOEG45KBTB	AOEG54KBTB	AOEG45KRTA	AOEG54KRTA
Power Source			Single phase, ~230 V, 50 Hz		3-phase, ~400 V, 50 Hz	
Capacity	Cooling	Rated Min.-Max.	12.1	13.4	12.1	13.4
	Heating	Rated Min.-Max.	4.0-14.0	5.0-14.5	4.0-14.0	5.0-14.5
			13.5	15.5	13.5	15.5
Input Power	Cooling/Heating		kW	5.0-16.2	5.5-18.0	5.0-16.2
EER	Cooling			4.16/3.61	4.77/4.18	4.16/3.61
COP	Heating			2.91	2.81	2.91
Pdesign	Cooling/Heating (-10°C)		kW	3.74	3.71	3.74
SEER	Cooling			-	-	-
SCOP	Heating			-	-	-
Energy Efficiency Class	Cooling			-	-	-
	Heating			-	-	-
Max. Operating Current	Cooling/Heating		A	28.5/28.5	28.5/28.5	14.0/14.0
Annual Energy Consumption	Cooling		kWh/a	-	-	-
	Heating			-	-	-
Moisture Removal			l/h	1.5	2.0	1.5
Sound Pressure Level	Indoor (Cooling)	H/M/L		47/43/40	47/43/40	47/43/40
	Indoor (Heating)	H/M/L		47/43/40	47/43/40	47/43/40
Sound Power Level	Outdoor (Cooling/Heating)	High		57/57	57/59	57/57
	Indoor (Cooling/Heating)	High		75/74	75/74	75/74
Airflow Rate	Outdoor (Cooling/Heating)	High		71/71	73/73	71/71
	Indoor/Outdoor (Cooling)	High	m³/h	3,350/4,450	3,350/4,450	3,350/4,450
Static pressure range (Standard)	Indoor/Outdoor (Heating)	High		3,350/4,450	3,350/4,450	3,350/4,450
			Pa	100 to 250 (100)	100 to 250 (100)	100 to 250 (100)
Net Dimensions	Indoor		mm	400 × 1,050 × 500	400 × 1,050 × 500	400 × 1,050 × 500
	Outdoor		mm	998 × 940 × 320	998 × 940 × 320	998 × 940 × 320
Weight	Indoor		kg	46	46	46
	Outdoor		kg	67	67	67
Connection Pipe Diameter (Liquid/Gas)			mm	9.52/15.88	9.52/15.88	9.52/15.88
				23.4/25.4	23.4/25.4	23.4/25.4
Drain port Diameter (I.D./O.D.)			m	50 (30)	50 (30)	50 (30)
Max. Pipe Length (Pre-Charge)				30	30	30
				-15 to 46	-15 to 46	-15 to 46
Max. Height Difference				-15 to 24	-15 to 24	-15 to 24
				-15 to 46	-15 to 46	-15 to 46
Operating Range	Cooling		°CDB	-15 to 46	-15 to 46	-15 to 46
	Heating			-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge	kg (CO <sub>2</sub> eq-T)	2.70 (1.823)	2.70 (1.823)	2.70 (1.823)	2.70 (1.823)

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

Wired Remote Controller (Design type): UTY-RVRY	Remote sensor unit: UTY-XSXZ1	Network Convertor for single split (DC power supply type): UTY-VTGX
Compact wired remote controller: UTY-RCRY1	Long-life filter: UTD-LF60KA	Network Convertor for single split (AC power supply type): UTY-VGKV
Wired remote controller (touch panel): UTY-RNRYZ5	External switch controller: UTY-TERX	Silver Ion Filter: UTD-HFKB
Wired remote controller: UTY-RLRY	WLAN adapter: UTY-TFSX1	External connect kit: UTY-XWZXG
Simple remote controller: UTY-RSRY	UTY-TFSXJ3	(Outdoor unit)
UTY-RHRY	FG-AC-WIF1Z1	External connect kit: UTY-XWZX3
IR Receiver unit: UTY-LBTYM	External input and output PCB: UTY-XCSX+UTZ-GXEA	

### Dimensions

(Unit: mm)



\*The design of the service access depends on the installation method. Refer to the installation manual for more information.

## High Static Pressure Duct




ALL DC



### High energy efficiency

Much greater efficiency is achieved by the use of all-DC inverter technology.

### Design also corresponding to high static pressure




### Easy installation (Compact & Lightweight)

The indoor unit is designed to be compact and light by reducing the basic chassis size and the overall material weight.



### Low noise

Slanted corners at the top help reduce turbulent airflow. Low noise is realized by adopting a plastic case and a plastic fan.



### Link up with a variety of central control system (Option)

Centralized control including facilities and equipment in addition to air conditioning is possible by linking up with MODBUS, KNX interfaces.



Model: ARYG60LHTA [3-phase]



### Specifications

Model name	Indoor unit		Outdoor unit		ARYG60LHTA
	Cooling	Rated Min.-Max.	kW	AOYG60LATT	
Capacity	Heating	Rated Min.-Max.		3-phase, ~400 V, 50 Hz	
Input Power	Cooling/Heating		kW		15.0 6.2-17.5
EER	Cooling				18.0 6.2-20.0
COP	Heating				4.70/5.15 3.19
Max. Operating Current	Cooling/Heating		A		3.50 12.5/12.5
Moisture Removal			I/h		2.0 45/40/36/-
Sound Pressure	Indoor (Cooling)	H/M/L/Q	dB(A)		45/40/36/- 45/40/36/-
	Indoor (Heating)	H/M/L/Q			56/58
Airflow Rate	Outdoor (Cooling/Heating)	High	m³/h		3,550/6,900 3,550/7,300
Static pressure range (Standard)			Pa		60 to 260 (60)
Net Dimensions H x W x D	Indoor		mm		425 x 1,250 x 490
	Outdoor		mm		1,290 x 900 x 330
Weight	Indoor		kg		54 104
Connection Pipe Diameter (Liquid/Gas)					9.52/15.88
Drain Hose Diameter (I.D./O.D.)			mm		23.4/25.4
Max. Pipe Length (Pre-Charge)			m		75 (30) 30
Max. Height Difference					-15 to 46 -15 to 24
Operating Range	Cooling		°CDB		R410A (2,088) 3.45 (7.204)
Refrigerant	Heating				




### Optional parts

Wired remote controller:	UTY-RNNYM	Network Convertor for single split (DC power supply type): UTY-VTGX
Wired remote controller:	UTY-RVNYM	Network Convertor for single split (AC power supply type): UTY-VTGXV
External switch controller:	UTY-TERX	External connect kit: UTD-ECSSA
WLAN adapter:	UTY-TFNXZ1	(Outdoor unit)
	FG-RC-WIFIZ2	External connect kit: UTY-XWZX22
Remote sensor unit:	UTY-XSZZ1	
IR receiver unit:	UTY-LRHYM	


\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.

### Dimensions

(Unit: mm)



\*The design of the service access depends on the installation method. Refer to the installation manual for more information.



## Big Duct




ALL DC




### Splittable, lightweight, and compact design

The indoor unit can be split into a fan unit and a heat exchanger unit to make installation easier.



### Quiet operation


The combination of a V-shaped heat exchanger, an air stabilizer, and a high-efficiency DC fan motor enables this compact unit to operate quietly.



### Automatic airflow adjustment function

The optimum airflow can be set automatically to facilitate faster installation.

Automatically adjust !



It was necessary to calculate

### Link up with a variety of central control system (Option)

Centralized control including facilities and equipment in addition to air conditioning is possible by linking up with MODBUS, KNX interfaces.



Model: ARYG72LHTA / ARYG90LHTA



### Specifications


Model name	Indoor unit		ARYG72LHTA		ARYG90LHTA	
	Outdoor unit		AOYG72LRLA		AOYG90LRLA	
Power Source	Indoor		Single phase, ~230 V, 50 Hz		3-phase, ~400 V, 50 Hz	
Capacity	Cooling	Rated	kW	19.0	22.0	22.0
		Min.-Max.		8.4-20.9	10.3-24.2	10.3-24.2
	Heating	Rated		22.4	27.0	27.0
		Min.-Max.		7.2-24.6	8.5-29.7	8.5-29.7
Input Power	Cooling/Heating		kW	6.46/6.59	7.77/8.18	7.77/8.18
EER	Cooling			2.94	2.83	2.83
COP	Heating			3.40	3.30	3.30
Max. Operating Current	Indoor (Cooling/Heating)		A	-	-	-
	Outdoor (Cooling/Heating)			-	-	-
Moisture Removal	I/h			4.5	6.0	6.0
Sound Pressure	Indoor (Cooling)	H/M/L/Q		46/43/41/39	47/44/42/40	47/44/42/40
	Indoor (Heating)	H/M/L/Q		46/43/41/39	47/44/42/40	47/44/42/40
	Outdoor (Cooling/Heating)	High		55/55	55/57	55/57
Airflow Rate	Indoor/Outdoor (Cooling)	High	m³/h	4,300/8,400	4,300/8,400	4,300/8,400
		High		4,300/8,400	4,300/9,000	4,300/9,000
Static pressure range (Standard)	Indoor		Pa	50 to 150 (72)	50 to 200 (72)	50 to 200 (72)
Net Dimensions H x W x D	Indoor		mm	360 × 1,400 × 850	360 × 1,400 × 850	360 × 1,400 × 850
Weight	Indoor		kg	1,428 × 1,080 × 480	1,428 × 1,080 × 480	1,428 × 1,080 × 480
	Outdoor		kg	69	80	80
Connection Pipe Diameter (Liquid/Gas)	Indoor		mm	12.7/25.4	12.7/25.4	12.7/25.4
Drain Hose Diameter (I.D./O.D.)	Indoor			25/32	25/32	25/32
Max. Pipe Length (Pre-Charge)	Indoor		m	100 (30)	100 (30)	100 (30)
Max. Height Difference	Indoor		m	30	30	30
Operating Range	Cooling	°CDB		-15 to 46	-15 to 46	-15 to 46
				-20 to 24	-20 to 24	-20 to 24
Refrigerant	Type (Global Warming Potential)			R410A (2,088)	R410A (2,088)	R410A (2,088)
	Charge		kg (CO <sub>2</sub> eq-T)	5.6 (11.693)	5.6 (11.693)	7.1 (14.825)

### Optional parts

* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.						
Wired Remote Controller (Design type):	UTY-RVRY	WLAN adapter:	UTY-TFSXZ1	Network Converter for single split (DC power supply type):	UTY-VTGX	
Compact wired remote controller:	UTY-RCRYZ1	FG-RC-WIF1Z2	FG-RC-WIF1Z2	Network Converter for single split (AC power supply type):	UTY-VTGV	
Wired remote controller (touch panel):	UTY-RNRYZ5	UTY-TFSXJ3	UTY-TFSXJ3	IR receiver unit:	UTY-LBTYM	
Wired remote controller:	UTY-RNRY	FG-AC-WIF1Z1	FG-AC-WIF1Z1		UTY-LRHYM	
	UTY-RNNYM	UTY-XCSX	UTY-XCSX	Silver Ion Filter:	UTD-HFKA	
	UTY-RVNYM	UTY-XSZXZ1	UTY-XSZXZ1	(Outdoor unit)	UTY-XWZXZ	
Simple remote controller (without operation mode):	UTY-RHRY	UDT-LFKA	UDT-LFKA	External connect kit:	UTY-XWZXZ	
Simple remote controller:	UTY-RSRY	External connect kit:	UTY-XWZXZG		UTY-PX1NAB	
External switch controller:	UTY-TERX	External switch controller:	Drain pump unit:			

### Dimensions

(Unit: mm)



\*The design of the service access depends on the installation method. Refer to the installation manual for more information.

## Floor

Compact Size

ALL  
DC


### High energy saving

The Floor 09 class achieves a top-class SEER of 8.50 and an A+++ seasonal efficiency rank for cooling.  
The Floor 09 class achieves an improved SCOP of 4.30 and an A+ seasonal efficiency rank for heating.

Rank \*1  
Cooling A+++  
Heating A+  
SEER 8.50 \*1 SCOP 4.30 \*1  
\*1: 09 model

### Flexible & easy installation

The compact and whole-surface suction design provides flexible installation options, including floor-standing, embedded, half concealed, and wall mount installation to match the room layout.





(Unit: mm)

\* Concaved position installation with concealment is prohibited.

### Low ambient operation


Factory-guaranteed cooling operation down to -10°C ambient temperature.



### Smart device control (Option)


With the optional WLAN adapter installed in the air conditioner, you can control it from anywhere with your smart device.

\* See page C-020 for details on smart device control.



### 10°C heat

The room temperature can be set to go no lower than 10°C, thus ensuring that the room does not get too cold when not occupied.



Model: AGEG09KVCA / AGEG12KVCA / AGEG14KVCA



Wireless RC



For AGEG09/12KVCA



For AGEG14KVCA

### Specifications

Model name	Indoor unit		AOEG09KVCA	AOEG12KVCA	AOEG14KVCA		
	Outdoor unit						
Power Source							
Capacity	Cooling	Rated Min.-Max.	kW	2.5	3.5		
	Heating	Rated Min.-Max.		0.9-3.5	0.9-4.0		
				3.5	4.5		
Input Power	Cooling/Heating		kW	0.9-5.1	0.9-5.3		
	Cooling			0.53/0.81	0.88/1.22		
	Heating			4.70	4.00		
Pdesign	Cooling/Heating (-10°C)		kW	2.50/2.60	3.50/3.50		
	Cooling			8.50	8.20		
	Heating (Average)			4.30	4.10		
Energy Efficiency Class	Cooling		A++	A++	A++		
	Heating (Average)			A+	A+		
	Cooling/Heating			7.0/8.5	7.0/8.5		
Max. Operating Current	Cooling	A	kWh/a	103	149		
	Heating (Average)			845	1,192		
	Heating			1.3	1.8		
Moisture Removal	Single phase, -230 V, 50 Hz		l/h	40/35/29/22	40/35/29/22		
	Indoor (Cooling)	H/M/L/Q		41/35/29/22	41/35/29/22		
	Indoor (Heating)	H/M/L/Q		43/47	45/51		
Sound Pressure Level	Outdoor (Cooling/Heating)	High	dB(A)	53/54	53/54		
	Indoor (Cooling/Heating)	High		58/61	61/64		
	Outdoor (Cooling/Heating)	High		570/1,530	570/1,530		
Sound Power Level	Indoor/Outdoor (Cooling)	High	m³/h	600/1,510	650/2,210		
	Indoor/Outdoor (Heating)	High		600/1,510	650/2,100		
	Indoor			600 × 740 × 200	600 × 740 × 200		
Airflow Rate	Outdoor		mm	542 × 799 × 290	542 × 799 × 290		
	Indoor	kg		14	14		
	Outdoor	kg		31	38		
Net Dimensions H x W x D	Connection Pipe Diameter (Liquid/Gas)	mm	mm	6.35/9.52	6.35/9.52		
	Drain Hose Diameter (I.D./O.D.)	mm		13.8/15.8 to 16.7	13.8/15.8 to 16.7		
	Max. Pipe Length (Pre-Charge)	m		20 (15)	20 (15)		
Max. Height Difference	Max. Height Difference		m	15	15		
	Operating Range Cooling	°CDB		-10 to 46	-10 to 46		
	Heating			-15 to 24	-15 to 24		
Operating Range	Type (Global Warming Potential)		kg (CO <sub>2</sub> eq-T)	R32 (675)	R32 (675)		
	Charge			0.85 (0.574)	0.94 (0.635)		

### Optional parts

\* For optional parts compatibility of Intesis devices, please refer to the optional parts compatibility list page C-050 to C-053 and C-066.



Wired Remote Controller (Design type):  
Compact wired remote controller:  
Wired remote controller (touch panel):  
Wired remote controller:  
Simple remote controller (without operation mode):  
Simple remote controller:

UTY-RVRY  
UTY-RCRY21  
UTY-RNRY25  
UTY-LRLY  
UTY-RHRY  
UTY-RSRY  
External switch controller: UTY-TERX  
WLAN adapter: UTY-TFSXZ1  
FG-AC-WIF1Z1  
UTY-TFSXJ3  
UTY-STA  
UTY-TWRXZ3  
Half concealed kit:  
Communication kit:

Network Converter for single split (DC power supply type): UTY-VTGX  
Network Converter for single split (AC power supply type): UTY-VTGVX  
Silver Ion Filter: UTR-FA03-5  
External connect kit: UTY-XWZXZ5

### Dimensions

(Unit: mm)





## Wall-mounted Specifications



**Designer Series**  
High-Spec & Design (WLAN adapter Internal Models)

Model name	Indoor unit		ASYG07KGTF	ASYG09KGTF	ASYG12KGTF	ASYG14KGTF
	Outdoor unit		AOYG07KGCB	AOYG09KGCB	AOYG12KGCB	AOYG14KGCB
Power Source					Single phase, ~230 V, 50 Hz	
Capacity	Cooling	Rated	kW	2.0	2.5	3.4
		Min.-Max.		0.9-3.2	0.9-3.4	0.9-4.1
	Heating	Rated		2.5	2.8	4.0
		Min.-Max.		0.9-5.2	0.9-5.4	0.9-6.1
Input Power	Cooling/Heating		kW	0.400/0.500	0.555/0.560	0.805/0.910
EER	Cooling			5.00	4.50	4.22
COP	Heating			5.00	5.00	4.40
Pdesign	Cooling/Heating (-10°C)		kW	2.0/2.3	2.5/2.4	3.4/2.5
SEER	Cooling			8.10	8.90	8.70
SCOP	Heating (Average)			5.30	5.20	4.50
Energy Efficiency Class	Cooling			A++	A+++	A+++
	Heating (Average)			A+++	A+++	A++
Max. Operating Current	Cooling/Heating		A	6.5/9.0	6.5/9.0	6.5/9.0
Annual Energy Consumption	Cooling			86	98	137
	Heating			606	645	673
Moisture Removal			I/h	1.0	1.3	1.8
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	dB(A)	38/33/29/19	40/34/29/19	40/35/30/19
	Indoor (Heating)	H/M/L/Q		41/35/31/21	42/36/31/21	42/38/33/21
	Outdoor (Cooling/Heating)	High		46/46	46/48	50/50
Sound Power Level	Indoor (Cooling/Heating)	High		54/56	55/57	56/58
	Outdoor (Cooling/Heating)	High		61/62	61/63	65/66
Airflow Rate	Indoor/Outdoor (Cooling)	High	m³/h	650/1,610	700/1,610	700/1,680
	Indoor/Outdoor (Heating)	High		720/1,560	750/1,610	770/1,580
Net Dimensions H x W x D	Indoor	mm		270 x 834 x 215	270 x 834 x 215	270 x 834 x 215
	Outdoor	mm		542 x 799 x 290	542 x 799 x 290	542 x 799 x 290
Weight	Indoor	kg		10	10	10
	Outdoor	kg		30	30	31
Connection Pipe Diameter (Liquid/Gas)				6.35/9.52		
Drain Hose Diameter (I.D./O.D.)					13.8/15.0 to 16.8	
Max. Pipe Length (Pre-Charge)			m		20 (15)	
Max. Height Difference					15	
Operating Range	Cooling	°CDB			-10 to 46	
	Heating				-15 to 24	
Refrigerant	Type (Global Warming Potential)		kg (CO <sub>2</sub> eq-T)		R32 (675)	
	Charge			0.75 (0.506)	0.75 (0.506)	0.85 (0.574)
					0.85 (0.574)	0.85 (0.574)

**Designer Series**  
High Spec & Design (WLAN adapter Option Models)

Model name	Indoor unit		ASYG07KGTE	ASYG09KGTE	ASYG12KGTE	ASYG14KGTE
	Outdoor unit		AOYG07KGCA	AOYG09KGCA	AOYG12KGCA	AOYG14KGCA
Power Source					Single phase, ~230 V, 50 Hz	
Capacity	Cooling	Rated	kW	2.0	2.5	3.4
		Min.-Max.		0.9-3.2	0.9-3.4	0.9-4.1
	Heating	Rated		2.5	2.8	4.0
		Min.-Max.		0.9-5.2	0.9-5.4	0.9-6.1
Input Power	Cooling/Heating		kW	0.400/0.500	0.555/0.560	0.805/0.910
EER	Cooling			5.00	4.50	4.22
COP	Heating			5.00	5.00	4.40
Pdesign	Cooling/Heating (-10°C)		kW	2.0/2.3	2.5/2.4	3.4/2.5
SEER	Cooling			9.10	9.20	9.20
SCOP	Heating (Average)			5.30	5.20	4.50
Energy Efficiency Class	Cooling			A+++	A+++	A+++
	Heating (Average)			A+++	A+++	A++
Max. Operating Current	Cooling/Heating		A	6.5/9.0	6.5/9.0	6.5/9.0
Annual Energy Consumption	Cooling			77	95	129
	Heating			607	645	672
Moisture Removal			I/h	1.0	1.3	1.8
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	dB(A)	38/33/29/19	40/34/29/19	40/35/30/19
	Indoor (Heating)	H/M/L/Q		41/35/31/21	42/36/31/21	42/38/33/21
	Outdoor (Cooling/Heating)	High		46/46	46/48	50/50
Sound Power Level	Indoor (Cooling/Heating)	High		54/56	55/57	56/58
	Outdoor (Cooling/Heating)	High		61/62	61/63	65/66
Airflow Rate	Indoor/Outdoor (Cooling)	High	m³/h	650/1,610	700/1,610	700/1,680
	Indoor/Outdoor (Heating)	High		720/1,560	750/1,610	770/1,580
Net Dimensions H x W x D	Indoor	mm		270 x 834 x 215	270 x 834 x 215	270 x 834 x 215
	Outdoor	mm		542 x 799 x 290	542 x 799 x 290	542 x 799 x 290
Weight	Indoor	kg		10	10	10
	Outdoor	kg		30	30	31
Connection Pipe Diameter (Liquid/Gas)				6.35/9.52		
Drain Hose Diameter (I.D./O.D.)					13.8/15.0 to 16.8	
Max. Pipe Length (Pre-Charge)			m		20 (15)	
Max. Height Difference					15	
Operating Range	Cooling	°CDB			-10 to 46	
	Heating				-15 to 24	
Refrigerant	Type (Global Warming Potential)		kg (CO <sub>2</sub> eq-T)		R32 (675)	
	Charge			0.75 (0.506)	0.75 (0.506)	0.85 (0.574)
					0.85 (0.574)	0.85 (0.574)

**Designer Series**  
Cool Beauty Design

Model name	Indoor unit		ASYG07KETE ASYG07KETE-B	ASYG09KETE ASYG09KETE-B	ASYG12KETE ASYG12KETE-B	ASYG14KETE ASYG14KETE-B	
	Outdoor unit		AOYG07KETA	AOYG09KETA	AOYG12KETA	AOYG14KETA	
<b>Power Source</b>							
Capacity	Cooling	Rated	kW	2.0	2.5	3.4	4.2
		Min.-Max.		0.9 - 3.0	0.9 - 3.2	0.9 - 3.9	0.9 - 4.4
	Heating	Rated		2.5	2.8	4.0	5.4
		Min.-Max.		0.9 - 3.4	0.9 - 4.0	0.9 - 5.3	0.9 - 6.0
Input Power							
Cooling/Heating		kW	0.450/0.555	0.630/0.620	0.935/0.960	1.220/1.410	
EER	Cooling	W/W	4.43	3.97	3.65	3.44	
COP	Heating		4.52	4.52	4.17	3.83	
Pdesign	Cooling/Heating (-10°C)	kW	2.0/2.3	2.5/2.4	3.4/2.5	4.2/4.0	
SEER	Cooling	W/W	7.40	7.40	7.30	6.90	
SCOP	Heating (Average)		4.10	4.10	4.40	4.10	
Energy Efficiency Class	Cooling		A++	A++	A++	A++	
	Heating (Average)		A+	A+	A+	A+	
Max. Operating Current	Cooling/Heating	A	6.5/9.0	6.5/9.0	6.5/9.0	6.5/9.0	
Annual Energy Consumption	Cooling	kWh/a	95	118	163	213	
	Heating		785	819	795	1,367	
Moisture Removal		l/h	1.0	1.3	1.8	2.1	
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	38/33/29/20	40/34/29/20	40/35/30/20	43/36/30/20	
	Indoor (Heating)	H/M/L/Q	41/35/31/22	42/36/31/22	42/38/33/22	44/39/33/24	
	Outdoor (Cooling/Heating)	High	46/46	46/46	50/50	50/50	
	Outdoor (Cooling/Heating)	High	54/56	55/57	55/58	57/59	
Sound Power Level	Indoor (Cooling/Heating)	High	61/61	61/62	65/65	65/66	
	Indoor/Outdoor (Cooling)	High	650/1,650	700/1,650	700/1,700	770/1,680	
Airflow Rate	Indoor/Outdoor (Heating)	High	720/1,450	750/1,450	770/1,470	800/1,580	
Net Dimensions		mm	295 × 950 (wall side: 840) × 230				
H x W x D	Indoor	mm	541 × 663 × 290	541 × 663 × 290	541 × 663 × 290	542 × 799 × 290	
	Outdoor	mm					
Weight	Indoor	kg	11	11	11	11.5	
	Outdoor	kg	23	23	25	31	
Connection Pipe Diameter (Liquid/Gas)		mm	6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52	
Drain Hose Diameter (I.D./O.D.)		mm	13.8/15.0 to 16.8	13.8/15.0 to 16.8	13.8/15.0 to 16.8	13.8/15.0 to 16.8	
Max. Pipe Length (Pre-Charge)		m	20 (15)	20 (15)	20 (15)	20 (15)	
Max. Height Difference			15	15	15	15	
Operating Range	Cooling	°CDB	-10 to 46	-10 to 46	-10 to 46	-10 to 46	
	Heating		-15 to 24	-15 to 24	-15 to 24	-15 to 24	
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)	
	Charge	kg (CO <sub>2</sub> eq-T)	0.6 (0.405)	0.6 (0.405)	0.7 (0.473)	0.85 (0.574)	



**Standard Series**  
High-Efficiency & Comfort



Model name	Indoor unit	W-LAN Adapter Internal Models	ASYG07KMCF	ASYG09KMCF	ASYG12KMCF	ASYG14KMCF	
		W-LAN Adapter Option Models	ASYG07KMCE	ASYG09KMCE	ASYG12KMCE	ASYG14KMCE	
Outdoor unit			AOYG07KMCC	AOYG09KMCC	AOYG12KMCC	AOYG14KMCC	
<b>Power Source</b>							
Capacity	Cooling	Rated	kW	2.0	2.5	3.4	4.2
		Min.-Max.		0.9-3.0	0.9-3.2	0.9-3.9	0.9-4.4
	Heating	Rated		2.5	2.8	4.0	5.4
		Min.-Max.		0.9-3.4	0.9-4.0	0.9-5.3	0.9-6.0
Input Power		kW	0.450/0.555	0.630/0.620	0.935/0.960	1.220/1.410	
EER	Cooling	W/W	4.43	3.97	3.65	3.44	
COP	Heating		4.52	4.52	4.17	3.83	
Pdesign	Cooling/Heating (-10°C)	kW	2.0/2.3	2.5/2.4	3.4/2.5	4.2/4.0	
SEER	Cooling	W/W	7.40	7.40	7.30	6.90	
SCOP	Heating (Average)		4.10	4.10	4.40	4.10	
Energy Efficiency Class	Cooling		A++	A++	A++	A++	
	Heating (Average)		A+	A+	A+	A+	
Max. Operating Current	Cooling/Heating	A	6.5/9.0	6.5/9.0	6.5/9.0	6.5/9.0	
Annual Energy Consumption	Cooling	kWh/a	95	118	163	213	
	Heating		785	819	795	1,367	
Moisture Removal		l/h	1.0	1.3	1.8	2.1	
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	38/33/29/20	40/34/29/20	40/35/30/20	43/36/30/20	
	Indoor (Heating)	H/M/L/Q	41/35/31/22	42/36/31/22	42/38/33/22	44/39/33/24	
	Outdoor (Cooling/Heating)	High	46/46	46/46	50/50	50/50	
	Outdoor (Cooling/Heating)	High	54/56	55/57	55/58	57/59	
Sound Power Level	Indoor (Cooling/Heating)	High	61/61	61/62	65/65	65/66	
	Indoor/Outdoor (Cooling)	High	650/1,650	700/1,650	700/1,700	770/1,680	
Airflow Rate	Indoor/Outdoor (Heating)	High	720/1,450	750/1,450	780/1,470	820/1,580	
Net Dimensions		mm	270 × 834 × 222	270 × 834 × 222	270 × 834 × 222	270 × 834 × 222	
H x W x D	Indoor	mm	541 × 663 × 290	541 × 663 × 290	541 × 663 × 290	542 × 799 × 290	
	Outdoor	mm					
Weight	Indoor	kg	10	10	10	10	
	Outdoor	kg	22	22	24	31	
Connection Pipe Diameter (Liquid/Gas)		mm	6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52	
Drain Hose Diameter (I.D./O.D.)		mm	13.8/15.0 to 16.8	13.8/15.0 to 16.8	13.8/15.0 to 16.8	13.8/15.0 to 16.8	
Max. Pipe Length (Pre-Charge)		m	20 (15)	20 (15)	20 (15)	20 (15)	
Max. Height Difference			15	15	15	15	
Operating Range	Cooling	°CDB	-10 to 46	-10 to 46	-10 to 46	-10 to 46	
	Heating		-15 to 24	-15 to 24	-15 to 24	-15 to 24	
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)	R32 (675)	R32 (675)	
	Charge	kg (CO <sub>2</sub> eq-T)	0.6 (0.405)	0.6 (0.405)	0.7 (0.473)	0.85 (0.574)	



## ECO Series Lineup Specifications

## Compact Cassette



Model name	Indoor unit		AUXG09KVLA	AUXG12KVLA	AUXG14KVLA	AUXG18KVLA	AUXG22KVLA	AUXG24KVLA	
	Outdoor unit		AOEG09KATA	AOEG12KATA	AOEG14KATA	AOEG18KATA	AOEG22KATA	AOEG24KATA	
<b>Power Source</b>									
Capacity	Cooling	Rated	kW	2.5	3.5	4.3	5.2	6.0	6.8
		Min.-Max.		0.9-2.7	0.9-3.7	0.9-4.5	0.9-5.4	0.9-6.3	0.9-7.4
	Heating	Rated		3.2	4.1	5.0	6.0	7.0	7.5
Input Power	Cooling/Heating		kW	0.68/0.88	1.09/1.17	1.37/1.42	1.69/1.72	1.95/2.00	2.26/2.08
	Cooling			3.68	3.21	3.14	3.08	3.08	3.01
	Heating			3.64	3.50	3.52	3.49	3.50	3.61
EER	Cooling		W/W	2.5/2.3	3.5/2.8	4.3/3.2	5.2/3.8	6.0/4.4	6.8/5.4
				6.2	6.1	6.1	6.1	5.9	
	Heating			4.0	4.0	4.0	3.9	3.9	3.8
COP	Cooling		W/W	A++	A++	A++	A++	A++	A+
				A+	A+	A+	A	A	A
	Heating			6.9/6.9	7.7/7.7	9.2/9.2	10.1/10.1	11.6/11.6	12.6/12.6
Pdesign	Cooling/Heating (-10°C)		kW	141	201	247	298	344	403
	Cooling			804	979	1,120	1,362	1,578	1,988
	Heating			0.6	1.2	1.5	2.2	2.6	2.7
SEER	Cooling		W/W	33/31/29/27	37/34/30/27	38/34/30/26	38/34/26/30	49/44/36/30	49/44/36/30
				34/32/29/27	37/34/31/29	43/38/34/30	43/38/34/30	45/43/40/33	49/45/40/33
	Heating			47/48	49/50	50/51	51/52	52/53	54/55
SCOP	Cooling		W/W	46/47	49/49	50/55	50/55	56/57	59/61
				60/60	62/62	63/63	63/64	64/65	66/67
	Heating			540/1,610	600/1,630	680/1,670	680/1,710	830/2,240	930/2,885
Energy Efficiency Class	Cooling		m³/h	540/1,550	600/1,410	800/1,580	800/1,840	860/2,240	930/2,350
				15 (15)	15 (15)	20 (15)	20 (15)	25 (15)	25 (20)
	Heating			15	15	15	15	20	20
Max. Operating Current	Cooling/Heating		A	10.1/10.1	11.6/11.6	12.6/12.6			
	Cooling			293	338	390			
	Heating			1,297	1,502	1,887			
Annual Energy Consumption	Cooling		kWh/a	1.5	2.2	2.7			
				33/32/31/28	33/32/31/28	35/33/32/29			
	Heating			51/52	52/53	54/55			
Moisture Removal	Indoor (Cooling)	H/M/L/Q	dB(A)	47/47	49/49	49/49			
	Indoor (Heating)	H/M/L/Q		63/64	64/65	66/67			
	Outdoor (Cooling/Heating)	High		1,050/1,710	1,050/2,240	1,150/2,885			
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	mm	246 × 840 × 840	246 × 840 × 840	246 × 840 × 840			
	Indoor (Heating)	H/M/L/Q		542 × 799 × 290	632 × 799 × 290	632 × 799 × 290			
	Outdoor (Cooling/Heating)	High		1,050/1,840	1,050/2,240	1,150/2,350			
Sound Power Level	Indoor (Cooling/Heating)	High	dB(A)	25/32	25/32	25/32			
	Indoor (Cooling/Heating)	High		20 (15)	25 (15)	25 (20)			
	Outdoor (Cooling/Heating)	High		15	20	20			
Airflow Rate	Indoor/Outdoor (Cooling)	High	m³/h	-10 to 46	-10 to 46	-10 to 46			
	Indoor/Outdoor (Heating)	High		-15 to 24	-15 to 24	-15 to 24			
	Indoor/Outdoor (Heating)	High		25/32	25/32	25/32			
Net Dimensions	Indoor		mm	49 × 620 × 620	49 × 620 × 620	49 × 620 × 620			
	Outdoor			49 × 620 × 620	49 × 620 × 620	49 × 620 × 620			
	Weight	kg		2.3	2.3	2.3			
Connection Pipe Diameter (Liquid/Gas)	Indoor		mm	6.35/12.70	6.35/12.70	6.35/12.70			
	Outdoor			25/32	25/32	25/32			
	Weight	kg		33	36	38			
Drain port Diameter (I.D./O.D.)	Indoor		mm	6.35/12.70	6.35/12.70	6.35/12.70			
	Outdoor			25/32	25/32	25/32			
	Weight	kg		20 (15)	25 (15)	25 (20)			
Max. Pipe Length (Pre-Charge)	Indoor		m	15	20	20			
	Outdoor			15	20	20			
	Weight	kg		2.3	2.3	2.3			
Max. Height Difference	Cooling		°CDB	-10 to 46	-10 to 46	-10 to 46			
	Heating			-15 to 24	-15 to 24	-15 to 24			
	Heating			25/32	25/32	25/32			
Operating Range	Type (Global Warming Potential)		kg (CO2eq-T)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge			0.6 (0.605)	0.7 (0.473)	0.85 (0.574)	0.9 (0.608)	1.1 (0.743)	1.25 (0.844)
	Model name			UTG-UFYF-W: White wired remote controller (touch panel) UTG-UKYA-W: White wired remote controller (touch panel)					
Cassette Grille	Dimensions (H × W × D)	mm	kg	53 × 950 × 950	53 × 950 × 950	53 × 950 × 950	53 × 950 × 950	53 × 950 × 950	53 × 950 × 950
	Weight	kg		6.0	6.0	6.0	6.0	6.0	6.0
	Weight	kg		2.3	2.3	2.3	2.3	2.3	2.3

\*1: IR Receiver kit and Human sensor kit cannot be connected.

## Circular Cassette (Large type)



Model name	Indoor unit		AUXG30KRLB	AUXG36KRLB	AUXG45KRLB	AUXG54KRLB	AUXG36KRLB	AUXG45KRLB	AUXG54KRLB	
	Outdoor unit		AOEG30KATA	AOEG36KATA	AOEG45KATA	AOEG54KATA	AOEG36QATA	AOEG45QATA	AOEG54QATA	
<b>Power Source</b>										
Capacity	Cooling	Rated	kW	8.5	9.5	12.1	13.4	9.5	12.1	13.4
		Min.-Max.		2.8-9.6	2.8-10.6	4.0-12				

## Medium Static Pressure Duct (High-Efficiency &amp; Comfort)



Model name	Indoor unit		ARXH12KMTAP	ARXH14KMTAP	ARXH18KMTAP	ARXH22KMTAP	ARXH24KMTAP
	Outdoor unit		AOEG12KATA	AOEG14KATA	AOEG18KATA	AOEG22KATA	AOEG24KATA
<b>Power Source</b>							
Capacity	Cooling	Rated	kW	3.5	4.3	5.2	6.0
		Min.-Max.		0.9-3.7	0.9-4.5	0.9-5.4	0.9-6.3
	Heating	Rated	kW	4.1	5.0	6.0	7.0
		Min.-Max.		0.9-4.4	0.9-5.3	0.9-6.3	0.9-7.4
Input Power							
EER	Cooling		kW	1.060 / 1.170	1.340 / 1.420	1.730 / 1.820	1.85 / 1.97
COP	Heating		W/W	3.30	3.21	3.00	3.24
Pdesign	Cooling/Heating (-10°C)		kW	3.5 / 2.8	4.3 / 3.2	5.2 / 3.8	6.0 / 4.4
SEER	Cooling		W/W	6.00	5.80	5.90	6.00
SCOP	Heating (Average)			3.90	3.90	3.90	3.90
Energy Efficiency Class	Cooling			A+	A+	A+	A+
	Heating (Average)			A	A	A	A
Max. Operating Current	Cooling/Heating		A	7.7 / 7.7	9.2 / 9.2	10.1 / 10.1	11.6 / 11.6
Annual Energy Consumption	Cooling		kWh/a	212	267	316	358
	Heating			1,005	1,148	1,363	1,578
Moisture Removal			I/h	1.3	1.3	2.0	1.5
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	dB(A)	29 / 27 / 25 / 23	32 / 29 / 27 / 25	33 / 30 / 28 / 26	32 / 28 / 25 / 24
	Indoor (Heating)	H/M/L/Q		29 / 27 / 25 / 23	32 / 29 / 27 / 25	33 / 30 / 28 / 26	34 / 30 / 28 / 26
Sound Power Level	Outdoor (Cooling/Heating)	High		49 / 50	50 / 51	51 / 52	52 / 53
	Indoor (Cooling/Heating)	High		58 / 58	59 / 59	60 / 60	58 / 58
Airflow Rate	Indoor/Outdoor (Cooling)	High	m³/h	650 / 1,630	800 / 1,670	840 / 1,710	1,150 / 2,240
	Indoor/Outdoor (Heating)	High		650 / 1,410	800 / 1,580	840 / 1,840	1,150 / 2,240
Static pressure range (Standard)		Pa		30 to 150 (40)	30 to 150 (40)	30 to 150 (40)	30 to 150 (50)
Net Dimensions H x W x D	Indoor	mm		240 × 700 × 700	240 × 700 × 700	240 × 700 × 700	240 × 1,000 × 700
	Outdoor	mm		541 × 663 × 290	542 × 799 × 290	632 × 799 × 290	632 × 799 × 290
Weight	Indoor	kg		24	24	31	31
	Outdoor	kg		25	32	33	36
Connection Pipe Diameter (Liquid/Gas)		mm		6.35 / 9.52	6.35 / 9.52	6.35 / 12.7	6.35 / 12.70
Drain Hose Diameter (I.D./O.D.)		mm		25 / 32	25 / 32	25 / 32	25 / 32
Max. Pipe Length (Pre-Charge)		m		15 (15)	20 (15)	20 (15)	25 (20)
Max. Height Difference				15	15	15	20
Operating Range	Cooling	°CDB		-10 to 46	-10 to 46	-10 to 46	-10 to 46
	Heating			-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)			R32 (675)	R32 (675)	R32 (675)	R32 (675)
	Charge	kg (CO <sub>2</sub> eq-T)		0.70 (0.473)	0.85 (0.574)	0.90 (0.608)	1.10 (0.743)
							1.25 (0.844)

## Medium Static Pressure Duct (Standard)



Model name	Indoor unit		ARXG22KMLB	ARXG24KMLA	ARXG30KMLA	ARXG36KMLA	ARXG45KMLA	ARXG36KMLA	ARXG45KMLA
	Outdoor unit		AOEG22KATA	AOEG24KATA	AOEG30KATA	AOEG36KATA	AOEG45KATA	AOEG36QOTA	AOEG45QOTA
<b>Power Source</b>									
Capacity	Cooling	Rated	kW	3.5	4.3	5.2	6.0	6.8	7.5
		Min.-Max.		0.9-3.7	0.9-4.5	0.9-5.4	0.9-6.3	0.9-7.4	0.9-8.6
	Heating	Rated	kW	4.1	5.0	6.0	7.0	7.5	10.0
		Min.-Max.		0.9-4.4	0.9-5.3	0.9-6.3	0.9-7.4	0.9-8.6	13.5
Input Power									
EER	Cooling		kW	1.060 / 1.170	1.340 / 1.420	1.730 / 1.820	1.85 / 1.97	2.06 / 1.97	2.19 / 2.00
COP	Heating		W/W	3.30	3.21	3.00	3.24	3.06	3.04
Pdesign	Cooling/Heating (-10°C)		kW	3.5 / 2.8	4.3 / 3.2	5.2 / 3.8	6.0 / 4.4	6.8 / 5.4	8.5 / 8.0
SEER	Cooling		W/W	6.00	5.80	5.90	6.00	5.8	5.6
SCOP	Heating (Average)			3.90	3.90	-	3.90	3.9	3.9
Energy Efficiency Class	Cooling			A+	A+	-	A+	A+	A+
	Heating			A	A	-	A	A	A
Max. Operating Current	Cooling/Heating		A	7.7 / 7.7	9.2 / 9.2	10.1 / 10.1	11.6 / 11.6	12.6 / 12.6	12.5 / 12.5
Annual Energy Consumption	Cooling		kWh/a	212	267	316	358	513	594
	Heating			1,005	1,148	1,363	1,578	2,871	3,122
Moisture Removal			I/h	1.3	1.3	2.0	1.5	2.5	3.0
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	dB(A)	29 / 27 / 25 / 23	32 / 29 / 27 / 25	33 / 30 / 28 / 26	34 / 30 / 28 / 26	31 / 29 / 27 / 25	31 / 29 / 27 / 25
	Indoor (Heating)	H/M/L/Q		29 / 27 / 25 / 23	32 / 29 / 27 / 25	33 / 30 / 28 / 26	34 / 30 / 28 / 26	31 / 29 / 27 / 25	31 / 29 / 27 / 25
Sound Power Level	Outdoor (Cooling/Heating)	High		49 / 50	50 / 51	51 / 52	52 / 53	52 / 53	53 / 55
	Indoor (Cooling/Heating)	High		58 / 58	59 / 59	60 / 60	58 / 58	60 / 62	65 / 69
Airflow Rate	Indoor/Outdoor (Cooling)	High	m³/h	650 / 1,630	800 / 1,670	840 / 1,710	1,150 / 2,240	1,100 / 2,400	1,900 / 3,750
	Indoor/Outdoor (Heating)	High		650 / 1,410	800 / 1,580	840 / 1,840	1,150 / 2,240	1,100 / 2,400	2,100 / 4,450
Static pressure range (Standard)		Pa		30 to 150 (40)	30 to 150 (40)	30 to 150 (40)	30 to 150 (50)	30 - 150 (35)	30 - 150 (47)
Net Dimensions H x W x D	Indoor	mm		240 × 700 × 700	240 × 700 × 700	240 × 700 × 700	240 × 1,000 × 700	270 × 1,135 × 700	270 × 1,135 × 700
	Outdoor	mm		541 × 663 × 290	542 × 799 × 290	632 × 799 × 290	632 × 799 × 290	632 × 799 × 290	632 × 799 × 290
Weight	Indoor	kg		24	24	31	31	35	38
	Outdoor	kg		25	32	33	36	38	40
Connection Pipe Diameter (Liquid/Gas)		mm		6.35 / 9.52	6.35 / 9.52	6.35 / 12.7	6.35 / 12.70	6.35 / 12.70	6.35 / 12.70
Drain Hose Diameter (I.D./O.D.)		mm		25 / 32	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32
Max. Pipe Length (Pre-Charge)		m		15 (15)	20 (15)	20 (15)	25 (20)	30 (30)	30 (30)
Max. Height Difference				15	15	15	20	30	30
Operating Range	Cooling	°CDB		-10 to 46					
	Heating			-15 to 24					
Refrigerant	Type (Global Warming Potential)			R32 (					

# Feature Summary

Type	Wall-mounted type				Wall-mounted type			
Series	Designer Range		Standard Range		Standard Range		ECO Range	
Model name								
Energy-Saving Features		●			●			
		●	●	●	●	●	●	●
		○	○	○	○	○		
		○	○	○	○			
Features for Comfort								
		●	●	●	●	●	●	●
		●	●	●	●	●	●	
		●	●	●	●	●		
		●	●	●	●	●	●	●
		●	●	●		●	●	●
					●	●		
		●	●	●	●	●	●	●
		●	●	●	●	●	●	●
		○	○	○	○	○		
Convenience Features		●	●	●	●	●	●	●
		●	●	●	●	●	●	●
		●	●	○	●	●	●	●
		○	○	○	○	○		
		●	●	●	●	●	●	●
		○	○	○	○	○		
		○	○	○	○	○		
		● (KGTF, KGTG) ○ (KGTE)	● (KETF, KETF-B) ○ (KETE, KETE-B)	● (KMCF, KMCG) ○ (KMCE)	○	○	●	○
						○		
						● *2		
Clean Features		●	●	●	●	●		
		●	●	●	●	●		
		●	●	●	●	●	●	●
		○	○	○	○	○	○	○
Installation/ Support								
					●	●		●
		○ (KGTF)		○ (KMCG)	○	○		○

\*1 For details of Multi System Control function, refer to C-013. \*2 Wired remote controller (UTY-RNRYZS) is required to use Special Cooling function.

\*3: It is only available on the AIRSTAGE Mobile application and wired remote controller. It can not be used via wireless remote controller.

○: Optional function

# Feature Summary

Type	Cassette			Duct			Duct			Floor	Ceiling
Series	Compact 4-way Flow Series	Circular Flow Series	Slim (With drain pump)	Medium Static Pressure (High-Efficiency & Comfort)	Medium Static Pressure (Compact size)	Medium Static Pressure (Standard)	High Static Pressure	Big			
Model name	AUXG 09/12/14/18/22/24 KVLA	AUXG 18/22/24/30/36/45/54 KRLB	ARXG 09/12/14/18 KLLAP	ARXH 12/14/18/22/24/ 30/36/45/54 KMTAP	ARXG 12/14/18/22/ 24/30/36/45/54 KHTAP	ARXG22KMLB ARXG24/30/36/45KMLA	ARXG45/54KHTB	ARYG60LHTA	ARYG72/90LHTA	AGEG09/12/14KVCA	ABEG 18/22/24/30/36/45/54 KRTA
Energy-Saving Features	    										
Features for Comfort	            										
Convenience Features	          										
Clean Features	    										
Installation/Support	   										

\*1 For details of Multi System Control function, refer to C-013. \*2 Wired remote controller (UTY-RNRYZS) is required to use Special Cooling function.

\*3: It is only available on the AIRSTAGE Mobile application and wired remote controller. It can not be used via wireless remote controller.

O: Optional function



## Light Commercial & Residential MULTI-SPLIT

- M-002 Multi-split Overview
- M-004 Multi-split Outdoor Units Lineup
- M-006 2-unit to 5-unit Multi-split Connectable Indoor Units
- M-008 6-unit Multi-split Connectable Indoor Units
- M-010 Simultaneous Multi-split Connectable Indoor Units
- M-044 Feature Summary



### Refrigerant type R32 models

- M-012 2-unit to 5-unit Multi-split
- M-018 Simultaneous Multi-split Twin/Triple

[M-022 2-unit to 5-unit Multi-split Indoor Units Specifications](#)

[M-028 2-unit to 5-unit Multi-split Combination Table](#)




### Refrigerant type R410A models

- M-016 6-unit Multi-split
- M-020 Simultaneous Multi-split Twin/Triple/Double Twin

[M-026 6-unit Multi-split Indoor Units Specifications](#)

[M-038 6-unit Multi-split Combination Table](#)



A single outdoor unit drives multiple indoor units, offering greater flexibility in system configuration.


If you wish to keep an entire floor or two or more rooms comfortable, we recommend you choose a multi-split air conditioning system with a single outdoor unit. Choose one that meets your air conditioning requirements from the variety of models we offer. You can mix and match indoor and outdoor units as you wish to build the system that best suits your needs.

# Multi-split Overview

Multi-split's space-saving outdoor unit allows for connections of up to eight indoor units for multiple rooms. Added to the lineup are models compatible with the new R32 refrigerant, offering environmentally friendly comfort in homes, offices, stores, and various other settings.



## 3-unit, 4-unit, 5-unit Multi-split Types



## 2-unit Multi-split



## 2-unit to 6-unit Multi-split

Recommended for residences, offices, and other situations where multiple rooms require air conditioning. Each of the 2 to 6 connected indoor units can also be operated individually. Operation control, time scheduling for each room, and energy-saving options can be set on both individual and central remote controllers. The outdoor unit is designed to save space and is flexible enough to be installed on a balcony or underneath a waist-high window.

## Twin / Triple



## Simultaneous Multi-split Type

Suitable for a small building, the entrance hall of a small office, meeting rooms, educational facilities, and other roomy areas where multiple indoor units need to be operated simultaneously. Up to 4 indoor units can be operated simultaneously, making the system perfect for air conditioning not only offices with large spaces, but also spaces with atypical layouts.



# Multi-split Outdoor Units Lineup



FUJITSU GENERAL (Euro) GmbH participates in the ECP program for AC.  
Check ongoing validity of certificate:  
[www.eurovent-certification.com](http://www.eurovent-certification.com)  
\*Models so marked are not ECC certified.

		Class Cooling rated capacity (kW)	14 4.0	18 5.0	18 5.4	24 6.8	30 8.0	36 10.0	45 12.5	45 14.0	54 14.0	72 19.0	90 22.0
2-unit, 3-unit, 4-unit, 5-unit Multi-split	2-unit Multi-split Up to 2 units			AOEG14KBCA2	AOEG18KBCA2								
	3-unit Multi-split Up to 3 units					AOEG18KBCA3	AOEG24KBCA3						
	4-unit Multi-split Up to 4 units							AOEG30KBTB4					
	5-unit Multi-split Up to 5 units								AOEG36KBTB5*1				
6-unit Multi-split	6-unit Multi-split Up to 6 units									AOYG45LBLA6*			
Simultaneous Multi-split	Twin Single-phase								AOEG36KBTB	AOEG45KBTB			
	Twin 3-phase								AOEG36KRTA	AOEG45KRTA			
	Twin/Triple Single-phase										AOEG54KBTB		
	Twin/Triple 3-phase										AOEG54KRTA		
	Twin/Triple/ Double Twin 3-phase											AOYG72LRLA	AOYG90LRLA

Notes: **1. 2-unit Multi-split:** Connectable indoor units are 2 units.

AOEG14KBCA2: Total capacity of indoor units connected must be between 4.0 kW and 6.0 kW.

AOEG18KBCA2: Total capacity of indoor units connected must be between 4.0 kW and 7.5 kW.

**2. 3-unit Multi-split:** Connectable indoor units are 2 to 3 units.

AOEG18KBCA3: Total capacity of indoor units connected must be between 4.0 kW and 8.5 kW.

AOEG24KBCA3: Total capacity of indoor units connected must be between 4.0 kW and 10.5 kW.

**3. 4-unit Multi-split:** Connectable indoor units are 2 to 4 units.

AOEG18KBTB4: Total capacity of indoor units connected must be between 7.5 kW and 14.0 kW.

Connectable indoor units are 2 to 5 units

AOEG30KBTB5: Total capacity of indoor units connected must be between 7.5 kW and 15.5 kW.

**5. 6-unit Multi-split:** Connectable indoor units are 2 to 6 units.

AOYG45LBLA6: Total capacity of indoor units connected must be between 9.5 kW and 18.0 kW.

Cooling rated capacity: \*1: 9.5 kW

## 2-unit to 5-unit Multi-split Connectable Indoor Units



Type	2-unit		3-unit		4-unit	5-unit	
Model name	AOEG14KBCA2	AOEG18KBCA2	AOEG18KBCA3	AOEG24KBCA3	AOEG30KBT4	AOEG36KBT5	
Multi-split Type Outdoor Unit							
Capacity (kW)	Cooling	4.0	5.0	5.4	6.8	8.0	9.5
	Heating	4.4	5.6	6.8	8.0	9.6	10.6

Indoor Unit	BTU	kW Class	7,000	2.0	●	●	●	●	●	●
ASEH07/09/12/14KGTC ASEG07/09/12/14KETF ASYG07/09/12/14KTE	9,000	2.5	●	●	●	●	●	●	●	●
ASEH07/09/12/14KMCG ASEG07/09/12/14KETF-B ASYG07/09/12/14KMCE ASYG07/09/12/14KETE-B	12,000	3.5	●	●	●	●	●	●	●	●
	14,000	4.0	—	●	●	●	●	●	●	●
ASEH05/07/09/12KNCA	5,000	1.5	●*	●*	●*	●*	●*	●*	●*	●*
	7,000	2.0	●	●	●	●	●	●	●	●
	9,000	2.5	●	●	●	●	●	●	●	●
	12,000	3.5	●	●	●	●	●	●	●	●
ASEG18/22/24KMTE	18,000	5.0	—	—	—	●	●	●	●	●
	22,000	6.0	—	—	—	—	●	●	●	●
	24,000	7.0	—	—	—	—	●	●	●	●
AGEG09/12/14KVCA	9,000	2.5	●	●	●	●	●	●	●	●
	12,000	3.5	●	●	●	●	●	●	●	●
	14,000	4.0	—	●	●	●	●	●	●	●
AUXG07/09/12/14/18/22KVLA	7,000	2.0	●	●	●	●	●	●	●	●
	9,000	2.5	●	●	●	●	●	●	●	●
	12,000	3.5	●	●	●	●	●	●	●	●
	14,000	4.0	—	●	●	●	●	●	●	●
	18,000	5.0	—	—	—	●	●	●	●	●
	22,000	6.0	—	—	—	—	●	●	●	●

\*Please consult your dealer for compatible outdoor units with 5kW models.



Type	2-unit		3-unit		4-unit	5-unit				
Model name	AOEG14KBCA2	AOEG18KBCA2	AOEG18KBCA3	AOEG24KBCA3	AOEG30KBT4	AOEG36KBT5				
Multi-split Type Outdoor Unit										
Capacity (kW)	Cooling	4.0	5.0	5.4	6.8	8.0	9.5			
	Heating	4.4	5.6	6.8	8.0	9.6	10.6			
Indoor Unit	BTU	kW Class	7,000	2.0	●	●	●	●	●	●
ARXG07/09/12/14/18KSLAP	9,000	2.5	●	●	●	●	●	●	●	●
	12,000	3.5	●	●	●	●	●	●	●	●
	14,000	4.0	—	—	●	●	●	●	●	●
	18,000	5.0	—	—	—	●	●	●	●	●
ARXG07/09/12/14/18KLLAP	7,000	2.0	●	●	●	●	●	●	●	●
	9,000	2.5	●	●	●	●	●	●	●	●
	12,000	3.5	●	●	●	●	●	●	●	●
	14,000	4.0	—	—	●	●	●	●	●	●
	18,000	5.0	—	—	—	●	●	●	●	●
ARXH12/14/18/22KMTAP	12,000	3.5	●	●	●	●	●	●	●	●
	14,000	4.0	—	—	●	●	●	●	●	●
	18,000	5.0	—	—	—	●	●	●	●	●
	22,000	6.0	—	—	—	—	●	●	●	●
ARXG22KMLB	22,000	6.0	—	—	—	—	●	●	●	●
ABEG18/22KRTA	18,000	5.0	—	—	—	●	●	●	●	●
	22,000	6.0	—	—	—	—	●	●	●	●

## 6-unit Multi-split Connectable Indoor Units



Type	6-unit	
Model name	AOYG45LBLA6	
Multi-split Type Outdoor Unit		
Capacity (kW)	Cooling	12.5
	Heating	13.5
Indoor Unit	BTU	kW Class
	7,000	2.0
	9,000	2.5
	12,000	3.5
	14,000	4.0
	18,000	5.0
	24,000	7.0
	18,000	5.0
	9,000	2.5
	12,000	3.5
	14,000	4.0
	7,000	2.0
	9,000	2.5
	12,000	3.5
	14,000	4.0
	18,000	5.0
	14,000	4.0
	18,000	5.0
	7,000	2.0
	9,000	2.5
	12,000	3.5
	14,000	4.0
	18,000	5.0
	7,000	2.0
	9,000	2.5
	12,000	3.5
	14,000	4.0
	18,000	5.0



# Simultaneous Multi-split Connectable Indoor Units



Type	4HP		5HP		6HP	
Model name	AOEG36KBTB	AOEG36KRTA	AOEG45KBTB	AOEG45KRTA	AOEG54KBTB	AOEG54KRTA
Simultaneous Multi-split Type Outdoor Unit						
Capacity (kW)	Cooling	9.5	12.1	13.4	13.4	
	Heating	10.8	13.5	15.5	15.5	
Indoor Unit	BTU	kW Class	Twin	Triple	Double Twin	
	18,000	5.0	● × 2	–	–	● × 3
	22,000	6.5	–	● × 2	–	–
	24,000	7.0	–	–	● × 2	–
	18,000	5.0	● × 2	–	–	● × 3
	22,000	6.5	–	● × 2	–	–
	24,000	7.0	–	–	● × 2	–
	18,000	5.0	● × 2	–	–	● × 3
	22,000	6.5	–	● × 2	–	–
	24,000	7.0	–	–	● × 2	–
Separation tube	UTP-SX236A (18/22/24)			UTP-SX354A (18)		

Note : Please be aware that 2-wired group control is not possible with Simultaneous Multi-split.



Type	8HP		10HP	
Model name	AOYG72LRLA		AOYG90LRLA	
Simultaneous Multi-split Outdoor Unit				
Capacity (kW)	Cooling	19.0	22.0	
	Heating	22.4	27.0	
Indoor Unit	BTU	kW Class	Twin	Triple
	18,000	5.0	–	–
	22,000	6.5	–	–
	24,000	7.0	–	● × 3
	30,000	8.8	–	–
	36,000	10.6	● × 2	–
	45,000	12.5	–	–
	18,000	5.0	–	–
	22,000	6.5	–	–
	24,000	7.0	–	● × 4
	30,000	8.8	–	–
	36,000	10.6	● × 2	–
	45,000	12.5	–	–
	18,000	5.0	–	–
	22,000	6.5	–	–
	24,000	7.0	–	● × 3
	30,000	8.8	–	–
	36,000	10.6	● × 2	–
	45,000	12.5	–	–
Separation tube	UTP-SX272A × 1	UTP-SX372A × 1	UTP-SX272A × 1, UTP-SX236A × 2	UTP-SX272A × 1

## MULTI-SPLIT

**2-unit,  
3-unit,  
4-unit,  
5-unit,  
Multi-split**




**ALL  
DC**

**High energy saving**

With the adoption of a high-efficiency DC twin-rotary compressor, all models achieved an energy efficiency scale of A+++ for cooling and A++ for heating.

**Rank**  
Cooling  
**A+++**  
Heating  
**A++**  
**SEER** **8.7\***   **SCOP** **4.7**

\*: 2-unit 14 class

**R32 refrigerant model**

In addition to its high energy efficiency, the R32 refrigerant has a larger volumetric capacity than the R410A refrigerant, which means the R32 refrigerant models require less refrigerant charge than the R410A models.

	Pre-charge refrigerant amount (kg)	
2-unit 14 class	<b>0.9</b>	1.25
2-unit 18 class	<b>1.02</b>	1.30
3-unit 18 class	<b>1.8</b>	2.2
3-unit 24 class	<b>1.8</b>	2.2
4-unit 30 class	<b>2.2</b>	3.3
5-unit 36 class	<b>2.5</b>	4.0

**Quiet operation**

The sound power level is reduced by up to 7 dB compared to the current R410 models.

**Sound Power Level**

**61 dB(A)**



\*3-unit 24 class (cooling)

**68 dB(A)**


**-7 dB(A)**

**Space-saving installation**


Multiple indoor units can be connected to 1 outdoor unit by long piping as well. Unlike a single type, the outdoor unit can be installed in the most space-saving location.

**Compact design**

Unlike a single type, the outdoor unit can be installed in the most space-saving location.

**Easy evacuation**

All connected pipes and indoor units can be evacuated quickly via our centralized valve method. Requires evacuation only once.

**Wide range of indoor units with various models**

We offer 41 models in 5 types in a capacity range from 2.0 kW to 6.0 kW. Wide range of requirements can be realized from private homes through to large shops and hotels.

**Models equipped with the New R32 Refrigerant**

Wall-mounted type with sophisticated design

**Designer Series**

Cool Beauty Design  
07/09/12/14 kBTU



High Spec & Design  
07/09/12/14 kBTU

**Standard Series**

High Efficiency & Comfort  
07/09/12/14 kBTU



Compact Size  
05/07/09/12 kBTU



High Efficiency & Large Rooms  
18/22/24 kBTU

Middle and small capacity models are available. This makes installation easier in small spaces.



Mini Duct  
07/09/12/14/18 kBTU



Slim Duct  
07/09/12/14/18 kBTU



Medium static pressure duct  
12/14/18/22 kBTU  
22 kBTU



Compact Cassette  
07/09/12/14/18/22 kBTU



Floor  
09/12/14 kBTU



Ceiling  
18/22 kBTU

**MULTI-SPLIT**
**2-unit: AOEG14KBCA2 / AOEG18KBCA2**
**3-unit: AOEG18KBCA3 / AOEG24KBCA3**
**4-unit: AOEG30KBT4**
**5-unit: AOEG36KBT5**


2-unit

3-unit



4-unit, 5-unit

**Specifications (2-unit)**

Model name	AOEG14KBCA2			AOEG18KBCA2		
Power Source	Single phase, ~230 V, 50 Hz					
Rated Capacity	Cooling	Rated	4.0		5.0	
		Min.-Max.	1.4-4.6		1.7-5.8	
	Heating	Rated	4.4		5.6	
		Min.-Max.	1.1-5.5		1.8-6.6	
EER	Cooling		4.12		4.03	
COP	Heating		4.63		4.59	
Sound Pressure Level (High)	Cooling		47		47	
	Heating		49		50	
Sound Power Level (High)	Cooling		60		60	
	Heating		62		62	
Airflow Rate	Cooling/Heating	m³/h	1,670/1,670		1,960/2,020	
Net Dimensions H × W × D		mm	542 × 799 × 290		632 × 799 × 290	
Weight		kg	33		37	
Connection Pipe Diameter	Liquid	mm	6.35 × 2		6.35 × 2	
	Gas		9.52 × 2		9.52 × 2	
Max. Pipe Length	Total/Each	m	30/20		30/20	
Max. Height Difference	Between Outdoor Unit and Each Indoor Unit	m	15		15	
Between Indoor Units			10		10	
Operating Range	Cooling	°CDB	-10 to 46		-10 to 46	
	Heating		-15 to 24		-15 to 24	
Refrigerant	Type (Global Warming Potential)		R32 (675)		R32 (675)	
Charge	[kg (CO <sub>2</sub> eq-T)]		0.9 (0.608)		1.02 (0.689)	

**Dimensions**

(Unit: mm)




**2-unit: AOEG14KBCA2**

**2-unit: AOEG18KBCA2**

**Specifications (3-unit)**

Model name	AOEG18KBCA3			AOEG24KBCA3		
Power Source	Single phase, ~230 V, 50 Hz					
Rated Capacity	Cooling	Rated	5.4		6.8	
		Min.-Max.	1.8-7.0		1.8-8.5	
	Heating	Rated	6.8		8.0	
		Min.-Max.	2.0-8.0		2.0-9.2	
EER	Cooling		4.78		3.90	
COP	Heating		4.89		4.40	
Sound Pressure Level (High)	Cooling		46		48	
	Heating		49		53	
Sound Power Level (High)	Cooling		59		61	
	Heating		61		67	
Airflow Rate	Cooling/Heating	m³/h	2,220/2,160		2,270/2,730	
Net Dimensions H × W × D		mm	716 × 820 × 315		716 × 820 × 315	
Weight		kg	46		46	
Connection Pipe Diameter	Liquid	mm	6.35 × 3		6.35 × 3	
	Gas		9.52 × 3		9.52 × 2, 12.70 × 1 adapter [12.70 → 9.52] × 1	
Max. Pipe Length	Total/Each	m	50/25		50/25	
Max. Height Difference	Between Outdoor Unit and Each Indoor Unit	m	15		15	
Between Indoor Units			10		10	
Operating Range	Cooling	°CDB	-10 to 46		-10 to 46	
	Heating		-15 to 24		-15 to 24	
Refrigerant	Type (Global Warming Potential)		R32 (675)		R32 (675)	
Charge	[kg (CO <sub>2</sub> eq-T)]		1.8 (1.215)		1.8 (1.215)	

**Specifications (4-unit, 5-unit)**

Model name	AOEG30KBT4			AOEG36KBT5		
Power Source	Single phase, ~230 V, 50 Hz					
Rated Capacity	Cooling	Rated	8.0		9.5	
		Min.-Max.	2.4-10.1		3.0-11.0	
	Heating	Rated	9.6		10.6	
		Min.-Max.	3.0-11.2		3.5-12.0	
EER	Cooling		3.90		3.80	
COP	Heating		4.55		4.50	
Sound Pressure Level (High)	Cooling		50		52	
	Heating		54		55	
Sound Power Level (High)	Cooling		63		65	
	Heating		66		68	
Airflow Rate	Cooling/Heating	m³/h	2,400/2,950		2,450/2,900	
Net Dimensions H × W × D		mm	884 × 820 × 315		884 × 820 × 315	
Weight		kg	55		59	
Connection Pipe Diameter	Liquid	mm	6.35 × 4		6.35 × 5	
	Gas		9.52 × 2, 12.70 × 2 adapter [12.70 → 9.52] × 2		9.52 × 3, 12.70 × 2 adapter [12.70 → 9.52] × 2 adapter [9.52 → 12.70] × 1	
Max. Pipe Length*	Total/Each	m	70/25		75/25	
Max. Height Difference	Between Outdoor Unit and Each Indoor Unit	m	15		15	
Between Indoor Units			10		10	
Operating Range	Cooling	°CDB	-10 to 46		-10 to 46	
	Heating		-15 to 24		-15 to 24	
Refrigerant	Type (Global Warming Potential)		R32 (675)		R32 (675)	
Charge	[kg (CO <sub>2</sub> eq-T)]		2.2 (1.485)		2.5 (1.688)	

\*Length not applicable when floor units are connected. For details, refer to the installation manual.

**3-unit: AOEG18KBCA3 / AOEG24KBCA3**

**4-unit: AOEG30KBT4**

**5-unit: AOEG36KBT5**



## 6-unit Multi-split



ALL  
DC

### A wide variety of models to choose from

We offer 26 models in 5 types in a capacity range from 2.0 kW to 7.0 kW. Wide range of requirements can be realized from private homes through to large shops and hotels.




### Compact design

Multiple indoor units can be connected to 1 outdoor unit by long piping as well. Unlike a single type, the outdoor unit can be installed in the most space-saving location.



### Easy installation

All connected pipes and indoor units can be evacuated quickly via our centralized valve method. Requires evacuation only once.



### Central & Individual control

- Batched control of up to 6 indoor units. Unified setting of room temperature, airflow volume, and local control restrictions across units.
- Language can be selected from English, French, German, Greek, Italian, Portuguese, Russian, Spanish, or Turkish.
- Large backlit LED screen
- Large easy-to-see operation panel

Max. Controllable  
**1** multi-system  
Max. Controllable  
**6** indoor units



6-unit: AOYG45LBLA6







### Specifications

Model name		AOYG45LBLA6	
Power Source		Single phase, ~230 V, 50 Hz	
Rated Capacity	Cooling	Rated Min.-Max.	kW
	Heating	Rated Min.-Max.	
EER	Cooling		W/W
COP	Heating		
Sound Pressure Level (High)	Cooling		dB(A)
	Heating		
Sound Power Level (High)	Cooling		-
	Heating		
Airflow Rate	Cooling/Heating	m³/h	4,200/4,200
Net Dimensions H × W × D		mm	
Weight		kg	94
Connection Pipe Diameter	Liquid	mm	6.35 × 6
	Gas		9.52 × 4, 12.70 × 2
Max. Pipe Length	Total/Each		80/25
Max. Height Difference	Between Outdoor Unit and Each Indoor Unit.		15
	Between Indoor Units.		10
Operating Range	Cooling	°CDB	-10 to 46
	Heating		-15 to 24
Refrigerant	Type (Global Warming Potential)		R410A (2,088)
	Charge	kg (CO <sub>2</sub> eq-T)	4.00 (8.352)

### Dimensions

(Unit: mm)



## Simultaneous Multi-split Type

Twin / Triple




ALL DC




**Meets a variety of installation needs from offices to commercial spaces, with up to 3 indoor units in the same room connected to an outdoor unit.**

Select indoor units according to floor layout and heat load estimated by the number of people working in the room and the direction and intensity of sunlight entering the room. Perfect airflow distribution can be achieved for optimum comfort.

Installation according to floor layout




Installation according to lighting conditions



### Design flexibility


#### Slim & Compact Design

The outdoor unit in this series is 22.7% shorter\* than a twin-fan outdoor unit. The reduced height makes it easy to install in tight spaces.



### Flexible installation

Pipe length of up to 50 m and a height difference of up to 30 m can be accommodated. Multi-split systems can be installed in large residences and multi-story buildings.



### New lineup of indoor units

The indoor units, available in 6 models of 3 types, can be selected according to room size and conditions.



Compact Cassette



Slim Duct



Duct

Note : Please be aware that 2-wired group control is not possible with Simultaneous Multi-split.

**Model: AOEG36KBTB / AOEG45KBTB / AOEG54KBTB  
AOEG36KRTA [3-phase] / AOEG45KRTA [3-phase] / AOEG54KRTA [3-phase]**



### Specifications (Indoor units/Outdoor units)

Indoor Units Model name	Compact Cassette		
	AUXG18KVLA	AUXG22KVLA	AUXG24KVLA
Power Source			Single phase, ~230 V, 50 Hz
Airflow Rate	Cooling H/M/L/Q Heating H/M/L/Q	m³/h	680/580/490/410 800/680/580/450 860/760/700/530
Net Dimensions H × W × D	mm	245 × 570 × 570	245 × 570 × 570
Weight	kg	15	16
Cassette Grille		UTG-UFYF-W	UTG-UFYF-W

Indoor Units Model name	Duct		
	ARXG18KLLAP	ARXG22KMLB	ARXG24KMLA
Power Source			Single phase, ~230 V, 50 Hz
Airflow Rate	Cooling H/M/L/Q Heating H/M/L/Q	m³/h	940/880/820/750 940/880/820/750
Net Dimensions H × W × D	mm	1,100/910/750/580 1,100/910/750/580	1,100/910/750/580
Weight	kg	20	35

Outdoor Units Model name	AOEG36KBTB AOEG45KBTB AOEG54KBTB AOEG36KRTA AOEG45KRTA AOEG54KRTA					
	Cooling	Heating	kW	9.5	12.1	13.4
Capacity				10.8	13.5	15.5
Power Source	Single phase, ~230 V, 50 Hz					
Pdesign	Cooling Heating (-10°C)	kW	9.5 8.7	— —	— —	— —
SEER	Cooling	W/W	6.10	—	—	—
SCOP	Heating		4.00	—	—	—
Annual Energy Consumption	Cooling Heating	kWh/a	545 3,044	— —	— —	— —
Energy Efficiency Class	Cooling Heating		A++ A+	— —	— —	— —
Sound Pressure Level (High)	Cooling Heating	dB(A)	55 55 70	57 57 71	57 59 73	57 59 73
Sound Power Level (High)	Cooling Heating		70 70	71 71	70 71	70 71
Airflow Rate	Cooling/Heating	m³/h	3,750/3,750 4,450/4,450	4,450/4,450 4,450/4,450	3,750/3,750 4,450/4,450	3,750/3,750 4,450/4,450
Net Dimensions H × W × D	mm	788 × 940 × 320	998 × 940 × 320	998 × 940 × 320	788 × 940 × 320	998 × 940 × 320
Weight	kg	52	67	67	53	67
Connection Pipe Diameter (Liquid/Gas)	mm	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88
Max. Pipe Length (Pre-Charge)	m	50 (30)	50 (30)	50 (30)	50 (30)	50 (30)
Max. Height Difference		30	30	30	30	30
Operating Range	Cooling Heating	°CDB	-15 to 46 -15 to 24			
Refrigerant	Type (Global Warming Potential) Charge	kg (CO <sub>2</sub> eq-T)	R32 (675) 1.90 (1.283)	R32 (675) 2.70 (1.823)	R32 (675) 2.70 (1.823)	R32 (675) 2.70 (1.823)
Separation tube			UTP-SX236A (Twin) UTP-SX354A (Triple)	UTP-SX236A (Twin) UTP-SX354A (Triple)	UTP-SX236A (Twin) UTP-SX354A (Triple)	UTP-SX236A (Twin) UTP-SX354A (Triple)


\* Indoor units of different types and capacity cannot be connected.

\* The above specifications apply when used with a cassette type indoor unit.


### Dimensions

(Unit: mm)

#### AOEG36KBTB / AOEG54KBTB




#### AOEG36KRTA / AOEG45KRTA



#### AOEG45KBTB / AOEG54KBTB



#### AOEG54KRTA / AOEG45KRTA



## Simultaneous Multi-split Type

Twin / Triple / Double Twin




ALL  
DC




**Meets a variety of installation needs from an open-plan office to a retail store, with up to 4 indoor units connected to an outdoor unit.**

Select indoor units according to floor layout and heat load estimated by the number of people working in the room and the direction and intensity of sunlight entering the room. Perfect airflow distribution can be achieved for optimum comfort.



### Simultaneous control

Up to 16 indoor units can be controlled simultaneously with a wired remote controller.



Set the indoor unit number using DIP switch on indoor unit circuit board.

\*The following functions are not provided by a wireless remote controller: Timer operation, Sleep Timer operation, 10°C Heat operation

### Indoor unit lineup

The indoor units, available in 18 models of 6 types, can be selected according to room size and conditions.



Model: A0YG72LRLA [3-phase] / A0YG90LRLA [3-phase]



### Specifications (Indoor units/Outdoor units)

Indoor Units Model name	Compact Cassette, Cassette						
	AUYG18LVLB	AUYG22LVL	AUYG24LVL	AUYG30LRLE	AUYG36LRLE	AUYG45LRLA	
Power Source	Single phase, -230 V, 50 Hz						
Airflow Rate	Cooling H/M/L/Q Heating H/M/L/Q	m³/h	750/610/520/410 800/710/600/450	930/830/600/450 930/860/700/530	1,600/1,400/1,270/1,150 1,800/1,400/1,270/1,150	1,800/1,400/1,270/1,150 1,900/1,640/1,460/1,250	
Net Dimensions H × W × D	mm	245 × 570 × 570	245 × 570 × 570	245 × 570 × 570	288 × 840 × 840	288 × 840 × 840	
Weight	kg	15	16	16	26	26	
Cassette Grille		UTG-UFYD-W					

Indoor Units Model name	Duct					
	ARYG18LLTB	ARYG22LMLA	ARYG24LMLA	ARYG30LMLE	ARYG36LMLE	ARYG45LMLA
Power Source	Single phase, -230 V, 50 Hz					
Airflow Rate	Cooling H/M/L/Q Heating H/M/L/Q	m³/h	940/880/820/750 940/880/820/750	1,100/910/750/580 1,100/910/750/580	1,100/910/750/580 1,200/1,620/1,270/980	1,900/1,620/1,270/980 2,100/1,750/1,350/1,070
Net Dimensions H × W × D	mm	198 × 900 × 620	270 × 1135 × 700	270 × 1135 × 700	270 × 1135 × 700	270 × 1135 × 700
Weight	kg	23	38	40	40	40 (88)

Indoor Units Model name	Floor/Ceiling, Ceiling					
	ABYG18LVTB	ABYG22LVT	ABYG24LVT	ABYG30LRT	ABYG36LRT	ABYG45LRTA
Power Source	Single phase, -230 V, 50 Hz					
Airflow Rate	Cooling H/M/L/Q Heating H/M/L/Q	m³/h	780/700/560/500 780/700/560/500	980/820/680/540 980/820/680/540	1,660/1,500/1,200/1,000 1,660/1,500/1,200/1,000	1,900/1,500/1,200/1,000 2,100/1,700/1,400/1,100
Net Dimensions H × W × D	mm	199 × 990 × 655	199 × 990 × 655	199 × 990 × 655	240 × 1660 × 700	240 × 1660 × 700
Weight	kg	27	27	27	46	46

Outdoor Units Model name	AOYG72LRLA			AOYG90LRLA		
	Capacity	Cooling kW	Heating kW	3-phase, ~400 V, 50 Hz	55/55	55/57
Power Source					1,660/1,500/1,200/1,000	1,900/1,500/1,200/1,000
Sound Pressure Level (High)	Cooling/Heating	dB(A)		8,400/8,400	8,400/9,000	
Airflow Rate	Cooling/Heating	m³/h		1,428 × 1,080 × 480	1,428 × 1,080 × 480	
Net Dimensions H × W × D	mm					
Weight	kg			163	172	
Connection Pipe Diameter (Liquid/Gas)	mm			12.7/25.4	12.7/25.4	
Max. Pipe Length (Pre-Charge)	m			100 (30)	100 (30)	
Max. Height Difference				30	30	
Operating Range	Cooling Heating	°CDB		-15 to 46 -20 to 24	-15 to 46 -20 to 24	
Refrigerant	Type (Global Warming Potential) Charge	kg (CO <sub>2</sub> eq-T)		R410A (2,088) 5.6 (11.693)	R410A (2,088) 7.1 (14.825)	
Separation tube				UTP-SX272A × 1 (Twin) UTP-SX372A × 1 (Triple) UTP-SX272A × 1 (Twin) UTP-SX372A × 1 (Triple)	UTP-SX272A × 1 (Twin) UTP-SX236A × 2 (Double Twin) UTP-SX272A × 1 (Twin) UTP-SX254A × 2 (Double Twin)	UTP-SX272A × 1 (Twin) UTP-SX254A × 2 (Double Twin)


\*: That specification is not fixed yet.

• Indoor units of different types and capacity cannot be connected.

• The above specifications apply when used with a cassette type indoor unit.

### Dimensions

(Unit: mm)



# 2-unit to 5-unit Multi-split Indoor Units Specifications



## Wall-mounted type

NEW

Model name	Indoor unit		ASEH07KGTG ASYG07KGTE	ASEH09KGTG ASYG09KGTE	ASEH12KGTG ASYG12KGTE	ASEH14KGTG ASYG14KGTE	
kW Class			kW	2.0	2.5	3.5	4.0
Power Source							
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	38/33/29/21	40/34/29/21	40/35/30/21	43/36/30/21
	Heating			41/35/31/22	42/36/31/22	42/38/33/22	44/39/33/24
Sound Power Level	Cooling	H	dB(A)	54	55	56	57
	Heating			56	57	58	59
Airflow Rate	Cooling	H/M/L/Q	m³/h	650/540/430/270	700/560/430/270	700/560/430/270	770/600/450/280
	Heating			720/580/460/330	750/610/470/330	770/640/520/330	800/660/520/340
Net Dimensions		mm		270 × 834 × 215	270 × 834 × 215	270 × 834 × 215	270 × 834 × 215
Weight		kg		10	10	10	10
Connection Pipe Diameter	Liquid/Gas	mm		6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52

## Wall-mounted type

NEW

Model name	Indoor unit		ASEH07KETF ASEH07KETF-B ASYG07KETE ASYG07KETE-B	ASEH09KETF ASEH09KETF-B ASYG09KETE ASYG09KETE-B	ASEH12KETF ASEH12KETF-B ASYG12KETE ASYG12KETE-B	ASEH14KETF ASEH14KETF-B ASYG14KETE ASYG14KETE-B	
kW Class			kW	2.0	2.5	3.5	4.0
Power Source							
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	38/33/29/21	40/34/29/21	40/35/30/21	43/36/30/21
	Heating			41/35/31/22	42/36/31/22	42/38/33/22	44/39/33/24
Sound Power Level	Cooling	H	dB(A)	54	55	55	57
	Heating			56	57	58	59
Airflow Rate	Cooling	H/M/L/Q	m³/h	650/540/430/270	700/560/430/270	700/560/430/270	770/600/450/280
	Heating			720/580/460/330	750/610/470/330	770/640/520/330	800/660/520/340
Net Dimensions		mm		295 × 950 (wall side: 840) × 230	295 × 950 (wall side: 840) × 230	295 × 950 (wall side: 840) × 230	295 × 950 (wall side: 840) × 230
Weight		kg		11	11	11	11.5
Connection Pipe Diameter	Liquid/Gas	mm		6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52

## Wall-mounted type

NEW

Model name	Indoor unit		ASEH07KMCG ASYG07KMCE	ASEH09KMCG ASYG09KMCE	ASEH12KMCG ASYG12KMCE	ASEH14KMCG ASYG14KMCE	
kW Class			kW	2.0	2.5	3.5	4.0
Power Source							
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	38/33/29/21	40/34/29/21	40/35/30/21	43/36/30/21
	Heating			41/35/31/22	42/36/31/22	42/38/33/22	44/39/33/24
Sound Power Level	Cooling	H	dB(A)	54	55	55	57
	Heating			56	57	58	59
Airflow Rate	Cooling	H/M/L/Q	m³/h	650/540/430/320	700/560/430/320	700/560/430/320	770/600/450/310
	Heating			720/580/460/330	750/610/470/330	780/640/520/330	820/660/520/340
Net Dimensions		mm		270 × 834 × 222	270 × 834 × 222	270 × 834 × 222	270 × 834 × 222
Weight		kg		10	10	10	10
Connection Pipe Diameter	Liquid/Gas	mm		6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52

## Wall-mounted type

NEW

Model name	Indoor unit		ASEH05KNCA	ASEH07KNCA	ASEH09KNCA	ASEH12KNCA	
kW Class			kW	1.5	2.0	2.5	3.5
Power Source							
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	34/33/29/21	36/33/29/21	41/35/29/21	42/36/32/21
	Heating			34/32/30/22	36/33/30/22	41/34/30/22	42/35/31/22
Sound Power Level	Cooling	H	dB(A)	50	51	56	57
	Heating			50	51	56	57
Airflow Rate	Cooling	H/M/L/Q	m³/h	500/450/390/250	530/460/390/250	640/500/390/250	660/520/440/250
	Heating			500/450/420/280	530/460/420/280	640/500/420/280	660/520/440/280
Net Dimensions		mm		270 × 784 × 222	270 × 784 × 222	270 × 784 × 222	270 × 784 × 222
Weight		kg		9	9	9	9
Connection Pipe Diameter	Liquid/Gas	mm		6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52

## Wall-mounted type

NEW

Model name	Indoor unit		ASEG18KMTE	ASEG22KMTE	ASEG24KMTE	
kW Class			kW	5.0	6.0	7.0
Power Source						
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	45/40/35/29	48/40/35/29	49/40/35/29
	Heating			46/40/35/29	48/40/35/29	49/40/35/29
Sound Power Level	Cooling	H	dB(A)	60	62	65
	Heating			61	62	65
Airflow Rate	Cooling	H/M/L/Q	m³/h	980/810/640/510	1,060/810/640/510	1,170/850/640/510
	Heating			1,020/850/640/510	1,060/850/640/510	1,170/850/640/510
Net Dimensions		mm		280 × 980 × 240	280 × 980 × 240	280 × 980 × 240
Weight		kg		12.5	12.5	12.5
Connection Pipe Diameter	Liquid/Gas	mm		6.35/12.70	6.35/12.70	6.35/12.70

## Floor

Model name	Indoor unit		AGEG09KVCA	AGEG12KVCA	AGEG14KVCA	
kW Class			kW	2.5	3.5	4.0




<tbl\_r cells="

## 2-unit to 5-unit Multi-split Indoor Units Specifications

### Ceiling



Model name	Indoor unit		ABEG18KRTA		ABEG22KRTA	
kW Class			kW		5.0	
Power Source						
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	38/36/33/31	42/37/34/31	
	Heating			38/36/33/31	42/37/34/31	
Sound Power Level	Cooling	H	dB(A)	53	57	
	Heating			53	57	
Airflow Rate	Cooling	H/M/L/Q	m³/h	840/790/710/650	900/790/710/650	
	Heating			840/790/710/650	900/790/710/650	
Net Dimensions		mm		235 × 1,080 × 705	235 × 1,080 × 705	
Weight		kg		24	24	
Connection Pipe Diameter	Liquid/Gas	mm		6.35/12.70	6.35/12.70	

### Medium Static Pressure Duct



Model name	Indoor unit		ARXH12KMTAP		ARXH14KMTAP		ARXH18KMTAP		ARXH22KMTAP	
kW Class			kW		3.5		4.0		5.0	
Power Source										
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	29/27/25/23	32/29/27/25	33/30/28/26	32/28/25/24			
	Heating			29/27/25/23	32/29/27/25	33/30/28/26	32/28/25/24			
Sound Power Level	Cooling	H	dB(A)	58	59	60	58			
	Heating			58	59	60	58			
Airflow Rate	Cooling	H/M/L/Q	m³/h	650 / 520 / 460 / 390	800 / 640 / 560 / 480	840 / 720 / 630 / 540	1,150 / 920 / 800 / 700			
	Heating			650 / 520 / 460 / 390	800 / 640 / 560 / 480	840 / 720 / 630 / 540	1,150 / 920 / 800 / 700			
Net Dimensions		mm		240 × 700 × 700	240 × 700 × 700	240 × 700 × 700	240 × 700 × 700			
Weight		kg		24	24	24	31			
Connection Pipe Diameter	Liquid/Gas	mm		6.35 / 9.52	6.35 / 9.52	6.35 / 12.7	6.35 / 12.70			
External static pressure		Pa		30 to 150	30 to 150	30 to 150	30 to 150			
Drain pump				Standard	Standard	Standard	Standard			

### Compact Cassette Grid Type



Model name	Indoor unit		AUXG07KVLA	AUXG09KVLA	AUXG12KVLA	AUXG14KVLA	AUXG18KVLA	AUXG22KVLA	
kW Class			kW	2.0	2.5	3.5	4.0	5.0	6.0
Power Source									Single phase, ~230 V, 50 Hz
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	33/31/29/27	33/31/29/27	37/34/31/28	38/35/32/29	38/35/32/29	44/42/36/30
	Heating			34/32/29/27	34/32/29/27	37/34/31/29	43/38/34/30	43/38/34/30	45/43/40/33
Sound Power Level	Cooling	H	dB(A)	46	46	49	50	50	56
	Heating			47	47	49	55	55	57
Airflow Rate	Cooling	H/M/L/Q	m³/h	540/490/440/390	540/490/440/390	610/530/470/410	680/580/490/410	680/580/490/410	830/740/600/450
	Heating			540/490/440/390	540/490/440/390	610/530/470/410	790/680/580/450	790/680/580/450	860/760/700/530
Net Dimensions		mm		245 × 570 × 570	245 × 570 × 570	245 × 570 × 570	245 × 570 × 570	245 × 570 × 570	
Weight		kg		15	15	15	15	15	16
Panel				UTG-UFYF-W	UTG-UFYF-W	UTG-UFYF-W	UTG-UFYF-W	UTG-UFYF-W	
Connection Pipe Diameter	Liquid/Gas	mm		6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.70	6.35/12.70

### Medium Static Pressure Duct



Model name	Indoor unit		ARXG22KMLB	
kW Class			kW	
Power Source				
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	31/29/27/25
	Heating			31/29/27/25
Sound Power Level	Cooling	H	dB(A)	60
	Heating			62
Airflow Rate	Cooling	H/M/L/Q	m³/h	1,100/910/750/580
	Heating			1,100/910/750/580
Net Dimensions		mm		270 × 1,135 × 700
Weight		kg		35
Connection Pipe Diameter	Liquid/Gas	mm		6.35/12.70
External static pressure		Pa		30 to 150
Drain pump				Option

### Mini duct



Model name	Indoor unit		ARXG07KSLAP	ARXG09KSLAP	ARXG12KSLAP	ARXG14KSLAP	ARXG18KSLAP		
kW Class			kW	2.0	2.5	3.5	4.0	5.0	
Power Source									Single phase, ~230 V, 50 Hz
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	29/26/24/23	29/26/24/23	31/27/25/23	35/30/27/23	33/29/26/23	
	Heating			29/26/24/23	29/26/24/23	31/27/25/23	35/30/27/23	33/29/26/23	
Sound Power Level	Cooling	H	dB(A)	52	54	55	60	58	
	Heating			53	56	57	62	59	
Airflow Rate	Cooling	H/M/L/Q	m³/h	550/440/390/360	600/450/400/360	650/490/430/360	800/640/530/360	940/750/540/480	
	Heating			550/440/390/360	600/450/400/360	650/490/430/360	800/640/530/360	940/750/540/480	
Net Dimensions		mm		198 × 700 × 450	198 × 700 × 450	198 × 700 × 450	198 × 700 × 450	198 × 900 × 450	
Weight		kg		15.5	15.5	15.5	15.5	18.5	
Connection Pipe Diameter	Liquid/Gas	mm		6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.70	
External static pressure		Pa		0 to 30	0 to 30	0 to 30	0 to 50	0 to 50	</

# 6-unit Multi-split Indoor Units Specifications

## Compact wall-mounted



Model name	Indoor unit		ASYG07LUCA	ASYG09LUCA	ASYG12LUCA	ASYG14LUCA	
kW Class			kW	2.0	2.5	3.5	4.0
Power Source							
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	35/30/28/21	36/32/28/21	37/34/31/21	41/36/33/25
	Heating			35/30/28/21	36/32/28/21	37/34/31/21	41/36/34/27
Sound Power Level	Cooling	H	dB(A)	53	54	55	59
	Heating			53	54	55	59
Airflow Rate	Cooling	H/M/L/Q	m³/h	570/520/470/330	600/550/470/330	660/600/530/330	710/640/570/390
	Heating			570/520/470/330	600/550/470/330	660/600/530/330	710/640/590/430
Net Dimensions		mm		282 × 870 × 185	282 × 870 × 185	282 × 870 × 185	282 × 870 × 185
Weight		kg		9.5	9.5	9.5	9.5
Connection Pipe Diameter	Liquid/Gas	mm		6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.70

## Wall-mounted type



Model name	Indoor unit		ASYG18LFCA	ASYG24LFCC	
kW Class			kW	5.0	7.0
Power Source					
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	43/37/33/26	49/42/37/33
	Heating			42/37/33/25	48/42/37/33
Sound Power Level	Cooling	H	dB(A)	58	64
	Heating			58	64
Airflow Rate	Cooling	H/M/L/Q	m³/h	900/740/620/550	1,120/900/740/620
	Heating			900/740/620/550	1,100/900/740/620
Net Dimensions		mm		320 × 998 × 238	320 × 998 × 238
Weight		kg		14	14
Connection Pipe Diameter	Liquid/Gas	mm		6.35/12.70	6.35/15.88

## Compact wall-mounted



Model name	Indoor unit		ASYG07LMCE	ASYG09LMCE	ASYG12LMCE	ASYG14LMCE	
kW Class			kW	2.0	2.5	3.5	4.0
Power Source							
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	36/32/29/21	37/33/29/21	40/36/30/21	42/38/33/25
	Heating			36/32/29/22	37/33/29/22	40/36/31/22	42/38/35/27
Sound Power Level	Cooling	H	dB(A)	51	52	54	56
	Heating			51	52	55	57
Airflow Rate	Cooling	H/M/L/Q	m³/h	560/500/430/310	600/520/430/310	660/560/450/310	730/600/530/360
	Heating			560/500/430/330	600/520/430/330	660/560/470/330	730/615/560/375
Net Dimensions		mm		270 × 870 × 204	270 × 870 × 204	270 × 870 × 204	270 × 870 × 204
Weight		kg		8.5	8.5	8.5	8.5
Connection Pipe Diameter	Liquid/Gas	mm		6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.70

## Floor



Model name	Indoor unit		AGY09LVCA	AGY12LVCA	AGY14LVCA	
kW Class			kW	2.5	3.5	4.0
Power Source						
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	39/34/28/22	42/36/30/22	44/38/31/22
	Heating			39/35/30/22	42/38/32/22	44/39/33/22
Sound Power Level	Cooling	H	dB(A)	52	55	56
	Heating			52	55	56
Airflow Rate	Cooling	H/M/L/Q	m³/h	530/440/360/270	600/490/380/270	650/520/400/270
	Heating			530/460/380/270	600/510/410/270	650/540/430/270
Net Dimensions		mm		600 × 740 × 200	600 × 740 × 200	600 × 740 × 200
Weight		kg		14	14	14
Connection Pipe Diameter	Liquid/Gas	mm		6.35/9.52	6.35/9.52	6.35/12.70

## Floor ceiling



Model name	Indoor unit		ABYG14LVTA	ABYG18LVTB	
kW Class			kW	4.0	5.0
Power Source					
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	36/34/33/29 (Under ceiling)	41/38/34/32 (Under ceiling)
	Heating			39/37/36/32 (Floor console)	44/41/37/35 (Floor console)
Sound Power Level	Cooling	H	dB(A)	36/34/33/29 (Under ceiling)	41/38/34/32 (Under ceiling)
	Heating			39/37/36/32 (Floor console)	44/41/37/35 (Floor console)
Airflow Rate	Cooling	H/M/L/Q	m³/h	51	55
	Heating			51	55
Net Dimensions		mm		640/590/540/480	780/700/560/500
Weight		kg		640/590/540/480	780/700/560/500
Connection Pipe Diameter	Liquid/Gas	mm		199 × 990 × 655	199 × 990 × 655

## Compact cassette



Model name	Indoor unit		AUYG07LVLA	AUYG09LVLA	AUYG12LVLB	AUYG14LVLB	AUYG18LVLB	
kW Class			kW	2.0	2.5	3.5	4.0	5.0
Power Source								
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	33/31/29/27	33/31/29/27	37/33/31/28	40/35/32/29	42/37/33/29
	Heating			34/32/29/27	34/32/29/27	37/33/31/28	40/37/34/29	44/40/37/30
Sound Power Level	Cooling	H	dB(A)	46	46	49	52	54
	Heating			47	47	49	52	56
Airflow Rate	Cooling	H/M/L/Q	m³/h	540/490/440/390	540/490/440/390	610/530/470/410	680/580/490/410	750/610/520/410
	Heating			540/490/440/390	540/490/440/390	610/530/470/410	700/620/550/430	800/710/600/450
Net Dimensions		mm		245 × 570 × 570	245 × 570 × 570	245 × 570 × 570	245 × 570 × 570	245 × 570 × 570
Weight		kg		15	15</td			

## 2-unit Multi-split Combination Table-Cooling/Heating

### 2-unit Multi-split cooling

AOEG14KBCA2	Combination of Indoor Units	Cooling Operation							
		Cooling Capacity			Input Power (Min. - Max.)	EER	Seasonal Data		
		Unit 1 kW	Unit 2 kW	Total Capacity (Min. - Max.) kW			Pdesign kW	SEER	Energy efficiency class
2-unit connection	7   7	2.00	2.00	4.00 (1.4-4.6)	0.97 (0.25-1.20)	4.12	4.0	8.7	A+++
	7   9	1.75	2.25	4.00 (1.4-4.6)	0.97 (0.25-1.20)	4.12	4.0	8.7	A+++
	7   12	1.47	2.53	4.00 (1.4-4.6)	0.97 (0.25-1.20)	4.12	4.0	8.7	A+++
	9   9	2.00	2.00	4.00 (1.4-4.6)	0.97 (0.25-1.20)	4.12	4.0	8.7	A+++
	9   12	1.71	2.29	4.00 (1.4-4.6)	0.97 (0.25-1.20)	4.12	4.0	8.7	A+++

Notes: •7: 7000 Btu/h/9: 9000 Btu/h/12: 12000 Btu/h models

•The above specifications apply when connected with a wall-mounted [KG/KM] unit.

•2 or more indoor units should be connected.

•Cooling capacity is determined based on 27°CDB/19°CWB (indoor temperature) and 35°CDB (outdoor temperature).

•Pipe Length: 5 m, Height difference: 0 m (Outdoor unit to Indoor unit)

•Total capacity of indoor units connected must be between 4.0 kW and 6.0 kW.

•Please refer to the Design & Technical manual for the combination tables with 5kW model.

### 2-unit Multi-split heating

AOEG14KBCA2	Combination of Indoor Units	Heating Operation							
		Heating Capacity			Input Power (Min. - Max.)	COP	Seasonal Data		
		Unit 1 kW	Unit 2 kW	Total Capacity (Min. - Max.) kW			Pdesign kW	SCOP	Energy efficiency class
2-unit connection	7   7	2.20	2.20	4.40 (1.1-5.5)	0.95 (0.25-1.65)	4.63	3.5	4.7	A++
	7   9	1.92	2.48	4.40 (1.1-5.5)	0.95 (0.25-1.65)	4.63	3.5	4.7	A++
	7   12	1.62	2.78	4.40 (1.1-5.5)	0.95 (0.25-1.65)	4.63	3.5	4.7	A++
	9   9	2.20	2.20	4.40 (1.1-5.5)	0.95 (0.25-1.65)	4.63	3.5	4.7	A++
	9   12	1.89	2.51	4.40 (1.1-5.5)	0.95 (0.25-1.65)	4.63	3.5	4.7	A++

Notes: •7: 7000 Btu/h/9: 9000 Btu/h/12: 12000 Btu/h models

•The above specifications apply when connected with a wall-mounted [KG/KM] unit.

•2 or more indoor units should be connected.

•Heating capacity is determined based on 20°CDB (indoor temperature) and 7°CDB/6°CWB (outdoor temperature).

•Pipe Length: 5 m, Height difference: 0 m (Outdoor unit to Indoor unit)

•Total capacity of indoor units connected must be between 4.0 kW and 6.0 kW.

•Please refer to the Design & Technical manual for the combination tables with 5kW model.

AOEG18KBCA2	Combination of Indoor Units	Cooling Operation							
		Cooling Capacity			Input Power (Min. - Max.)	EER	Seasonal Data		
		Unit 1 kW	Unit 2 kW	Total Capacity (Min. - Max.) kW			Pdesign kW	SEER	Energy efficiency class
2-unit connection	7   7	2.00	2.00	4.00 (1.7-5.0)	0.92 (0.25-1.23)	4.35	4.0	8.8	A+++
	7   9	2.00	2.50	4.50 (1.7-5.7)	1.07 (0.25-1.45)	4.22	4.5	8.7	A+++
	7   12	1.84	3.16	5.00 (1.7-5.8)	1.24 (0.25-1.55)	4.03	5.0	8.6	A+++
	7   14	1.67	3.33	5.00 (1.7-5.8)	1.24 (0.25-1.55)	4.03	5.0	8.6	A+++
	9   9	2.50	2.50	5.00 (1.7-5.8)	1.24 (0.25-1.55)	4.03	5.0	8.6	A+++
	9   12	2.14	2.86	5.00 (1.7-5.8)	1.24 (0.25-1.55)	4.03	5.0	8.6	A+++
	9   14	1.96	3.04	5.00 (1.7-5.8)	1.24 (0.25-1.55)	4.03	5.0	8.6	A+++
	12   12	2.50	2.50	5.00 (1.7-5.8)	1.24 (0.25-1.55)	4.03	5.0	8.6	A+++
	12   14	2.31	2.69	5.00 (1.7-5.8)	1.24 (0.25-1.55)	4.03	5.0	8.6	A+++

Notes: •7: 7000 Btu/h/9: 9000 Btu/h/12: 12000 Btu/h/14: 14000 Btu/h models

•The above specifications apply when connected with a wall-mounted [KG/KM] unit.

•2 or more indoor units should be connected.

•Cooling capacity is determined based on 27°CDB/19°CWB (indoor temperature) and 35°CDB (outdoor temperature).

•Pipe Length: 5 m, Height difference: 0 m (Outdoor unit to Indoor unit)

•Total capacity of indoor units connected must be between 4.0 kW and 7.5 kW.

•Please refer to the Design & Technical manual for the combination tables with 5kW model.

Notes: •7: 7000 Btu/h/9: 9000 Btu/h/12: 12000 Btu/h/14: 14000 Btu/h models

•The above specifications apply when connected with a wall-mounted [KG/KM] unit.

•2 or more indoor units should be connected.

•Heating capacity is determined based on 20°CDB (indoor temperature) and 7°CDB/6°CWB (outdoor temperature).

•Pipe Length: 5 m, Height difference: 0 m (Outdoor unit to Indoor unit)

•Total capacity of indoor units connected must be between 4.0 kW and 7.5 kW.

•Please refer to the Design & Technical manual for the combination tables with 5kW model.

AOEG18KBCA2	Combination of Indoor Units	Heating Operation							
		Heating Capacity			Input Power (Min. - Max.)	COP	Seasonal Data		
		Unit 1 kW	Unit 2 kW	Total Capacity (Min. - Max.) kW			Pdesign kW	SCOP	Energy efficiency class
2-unit connection	7   7	2.40	2.40	4.80 (1.7-5.6)	0.99 (0.25-1.35)	4.85	3.8	4.7	A++
	7   9	2.40	3.00	5.40 (1.7-6.4)	1.15 (0.25-1.60)	4.70	4.0	4.7	A++
	7   12	2.06	3.54	5.60 (1.7-7.0)	1.22 (0.25-1.80)	4.59	4.2	4.7	A++
	7   14	1.87	3.73	5.60 (1.7-7.0)	1.22 (0.25-1.80)	4.59	4.2	4.7	A++
	9   9	2.80	2.80	5.60 (1.7-7.0)	1.22 (0.25-1.80)	4.59	4.2	4.7	A++
	9   12	2.40	3.20	5.60 (1.7-7.0)	1.22 (0.25-1.80)	4.59	4.2	4.7	A++
	9   14	2.19	3.41	5.60 (1.7-7.0)	1.22 (0.25-1.80)	4.59	4.2	4.7	A++
	12   12	2.80	2.80	5.60 (1.7-7.0)	1.22 (0.25-1.80)	4.59	4.2	4.7	A++
	12   14	2.58	3.02	5.60 (1.7-7.0)	1.22 (0.25-1.80)	4.59	4.2	4.7	A++

# 3-unit Multi-split Combination Table-Cooling/Heating

## 3-unit Multi-split cooling

AOEG18KBCA3	Combination of Indoor Units	Cooling Operation								
		Cooling Capacity				Input Power (Min. - Max.)	EER	Seasonal Data		
		Unit 1 kW	Unit 2 kW	Unit 3 kW	Total Capacity (Min. - Max.) kW			Pdesign kW	SEER	Energy efficiency
2-unit connection	7 7 -	2.00	2.00	-	4.00 (1.8-5.0)	0.86 (0.35-1.35)	4.65	4.0	8.3	A++
	7 9 -	2.00	2.50	-	4.50 (1.8-5.7)	1.03 (0.35-1.50)	4.36	4.5	8.2	A++
	7 12 -	1.99	3.41	-	5.40 (1.8-6.8)	1.41 (0.35-1.81)	3.83	5.4	8.0	A++
	7 14 -	1.80	3.60	-	5.40 (1.8-7.0)	1.41 (0.35-1.90)	3.83	5.4	8.0	A++
	9 9 -	2.50	2.50	-	5.00 (1.8-6.4)	1.23 (0.35-1.70)	4.06	5.0	8.1	A++
	9 12 -	2.31	3.09	-	5.40 (1.8-7.0)	1.41 (0.35-1.90)	3.83	5.4	8.0	A++
	9 14 -	2.11	3.29	-	5.40 (1.8-7.0)	1.41 (0.35-1.90)	3.83	5.4	8.0	A++
	12 12 -	2.70	2.70	-	5.40 (1.8-7.0)	1.41 (0.35-1.90)	3.83	5.4	8.0	A++
	12 14 -	2.49	2.91	-	5.40 (1.8-7.0)	1.41 (0.35-1.90)	3.83	5.4	8.0	A++
	14 14 -	2.70	2.70	-	5.40 (1.8-7.0)	1.41 (0.35-1.90)	3.83	5.4	8.0	A++
	7 7 7	1.80	1.80	5.40 (1.8-7.0)	1.13 (0.35-1.90)	4.78	5.4	8.6	A+++	
	7 7 9	1.64	1.64	2.12	5.40 (1.8-7.0)	1.13 (0.35-1.90)	4.78	5.4	8.6	A+++
3-unit connection	7 7 12	1.45	1.45	2.50	5.40 (1.8-7.0)	1.13 (0.35-1.90)	4.78	5.4	8.6	A+++
	7 7 14	1.35	1.35	2.70	5.40 (1.8-7.0)	1.13 (0.35-1.90)	4.78	5.4	8.6	A+++
	7 9 9	1.52	1.94	1.94	5.40 (1.8-7.0)	1.13 (0.35-1.90)	4.78	5.4	8.6	A+++
	7 9 12	1.35	1.74	2.31	5.40 (1.8-7.0)	1.13 (0.35-1.90)	4.78	5.4	8.6	A+++
	7 9 14	1.26	1.62	2.52	5.40 (1.8-7.0)	1.13 (0.35-1.90)	4.78	5.4	8.6	A+++
	9 9 9	1.80	1.80	1.80	5.40 (1.8-7.0)	1.13 (0.35-1.90)	4.78	5.4	8.6	A+++
	9 9 12	1.62	1.62	2.16	5.40 (1.8-7.0)	1.13 (0.35-1.90)	4.78	5.4	8.6	A+++

AOEG24KBCA3	Combination of Indoor Units	Cooling Operation								
		Cooling Capacity				Input Power (Min. - Max.)	EER	Seasonal Data		
		Unit 1 kW	Unit 2 kW	Unit 3 kW	Total Capacity (Min. - Max.) kW			Pdesign kW	SEER	Energy efficiency
2-unit connection	7 7 -	2.00	2.00	-	4.00 (1.8-5.0)	0.86 (0.35-1.35)	4.65	4.0	8.3	A++
	7 9 -	2.00	2.50	-	4.50 (1.8-5.7)	1.03 (0.35-1.54)	4.36	4.5	8.2	A++
	7 12 -	2.00	3.50	-	5.50 (1.8-6.8)	1.46 (0.35-1.85)	3.77	5.5	8.0	A++
	7 14 -	2.00	4.00	-	6.00 (1.8-7.5)	1.73 (0.35-2.20)	3.48	6.0	7.6	A++
	7 18 -	1.90	4.90	-	6.80 (1.8-8.5)	2.26 (0.35-2.65)	3.01	6.8	6.9	A++
	9 9 -	2.50	2.50	-	5.00 (1.8-6.4)	1.23 (0.35-1.74)	4.06	5.0	8.1	A++
	9 12 -	2.50	3.50	-	6.00 (1.8-7.5)	1.73 (0.35-2.20)	3.48	6.0	7.6	A++
	9 14 -	2.50	4.00	-	6.50 (1.8-8.2)	2.04 (0.35-2.46)	3.19	6.5	7.2	A++
	9 18 -	2.27	4.53	-	6.80 (1.8-8.5)	2.26 (0.35-2.65)	3.01	6.8	6.9	A++
	12 12 -	3.40	3.40	-	6.80 (1.8-8.5)	2.26 (0.35-2.65)	3.01	6.8	6.9	A++
	12 14 -	3.14	3.66	-	6.80 (1.8-8.5)	2.26 (0.35-2.65)	3.01	6.8	6.9	A++
	12 18 -	2.72	4.08	-	6.80 (1.8-8.5)	2.26 (0.35-2.65)	3.01	6.8	6.9	A++
3-unit connection	14 14 -	3.40	3.40	-	6.80 (1.8-8.5)	2.26 (0.35-2.65)	3.01	6.8	6.9	A++
	14 18 -	2.98	3.82	-	6.80 (1.8-8.5)	2.26 (0.35-2.65)	3.01	6.8	6.9	A++
	7 7 7	2.00	2.00	2.00	6.00 (1.8-7.5)	1.37 (0.35-2.20)	4.37	6.0	8.6	A+++
	7 7 9	2.00	2.50	2.50	6.50 (1.8-8.2)	1.59 (0.35-2.46)	4.08	6.5	8.5	A+++
	7 7 12	1.83	1.83	3.14	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	7 7 14	1.70	1.70	3.40	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	7 7 18	1.49	1.49	3.82	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	7 9 9	1.90	2.45	2.45	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	7 9 12	1.70	2.19	2.91	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	7 9 14	1.59	2.04	3.17	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	7 9 18	1.40	1.80	3.60	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	7 12 12	1.54	2.63	2.63	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	7 12 14	1.44	2.47	2.89	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	7 14 14	1.36	2.72	2.72	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	9 9 9	2.27	2.27	2.27	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	9 9 12	2.04	2.72	2.72	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	9 9 14	1.91	2.98	2.98	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	9 9 18	1.70	3.40	3.40	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	9 12 12	1.86	2.47	2.47	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	9 12 14	1.75	2.33	2.72	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++
	12 12 12	2.27	2.27	2.27	6.80 (1.8-8.5)	1.74 (0.35-2.65)	3.90	6.8	8.5	A+++

Notes: •7: 7000 Btu/h/9: 9000 Btu/h/12:

# 4-unit Multi-split Combination Table-Cooling/Heating

## 4-unit Multi-split cooling

AOEG30KBTA4	Combination of Indoor Units	Cooling Operation								
		Cooling Capacity				Input Power (Min. - Max.)	EER	Seasonal Data		
		Unit 1 kW	Unit 2 kW	Unit 3 kW	Unit 4 kW			Pdesign kW	SEER	Energy efficiency
2-unit connection	7 22 - -	2.00	6.00	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	A++
	7 24 - -	1.81	6.19	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	A++
	9 22 - -	2.32	5.68	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	A++
	9 24 - -	2.18	5.82	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	A++
	12 18 - -	3.20	4.80	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	A++
	12 22 - -	2.82	5.18	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	A++
	12 24 - -	2.67	5.33	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	A++
	14 18 - -	3.50	4.50	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	A++
	14 22 - -	3.11	4.89	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	A++
	14 24 - -	2.95	5.05	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	A++
	18 18 - -	4.00	4.00	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	A++
	18 22 - -	3.60	4.40	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	A++
	18 24 - -	3.43	4.57	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	A++
	22 22 - -	4.00	4.00	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	A++
	22 24 - -	3.83	4.17	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	A++
	24 24 - -	4.00	4.00	-	-	8.00 (2.4-10.1)	2.67 (0.45-3.25)	3.00	8.0	A++
3-unit connection	7 7 12 -	2.00	2.00	3.50	-	7.50 (2.4-9.3)	2.10 (0.45-2.84)	3.57	7.5	A++
	7 7 14 -	2.00	2.00	4.00	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	7 7 18 -	1.75	1.75	4.50	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	7 7 22 -	1.56	1.56	4.88	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	7 7 24 -	1.47	1.47	5.06	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	7 9 9 -	2.00	2.50	2.50	-	7.00 (2.4-8.9)	1.90 (0.45-2.65)	3.69	7.0	A++
	7 9 12 -	2.00	2.50	3.50	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	7 9 14 -	1.87	2.40	3.73	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	7 9 18 -	1.64	2.12	4.24	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	7 9 22 -	1.47	1.89	4.64	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	7 9 24 -	1.40	1.80	4.80	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	7 12 12 -	1.80	3.10	3.10	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	7 12 14 -	1.70	2.91	3.39	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	7 12 18 -	1.51	2.59	3.90	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	7 12 22 -	1.37	2.34	4.29	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	7 12 24 -	1.30	2.23	4.47	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	7 14 14 -	1.60	3.20	3.20	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	7 14 18 -	1.44	2.87	3.69	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	7 14 22 -	1.30	2.60	4.10	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	7 14 24 -	1.24	2.49	4.27	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
3-unit connection	7 18 18 -	1.30	3.35	3.35	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	7 18 22 -	1.19	3.06	3.75	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	7 18 24 -	1.14	2.94	3.92	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	9 9 9 -	2.50	2.50	2.50	-	7.50 (2.4-9.6)	2.10 (0.45-3.01)	3.57	7.5	A++
	9 9 12 -	2.40	2.40	3.20	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	9 9 14 -	2.25	2.25	3.50	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	9 9 18 -	2.00	2.00	4.00	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	9 9 22 -	1.80	1.80	4.40	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	9 9 24 -	1.71	1.71	4.58	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	9 12 12 -	2.18	2.91	-	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	9 12 14 -	2.06	2.74	3.20	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	9 12 18 -	1.85	2.46	3.69	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	9 12 22 -	1.67	2.23	4.10	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	9 12 24 -	1.60	2.13	4.27	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	9 14 14 -	1.94	3.03	3.03	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	9 14 18 -	1.76	2.73	3.51	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	9 14 22 -	1.60	2.49	3.91	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	9 14 24 -	1.53	2.38	4.09	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
4-unit connection	9 18 18 -	1.60	3.20	3.20	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	9 18 22 -	1.40	2.80	3.20	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	9 18 24 -	1.28	2.55	3.27	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	12 12 12 -	2.67	2.67	-	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	12 12 14 -	2.53	2.53	2.94	-	8.00 (2.4-10.1)	2.32 (0.45-3.25)	3.45	8.0	A++
	12 12 18 -	2.29								

# 5-unit Multi-split Combination Table-Cooling

## 5-unit Multi-split cooling

AOEG36KBTAS	Combination of Indoor Units	Cooling Operation					Input Power (Min. - Max.)	EER	Seasonal Data		
		Cooling Capacity							Pdesign kW	SEER	Energy efficiency
		Unit 1 kW	Unit 2 kW	Unit 3 kW	Unit 4 kW	Unit 5 kW	Total Capacity (Min. - Max.)	kW	kW		
2-unit connection	7   24   -   -   -   -   -   -   -   -   -   -	2.00	7.00	-	-	-	9.00 (3.0-11.0)	2.91 (0.30-3.45)	3.09	9.0	A++
	9   22   -   -   -   -   -   -   -   -   -   -	2.50	6.00	-	-	-	8.50 (3.0-11.0)	2.67 (0.30-3.45)	3.18	8.5	A++
	9   24   -   -   -   -   -   -   -   -   -   -	2.50	7.00	-	-	-	9.50 (3.0-11.0)	3.17 (0.30-3.45)	3.00	9.5	A++
	12   22   -   -   -   -   -   -   -   -   -   -	3.50	6.00	-	-	-	9.50 (3.0-11.0)	3.17 (0.30-3.45)	3.00	9.5	A++
	12   24   -   -   -   -   -   -   -   -   -   -	3.17	6.33	-	-	-	9.50 (3.0-11.0)	3.17 (0.30-3.45)	3.00	9.5	A++
	14   22   -   -   -   -   -   -   -   -   -   -	3.69	5.81	-	-	-	9.50 (3.0-11.0)	3.17 (0.30-3.45)	3.00	9.5	A++
	14   24   -   -   -   -   -   -   -   -   -   -	3.50	6.00	-	-	-	9.50 (3.0-11.0)	3.17 (0.30-3.45)	3.00	9.5	A++
	18   18   -   -   -   -   -   -   -   -   -   -	4.75	4.75	-	-	-	9.50 (3.0-11.0)	3.17 (0.30-3.45)	3.00	9.5	A++
	18   22   -   -   -   -   -   -   -   -   -   -	4.27	5.23	-	-	-	9.50 (3.0-11.0)	3.17 (0.30-3.45)	3.00	9.5	A++
	18   24   -   -   -   -   -   -   -   -   -   -	4.07	5.43	-	-	-	9.50 (3.0-11.0)	3.17 (0.30-3.45)	3.00	9.5	A++
4-unit connection	22   22   -   -   -   -   -   -   -   -   -   -	4.75	4.75	-	-	-	9.50 (3.0-11.0)	3.17 (0.30-3.45)	3.00	9.5	A++
	22   24   -   -   -   -   -   -   -   -   -   -	4.54	4.96	-	-	-	9.50 (3.0-11.0)	3.17 (0.30-3.45)	3.00	9.5	A++
	24   24   -   -   -   -   -   -   -   -   -   -	4.75	4.75	-	-	-	9.50 (3.0-11.0)	3.17 (0.30-3.45)	3.00	9.5	A++
	7   7   14   -   -   -   -   -   -   -   -   -	2.00	2.00	4.00	-	-	8.00 (3.0-10.0)	2.26 (0.30-2.88)	3.54	8.0	A++
	7   7   18   -   -   -   -   -   -   -   -   -	2.00	2.00	5.00	-	-	9.00 (3.0-11.0)	2.68 (0.30-3.45)	3.36	9.0	A++
	7   7   22   -   -   -   -   -   -   -   -   -	1.85	5.80	-	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
	7   7   24   -   -   -   -   -   -   -   -   -	1.75	6.00	-	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
	7   9   12   -   -   -   -   -   -   -   -   -	2.00	2.50	3.50	-	-	8.00 (3.0-10.0)	2.26 (0.30-2.88)	3.54	8.0	A++
	7   9   14   -   -   -   -   -   -   -   -   -	2.00	2.50	4.00	-	-	8.50 (3.0-10.7)	2.46 (0.30-3.27)	3.45	8.5	A++
	7   9   18   -   -   -   -   -   -   -   -   -	2.00	2.50	5.00	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
3-unit connection	7   9   22   -   -   -   -   -   -   -   -   -	1.75	2.25	5.50	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
	7   9   24   -   -   -   -   -   -   -   -   -	1.66	2.14	5.70	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
	7   12   12   -   -   -   -   -   -   -   -   -	2.00	3.50	3.50	-	-	9.00 (3.0-11.0)	2.68 (0.30-3.45)	3.36	9.0	A++
	7   12   14   -   -   -   -   -   -   -   -   -	2.00	3.50	4.00	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
	7   12   18   -   -   -   -   -   -   -   -   -	1.80	3.08	4.62	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
	7   12   22   -   -   -   -   -   -   -   -   -	1.62	2.78	5.10	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
	7   12   24   -   -   -   -   -   -   -   -   -	1.55	2.65	5.30	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
	7   14   14   -   -   -   -   -   -   -   -   -	1.90	3.80	3.80	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
	7   14   18   -   -   -   -   -   -   -   -   -	1.71	3.41	4.38	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
	7   14   22   -   -   -   -   -   -   -   -   -	1.55	3.09	4.86	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
5-unit connection	7   14   24   -   -   -   -   -   -   -   -   -	1.47	2.96	5.07	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
	7   18   18   -   -   -   -   -   -   -   -   -	1.54	3.98	3.98	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
	7   18   22   -   -   -   -   -   -   -   -   -	1.41	3.64	4.45	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
	7   18   24   -   -   -   -   -   -   -   -   -	1.36	3.49	4.65	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
	9   9   9   -   -   -   -   -   -   -   -   -	2.50	2.50	2.50	-	-	7.50 (3.0-9.6)	2.07 (0.30-2.70)	3.63	7.5	A++
	9   9   12   -   -   -   -   -   -   -   -   -	2.50	2.50	3.50	-	-	8.50 (3.0-10.7)	2.46 (0.30-3.27)	3.45	8.5	A++
	9   9   14   -   -   -   -   -   -   -   -   -	2.50	2.50	4.00	-	-	9.00 (3.0-11.0)	2.68 (0.30-3.45)	3.36	9.0	A++
	9   9   18   -   -   -   -   -   -   -   -   -	2.38	3.29	4.74	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
	9   9   22   -   -   -   -   -   -   -   -   -	2.14	2.14	5.22	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
	9   9   24   -   -   -   -   -   -   -   -   -	2.04	2.04	5.42	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
4-unit connection	9   9   26   -   -   -   -   -   -   -   -   -	2.04	2.04	5.50	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
	9   12   12   -   -   -   -   -   -   -   -   -	2.50	3.50	3.50	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
	9   12   14   -   -   -   -   -   -   -   -   -	2.44	3.26	3.80	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
	9   12   18   -   -   -   -   -   -   -   -   -	2.19	2.92	4.39	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
	9   12   22   -   -   -   -   -   -   -   -   -	1.99	2.65	4.86	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
	9   12   24   -   -   -   -   -   -   -   -   -	1.90	2.53	5.07	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
	9   14   14   -   -   -   -   -   -   -   -   -	2.32	3.59	3.59	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
	9   14   18   -   -   -   -   -   -   -   -   -	2.09	3.24	4.17	-	-	9.50 (3.0-11.0)	2.91 (0.30-3.45)	3.27	9.5	A++
	9   14   22   -   -   -   -   -   -   -   -   -	1.90	2.96	4.64</td							

# 5-unit Multi-split Combination Table-Heating

## 5-unit Multi-split heating

AOEG36KBTAS	Combination of Indoor Units	Heating Operation					COP	Seasonal Data			
		Heating Capacity						Pdesign kW	SCOP	Energy efficiency	
		Unit 1 kW	Unit 2 kW	Unit 3 kW	Unit 4 kW	Unit 5 kW					
2-unit connection	7   24   -   -   -   -   -   -   -   -   -	2.39	8.21	-	-	-	10.60 (3.5-12.0)	2.65 (0.25-3.25)	4.00	7.0	A+
	9   22   -   -   -   -   -   -   -   -   -	3.00	7.20	-	-	-	10.60 (3.5-12.0)	2.52 (0.25-3.25)	4.04	6.8	A+
	9   24   -   -   -   -   -   -   -   -   -	2.89	7.71	-	-	-	10.60 (3.5-12.0)	2.65 (0.25-3.25)	4.00	7.0	A+
	12   22   -   -   -   -   -   -   -   -   -	3.74	6.86	-	-	-	10.60 (3.5-12.0)	2.65 (0.25-3.25)	4.00	7.0	A+
	12   24   -   -   -   -   -   -   -   -   -	3.53	7.07	-	-	-	10.60 (3.5-12.0)	2.65 (0.25-3.25)	4.00	7.0	A+
	14   22   -   -   -   -   -   -   -   -   -	4.12	6.48	-	-	-	10.60 (3.5-12.0)	2.65 (0.25-3.25)	4.00	7.0	A+
	14   24   -   -   -   -   -   -   -   -   -	3.91	6.69	-	-	-	10.60 (3.5-12.0)	2.65 (0.25-3.25)	4.00	7.0	A+
	18   18   -   -   -   -   -   -   -   -   -	5.30	5.30	-	-	-	10.60 (3.5-12.0)	2.65 (0.25-3.25)	4.00	7.0	A+
	18   22   -   -   -   -   -   -   -   -   -	4.77	5.83	-	-	-	10.60 (3.5-12.0)	2.65 (0.25-3.25)	4.00	7.0	A+
	18   24   -   -   -   -   -   -   -   -   -	4.54	6.06	-	-	-	10.60 (3.5-12.0)	2.65 (0.25-3.25)	4.00	7.0	A+
4-unit connection	22   22   -   -   -   -   -   -   -   -   -	5.30	5.30	-	-	-	10.60 (3.5-12.0)	2.65 (0.25-3.25)	4.00	7.0	A+
	22   24   -   -   -   -   -   -   -   -   -	5.07	5.53	-	-	-	10.60 (3.5-12.0)	2.65 (0.25-3.25)	4.00	7.0	A+
	24   24   -   -   -   -   -   -   -   -   -	5.30	5.30	-	-	-	10.60 (3.5-12.0)	2.65 (0.25-3.25)	4.00	7.0	A+
	7   7   14   -   -   -   -   -   -   -   -	2.40	2.40	4.80	-	-	9.60 (3.5-11.2)	2.25 (0.25-2.87)	4.26	6.5	A+
	7   7   18   -   -   -   -   -   -   -   -	2.32	2.32	5.96	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	7   7   22   -   -   -   -   -   -   -   -	2.06	2.06	6.48	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	7   7   24   -   -   -   -   -   -   -   -	1.95	1.95	6.70	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	7   9   12   -   -   -   -   -   -   -   -	2.40	3.00	4.20	-	-	9.60 (3.5-11.2)	2.25 (0.25-2.87)	4.26	6.5	A+
	7   9   14   -   -   -   -   -   -   -   -	2.40	3.00	4.80	-	-	10.60 (3.5-12.0)	2.42 (0.25-3.25)	4.21	6.8	A+
	7   9   18   -   -   -   -   -   -   -   -	2.18	2.81	5.61	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
3-unit connection	7   9   22   -   -   -   -   -   -   -   -	1.95	2.51	6.14	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	7   9   24   -   -   -   -   -   -   -   -	1.85	2.39	6.36	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	7   12   12   -   -   -   -   -   -   -   -	2.40	4.10	4.10	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	7   12   14   -   -   -   -   -   -   -   -	2.25	3.85	4.50	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	7   12   18   -   -   -   -   -   -   -   -	2.00	3.44	5.16	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	7   12   22   -   -   -   -   -   -   -   -	1.81	3.10	5.69	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	7   12   24   -   -   -   -   -   -   -   -	1.72	2.96	5.92	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	7   14   14   -   -   -   -   -   -   -   -	2.12	4.24	4.24	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	7   14   18   -   -   -   -   -   -   -   -	1.90	3.81	4.89	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	7   14   22   -   -   -   -   -   -   -   -	1.73	3.45	5.43	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
5-unit connection	7   14   24   -   -   -   -   -   -   -   -	1.65	3.30	5.65	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	7   18   18   -   -   -   -   -   -   -   -	2.39	2.39	5.82	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	7   18   22   -   -   -   -   -   -   -   -	2.27	2.27	6.06	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	7   18   24   -   -   -   -   -   -   -   -	1.58	4.06	4.96	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	7   18   26   -   -   -   -   -   -   -   -	1.51	3.89	5.20	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	9   9   9   -   -   -   -   -   -   -   -	3.00	3.00	3.00	-	-	9.00 (3.5-10.8)	2.09 (0.25-2.70)	4.31	6.0	A+
	9   9   12   -   -   -   -   -   -   -   -	3.00	3.00	4.20	-	-	10.60 (3.5-12.0)	2.42 (0.25-3.25)	4.21	6.8	A+
	9   9   14   -   -   -   -   -   -   -   -	2.98	3.26	4.89	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	9   9   18   -   -   -   -   -   -   -   -	2.65	3.50	4.39	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	9   9   22   -   -   -   -   -   -   -   -	2.39	2.39	5.82	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
4-unit connection	9   9   24   -   -   -   -   -   -   -   -	2.27	2.27	6.06	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	9   12   12   -   -   -   -   -   -   -   -	2.90	3.85	3.85	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	9   12   14   -   -   -   -   -   -   -   -	2.73	3.63	4.24	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	9   12   18   -   -   -   -   -   -   -   -	2.45	3.26	4.89	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	9   12   22   -   -   -   -   -   -   -   -	2.22	2.96	5.42	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	9   12   24   -   -   -   -   -   -   -   -	2.12	2.83	5.65	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	9   14   14   -   -   -   -   -   -   -   -	2.58	4.01	4.01	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	9   14   18   -   -   -   -   -   -   -   -	2.33	3.62	4.65	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	9   14   22   -   -   -   -   -   -   -   -	2.12	3.30	5.18	-	-	10.60 (3.5-12.0)	2.54 (0.25-3.25)	4.18	7.0	A+
	9   14   24   -   -   -   -   -   -   -   -	2.03	3.16	5.41</							

# 6-unit Multi-split Combination Table-Cooling

## 6-unit Multi-split cooling

AOYG45LBLA6	Combination of Indoor Units						Cooling Operation						Input Power (Min. - Max.)	EER	
							Cooling Capacity			Unit 1					
	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW		
2-unit connection	12	24	-	-	-	-	3.50	7.00	-	-	-	-	10.5 (3.5-11.5)	3.06 (0.8-3.32)	3.43
	14	24	-	-	-	-	4.00	7.00	-	-	-	-	11.0 (3.5-12.1)	3.28 (0.8-3.70)	3.35
	18	18	-	-	-	-	5.00	5.00	-	-	-	-	10.0 (3.5-11.5)	2.92 (0.8-3.32)	3.42
	18	24	-	-	-	-	5.00	7.00	-	-	-	-	12.0 (3.5-13.4)	3.75 (0.8-4.46)	3.20
	24	24	-	-	-	-	6.25	6.25	-	-	-	-	12.5 (3.5-14.0)	4.01 (0.8-4.84)	3.12
	7	7	24	-	-	-	2.00	2.00	7.00	-	-	-	11.0 (3.5-12.1)	3.19 (0.8-3.70)	3.45
	7	9	18	-	-	-	2.00	2.50	5.00	-	-	-	9.5 (3.5-10.8)	2.55 (0.8-2.93)	3.73
	7	9	24	-	-	-	2.00	2.50	7.00	-	-	-	11.5 (3.5-12.7)	3.41 (0.8-4.08)	3.37
	7	12	18	-	-	-	2.00	3.50	5.00	-	-	-	10.5 (3.5-11.8)	3.02 (0.8-3.51)	3.48
	7	12	24	-	-	-	2.00	3.50	6.90	-	-	-	12.4 (3.5-13.7)	3.82 (0.8-4.65)	3.25
3-unit connection	7	14	14	-	-	-	2.00	4.00	4.00	-	-	-	10.0 (3.5-11.1)	2.81 (0.8-3.13)	3.56
	7	14	18	-	-	-	2.00	4.00	5.00	-	-	-	11.0 (3.5-12.4)	3.23 (0.8-3.89)	3.41
	7	14	24	-	-	-	1.94	3.89	6.67	-	-	-	12.5 (3.5-14.0)	3.89 (0.8-4.84)	3.21
	7	18	18	-	-	-	2.00	5.00	5.00	-	-	-	12.0 (3.5-13.7)	3.69 (0.8-4.65)	3.25
	7	18	24	-	-	-	1.79	4.59	6.12	-	-	-	12.5 (3.5-14.0)	3.87 (0.8-4.84)	3.23
	7	24	24	-	-	-	1.60	5.45	5.45	-	-	-	12.5 (3.5-14.0)	3.83 (0.8-4.84)	3.26
	9	9	18	-	-	-	2.50	2.50	5.00	-	-	-	10.0 (3.5-11.5)	2.84 (0.8-3.32)	3.52
	9	9	24	-	-	-	2.50	2.50	7.00	-	-	-	12.0 (3.5-13.4)	3.65 (0.8-4.46)	3.29
	9	12	14	-	-	-	2.50	3.50	4.00	-	-	-	10.0 (3.5-11.1)	2.81 (0.8-3.13)	3.56
	9	12	18	-	-	-	2.50	3.50	5.00	-	-	-	11.0 (3.5-12.4)	3.23 (0.8-3.89)	3.41
4-unit connection	9	12	24	-	-	-	2.50	3.33	6.67	-	-	-	12.5 (3.5-14.0)	3.89 (0.8-4.84)	3.21
	9	14	14	-	-	-	2.50	4.00	4.00	-	-	-	10.5 (3.5-11.8)	3.02 (0.8-3.51)	3.48
	9	14	18	-	-	-	2.40	3.72	6.38	-	-	-	12.5 (3.5-14.0)	3.88 (0.8-4.84)	3.22
	9	18	18	-	-	-	2.50	5.00	5.00	-	-	-	12.5 (3.5-14.0)	3.89 (0.8-4.84)	3.21
	9	18	24	-	-	-	2.21	4.41	5.88	-	-	-	12.5 (3.5-14.0)	3.86 (0.8-4.84)	3.24
	9	24	24	-	-	-	1.98	5.26	5.26	-	-	-	12.5 (3.5-14.0)	3.82 (0.8-4.84)	3.27
	12	12	12	-	-	-	3.50	3.50	2.50	-	-	-	10.5 (3.5-11.5)	2.98 (0.8-3.32)	3.52
	12	12	14	-	-	-	3.50	3.50	4.00	-	-	-	11.0 (3.5-12.1)	3.19 (0.8-3.70)	3.45
	12	12	18	-	-	-	3.50	3.50	5.00	-	-	-	12.0 (3.5-13.4)	3.65 (0.8-4.46)	3.29
	12	12	24	-	-	-	3.13	6.24	-	-	-	-	12.5 (3.5-14.0)	3.87 (0.8-4.84)	3.23
5-unit connection	12	14	14	-	-	-	3.50	4.00	4.00	-	-	-	11.5 (3.5-12.7)	3.41 (0.8-4.08)	3.37
	12	14	18	-	-	-	3.50	4.00	4.00	-	-	-	12.5 (3.5-14.0)	3.89 (0.8-4.84)	3.21
	12	14	24	-	-	-	3.00	3.50	6.00	-	-	-	12.5 (3.5-14.0)	3.86 (0.8-4.84)	3.24
	12	18	18	-	-	-	3.12	4.69	4.69	-	-	-	12.5 (3.5-14.0)	3.87 (0.8-4.84)	3.23
	12	18	24	-	-	-	2.78	4.17	5.55	-	-	-	12.5 (3.5-14.0)	3.85 (0.8-4.84)	3.25
	12	24	24	-	-	-	2.50	5.00	5.00	-	-	-	12.5 (3.5-14.0)	3.81 (0.8-4.84)	3.28
	14	14	14	-	-	-	4.00	4.00	4.00	-	-	-	12.0 (3.5-13.4)	3.25 (0.8-4.46)	3.29
	14	14	18	-	-	-	3.80	4.90	4.90	-	-	-	12.5 (3.5-14.0)	3.88 (0.8-4.84)	3.22
	14	14	24	-	-	-	3.37	5.76	-	-	-	-	12.5 (3.5-14.0)	3.85 (0.8-4.84)	3.25
	14	18	18	-	-	-	3.50	4.50	4.50	-	-	-	12.5 (3.5-14.0)	3.86 (0.8-4.84)	3.24
4-unit connection	14	18	24	-	-	-	3.13	4.02	5.35	-	-	-	12.5 (3.5-14.0)	3.83 (0.8-4.84)	3.26
	14	24	24	-	-	-	2.82	4.84	4.84	-	-	-	12.5 (3.5-14.0)	3.80 (0.8-4.84)	3.29
	18	18	18	-	-	-	4.17	4.17	4.17	-	-	-	12.5 (3.5-14.0)	3.85 (0.8-4.84)	3.25
	18	18	24	-	-	-	3.75	5.00	-	-	-	-	12.5 (3.5-14.0)	3.81 (0.8-4.84)	3.28
	18	24	24	-	-	-	2.00	2.00	4.00	-	-	-	10.0 (3.5-11.1)	2.50 (0.8-3.13)	4.00
	18	24	24	-	-	-	2.00	2.00	5.00	-	-	-	11.0 (3.5-12.4)	3.06 (0.8-3.89)	3.59
	18	24	24	-	-	-	1.94	1.94	6.68	-	-	-	12.5 (3.5-14.0)	3.77 (0.8-4.84)	3.32
	18	24	24	-	-	-	2.00	2.00	2.50	-	-	-	10.0 (3.5-11.1)	2.50 (0.8-3.13)	4.00
	18	24	24	-	-	-	2.00	2.00	2.50	-	-	-	10.5 (3.5-11.8)	2.79 (0.8-3.51)	3.76
	18	24	24	-	-	-	2.00	2.00	2.50	-	-	-	11.5 (3.5-13.0)	3.33 (0.8-4.27)	3.45
5-unit connection	18</														

# 6-unit Multi-split Multi Combination Table-Cooling/Heating

## 6-unit Multi-split cooling

AOYG45LBLA6	Combination of Indoor Units	Cooling Operation						Input Power (Min. - Max.)	EER
		Unit 1 kW	Unit 2 kW	Unit 3 kW	Unit 4 kW	Unit 5 kW	Unit 6 kW		
7	7	7	7	7	7	7	7	2.00	3.61
7	7	7	7	7	7	7	7	2.00	3.50
7	7	7	7	7	12	1.86	1.86	2.50	3.52
7	7	7	7	7	14	1.79	1.79	3.55	3.53
7	7	7	7	7	18	1.65	1.65	4.25	3.56
7	7	7	7	7	24	1.48	1.48	5.10	3.59
7	7	7	7	9	9	1.90	1.90	2.45	3.51
7	7	7	7	9	12	1.79	1.79	3.05	3.53
7	7	7	7	9	14	1.72	1.72	3.42	3.54
7	7	7	7	9	18	1.59	1.59	4.09	3.57
7	7	7	7	9	24	1.43	1.43	4.93	3.60
7	7	7	7	12	12	1.68	1.68	2.89	3.55
7	7	7	7	12	14	1.62	1.62	2.78	3.56
7	7	7	7	12	18	1.51	1.51	3.87	3.59
7	7	7	7	14	14	1.56	1.56	3.13	3.57
7	7	7	7	14	18	1.46	1.46	2.92	3.60
7	7	7	9	9	9	1.82	1.82	2.34	3.52
7	7	7	9	9	12	1.72	1.72	2.21	3.54
7	7	7	9	9	14	1.65	1.65	2.12	3.56
7	7	7	9	9	18	1.54	1.54	1.97	3.58
7	7	7	9	9	24	1.62	1.62	2.08	3.56
7	7	7	9	12	12	1.56	1.56	2.68	3.57
7	7	7	9	12	14	1.46	1.46	3.02	3.59
7	7	7	9	12	18	1.51	1.51	3.02	3.59
7	7	7	12	12	12	1.54	1.54	2.63	3.58
7	7	7	12	12	14	1.48	1.48	2.54	3.59
7	7	7	12	12	14	1.43	1.43	2.47	3.60
7	7	7	9	9	175	1.75	1.75	2.25	3.54
7	7	9	9	9	12	1.65	1.65	2.12	3.56
7	7	9	9	9	16	1.59	1.59	2.05	3.57
7	7	9	9	9	18	1.48	1.48	1.91	3.59
7	7	9	9	9	24	1.56	1.56	2.50	3.57
7	7	9	9	12	18	1.46	1.46	3.02	3.59
7	7	9	9	14	14	1.51	1.51	3.02	3.59
7	7	9	12	12	12	1.54	1.54	3.02	3.58
7	7	9	12	12	14	1.48	1.48	2.94	3.59
7	7	9	12	12	14	1.43	1.43	2.87	3.60
7	7	9	9	9	175	1.75	1.75	2.25	3.53
7	7	9	9	9	12	1.65	1.65	2.12	3.51
7	7	9	9	9	16	1.59	1.59	2.05	3.57
7	7	9	9	9	18	1.48	1.48	1.91	3.59
7	7	9	9	9	24	1.56	1.56	2.50	3.57
7	7	9	9	12	18	1.46	1.46	3.02	3.59
7	7	9	9	14	14	1.51	1.51	3.02	3.59
7	7	9	12	12	12	1.54	1.54	3.02	3.58
7	7	9	12	12	14	1.48	1.48	2.94	3.59
7	7	9	12	12	14	1.43	1.43	2.87	3.60
7	7	9	9	9	175	1.75	1.75	2.25	3.53
7	7	9	9	9	12	1.65	1.65	2.12	3.51
7	7	9	9	9	16	1.59	1.59	2.05	3.57
7	7	9	9	9	18	1.48	1.48	1.91	3.59
7	7	9	9	9	24	1.56	1.56	2.50	3.57
7	7	9	9	12	18	1.46	1.46	3.02	3.59
7	7	9	9	14	14	1.51	1.51	3.02	3.59
7	7	9	12	12	12	1.54	1.54	3.02	3.58
7	7	9	12	12	14	1.48	1.48	2.94	3.59
7	7	9	12	12	14	1.43	1.43	2.87	3.60
7	7	9	9	9	175	1.75	1.75	2.25	3.53
7	7	9	9	9	12	1.65	1.65	2.12	3.51
7	7	9	9	9	16	1.59	1.59	2.05	3.57
7	7	9	9	9	18	1.48	1.48	1.91	3.59
7	7	9	9	9	24	1.56	1.56	2.50	3.57
7	7	9	9	12	18	1.46	1.46	3.02	3.59
7	7	9	9	14	14	1.51	1.51	3.02	3.59
7	7	9	12	12	12	1.54	1.54	3.02	3.58
7	7	9	12	12	14	1.48	1.48	2.94	3.59
7	7	9	12	12	14	1.43	1.43	2.87	3.60
7	7	9	9	9	175	1.75	1.75	2.25	3.53
7	7	9	9	9	12	1.65	1.65	2.12	3.51
7	7	9	9	9	16	1.59	1.59	2.05	3.57
7	7	9	9	9	18	1.48	1.48	1.91	3.59
7	7	9	9	9	24	1.56	1.56	2.50	3.57
7	7	9	9	12	18	1.46	1.46	3.02	3.59
7	7	9	9	14	14	1.51	1.51	3.02	3.59
7	7	9	12	12	12	1.54	1.54	3.02	3.58
7	7	9	12	12	14	1.48	1.48	2.94	3.59
7	7	9	12	12	14	1.43	1.43	2.87	3.60
7	7	9	9	9	175	1.75	1.75	2.25	3.53
7	7	9	9	9	12	1.65	1.65	2.12	3.51
7	7	9	9	9	16	1.59	1.59	2.05	3.57
7	7	9	9	9	18	1.48	1.48	1.91	3.59
7	7	9	9	9	24	1.56	1.56	2.50	3.57
7	7	9	9	12	18	1.46	1.46	3.02	3.59
7	7	9	9	14	14	1.51	1.51	3.02	3.59
7	7	9	12	12	12	1.54	1.54	3.02	3.58
7	7	9	12	12	14	1.48	1.48	2.94	3.59
7	7	9	12	12	14	1.43	1.43	2.87	3.60
7	7	9	9	9	175	1.75	1.75	2.25	3.53
7	7	9	9	9	12	1.65	1.65	2.12	3.51
7	7	9	9	9	16	1.59	1.59	2.05	3.57
7									

# 6-unit Multi-split Combination Table-Heating

## 6-unit Multi-split heating

AOYG45LBLA6	Combination of Indoor Units						Heating Operation						Input Power (Min. - Max.)	COP
							Heating Capacity			Input Power				
	Unit 1 kW	Unit 2 kW	Unit 3 kW	Unit 4 kW	Unit 5 kW	Unit 6 kW	Total Capacity (Min. - Max.) kW	kW						
4-unit connection	12	12	12	12	-	-	3.38	3.38	3.38	-	-	13.5 (3.5-16.0)	3.60 (0.7-4.41)	3.75
	12	12	12	14	-	-	3.24	3.24	3.24	3.78	-	13.5 (3.5-16.0)	3.60 (0.7-4.41)	3.75
	12	12	12	18	-	-	3.00	3.00	3.00	4.50	-	13.5 (3.5-16.0)	3.58 (0.7-4.41)	3.77
	12	12	12	24	-	-	2.70	2.70	2.70	5.40	-	13.5 (3.5-16.0)	3.57 (0.7-4.41)	3.78
	12	12	14	14	-	-	3.12	3.12	3.63	-	-	13.5 (3.5-16.0)	3.59 (0.7-4.41)	3.76
	12	12	14	18	-	-	2.89	2.89	3.38	4.34	-	13.5 (3.5-16.0)	3.58 (0.7-4.41)	3.77
	12	12	14	24	-	-	2.61	2.61	3.05	5.23	-	13.5 (3.5-16.0)	3.56 (0.7-4.41)	3.79
	12	12	18	18	-	-	2.70	2.70	4.05	-	-	13.5 (3.5-16.0)	3.57 (0.7-4.41)	3.78
	12	14	14	14	-	-	3.00	3.50	3.50	3.50	-	13.5 (3.5-16.0)	3.58 (0.7-4.41)	3.77
	12	14	14	18	-	-	2.79	3.26	4.19	-	-	13.5 (3.5-16.0)	3.57 (0.7-4.41)	3.78
	12	14	18	18	-	-	2.61	3.05	3.92	3.92	-	13.5 (3.5-16.0)	3.56 (0.7-4.41)	3.79
6-unit connection	7	7	7	7	7	-	2.40	2.40	2.40	2.40	-	12.0 (3.5-12.7)	2.82 (0.7-3.44)	4.26
	7	7	7	7	9	-	2.33	2.33	2.33	2.98	-	12.3 (3.5-13.5)	3.03 (0.7-3.65)	4.06
	7	7	7	7	12	-	2.24	2.24	2.24	3.84	-	12.8 (3.5-14.5)	3.29 (0.7-3.98)	3.89
	7	7	7	7	14	-	2.20	2.20	2.20	4.40	-	13.2 (3.5-15.3)	3.40 (0.7-4.20)	3.88
	7	7	7	7	18	-	2.05	2.05	2.05	5.30	-	13.5 (3.5-16.0)	3.49 (0.7-4.41)	3.87
	7	7	7	7	24	-	1.82	1.82	1.82	6.22	-	13.5 (3.5-16.0)	3.47 (0.7-4.41)	3.89
	7	7	9	9	-	-	2.28	2.28	2.93	-	-	12.7 (3.5-14.2)	3.23 (0.7-3.87)	3.93
	7	7	7	9	12	-	2.20	2.20	2.83	3.77	-	13.2 (3.5-15.3)	3.40 (0.7-4.20)	3.88
	7	7	7	9	14	-	2.15	2.15	2.76	4.29	-	13.5 (3.5-16.0)	3.49 (0.7-4.41)	3.87
	7	7	7	9	18	-	1.97	1.97	2.53	5.06	-	13.5 (3.5-16.0)	3.48 (0.7-4.41)	3.88
	7	7	7	9	24	-	1.75	1.75	2.25	6.00	-	13.5 (3.5-16.0)	3.46 (0.7-4.41)	3.90
5-unit connection	7	7	7	12	12	-	2.10	2.10	3.60	3.60	-	13.5 (3.5-16.0)	3.49 (0.7-4.41)	3.87
	7	7	7	12	14	-	2.01	2.01	3.45	4.02	-	13.5 (3.5-16.0)	3.48 (0.7-4.41)	3.88
	7	7	7	12	18	-	1.85	1.85	3.18	4.77	-	13.5 (3.5-16.0)	3.47 (0.7-4.41)	3.89
	7	7	7	12	24	-	1.66	1.66	2.84	5.68	-	13.5 (3.5-16.0)	3.45 (0.7-4.41)	3.91
	7	7	7	14	14	-	1.93	1.93	3.86	3.86	-	13.5 (3.5-16.0)	3.48 (0.7-4.41)	3.88
	7	7	7	14	18	-	1.78	1.78	3.57	4.59	-	13.5 (3.5-16.0)	3.47 (0.7-4.41)	3.89
	7	7	7	14	24	-	1.60	1.60	3.20	5.50	-	13.5 (3.5-16.0)	3.45 (0.7-4.41)	3.91
	7	7	7	18	18	-	1.66	1.66	4.26	4.26	-	13.5 (3.5-16.0)	3.45 (0.7-4.41)	3.91
	7	7	9	9	9	-	2.22	2.22	2.85	4.85	-	13.0 (3.5-14.9)	3.34 (0.7-4.09)	3.89
	7	7	9	9	12	-	2.15	2.15	2.76	3.68	-	13.5 (3.5-16.0)	3.49 (0.7-4.41)	3.87
	7	7	9	9	14	-	2.05	2.05	2.64	4.12	-	13.5 (3.5-16.0)	3.49 (0.7-4.41)	3.87
6-unit connection	7	7	9	9	18	-	1.89	1.89	2.43	4.86	-	13.5 (3.5-16.0)	3.48 (0.7-4.41)	3.88
	7	7	9	9	24	-	1.69	1.69	2.17	5.78	-	13.5 (3.5-16.0)	3.46 (0.7-4.41)	3.90
	7	7	9	12	12	-	2.01	2.01	3.45	4.45	-	13.5 (3.5-16.0)	3.48 (0.7-4.41)	3.88
	7	7	9	12	14	-	1.93	1.93	3.28	4.82	-	13.5 (3.5-16.0)	3.45 (0.7-4.41)	3.91
	7	7	9	12	18	-	1.78	1.78	2.29	3.06	-	13.5 (3.5-16.0)	3.45 (0.7-4.41)	3.91
	7	7	9	12	24	-	1.60	1.60	2.75	5.49	-	13.5 (3.5-16.0)	3.45 (0.7-4.41)	3.91
	7	7	9	14	14	-	1.85	1.85	2.38	3.71	-	13.5 (3.5-16.0)	3.45 (0.7-4.41)	3.89
	7	7	9	14	18	-	1.72	1.72	3.44	4.41	-	13.5 (3.5-16.0)	3.46 (0.7-4.41)	3.90
	7	7	9	14	24	-	1.55	1.55	3.10	5.31	-	13.5 (3.5-16.0)	3.44 (0.7-4.41)	3.92
	7	7	9	18	18	-	1.60	2.06	4.12	4.12	-	13.5 (3.5-16.0)	3.45 (0.7-4.41)	3.91
	7	7	9	12	12	-	1.89	1.89	3.24	3.24	-	13.5 (3.5-16.0)	3.48 (0.7-4.41)	3.88
5-unit connection	7	7	12	12	14	-	1.82	1.82	3.12	3.62	-	13.5 (3.5-16.0)	3.47 (0.7-4.41)	3.89
	7	7	12	12	18	-	1.69	1.69	2.89	4.34	-	13.5 (3.5-16.0)	3.46 (0.7-4.41)	3.90
	7	7	12	12	24	-	1.52	1.52	2.61	5.24	-	13.5 (3.5-16.0)	3.44 (0.7-4.41)	3.92
	7	7	12	14	14	-	1.75	1.75	3.00	3.50	-	13.5 (3.5-16.0)	3.46 (0.7-4.41)	3.90
	7	7	12	14	18	-	1.63	1.63	2.79	3.26	-	13.5 (3.5-16.0)	3.45 (0.7-4.41)	3.91
	7	7	12	18	18	-	1.52	1.52	2.62	3.92</				

# Feature Summary

Type	Wall-mounted type				Wall-mounted type				
Series	Designer Series		Standard Series		Standard Series		Designer Series		
Model name									
	ASEH07/09/12/14KGTG ASYG07/09/12/14KGTE	ASEG07/09/12/14KETF, ASEG07/09/12/14KETF-B, ASYG07/09/12/14KETE, ASYG07/09/12/14KETE-B	ASEH07/09/12/14KMCG ASYG07/09/12/14KMCE	ASEH05/07/09/12KNCA	ASEG18/22/24KMTE	ASYG07/09/12/14LUCA	ASYG07/09/12/14LMCE	ASYG18LFCA, ASYG24LFCC	
Refrigerant									
Energy-saving Features		●							
		●	●	●	●	●	●	●	
		○	○	○	○	○	○	○	
		○	○	○	○	○	○	○	
Features for Comfort									
		●	●	●	●	●			
		●	●	●	●	●	●	●	
		●	●	●	●	●			
		●	●	●	●	●	●	●	
		●	●	●	●	●	●	●	
								●	
		●	●	●	●	●	●	●	
		●	●	●	●	●	●	●	
		○	○	○		●	○	○	
		●	●	●		●	●	●	
Convenience Features		●	●	●		●	●	●	
		●	●	○		○	●	●	
		○	○	○		○	○	○	
		●	●	●		●	●	●	
		○	○	○		○	○	○	
		○	○	○		○	○	○	
		● (KGTG), ○ (KGTE)	● (KETF, KETF-B), ○ (KETE, KETE-B)	● (KMCG), ○ (KMCE)		●	○	○	
		●	●	●		●	●	●	
Clean Features		●	●	●		●	●	●	
		●	●	●		●	●	●	
		●	●	●		●	●	●	
Installation / Support									
					●			(30)	

○ : Optional function

# Feature Summary

Type	Cassette				Duct				Duct				Floor		Floor/Ceiling	Ceiling	
Series	Compact 4-way Flow Grid type Series	Compact 4-way Flow Series	4-way Flow Series		Mini (With drain pump)	Slim (With drain pump)		Slim (With drain pump)		Medium Static Pressure							
Model name																	
	AUXG 07/09/12/ 14/18/22/24 KVLA	AUYG07/09LVLA, AUYG12/14/18LVLB, AUYG22/24LVLA	AUYG30/36LRLE, AUYG36/45LRLA	ARXG 07/09/12/14/18 KSLAP	ARYG 07/09/12/14/18 LSLAP	ARXG 07/09/12/14/18 KLLAP		ARYG07/09LLTA, ARYG12/14/18LLTB	ARXH 12/14/18/22 KMTAP	ARXG22KMLB, ARXG24KMLA	ARYG 22/24/36/45 LMLA, ARYG 30/36LMLE	AGEG09/12/14KVCA	AGYG09/12/14LVCA	ABYG14/22/24LVTA, ABYG18LVTB	ABEG18/22KRTA	ABYG30/36LRTE, ABYG36/45LRTA	
Refrigerant																	
Energy-saving Features																	
		●	●	●	●	●	●	●	●	○	●	●	●	●	●	●	●
		○	○	○	●	●	○	○	○	○	○	○	○	○	○	●	○
		●	○	○	●	●	●	●	○	○	●	○	○	○	○	●	○
Features for Comfort																	
		●	●	○	○	○	○	○	○	○	○	○	●	●	●	○	●
													(45) (36LMLA)	●		○	(45/54)(36LRTA)
		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
		●	●	●	○	○	○	○	○				●	●		●	
																	●
		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
		○	●	●													●
		○	○	○				○		○	○	○				○	○
		●	○	○	●	●	●	●	○	●	●	●	●	●	●	●	●
		●	●	○	○	○	○	○	○	○	○	○	●	●	●	○	●
		●	●	●	○	○	○	○	○	●	●	●	●	●	●	●	●
		●			●	●	●	●					●	●		●	
		○	○	●				●		●	●	●		○	○		○
Convenience Features		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
					○	○										○	
		●	○	○	●	●	●	●	○	●	●	●	●	●	●	●	●
		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
															●	●	
															●	●	
															●	●	
Clean Features																	
		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
					(45/54)								(45)			(30/36/45/54)	(45)
Installation/ Support																	

○ : Optional function

## Light Commercial & Commercial, Residential VRF

VRF systems provide air conditioning solutions that meet the requirements of a diverse range of buildings.

VRF systems provide air conditioning solutions for large residences as well as large commercial buildings.

V-002 VRF Series Overview  
V-004 VRF Outdoor Units Lineup  
V-006 Features

### VRF Outdoor Units



#### VRF J Series Heat Pump for Small-capacity type

V-020 VRF J-VS  
V-026 VRF J-IVS  
V-030 VRF J-IV  
V-034 VRF J-IVL




#### VRF V Series Heat Recovery Modular type

V-040 VRF VR-IV  
Heat Pump Modular type  
V-050 VRF V-IV

### VRF INDOOR UNITS

V-058 VRF Indoor Unit Lineup for J-VS  
V-066 VRF Indoor Unit Lineup for J-IVS, J-IV, J-IVL, VR-IV, V-IV



FUJITSU GENERAL (Euro) GmbH participates in the ECP program for VRF.  
Check ongoing validity of certificate:  
[www.eurovent-certification.com](http://www.eurovent-certification.com)

**FUJITSU GENERAL LIMITED**

# VRF Series Overview

Recommended VRF products for various buildings



## VRF J-VS



### Maximum 6 HP Heat Pump

This product uses R32, a new environmentally friendly refrigerant. With TOP-class energy efficiency and compact design, it can be installed in a limited and narrow space without being conspicuous. Indoor unit connectable up to 130%.

- Sustainable(R32)
- Saving CO<sub>2</sub>
- Small Body
- Situational Piping Design
- Sightless installation



Page  
V-020

## VRF VR-IV



### Maximum 48 HP Heat Recovery

Smart, cutting-edge design Available in a wide range of models from 8 to 48 HP in 2 HP increments with the capacity ratio of indoor units connectable up to 150%.

- Excellent energy saving
- High design flexibility for placement in any building
- Easy installation and maintenance



Page  
V-040

## VRF J-IVS



### Maximum 6 HP Heat Pump

The 998 mm compact design does not obstruct the view even when installed underneath a waist-high window, ideal for large houses and retail stores. Indoor unit connectable up to 130%.

- Spaces saving and low sound level design
- Flexible system configuration for homes, stores, and small buildings



Page  
V-026

## VRF V-IV



### Maximum 48 HP Heat Pump

Smart, cutting-edge design Extensive lineup from 8 HP to 48 HP with the capacity ratio of indoor units connectable up to 150%.

- Simultaneous cooling and heating operation using a single refrigerant system
- Annual cooling operation
- Accommodating changes in temperature difference



Page  
V-050

## VRF J-IV



### Maximum 6 HP Heat Pump

J-IV is connectable with up to 14 indoor units (Indoor unit connectable up to 150%) making it suitable for commercial facilities housing a number of small stores.

- High energy efficiency
- Flexible system configuration for small and midsize buildings



Page  
V-030

## VRF J-IVL



### Maximum 18 HP Heat Pump

J-IVL is an outdoor unit with a slim design. Its flexibility in installation makes it ideal for midsize office buildings and hotels. With the newly added 14/16/18 HP models, up to 42 indoor units\* are connectable, making them ideal for hotels and educational facilities with many rooms.

- Slim Outdoor Unit
- Small room application
- Class-leading Low Operating Sound



Page  
V-034

### Design Simulator

When installing air conditioning equipment in each room of a building, it is necessary to select an indoor unit suitable for the heat load in the room and derive an outdoor unit that can cover the capacity of all indoor units. In addition, remote controls and converters are selected according to how the customer will manage the air conditioner, and in some cases, a design combined with options may be required to comply with established standards. The "Design Simulator" can be used to facilitate the selection of such complex equipment and the output of system drawings and estimates. (Software for PC)



For more information



# VRF Outdoor Units Lineup

Capacity (kW)	Refrigerant	12.1	14.0	15.1-15.5	22.4	28.0	33.5	40.0	45.0	50.0-50.4	55.9	61.5	67.0	73.5	78.5	85.0	90.0	95.0	100.5	107.0	112.0	118.5	123.5	130.0	135.0
HP		4	5	6	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48
J-VS Series <small>NEW</small>	R32																								
J-IVS Series	R410A																								
J-IV Series	R410A																								
J-IVL Series	R410A																								
VR-IV Series Heat Recovery	Space Saving	R410A																							
	Set Model					AJY072 GALDH	AJY090 GALDH	AJY108 GALDH	AJY126 GALDH	AJY144 GALDH	AJY162 GALDH	AJY180 GALDH	AJY198 GALDH	AJY216 GALDH	AJY234 GALDH	AJY252 GALDH	AJY270 GALDH	AJY288 GALDH	AJY306 GALDH	AJY324 GALDH	AJY342 GALDH	AJY360 GALDH	AJY378 GALDH	AJY396 GALDH	AJY414 GALDH
V-IV Series Heat Pump	Energy Efficiency	R410A																							
	Set Model									AJY144 GALDHH			AJY198 GALDHH		AJY216 GALDHH	AJY234 GALDHH	AJY252 GALDHH	AJY270 GALDHH	AJY288 GALDHH	AJY306 GALDHH	AJY324 GALDHH	AJY342 GALDHH	AJY360 GALDHH	AJY378 GALDHH	AJY396 GALDHH
	Space Saving	R410A																							
	Set Model					AJY072 LALDH	AJY090 LALDH	AJY108 LALDH	AJY126 LALDH	AJY144 LALDH	AJY162 LALDH	AJY180 LALDH	AJY198 LALDH	AJY216 LALDH	AJY234 LALDH	AJY252 LALDH	AJY270 LALDH	AJY288 LALDH	AJY306 LALDH	AJY324 LALDH	AJY342 LALDH	AJY360 LALDH	AJY378 LALDH	AJY396 LALDH	AJY414 LALDH
	Energy Efficiency	R410A																							
	Set Model									AJY144 LALDHH			AJY198 LALDHH		AJY216 LALDHH	AJY234 LALDHH	AJY252 LALDHH	AJY270 LALDHH	AJY288 LALDHH	AJY306 LALDHH	AJY324 LALDHH	AJY342 LALDHH	AJY360 LALDHH	AJY378 LALDHH	AJY396 LALDHH




## High-efficiency

High-efficiency is achieved significantly by the use of a DC twin-rotary compressor, inverter technology, and a large heat exchanger.




DC twin-rotary compressor



\* These specifications are determined by ducted combination.

### ALL DC High-efficiency design with top-class SEER/SCOP


All the VRF Series, including the J-IVL Series, have DC technology to achieve high-efficiency operation. This enhances the durability and reliability of the VRF Series.



## Efficient control of operation


### Setting temperature range limitation

Sets the minimum and maximum limits on room temperature to establish an optimum balance between energy-saving performance and a comfortable environment.




### Auto-off timer

The wired remote controller is equipped with an auto-off timer function that automatically stops operation after a fixed period of time has elapsed from the start of operation to avoid wasting energy. The function also allows you to set the interval for stopping operations.




### Energy-saving management

A variety of energy-saving operations can be set and managed depending on the season, climate, and time period.  
Excellent energy-saving operation using the system controller.




### Capacity-saving mode

Operation capacity can be reduced in 5 steps from the rated capacity. This mode cuts down on peak power consumption and eases the maximum load on the unit.



### Intelligent refrigerant control

Fujitsu General is proposing outdoor units equipped with refrigerant control function. The refrigerant control operates with subtle control corresponding to the heat load of the room and offers a more comfortable environment. The refrigerant control can also provide increased energy savings.




#### Current refrigerant control

Thermostat-ON/OFF occurs frequently.  
→ Frequent changes in room temperature interfere with comfort. The compressor starts and stops repeatedly, wasting energy.

#### New refrigerant control

The thermostat is turned on and off less frequently than under current control to maintain the room temperature at the target temperature. Compared to current control, the compressor will run longer, thus saving energy.

#### Current model



#### New model




\* The improvements due to the control and the actual sine wave vary depending on the combination of the indoor unit and system operating conditions.

# More Comfort




## Auto changeover

In Auto setting, the air conditioner switches between cooling and heating modes automatically according to the set temperature and the room temperature.




Auto changeover settings enable the indoor unit to easily switch between cooling and heating regardless of the operating mode of other indoor units. These settings can be made using a wired remote controller for a specific indoor unit. Provides a comfortable environment all year round.

## Automatic cooling/heating operation for each room is possible



## Precise control of refrigerant flow

The combination of DC inverter control and individual control of electronic expansion valves of an indoor unit enables precise and smooth control of the refrigerant flow. This means the room temperature can be set in increments of 0.5°C.




Thermal change of room  
\*Simulation in heating operation.  
Minimal change in room temperature for comfortable environment

## Quiet operation



### Quiet operation

Two low noise modes can be switched over automatically between one in which low noise is prioritized over performance, and the other in which performance is prioritized over low noise, depending on the room temperature and outdoor temperature. This feature can be controlled by external input from the outdoor unit or a system controller.



### Non-stop oil recovery operation


A comfortable room condition is maintained during oil recovery mode because the product continues to operate without stopping the cooling or heating operation.



## NEW Switching room temperature sensing position for improved heating comfort (Option)

The optional remote sensor kit (UTY-XSZX1) can be connected to the indoor unit to improve comfort by installing the unit at a height appropriate for the living environment.


Connectable products



# High Reliability


## Outdoor unit rotation

The compressor starting order is rotated to equalize the cumulative running time of each unit.




### Backup operation

If one compressor fails, the other compressors will initiate backup operation\*.  
Note: Backup operation may not be possible depending on the cause of failure.




### Advanced refrigerant control

Compressor control logic controls the inverter speed to balance the mass airflow rate of refrigerant in each outdoor unit.





## Protection against liquid flowback

The use of a large accumulator means that refrigerant that has not been completely vaporized stays inside the accumulator to ensure no liquid refrigerant is fed into the compressor.



### Blue fin heat exchanger

The anti-corrosion blue fin treatment is applied to the heat exchanger of the outdoor unit.



# Design Flexibility

## Class-leading compact design


An industry-leading compact outdoor unit with optimal airflow pattern design. (Up to 18 HP)



## Long pipe design


Pipe design suitable for long and narrow office buildings with elevation differences and low-rise stores with long distances

(VRF J-IVL Series)



## Max. allowable overall pipe length: 1,000 m

The class-leading pipe length of 1,000 m increases flexibility of installation in a wide variety of buildings.



## High-capacity connection

Series	Connectable indoor unit capacity range	Connectable indoor units
VRF J-VS Series Heat pump type	50% to 130%	up to 13 <sup>5</sup>
VRF J-IVS Series Heat pump type	50% to 130%	up to 13 <sup>5</sup>
VRF J-IV Series Heat pump type	50% to 150%	up to 14 <sup>5</sup>
VRF J-IVL Series 14/16/18 HP Heat pump type	50% to 150%	up to 42 <sup>3</sup>
VRF J-IVL Series 8/10/12 HP Heat pump type	50% to 150%	up to 30 <sup>4</sup>
VRF VR-IV Series Heat Recovery Modular type	25% <sup>5</sup> to 150%	up to 64
VRF V-IV Series Heat Pump Modular type	50% to 150% <sup>2</sup>	up to 64

\*2: The maximum capacity of the combination that includes the 18-HP outdoor unit is below 150%.

\*3: J-IVL Series 18-HP model only.

\*4: J-IVL Series 12-HP model only.

\*5: 6-HP model only.

## Designed for low refrigerant charge

The optimal design of the indoor and outdoor units reduces the amount of refrigerant required and can be easily installed in a room as small as 15 m<sup>2</sup>.



## Various optional parts

- Fresh air intake kit to bring in fresh air
- Comfortable temperature control with a remote sensor
- DX kit links ventilation equipment and air handling units.



## Low ambient operation

Our refrigeration cycle technology enables cooling operation even at -15°C.




## Wide operating temperature range

All outdoor units have a wide operating temperature range and can operate in extreme temperature conditions.


\*6: When multiple outdoor units are connected, their operating temperature range is from -5°C to 46°C in cooling.

\*7: The operating range is -15°C to 46°C only for systems with all indoor units rated at 5.6 kW or more.

VRF VR-IV Series Heat Recovery Modular type




VRF V-IV Series Heat Pump Modular type



VRF J-IVL Series Heat pump type



VRF J-VS & J-IVS & J-IVSeries Heat pump type




## Easy Installation



### Easily transported



A lifting strap can be hooked onto an outdoor unit  
Design of outdoor unit allows for lifting straps to be used




Transportable by forklift  
The outdoor unit can be lifted and transported by forklift.



Fits into a small elevator.


### Easy access

The removable L-shaped front panel provides more room for installation and service work. Multiple installations can be performed easily and efficiently even in tight spaces.




### Flexible pipe connection

Piping and wiring can be accessed from the front, left, right, and bottom.



### Simplified wiring work

The communication wiring can be installed seamlessly among indoor, outdoor, and RB units, which makes the installation of the wiring system easier.




Maximum wiring length:  
**3,600 m**

Note: The automatic address setting is not available on a serially connected multiple refrigerant system.


### Vacuum mode function for easy evacuation

The vacuum mode function enables all expansion valves of an indoor unit to be opened fully, allowing for easier evacuation of air inside pipe lines and indoor units.



### Automatic address setting

Addresses of connected indoor units, RB units, and Signal amplifier can all be set automatically from the PCB in the outdoor unit.



### Easy commissioning with Tools


#### • Service Tool (UTY-ASGXZ1)

The Service Tool checks the refrigerant temperature and pressure, and the operating status of the electronic expansion valves, making it easy to determine if the units are connected properly.



#### • Central Remote Controller (UTY-DCGYZ3)


After the VRF system has been installed. Conveniently, the "test run" required to verify proper system operation can be performed from a nearby Central RC.



# Easy Service and Maintenance

## Designed for easy maintenance

A 7-segment indicator lamp panel provides detailed information on the function setting status, refrigerant temperature and pressure, compressor operation time, and other factors, facilitating self-diagnosis for each unit.




### Easy-to-read 7-segment indicator lamp



Shows the following detailed operation and error status without need of any special tools.

### Error status can be checked on an outdoor unit's display

- System operation mode
- Discharge temperature and pressure
- Compressor operation status
- Address, type, and number of outdoor unit




- Error status can easily be checked on an outdoor unit's display.



## Error diagnosis by Service tool


### Connection to Service tool

- A detailed operation status and recent error history can be checked and analyzed using Service tool.
- The last 5 minutes of operation status can be recorded continuously.



## Remote monitoring

The Web Monitoring system enables the monitoring of the system's operation status at any time via the internet to ensure trouble-free operation. The operating VRF network system in the building can be monitored real time over the internet.






## Heat Pump for Small-capacity type

# VRF J-VS

### System configuration example

- Suitable for air conditioning small and medium-size buildings. One refrigerant system is used for each outdoor unit.
- Multiple indoor units are connected with separation tubes and headers.




Outdoor unit



R32 refrigerant  
with reduced  
global warming potential

- **Zero** Ozone Depletion Potential (ODP<sup>\*1</sup>)
- High environmental properties
- High performance
- Economically efficient



(Reference: IPCC 4th Report)

<sup>\*1</sup> ODP (Ozone Depleting Potential):  
a relative value that indicates the impact per unit weight of ozone-depleting substances released into the atmosphere when CFC-11 (trichlorofluoromethane, CCl<sub>3</sub>F) is fixed at 1.0

<sup>\*2</sup> GWP (Global Warming Potential):  
a measurement that indicates how much other greenhouse gases are capable of warming the Earth based on carbon dioxide. This is the integrated value of radiant energy given to the Earth (i.e., the estimated impact on global warming) expressed as a ratio to CO<sub>2</sub>.

## Sustainable

### European F-Gas Regulation Plan


In light of the UN recommendations, Japanese government targets, and recent social trends, we have set a new long-term target of FY2050 as the target year, and reviewed our medium-

term targets to achieve the long-term target. by resolution of the Board of Directors in August 2023.

2029	Available at J-VS	2033	2035	2050
Split AC & HP Over 12 kW: GWP 750 and above prohibited 12 kW or less: GWP 150 and above prohibited		Split AC & HP Over 12 kW: GWP 150 and above prohibited	Split AC & HP HFC use prohibited	an economy with <b>net-zero</b> greenhouse gas emissions.


### Refrigerant saving design

Refrigerant saving design the compact indoor unit, piping design, and optimization of heat exchanger volume significantly reduce the system refrigerant volume.



### Enhanced disaster safety measures

The system is designed to meet the environmental safety requirements specified in the IEC 60335-40 standard for the use of R32 refrigerant. The environment requiring safety measures is determined by the size of the room in relation to the amount of refrigerant required. For example, if the system is designed for maximum pipe length and the refrigerant charge is 6 kg, safety measures are required for rooms of 15 m<sup>2</sup> or less.




## Saving CO<sub>2</sub>

### TOP Class High Energy Saving

The use of large heat exchanger and a high-efficiency Rotary compressor achieves class-leading SEER/SCOP in all models.


SEER  
**8.27**  
\*045 model

SCOP  
**5.37**  
\*040 model




### More Energy-Saving compressor control

When the room temperature approaches the set temperature after the start of operation, the capacity required for the outdoor unit becomes lower. The minimum compressor speed at this time can now be controlled at a lower value than with conventional products, enabling more energy-efficient operation.



## Small Body

### Easy to carry, easy to install



### Small, lightweight outdoor unit

The outdoor units in this series are much more compact than conventional outdoor units of comparable capacity. They can be installed on a balcony, fitting below the height of the railing. With a height of less than 1 m, they can be installed in tight spaces such as under windows.



### Low noise design



Significantly low noise levels are achieved by the use of a DC twin-rotary compressor, inverter technology, and an advanced airflow pattern design.

## Situational Piping Design

### Long pipe length

Our advanced refrigerant control technology extends the maximum allowable length of refrigerant piping to 120 m. This provides high flexibility in system design.

Long piping lengths are achieved by installing a large-capacity accumulator. No liquid refrigerant is supplied to the compressor even when the required amount of refrigerant is charged in the long piping.



### Up to 13 indoor units\* can be connected

The combination of smaller but sufficiently powerful indoor units and a new outdoor unit with an optimized heat exchanging structure makes it possible to connect up to 13 indoor units, which is the best in its class.

\*: 6 HP model


Rating Capacity range (HP)	4	5	6
Max. Connectable indoor unit	1-11	1-12	1-13

## Sightliness installation

### External static pressure

External static pressure measures up to 30 Pa for 4/5/6 HP models.

Even if the outdoor unit is installed in a small space to hide it, the grille and duct airflow path required for exhaust air can be installed up to a static pressure value of 30 Pa.



### Cooling piping system

New Heat Rejection Technology Cooling piping system "Cooling piping system" is adopted to ensure reliability in high outside air.

Even when the outdoor unit is installed in an environment where heat tends to stay (small space), the cooling system using refrigerant can reduce damage caused by heat from PCBs.




### Specifications

Rated capacity range	HP	4	5	6
Model name		AJY040KCTAH	AJY045KCTAH	AJY054KCTAH
Maximum connectable indoor units		1-11	1-12	1-13
Power source				
Capacity	Cooling Nominal Heating Max. Heating	kW	12.1 12.1 13.6	14.0 14.0 16.0
Input power	Cooling Nominal Heating Max. Heating	kW	3.15 2.55 3.09	3.82 2.91 3.62
EER	Cooling	W/W	3.84	3.66
COP	Nominal Heating Max. Heating		4.74 4.40	4.80 4.41
SEER	Cooling		8.20	8.27
SCOP	Heating		5.37	4.93
$\eta_c$	Cooling	%	325.0	328.0
$\eta_h$	Heating		212.0	194.0
Airflow rate		m³/h	4,240	4,450
Sound pressure level/ Power level	Cooling Heating	dB(A)	52 / 70 54 / 71	53 / 71 55 / 72
Heat exchanger fin			Blue fin	Blue fin
Net Dimensions	Height Width Depth	mm	998 940 320	998 940 320
Weight		kg	74	74
Refrigerant	Type (Global Warming Potential) Charge	kg (CO <sub>2</sub> eq-T)	R32 (675) 2.7 (1.823)	R32 (675) 2.7 (1.823)
Connection pipe diameter	Liquid Gas	mm	9.52 15.88	9.52 15.88
Total pipe length		m	120	120
Max. height difference		m	30	30
Operating Range	Cooling Heating	°C	-5 to 46 -20 to 21	-5 to 46 -20 to 21
Note: Specifications are based on the following conditions. Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB. Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature of 7°CDB/6°CWB. Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. The protective function may work when using it outside the operation range.				

### Dimensions

(Unit: mm)






## Heat Pump for Small-capacity type

# VRF J-IVS


### System configuration example

- Suitable for air conditioning small and medium-size buildings. One refrigerant system is used for each outdoor unit.
- Multiple indoor units are connected with separation tubes and headers.



## New intelligent refrigerant control

Fujitsu General is proposing outdoor units equipped with refrigerant control function. The refrigerant control operates with suitable control corresponding to the heat load of the room and offers a more comfortable environment. The refrigerant control can also provide increased energy savings.




\* The improvements due to the control and the actual sine wave vary depending on the combination of the indoor unit and system operating conditions.

### External static pressure


External static pressure measures up to 25 Pa for 4/5/6 HP models.



### Advanced high-efficiency technology



## Easy to carry, easy to install



## Small, lightweight outdoor unit

The outdoor units in this series are much more compact than conventional outdoor units of comparable capacity. They can be installed on a balcony, fitting below the height of the railing. With a height of less than 1 m, they can be installed in tight spaces such as under windows.



### Low noise design

Significantly low noise levels are achieved by the use of a DC twin-rotary compressor, inverter technology, and an advanced airflow pattern design.

## Long pipe length


Our advanced refrigerant control technology extends the maximum allowable length of refrigerant piping to 80 m. This provides high flexibility in system design.

## Up to 13 indoor units\* can be connected

The combination of smaller but sufficiently powerful indoor units and a new outdoor unit with an optimized heat exchanging structure makes it possible to connect up to 13 indoor units, which is the best in its class.


\*: 6 HP model

Model	Current model (J-IIIS)			New model (J-IVS)		
Rating Capacity range (HP)	4	5	6	4	5	6
Max. Connectable indoor unit	1-7	1-8	1-8	1-11	1-12	1-13




## Non-stop oil recovery operation

A comfortable room condition is maintained during oil recovery mode because the product continues to operate without stopping the cooling or heating operation.



## Easier installation

**Connection check function:** Wiring connections and address settings can be checked thanks to the quick check run function.



- Displays the number of each connected indoor unit.
- Displays the duplicate address number assigned to an indoor unit.

4, 5, 6 HP: AJY040LCLDH / AJY045LCLDH / AJY054LCLDH



## Specifications

Rated capacity range	HP	4	5	6
Model name		AJY040LCLDH	AJY045LCLDH	AJY054LCLDH
Maximum connectable indoor units		1-11	1-12	1-13
Power source		Single phase, ~230 V, 50 Hz		
Capacity	Cooling Nominal Heating Max. Heating	kW	12.1 12.1 13.6	14.0 14.0 16.0
Input power	Cooling Nominal Heating Max. Heating	kW	3.75 3.22 3.99	4.71 3.77 5.04
EER	Cooling	W/W	3.22	2.97
COP	Nominal Heating Max. Heating		3.75 3.40	3.71 3.17
SEER	Cooling		5.83	5.58
SCOP	Heating		3.82	3.96
$\eta_c$	Cooling	%	230.2	220.2
$\eta_h$	Heating		149.8	155.4
Airflow rate		m³/h	4,240	4,400
Sound pressure level/ Power level	Cooling Heating	dB(A)	53 / 67 54 / 68	53 / 69 56 / 69
Heat exchanger fin			Blue fin	Blue fin
Net Dimensions	Height Width Depth	mm	998 970 370	998 970 370
Weight		kg	88	88
Refrigerant	Type (Global Warming Potential)		R410A (2,088)	R410A (2,088)
	Charge kg (CO <sub>2</sub> eq-T)		4.0 (8.4)	4.0 (8.4)
Connection pipe diameter	Liquid Gas	mm	9.52 15.88	9.52 15.88
Total pipe length		m	80	80
Max. height difference			30	30
Operating Range	Cooling Heating	°C	-5 to 46 -20 to 21	-5 to 46 -20 to 21

Note: Specifications are based on the following conditions.

Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.


Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature of 7°CDB/6°CWB.

Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m.

The protective function may work when using it outside the operation range.

## Dimensions

(Unit: mm)






## Heat Pump for Small-capacity type

VRF J-IV


### System configuration example

- Suitable for air conditioning small and medium-size buildings. One refrigerant system is used for each outdoor unit.
- Multiple indoor units are connected with separation tubes and headers.



## New intelligent refrigerant control

Fujitsu General is proposing outdoor units equipped with refrigerant control function. The refrigerant control operates with suitable control corresponding to the heat load of the room and offers a more comfortable environment. The refrigerant control can also provide increased energy savings.




\* The improvements due to the control and the actual sine wave vary depending on the combination of the indoor unit and system operating conditions.

### External static pressure

External static pressure measures up to 30 Pa for 4/5/6 HP.




## Advanced high-efficiency technology



## Efficiency in actual operating conditions

The use of a large heat exchanger and a high-efficiency Scroll compressor achieves class-leading EER/COP (Max. Heating) in all models.

High EER/COP (Maximum Heating)



\* These specifications are determined by cassette combination.

## Long pipe length


Our advanced refrigerant control technology allows us to achieve a total refrigerant pipe length of 180 m. This provides high flexibility in system design.

## Up to 14 indoor units\* can be connected

The combination of smaller but sufficiently powerful indoor units and outdoor units with an optimized heat exchanging structure makes it possible to connect up to 14 indoor units, which is the best in its class.


\*: 6 HP model

Model	Current model (J-III)			New model (J-IV)		
	4	5	6	4	5	6
Rating Capacity range (HP)	4	5	6	4	5	6
Max. Connectable indoor unit	1-9	1-10	1-13	1-11	1-12	1-14




## Non-stop oil recovery operation

A comfortable room condition is maintained during oil recovery mode because the product continues to operate without stopping the cooling or heating operation.



## Easier installation

**Connection check function:** Wiring connections and address settings can be checked thanks to the quick check run function.



- Displays the number of each connected indoor unit
- Displays the duplicate address number assigned to an indoor unit.

4,5,6HP: AJY040LBLDH / AJY045LBLDH / AJY054LBLDH  
AJY040LELDH [3-phase] / AJY045LELDH [3-phase] / AJY054LELDH [3-phase]




## Specifications

Rated capacity range	HP	4	5	6
Model name		AJY040LBLDH	AJY045LBLDH	AJY054LBLDH
Maximum connectable indoor units		1-11	1-12	1-14
Power source				
Capacity	Cooling	kW	Single phase, ~230 V, 50 Hz	
Nominal Heating			12.1	14.0
Max. Heating			13.6	16.0
Input power	Cooling	kW	3.44	4.15
Nominal Heating			3.14	3.60
Max. Heating			3.80	4.50
EER	Cooling	W/W	3.51	3.37
Nominal Heating			3.85	3.88
Max. Heating			3.57	3.55
COP	Cooling	W/W	6.50	6.30
Nominal Heating			3.83	3.93
Max. Heating			3.94	4.17
SEER	Cooling	W/W	257.0	249.0
SCOP	Heating		150.0	154.0
$\eta_c$	Cooling		150.0	155.0
$\eta_h$	Heating	%	6,200	6,600
Airflow rate			257.0	240.0
Sound pressure level/Power level	Cooling		50 / 65	52 / 66
	Heating	dB(A)	52 / 67	55 / 69
Heat exchanger fin			Blue fin	Blue fin
Net Dimensions	Height	mm	1,334	1,334
	Width		970	970
	Depth		370	370
Weight	kg		117	117
Refrigerant	Type (Global Warming Potential)		R410A (2,088)	R410A (2,088)
	Charge kg (CO <sub>2</sub> eq-T)		4.8 (10.0)	5.3 (11.1)
Connection pipe diameter	Liquid	mm	9.52	9.52
	Gas		15.88	15.88
Total pipe length	m		180	180
Max. height difference			50/40 (Outdoor unit: Upper/Lower)	
Operating Range	Cooling	°C	-5 to 46	-5 to 46
	Heating		-20 to 21	-20 to 21
		-5 to 46		
		-20 to 21		

Note: Specifications are based on the following conditions.  
Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.  
Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m.  
The protective function may work when using it outside the operation range.

## Dimensions

(Unit: mm)






## Heat Pump for Small-capacity type

VRF J-IVL


### System configuration example

- Suitable for air conditioning small and medium-size buildings. One refrigerant system is used for each outdoor unit.
- Multiple indoor units are connected with separation tubes and headers.



## New intelligent refrigerant control

Fujitsu General is proposing outdoor units equipped with refrigerant control function. The refrigerant control operates with suitable control corresponding to the heat load of the room and offers a more comfortable environment. The refrigerant control can also provide increased energy savings.



\* The improvements due to the control and the actual sine wave vary depending on the combination of the indoor unit and system operating conditions.


### External static pressure

External static pressure is available up to 60 Pa for 14/16/18 HP.  
(30 Pa for 8/10 HP, 40 Pa for 12 HP)

Capacities are slightly decreased relative to the rated values during high static pressure operations.



## Advanced high-efficiency technology





### Slim & Compact design



### Various installation methods



#### Installation

#### Low noise level in consideration of nearby residents

Front air discharge type with a width of about 1,000 mm, allowing for flexible installation even in narrow spaces.



#### Narrow space behind building Space saving

Small and thin, allowing for direct ground or wall mounting installations even in narrow alleys.




#### Installation on the back street of a building Flexible installation

Slim, low-body front air discharge meets the requirements for installation even in tight spaces. Installation flexibility without blocking the windows of buildings contributes to substantial space savings, even when multiple units are installed.


## Efficiency in actual operating conditions

The use of a large heat exchanger and a high-efficiency Scroll compressor achieves class-leading EER/COP (Max. Heating) in all models.




## Long pipe length

Our advanced refrigerant control technology extends the maximum allowable length of refrigerant piping to 400 m. This provides high flexibility in system design.




## Up to 42 indoor units\* can be connected.

The combination of smaller but sufficiently powerful indoor units and a new outdoor unit with an optimized heat exchanging structure makes it possible to connect up to 42 indoor units, which is the best in its class. \*: 18 HP model



## Class-leading low operating sound

The top-class low operating noise makes it ideal for use in densely populated areas. These low operating sound models are ideal for installation in densely populated areas.



8,10,12 HP: AJY072LELDH / AJY090LELDH / AJY108LELDH  
14,16,18 HP: AJY126LELDH / AJY144LELDH / AJY162LELDH



## Specifications

Rated capacity range	HP	8	10	12	14	16	18
Model name		AJY072LELDH	AJY090LELDH	AJY108LELDH	AJY126LELDH	AJY144LELDH	AJY162LELDH
Maximum connectable indoor units		1-20	1-25	1-30	1-36	1-40	1-42
Power source							
Capacity	Cooling	kW	22.4	28.0	33.5	40.0	45.0
	Nominal Heating		22.4	28.0	33.5	40.0	45.0
	Max. Heating		25.0	31.5	37.5	45.0	50.0
Input power	Cooling	kW	6.30	8.59	10.42	12.12	14.96
	Nominal Heating		4.65	6.61	8.18	9.71	11.81
	Max. Heating		5.45	8.29	10.25	11.81	14.29
EER	Cooling		3.56	3.26	3.22	3.30	3.01
	Nominal Heating		4.82	4.24	4.10	4.12	3.81
	Max. Heating		4.56	3.80	3.66	3.81	3.50
COP	Cooling		7.62	7.50	7.27	7.27	6.29
	Nominal Heating		3.89	3.61	3.63	3.53	3.54
	Max. Heating		301.8	297.0	287.8	287.8	248.6
SEER	Cooling		152.6	141.4	142.2	138.2	137.4
SCOP	Heating		480	480	480	480	480
$\eta_c$	Cooling	%	8,400	9,000	11,000/12,100	13,000	14,000
$\eta_h$	Heating		52/66	54/69	59/73	62/75	64/77
Airflow rate		m³/h	54/66	57/70	62/75	63/76	65/78
Sound pressure level/ Power level	Cooling	dB(A)	1,428	1,428	1,428	1,638	1,638
	Heating		1,080	1,080	1,080	1,080	1,080
Net Dimensions	Width	mm	480	480	480	480	480
	Depth		40	48	48	48	48
Weight		kg	170	177	178	213	217
Refrigerant	Type (Global Warming Potential)		R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)
	Charge kg (CO <sub>2</sub> eq-T)		7.0 (14.6)	7.5 (15.7)	7.5 (15.7)	11.0 (23.0)	11.8 (24.6)
Connection pipe diameter	Liquid	mm	9.52	9.52	12.70	12.70	12.70
	Gas		19.05	22.20	28.58	28.58	28.58
Total pipe length		m	400	400	400	400	400
Max. height difference			50/40 (Outdoor unit: Upper/Lower)				
Operating Range	Cooling	°C	-15 to 46	-15 to 46	-15 to 46	-5 to 46*	-5 to 46*
	Heating		-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21


Note: Specifications are based on the following conditions.

Cooling: Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.  
Heating: Indoor temperature of 20°CDB / 15°CWB, and outdoor temperature of 7°CDB / 6°CWB.  
Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m.

\* The cooling operation range of -15 to 46°C is allowed only when all of the indoor units connected to the system are higher than capacity of 5.6kW.

## Dimensions

(Unit: mm)






## Heat Recovery

Modular type


# VRF VR-IV

### Highly energy-efficient operation

Our heat recovery systems achieve high operating energy efficiency by drawing heat from the room to be cooled and transferring it as energy for rooms that are to be heated.




Our heat recovery systems achieve high operating energy efficiency by drawing heat from the room to be cooled and transferring it as energy for rooms that are to be heated.



## New intelligent refrigerant control

Fujitsu General is proposing outdoor units equipped with refrigerant control function.

The refrigerant control operates with suitable control corresponding to the heat load of the room and offers a more comfortable environment. The refrigerant control can also provide increased energy savings.



\* The improvements due to the control and the actual sine wave vary depending on the combination of the indoor unit and system operating conditions.

## Increase in the number of connectable indoor units

Capacity range of connectable indoor units


New model (VR-IV)	25%* to 150%
Current model (VR-II)	50% to 150%

\*: For modular type, 25% to 49.9% operation in the entire system is available.  
(by one unit operation)

Increased number of connectable indoor units and space saving combinations  
(Unit)

HP	10	12	14	16	...	28	30	32	...	48	
New model (VR-IV)	21	26	30	34	...	60	64	64	...	64	
Current model (VR-II)	15	16	17	21	24	...	42	45	48	...	64

## The energy-saving technology that boosted operation efficiency



## Extended connection ratio (applicable to multiple tenants)


Especially useful when starting partial air conditioning in a building under construction  
Installation can be added flexibly for each tenant.



### Stand-alone

Current model (VR-II)


**Example)** 50% of 12HP minimum connected indoor unit capacity is required



Installation is possible even for tenants who have not yet started operations.

### New model (VR-IV)

**Example)** 25% of 12HP minimum connected indoor unit capacity is required




Installation and commissioning can be added flexibly to meet the opening dates of other tenants.

### Modular type

One outdoor unit operates effectively for the capacities of connectable indoor units in the entire system. (Each of the multiple outdoor units does not dare to operate at 25% capacity: any one of the outdoor units will operate at 50% and the remaining units will each output 0%, i.e., stop operating.)


**Example:** One 10HP outdoor unit performs 25% of the total 20HP outdoor units system.

One 10HP outdoor unit performs 50% of its capacity  
→ Two outdoor units do not perform 25% of the operation.



## Additional installation is possible without changing the main pipe.

A main pipe of a diameter that can be used for the final system is installed at the beginning of the installation.  
Duplication of the work will be avoided as there is no need to change the main pipe as in the previous model.



### All-inverter compressor


#### Large-capacity DC inverter compressor

Large-capacity high-efficient DC twin-rotary compressor with excellent intermediate capability.




#### High-efficiency compressor speed control

The compressor speed control in 0.1 Hz increments ensures a comfortable space with less change in room temperature and less energy loss.



## Efficiency in actual operating conditions


Class-leading high COP (Maximum) The use of our proprietary heat exchanger structure and high-efficiency DC twin-rotary compressors achieves the class-leading coefficient of performance (COP) in every combination.



\* These specifications are determined by Cassette combination.  
\*Multiple outdoor units are not certified by Eurovent.


## Multiple outdoor operation control

When multiple outdoor units are connected, each compressor carries out sophisticated operation. Instead of operating one compressor at full load to distribute the refrigerant to one heat exchanger, all compressors operate at partial load to distribute the refrigerant to all heat exchangers, thereby improving the efficiency of the entire system.




## Heat exchanger refrigerant control

The heat exchanger in the outdoor unit is divided into two parts, upper and lower. The efficiency of the heat exchanger has been improved by adopting an optimum refrigerant path control where the refrigerant is distributed more into the top heat exchanger as this is where there is a greater air flow intake.



## Flexible pipe connection




More flexible refrigerant pipe work is possible due to the use of various piping and RB unit connections, for adjustments to the floor layout and building structure.




## Flexible installation of RB unit

Small and slim design with a height of 198 mm makes it easy to install in tight spaces with height constraints.

- A drain pipe is not required.
- Different positions of a control box can be chosen to accommodate installation conditions.
- Series connection for simplified installation



## Easy maintenance in tight spaces



**Outdoor units lineup** • Combinations other than those listed below are not recommended.

#### Space saving combination

22.4kW (8HP)  AJY072GALDH UNIT : AJY072GALDH	28.0kW (10HP)  AJY090GALDH UNIT : AJY090GALDH	33.5kW (12HP)  AJY108GALDH UNIT : AJY108GALDH	40.0kW (14HP)  AJY126GALDH UNIT : AJY126GALDH	45.0kW (16HP)  AJY144GALDH UNIT : AJY144GALDH
50.4kW (18HP)  AJY162GALDH UNIT : AJY090/072GALDH	56.0kW (20HP)  AJY180GALDH UNIT : AJY090/090GALDH	61.5kW (22HP)  AJY198GALDH UNIT : AJY108/090GALDH	67.0kW (24HP)  AJY216GALDH UNIT : AJY108/108GALDH	73.0kW (26HP)  AJY234GALDH UNIT : AJY144/090GALDH
78.5kW (28HP)  AJY252GALDH UNIT : AJY144/108GALDH	85.0kW (30HP)  AJY270GALDH UNIT : AJY144/126GALDH	90.0kW (32HP)  AJY288GALDH UNIT : AJY144/144GALDH	95.0kW (34HP)  AJY306GALDH UNIT : AJY108/108/090GALDH	100.5kW (36HP)  AJY324GALDH UNIT : AJY108/108/108GALDH
106.5kW (38HP)  AJY342GALDH UNIT : AJY144/108/090GALDH	112.0kW (40HP)  AJY360GALDH UNIT : AJY144/108/108GALDH	118.0kW (42HP)  AJY378GALDH UNIT : AJY144/144/090GALDH	123.5kW (44HP)  AJY396GALDH UNIT : AJY144/144/108GALDH	130.0kW (46HP)  AJY414GALDH UNIT : AJY144/144/126GALDH
135.0kW (48HP)  AJY432GALDH UNIT : AJY144/144/144GALDH				

#### Energy efficiency combination

44.8kW (16HP)  AJY144GALDHH UNIT : AJY072/072GALDH	62.4kW (22HP)  AJY198GALDHH UNIT : AJY126/072GALDH	67.2kW (24HP)  AJY216GALDHH UNIT : AJY072/072/072GALDH	72.8kW (26HP)  AJY234GALDHH UNIT : AJY090/072/072GALDH	78.4kW (28HP)  AJY252GALDHH UNIT : AJY090/090/072GALDH
84.0kW (30HP)  AJY270GALDHH UNIT : AJY090/090/090GALDH	90.4kW (32HP)  AJY288GALDHH UNIT : AJY126/090/072GALDH	96.0kW (34HP)  AJY306GALDHH UNIT : AJY126/090/090GALDH	102.4kW (36HP)  AJY324GALDHH UNIT : AJY126/126/072GALDH	108.0kW (38HP)  AJY342GALDHH UNIT : AJY126/126/090GALDH
113.0kW (40HP)  AJY360GALDHH UNIT : AJY144/126/090GALDH	120.0kW (42HP)  AJY378GALDHH UNIT : AJY126/126/126GALDH	125.0kW (44HP)  AJY396GALDHH UNIT : AJY144/126/126GALDH		


8,10,12HP : AJY072GALDH / AJY090GALDH / AJY108GALDH  
14,16HP : AJY126GALDH / AJY144GALDH







#### Dimensions

(Unit: mm)

##### 8, 10, 12 HP



##### 14, 16 HP



### Outdoor units specifications

#### Space saving combination

Rated capacity range	HP	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48	
Model name		AJY072GALDH	AJY090GALDH	AJY108GALDH	AJY126GALDH	AJY144GALDH	AJY162GALDH	AJY180GALDH	AJY198GALDH	AJY216GALDH	AJY234GALDH	AJY252GALDH	AJY270GALDH	AJY288GALDH	AJY306GALDH	AJY324GALDH	AJY360GALDH	AJY378GALDH	AJY396GALDH	AJY414GALDH	AJY432GALDH		
Unit 1		AJY072GALDH	AJY090GALDH	AJY108GALDH	AJY126GALDH	AJY144GALDH	AJY090GALDH	AJY090GALDH	AJY108GALDH	AJY108GALDH	AJY144GALDH	AJY108GALDH	AJY126GALDH	AJY144GALDH	AJY108GALDH	AJY144GALDH	AJY144GALDH	AJY144GALDH	AJY144GALDH	AJY144GALDH	AJY144GALDH		
Unit 2																							
Unit 3																							
Maximum connectable indoor units*	kW	17	21	26	30	34	39	43	47	52	56	60	64	64	64	64	64	64	64	64	64	64	
Connectable capacity range of indoor units	kW	5.6-33.6	7.0-42.0	8.4-50.2	10.0-60.0	11.3-67.5	12.6-75.6*	14.0-84.0*	15.4-92.2*	16.8-100.5*	18.3-109.5*	19.7-117.7*	21.3-127.5*	22.5-135.0*	23.8-142.5*	25.2-150.7*	26.7-159.7*	28.0-168.0*	29.5-177.0*	30.9-185.2*	32.5-195.0*	33.8-202.5*	
Power source		3-phase, 4-wire, 400 V, 50Hz												3-phase, 4-wire, 400 V, 50Hz									
Capacity	Cooling	kW	22.4	28.0	33.5	40.0	45.0	50.4	56.0	61.5	67.0	73.0	78.5	85.0	90.0	95.0	100.5	106.5	112.0	118.0	123.5	130.0	135.0
Nominal Heating			22.4	28.0	33.5	40.0	42.0	50.4	56.0	61.5	67.0	70.0	75.5	82.0	84.0	95.0	100.5	103.5	109.0	112.0	117.5	124.0	126.0
Max. Heating			25.0	31.5	37.5	45.0	48.0	56.5	63.0	69.0	75.0	79.5	85.5	93.0	96.0	106.5	112.5	117.0	123.0	127.5	133.5	141.0	144.0
Input power	Cooling	kW	6.26	9.53	11.89	13.16	16.71	15.79	19.06	21.42	23.78	26.24	28.60	29.87	33.42	33.31	35.67	38.13	40.49	42.95	45.31	46.58	50.13
Nominal Heating			5.37	7.38	9.16	10.80	11.81	12.75	14.76	16.54	18.32	19.19	20.97	22.61	23.62	25.70	27.48	28.35	30.13	31.00	32.78	34.42	35.43
Max. Heating			6.25	8.96	11.48	13.95	14.98	15.21	17.92	20.44	22.96	23.94	26.46	28.93	29.96	31.92	34.44	35.42	37.94	38.92	41.44	43.91	44.94
EER	Cooling	W/W	3.57	2.93	2.81	3.03	2.69	3.19	2.94	2.87	2.82	2.78	2.74	2.85	2.69	2.85	2.82	2.79	2.75	2.73	2.73	2.79	2.69
Nominal Heating			4.17	3.79	3.65	3.70	3.55	3.95	3.79	3.72	3.66	3.65	3.60	3.63	3.56	3.70	3.66	3.65	3.62	3.61	3.58	3.60	3.56
Max. Heating			4.00	3.51	3.26	3.22	3.20	3.71	3.52	3.38	3.27	3.32	3.23	3.20	3.34	3.27	3.30	3.24	3.22	3.21	3.20	3.22	3.20
SCOP	Cooling	%	7.16	6.61	6.73	6.76	6.27	6.89	6.61	6.67	6.73	6.44	6.50	6.52	6.69	6.73	6.54	6.58	6.42	6.43	6.27		
Heating			3.78	3.76	3.86	4.31	4.41	3.77	3.76	3.81	3.86	4.09	4.14	4.36	4.41	3.83	4.01	4.04	4.19	4.23	4.38	4.41	
ηc	Cooling		283.0	261.0	266.0	267.0	248.0	272.0	261.0	263.5	266.0	254.5	257.0	257.5	248.0	264.3	266.0	258.3	260.0	252.3	254.0	254.3	248.0
ηh	Heating		148.0	147.0	151.0	169.0	173.0	147.5	147.0	149.0	151.0	160.0	162.0	171.0	173.0	149.7	151.0	158.3	164.3	165.7	171.7	173.0	
Air flow rate	High	m³/h	11,100	11,100	13,000	13,000	11,100*2	11,100*2	11,100*2	11,100*2	13,000+11,100	13,000+11,100	13,000*2	13,000*2	11,100*3	11,100*3	13,000+11,100*2	13,000+11,100*2	13,000+2+11,100	13,000+2+11,100	13,000*3	13,000*3	
Sound pressure level*	Cooling	dB(A)	56 / 77	58 / 78	59 / 79	60 / 82	60 / 81	61 / 81	62 / 82	62 / 82	63 / 83	63 / 83	64 / 84	64 / 85	64 / 85	64 / 85	64 / 85	65 / 85	65 / 85	65 / 87	65 / 87	66 / 87	
Power level	Heating		58 / 79	59 / 79	63 / 82	62 / 83	63 / 83	62 / 82	62 / 82	64 / 84	66 / 85	66 / 86	66 / 86	67 / 86	67 / 86	67 / 86	67 / 86	67 / 86	67 / 87	67 / 87	68 / 87	68 / 87	
Max. External static pressure	Pa		80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	
Compressor motor output	kW		7.5	7.5	7.5	11.0	11.0	7.5 × 2	7.5 × 2	7.5 × 2	11.0 + 7.5	11.0 + 7.5	11.0 × 2	11.0 × 2	7.5 × 3	11.0 + 7.5 × 2	11.0 + 7.5 × 2	11.0 + 7.5 × 2	11.0 + 7.5 × 2	11.0 + 7.5 × 2	11.0 + 7.5 × 2	11.0 × 3	
Heat exchanger fin			Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin					
Net Dimensions	Height	mm	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	
Width			930	930	930	1,240	1,240	1,240	1,240	1,240	1,240	1,240	1,240	1,240	1,240	1,240	1,240	1,240	1,240	1,240	1,240	1,240	
Depth			765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	
Weight	kg		262	262	262	286	286	262 × 2	262 × 2	262 × 2	262 × 2	286 + 262	286 + 262	286 × 2	286 × 2	262 × 3	262 + 262 × 2	286 + 262 × 2	286 × 2 + 262	286 × 3	286 × 3	286 × 3	
Refrigerant	Type (Global Warming Potential)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)			
Charge	kg (O2eq-T)	11.8 (24.6)	11.8 (24.6)	11.8 (24.6)	11.8 (24.6)	11.8 (24.6)	11.8 × 2 (24.6 × 2)	11.8 × 2															





## Heat Pump

Modular type

# VRF V-IV


### System configuration example

- Suitable for air conditioning midsize and large buildings. Connecting each outdoor unit makes it possible to create a high-capacity system.
- Multiple indoor units are connected with separation tubes and headers.



## New intelligent refrigerant control

Fujitsu General is proposing outdoor units equipped with refrigerant control function. The refrigerant control operates with subtle control corresponding to the heat load of the room and offers a more comfortable environment. The refrigerant control can also provide increased energy savings.




\* The improvements due to the control and the actual sine wave vary depending on the combination of the indoor unit and system operating conditions.

### Efficiency in actual operating conditions


The use of our proprietary heat exchanger structure and high-efficiency DC twin-rotary compressors achieves the class-leading coefficient of performance (COP) in every combination.

#### Space saving combination



\* These specifications are determined by Cassette combination.

#### Energy efficiency combination



\* Multiple outdoor units are not certified by Eurovent.

### The energy-saving technology that boosted operation efficiency



#### Powerful large propeller fan

The fan uses CFD\* technology to achieve both high performance and low noise operation. \*CFD: Computational Fluid Dynamics

#### 3-phase DC fan motor

The use of a DC fan motor with sophisticated driver control improves energy efficiency substantially. In addition, low noise is realized by the DC fan motor.

#### Sine-wave DC inverter control

High-efficiency is realized by the adoption of reduced switching loss IPM.

#### 4-face heat exchanger

The 4-face heat exchanger increases the effective surface area and significantly improves heat-exchanging efficiency.

#### Subcooling heat exchanger

High heat exchange efficiency is achieved by using an internal projection-shape double-pipe construction.

#### High-efficient, large-capacity DC twin-rotary compressor

Large-capacity high-efficient DC twin-rotary compressor with excellent intermediate capability.

#### Front intake port (Corner cut air inlet structure)

In multiple outdoor unit installations, the unique front intake design improves airflow into the heat exchanger.

**Outdoor units lineup** • Combinations other than those listed below are not recommended.

#### Space saving combination

22.4 kW (8 HP)  AJY072LALDH UNIT: AJY072LALDH	28.0 kW (10 HP)  AJY090LALDH UNIT: AJY090LALDH	33.5 kW (12 HP)  AJY108LALDH UNIT: AJY108LALDH	40.0 kW (14 HP)  AJY126LALDH UNIT: AJY126LALDH	45.0 kW (16 HP)  AJY144LALDH UNIT: AJY144LALDH
50.4 kW (18 HP)  AJY162LALDH UNIT: AJY090/072LALDH	56.0 kW (20 HP)  AJY180LALDH UNIT: AJY090/090LALDH	62.4 kW (22 HP)  AJY198LALDH UNIT: AJY126/072LALDH	68.0 kW (24 HP)  AJY216LALDH UNIT: AJY126/090LALDH	73.0 kW (26 HP)  AJY234LALDH UNIT: AJY144/090LALDH
78.5 kW (28 HP)  AJY252LALDH UNIT: AJY144/108LALDH	85.0 kW (30 HP)  AJY270LALDH UNIT: AJY144/126LALDH	90.0 kW (32 HP)  AJY288LALDH UNIT: AJY144/144LALDH	95.4 kW (34 HP)  AJY306LALDH UNIT: AJY144/090/072LALDH	101.0 kW (36 HP)  AJY324LALDH UNIT: AJY144/090/090LALDH
106.5 kW (38 HP)  AJY342LALDH UNIT: AJY144/108/090LALDH	113.0 kW (40 HP)  AJY360LALDH UNIT: AJY144/126/090LALDH	118.0 kW (42 HP)  AJY378LALDH UNIT: AJY144/144/090LALDH	123.5 kW (44 HP)  AJY396LALDH UNIT: AJY144/144/108LALDH	130.0 kW (46 HP)  AJY414LALDH UNIT: AJY144/144/126LALDH
135.0 kW (48 HP)  AJY432LALDH UNIT: AJY144/144/144LALDH				

#### Energy efficiency combination

44.8 kW (16 HP)  AJY144LALDHH UNIT: AJY072/072LALDH	55.9 kW (20 HP)  AJY180LALDHH UNIT: AJY108/072LALDH	67.2 kW (24 HP)  AJY216LALDHH UNIT: AJY072/072/072LALDH	72.8 kW (26 HP)  AJY234LALDHH UNIT: AJY090/072/072LALDH	78.3 kW (28 HP)  AJY252LALDHH UNIT: AJY108/072/072LALDH
84.8 kW (30 HP)  AJY270LALDHH UNIT: AJY126/072/072LALDH	89.4 kW (32 HP)  AJY288LALDHH UNIT: AJY108/108/072LALDH	95.9 kW (34 HP)  AJY306LALDHH UNIT: AJY126/108/072LALDH	100.5 kW (36 HP)  AJY324LALDHH UNIT: AJY108/108/108LALDH	107.0 kW (38 HP)  AJY342LALDHH UNIT: AJY126/108/108LALDH
113.5 kW (40 HP)  AJY360LALDHH UNIT: AJY126/126/108LALDH	120.0 kW (42 HP)  AJY378LALDHH UNIT: AJY126/126/126LALDH	125.0 kW (44 HP)  AJY396LALDHH UNIT: AJY144/126/126LALDH		




8, 10 HP: AJY072LALDH / AJY090LALDH  
12, 14, 16 HP: AJY108LALDH / AJY126LALDH / AJY144LALDH







#### Dimensions

(Unit: mm)

**8, 10 HP**



**12, 14, 16 HP**



## Outdoor unit specifications

## Space saving combination

## Energy Efficiency Combination

Note: Specifications are subject to the following conditions:

Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.

Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.

Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m.

When cooling operation is conducted at an outdoor air temperature below -5°C,  
the outdoor unit must be installed in a position that is higher than or equal to that of the indoor units.

\* These specifications are determined by ducted combination.

\*Multiple outdoor units are not certified by Eurovent.

\*1 Minimum connectable indoor unit number is 2.  
However, the ARXC72 and ARXC90 can be used with a signal connection.

\*2 The noise level is the value measured in an anechoic room.

2 The noise levels are the values measured in dB on a decibel scale.

In measured in an actual installation, the measured value is typically lower than the indicated value due to ambient noise and reflections.

These specifications are determined by ducted combination.

Specimens are collected by local communities.

# VRF INDOOR UNITS

17 types and 95 models available to meet the requirements of any building design.

Indoor units for the VRF Systems are compact, highly efficient, quiet, and user-friendly. Fujitsu General offers a variety of types and capacities for its indoor units that are easy to install and maintain. In addition, a variety of optional parts are available to provide an even more desirable air conditioning experience to users.

- V-058 VRF Indoor Unit Lineup for J-VS
- V-060 Compact Cassette Grid type
- V-062 Low Static Pressure Duct Slim Duct/Slim Concealed Floor
- V-064 Wall-mounted type
  
- V-066 VRF Indoor Unit Lineup for J-IVS, J-IV, J-IVL, VR-IV, V-IV
- V-068 Compact Cassette Grid type
- V-070 Cassette Slim type Circular Flow
- V-072 Cassette Large type Circular Flow
- V-074 Cassette One-way Flow type
- V-076 3D Flow Cassette
- V-078 Low Static Pressure Duct Mini Duct
- V-080 Low Static Pressure Duct Slim Duct/Slim Concealed Floor
- V-082 Low Static Pressure Duct
- V-084 Medium Static Pressure Duct
- V-086 High Static Pressure Duct
- V-088 Compact Floor
- V-090 Floor/Ceiling
- V-092 Ceiling
- V-094 Wall-mounted (EEV Internal/external)



## VRF Indoor Unit Lineup for J-VS

Capacity range (kW)				1.1	1.7	2.2	2.8	3.6	4.0	4.5	5.6	7.1
Class				4	5	7	9	12	14	14	18	24
Cassette	Compact type	Compact Grid type/Standard type		AUXB004HLAH	AUXB005HLAH	AUXB007HLAH	AUXB009HLAH	AUXB012HLAH		AUXB014HLAH	AUXB018HLAH	
		High Efficiency*1					AUXN009HLAH	AUXN012HLAH		AUXN014HLAH		
Duct	Low Static Pressure Duct	Slim Duct (With drain pump)	 004 - 014    018    024	ARXD004HLAH	ARXD005HLAH	ARXD007HLAH	ARXD009HLAH	ARXD012HLAH		ARXD014HLAH	ARXD018HLAH	ARXD024HLAH
		High Efficiency*1	 009 - 014				ARXP009HLAH	ARXP012HLAH		ARXP014HLAH		
Wall-mounted type	Wall-mounted type		 004 - 014	ASYA004HCAH	ASYA005HCAH	ASYA007HCAH	ASYA009HCAH	ASYA012HCAH	ASYA014HCAH			
	Wall-mounted type (EEV external)		 004 - 014	ASYE004HCAH	ASYE005HCAH	ASYE007HCAH	ASYE009HCAH	ASYE012HCAH	ASYE014HCAH			

This model requires the EV kit to be connected.

This model requires the EV kit to be connected.

\*1: Production by order

Specifications and design are subject to change without notice.

\*Products other than ducts can be connected to J-IV, J-IVS, J-IVL, V-IV, VR-IV

NEW


## Compact Cassette

Grid type

DC  
FAN

### Compact and stylish panel

The compact and stylish panel fits nicely into a grid type ceiling. The linear design is a perfect fit into a grid of 620 mm × 620 mm in the ceiling.



### Easy maintenance

You can access the unit for maintenance just by removing a ceiling panel right next to the grille. As no inspection hole needs to be cut through the ceiling, no additional construction cost is incurred.



The air inlet grille can be installed to open in any direction for easy maintenance.



### Flexible installation

The unit fits nicely into the decor of a grid type ceiling and can be installed near a lighting or a ventilation opening.



### High ceiling mode

The cassette can be installed up to a height of 3.0 m.  
(012/014/018).

Model code	Maximum height from floor to ceiling (m)	
	Standard mode	High ceiling mode
004	2.7	-
005	2.7	-
007	2.7	-
009	2.7	-
012	2.7	3.0
014	2.7	3.0
018	2.7	3.0

Model: AUXB004HLAH / AUXB005HLAH / AUXB007HLAH / AUXB009HLAH  
AUXB012HLAH / AUXB014HLAH / AUXB018HLAH  
AUXN009HLAH / AUXN012HLAH / AUXN014HLAH \* Production by order



### Specifications

Model name	AUXB004HLAH	AUXB005HLAH	AUXB007HLAH	AUXB009HLAH	AUXB012HLAH	AUXB014HLAH	AUXB018HLAH	AUXN009HLAH	AUXN012HLAH	AUXN014HLAH
Power source	Single phase, 220-240V, 50Hz									
Capacity	Cooling	kW	1.1	1.7	2.2	2.8	3.6	4.5	5.6	2.8
	Heating		1.3	1.9	2.8	3.2	4.1	5.0	6.3	3.2
Input power		W	21	21	23	24	27	33	50	41
	High		530	530	540	550	600	680	820	750
Airflow rate (Cooling / Heating)*	Med-High		490 / 480	490 / 480	500	520	560	620	660	550
	Med		450 / 430	450 / 430	460	480	520	560	590	480
	Med-Low		420 / 380	420 / 380	420	440	480	500	520	440
	Low		390 / 340	390 / 340	390	400	430	440	460	400
	Quiet		350 / 300	350 / 300	350	350	390	390	400	350
	High		34	34	34	35	37	39	45	42
	Med-High		32 / 31	32 / 31	32	33	34	37	39	35
Sound pressure level (Cooling / Heating)*	Med		30 / 29	30 / 29	30	31	33	34	36	31
	Med-Low		28 / 26	28 / 26	28	29	31	32	33	31
	Low		27 / 24	27 / 24	27	27	29	30	30	29
	Quiet		25 / 21	25 / 21	25	25	27	27	27	27
Net Dimensions (H × W × D)		mm	245 × 570 × 570						245 × 570 × 570	
Weight		kg	14.5	14.5	15	15	15.5	15.5	17	15
Connection pipe diameter	Liquid (Flare)	mm	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35
	Gas (Flare)		9.52	9.52	9.52	9.52	12.70	12.70	12.70	12.70
Drain Hose Diameter (I.D./O.D.)		mm	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32
Cassette Grille	Model name		UTG-UFYH-W						UTG-UFYH-W	
	Net Dimensions (H × W × D)	mm	49 × 620 × 620						49 × 620 × 620	
	Weight	kg	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3

Note: Specifications are subject to the following conditions:


Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature of 7°CDB/6°CWB.

Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V]

\*The value is the same for cooling and heating if there is one value.


**Optional parts** \*For more details, please refer to the chapter "Optional parts".

Wireless remote controller:	UTY-LNVY	External power supply unit:	UTZ-GXXD
Flesh Air Intake Kit:	UTZ-VXA	WLAN adapter:	UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIF1Z1
Insulation kit for high humidity:	UTZ-KXGC	Gas sensor kit:	UTY-SGZY
Silver Ion Filter:	UTD-HFAA	Expansion kit:	UTZ-JXXA
Remote sensor kit:	UTY-XSZXZ1	Air Outlet Shutter Plate:	UTR-YDZB
Cassette Grille:	UTG-UFYH-W		



### Dimensions

(Unit: mm)



NEW


## Low Static Pressure Duct Slim Duct

DC FAN




### Slim design

Slim design allows for installation in a tight ceiling space.



### Air intake

Air intake direction can be selected to match the installation site.



### Wide range of static pressures

The use of a DC fan motor makes it possible to adjust the static pressure between 0 and 90 Pa.

The static pressure range can be changed by a remote controller.



Static pressure range  
0 to 90 Pa

\* 024 model static pressure range is 0 to 50 Pa.

### Auto louver grille kit (Option)


The optional clean-looking flat Auto louver blends into any interior and provides a comfortable airflow.



### Filter (Accessory)

ARXD004-018

ARXD024



Model: ARXD004HLAH / ARXD005HLAH / ARXD007HLAH / ARXD009HLAH

ARXD012HLAH / ARXD014HLAH / ARXD018HLAH / ARXD024HLAH

ARXP009HLAH / ARXP012HLAH / ARXP014HLAH \* Production by order



ARXD004/005/007/009/012/014HLAH  
ARXP009/012/014HLAH



ARXK018HLAH



ARXK024HLAH

### Specifications

Model name	ARXD004HLAH	ARXD005HLAH	ARXD007HLAH	ARXD009HLAH	ARXD012HLAH	ARXD014HLAH	ARXD018HLAH	ARXD024HLAH	ARXP009HLAH	ARXP012HLAH	ARXP014HLAH
Power source	Single phase, 220-240V, 50Hz										Single phase, 220-240V, 50Hz
Capacity	1.1	1.7	2.2	2.8	3.6	4.5	5.6	7.1	2.8	3.6	4.5
	1.3	1.9	2.8	3.2	4.0	5.0	6.3	8.0	3.2	4.0	5.0
Input power	38	38	41	47	48	84	76	107	77	128	128
	530	530	550	600	580	790	930	1,250	770	940	940
Airflow rate	High	480	480	520	550	720	880	1,180	630	810	810
	Med-High	440	440	480	500	520	640	780	1,060	530	660
	Med	410	410	450	460	480	560	670	930	480	580
	Med-Low	370	370	400	400	430	470	580	810	430	490
	Low	320	320	360	360	350	370	510	640	380	390
	Quiet										
Static pressure range	0 to 90	0 to 90	0 to 90	0 to 90	0 to 90	0 to 90	0 to 90	0 to 90	0 to 50	0 to 25	0 to 25
Standard static pressure	25	25	25	25	25	25	25	25	25	25	25
	26	26	28	29	30	34	34	35	36	40	40
Airflow rate	High	26	26	26	27	28	32	31	32	38	38
	Med-High	26	26	26	27	28	32	31	32	38	38
	Med	25	25	25	25	27	30	29	30	33	33
	Med-Low	24	24	24	24	26	28	27	27	31	31
	Low	22	22	22	22	24	25	25	24	27	27
	Quiet	21	21	21	21	22	22	23	21	23	24
Sound pressure level	dB(A)	Pa	m³/h	kW							
Net Dimensions (H × W × D)	mm	198 × 700 × 620							198 × 900 × 620	198 × 1,100 × 620	198 × 700 × 620
Weight	kg	16	16	16.5	16.5	17	17	21	25	16.5	17
Connection pipe diameter	Liquid (Flare)	6.35	6.35	6.35	6.35	6.35	6.35	9.52	9.52	6.35	6.35
	Gas (Flare)	9.52	9.52	9.52	9.52	12.70	12.70	12.70	12.70	15.88	12.70
	Drain Hose Diameter (I.D./O.D.)	mm	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32	25 / 32

Note: Specifications are subject to the following conditions:

Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.

Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature of 7°CDB/6°CWB.

Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V]


\*1: This value is under cooling operation.

### Optional parts

\*For more details, please refer to the chapter "Optional parts".


Wireless remote controller:	UTY-LNVA*	Auto Louver Grille Kit: UTD-GXTA-W (004-014)
Remote sensor unit:	UTY-XSZXZ1	UTD-GXTB-W (018)
IR receiver unit:	UTY-TRHX	UTD-GXTC-W (024)
WLAN adapter:	UTY-TFSXJ3	Silver Ion Filter: UTD-HFTA (004-014)
	UTY-TFSXZ1	UTD-HFTB (018)
	FG-AC-WIF1Z1	UTD-HFTC (024)
External power supply unit:	UTZ-GXXD	Gas sensor kit: UTY-SGZY
Expansion kit:	UTZ-JXXA	

\*IR receiver unit (UTY-TRHX) is required.




### Dimensions

(Unit: mm)



ARXD004-014HLAH	ARXD018HLAH	ARXD024HLAH
a 574	774	974
b P200×2=400	P200×3=600	P200×4=800
c 734	934	1,134
d 700	900	1,100
e 650	850	1,050
f P100×6=600	P100×8=800	P100×10=1,000

\*The design of the service access depends on the installation method. Refer to the installation manual for more information.



NEW

## Wall-mounted type



DC FAN

### Highly-efficiency, compact design

The 004-014 models share the same design. The high-density and large heat exchanger achieves a highly-efficiency and compact design. The compact body blends in well with conference rooms and offices, providing comfortable air conditioning.



### More comfortable airflow

The unique power diffuser provides comfortable air conditioning.

#### Heating

The vertical airflow provides powerful floor-level heating.




#### Cooling

The left/right airflow avoids blowing cool air directly at the occupants in a room.



### Quiet operation & 6-Step fan speed control


The airflow pattern achieves significant noise reduction. Multistep airflow adjustment to suit the environment



### The Occupancy sensor contributes to further energy savings.

Energy saving operation starts automatically by detecting the motion of a person. Two modes of save operation mode and stop mode can be selected.

\*If you want to use the Occupancy sensor control' function, you need an setting device that can set the Occupancy sensor control' function. For example: Wired RC (Touch panel).



**Model:** ASYA004HCAH / ASYA005HCAH / ASYA007HCAH  
ASYA009HCAH / ASYA012HCAH / ASYA014HCAH

[external EEV]  
ASYE004HCAH / ASYE005HCAH / ASYE007HCAH  
ASYE009HCAH / ASYE012HCAH / ASYE014HCAH



### Specifications

Model name	Single phase, 220-240V, 50Hz								Single phase, 220-240V, 50Hz																
	Power source		ASYA004HCAH		ASYA005HCAH		ASYA007HCAH		ASYA009HCAH		ASYA012HCAH		ASYA014HCAH		ASYE004HCAH		ASYE005HCAH		ASYE007HCAH		ASYE009HCAH		ASYE012HCAH		ASYE014HCAH
Capacity	Cooling	kW	1.1	1.7	2.2	2.8	3.6	4.0	1.1	1.7	2.2	2.8	3.6	4.0	1.1	1.7	2.2	2.8	3.6	4.0					
	Heating		1.3	1.9	2.8	3.2	4.0	4.5	1.3	1.9	2.8	3.2	4.0	4.5	1.3	1.9	2.8	3.2	4.0	4.5					
Input power	High	W	450	450	550	590	660	770	450	450	550	590	660	770	450	450	550	590	660	770					
	Med-High		430	430	490	550	590	710	430	430	490	550	590	710	430	430	490	550	590	710					
Airflow rate	Med	m³/h	400	400	450	490	550	650	400	400	450	490	550	650	400	400	450	490	550	650					
	Med-Low		380	380	390	420	510	590	380	380	390	420	510	590	380	380	390	420	510	590					
Sound pressure level	Low	dB(A)	360	360	360	450	530	360	360	360	450	530	360	360	360	360	450	530	360	360					
	Quiet		310	310	320	320	320	310	310	310	320	320	310	310	310	310	320	320	320	320					
Net Dimensions (H × W × D)	mm								268 × 840 × 203								268 × 840 × 203								
	Weight		kg	8	8	8.5	8.5	8.5	8.5	8	8	8.5	8.5	8.5	8.5	8	8	8.5	8.5	8.5	8.5				
Connection pipe diameter	Liquid (Flare)	mm	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35				
	Gas (Flare)		9.52	9.52	9.52	9.52	9.52	12.70	12.70	9.52	9.52	9.52	9.52	9.52	12.70	12.70	12.70	12.70	12.70	12.70	12.70				
Drain Hose Diameter (I.D./O.D.)	mm								13.8/15.8 to16.7								13.8/15.8 to16.7								
	EV kit (optional)		—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	UTR-EV09XC	UTR-EV14XC			

Note: Specifications are subject to the following conditions:

Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.

Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.

Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V]

When connecting ASY\*004G\*\*H, ASY\*007G\*\*H, ASY\*009G\*\*H to an outdoor unit other than the outdoor unit of the J-IVL Series, the gas pipe diameter should be Ø12.70 mm.



### Optional parts

\*For more details, please refer to the chapter "Optional parts".

Wireless remote controller:	UTY-LNVY
External power supply unit:	UTZ-GXXD
WLAN adapter:	UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIF1Z1
Silver Ion Filter:	UTR-FA16-5
Remote sensor kit:	UTY-XSZXZ1
Gas sensor kit:	UTY-SGZY
Expansion kit:	UTZ-JXXA

### Dimensions

(Unit: mm)



# VRF Indoor Unit Lineup for J-IVS J-IV J-IVL VR-IV V-IV

Capacity range (kW)			1.1	2.2	2.8	3.6	4.0	4.5	5.6	7.1	9.0	10.0	11.2	12.5	14.0	18.0	22.4	25.0	28.0
Class			4	7	9	12	14	14	18	24	30	34	36	45	54	60	72	90	96
Cassette	Compact type	Compact Grid type/Standard type		AUXB 004 GLEH	AUXB 007 GLEH	AUXB 009 GLEH	AUXB 012 GLEH			AUXB 014 GLEH	AUXB 018 GLEH	AUXB 024 GLEH							
	Slim type	Circular Flow								AUXM 018 GLEH	AUXM 024 GLEH	AUXM 030 GLEH							
	Large type	Circular Flow								AUXK 018 GLEH	AUXK 024 GLEH	AUXK 030 GLEH	AUXK 034 GLEH	AUXK 036 GLEH	AUXK 045 GLEH	AUXK 054 GLEH			
	One-way Flow type	One-way Flow	004 - 012 014 - 024	AUXV 004 GLEH	AUXV 007 GLEH	AUXV 009 GLEH	AUXV 012 GLEH			AUXV 014 GLEH	AUXV 018 GLEH	AUXV 024 GLEH							
	3D Flow type	3D Flow								AUXS 018 GLEH	AUXS 024 GLEH								
Duct	Low Static Pressure Duct	Mini Duct (With drain pump)	004 - 014 018 024	ARXK 004 GLGH	ARXK 007 GLGH	ARXK 009 GLGH	ARXK 012 GLGH			ARXK 014 GLGH	ARXK 018 GLGH	ARXK 024 GLGH							
		Slim Duct (With drain pump)	04/007 - 014 018 024	ARXD 04 GALH* <sup>2</sup>	ARXD 007 GLEH	ARXD 009 GLEH	ARXD 012 GLEH			ARXD 014 GLEH	ARXD 018 GLEH	ARXD 024 GLEH							
		High Efficiency* <sup>3</sup>									ARXP 018 GLFH		ARXP 030 GLFH						
	Medium static pressure duct	Normal										ARXA 024 GLEH	ARXA 030 GLEH		ARXA 036 GLEH	ARXA 045 GLEH			
	High Static Pressure Duct	Normal	036/45 - 60 072 - 090 096											ARXC 036 GTEH	ARXC 045 GTEH		ARXC 060 GTEH* <sup>1</sup>	ARXC 072 GTEH* <sup>1</sup>	ARXC 090 GTEH* <sup>1</sup>
Floor	Floor (*Same as Ceiling models)						ABYA 012 GTEH			ABYA 014 GTEH	ABYA 018 GTEH	ABYA 024 GTEH							
	Slim Concealed Floor (*Same as Slim Duct models)	04/007 - 014 018 024		ARXD 04 GALH* <sup>2</sup>	ARXD 007 GLEH	ARXD 009 GLEH	ARXD 012 GLEH			ARXD 014 GLEH	ARXD 018 GLEH	ARXD 024 GLEH							
	Compact Floor			AGYA 004 GCGH	AGYA 007 GCGH	AGYA 009 GCGH	AGYA 012 GCGH	AGYA 014 GCGH											
	Compact Floor (EEV external)			AGYE 004 GCEH	AGYE 007 GCEH	AGYE 009 GCEH	AGYE 012 GCEH	AGYE 014 GCEH											
Ceiling		012 - 024 030 - 054					ABYA 012 GTEH			ABYA 014 GTEH	ABYA 018 GTEH	ABYA 024 GTEH	ABYA 030 GTEH		ABYA 036 GTEH	ABYA 045 GTEH	ABYA 054 GTEH		
Wall-mounted type	Wall-mounted type	004 - 014 18 - 24 030 - 034		ASYA 004 GCGH	ASYA 007 GCGH	ASYA 009 GCGH	ASYA 012 GCGH	ASYA 014 GCGH			ASYA 18 GBCH	ASYA 24 GBCH	ASYA 030 GTEH	ASYA 034 GTEH					
	Wall-mounted type (EEV external)	004 - 014		ASYE 004 GCEH	ASYE 007 GCEH	ASYE 009 GCEH	ASYE 012 GCEH	ASYE 014 GCEH											

\*1: ARXC060/072/090/096G cannot be connected to J-IVS/J-IV Series.  
\*2: ARXD04GALH cannot be connected to J-IVS/J-IVL/VR-IV Series.

\*3: Production by order  
Specifications and design are subject to change without notice.

## Compact Cassette


Grid type



DC FAN

### Compact and stylish panel

The compact and stylish panel fits nicely into a grid type ceiling. The linear design is a perfect fit into a grid of 620 mm × 620 mm in the ceiling.



### Easy maintenance

You can access the unit for maintenance just by removing a ceiling panel right next to the grille. As no inspection hole needs to be cut through the ceiling, no additional construction cost is incurred.




The air inlet grille can be installed to open in any direction for easy maintenance.



### Flexible installation

The unit fits nicely into the decor of a grid type ceiling and can be installed near a lighting or a ventilation opening.



### High ceiling mode

The cassette can be installed up to a height of 3.0 m.  
(012/014/018/024).

Model code	Maximum height from floor to ceiling (m)	
	Standard mode	High ceiling mode
004	2.7	-
007	2.7	-
009	2.7	-
012	2.7	3.0
014	2.7	3.0
018	2.7	3.0
024	2.7	3.0

Model: AUXB004GLEH / AUXB007GLEH / AUXB009GLEH  
AUXB012GLEH / AUXB014GLEH / AUXB018GLEH  
AUXB024GLEH



### Specifications

Model name	AUXB004GLEH	AUXB007GLEH	AUXB009GLEH	AUXB012GLEH	AUXB014GLEH	AUXB018GLEH	AUXB024GLEH	
Power source	Single phase, ~230 V, 50 Hz							
Capacity	Cooling kW	1.1 1.3	2.2 2.8	2.8 3.2	3.6 4.1	4.5 5.0	5.6 6.3	
Input power	W	23	25	25	29	35	36	
Airflow rate	m³/h	530/530 490/480 450/430 420/380 390/340 350/300	540 500 460 420 400 350	550 520 480 440 430 350	600 560 520 480 440 390	680 620 560 500 460 400	710 660 590 520 460 400	1,030 910 790 680 560 450
Sound pressure level	dB(A)	34/34 32/31 30/29 28/26 27/24 25/21	34 32 30 28 27 25	35 33 31 29 27 25	37 34 33 31 29 27	38 37 34 32 30 27	41 39 36 33 30 30	50 46 43 39 35 30
Net Dimensions (H × W × D)	mm	245 × 570 × 570	245 × 570 × 570	245 × 570 × 570	245 × 570 × 570	245 × 570 × 570	245 × 570 × 570	245 × 570 × 570
Weight	kg	14.5	15	15	15	15	15	17
Connection pipe diameter	Liquid (Flare) mm	6.35	6.35	6.35	6.35	6.35	6.35	9.52
Drain Hose Diameter (I.D./O.D.)	mm	9.52	9.52	9.52	12.70	12.70	12.70	15.88
Cassette Grille	Model name Net Dimensions (H × W × D) Weight	UTG-UFYE-W/UTG-UFYC-W 49 × 620 × 620/50 × 700 × 700 2.3/2.6						


Note: Specifications are subject to the following conditions:  
Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature of 7°CDB/6°CWB.  
Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V]

\*1: This value is under cooling operation.

### Optional parts


\*For more details, please refer to the chapter "Optional parts".

Air Outlet Shutter Plate:	UTR-YDZB	Cassette Grille:	UTG-UFYE-W, UTG-UFYC-W
Flesh Air Intake Kit:	UTZ-VXA	External power supply unit:	UTZ-GXXA, UTZ-GXXC*
Insulation kit for high humidity:	UTZ-KXGC	WLAN adapter:	UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIF1Z1
Silver Ion Filter:	UTD-HFAA	Remote sensor kit:	UTY-XS2XZ1
Remote sensor kit:	UTY-XS2XZ1		



### Dimensions

(Unit: mm)




## Cassette Slim type Circular Flow

DC FAN



### Unique circular flow design

This Cassette type air conditioner is equipped with a high performance DC fan motor, a turbo fan, and a louver to propel powerful airflows in all directions.



### Uniform temperature air conditioning


Achieve a comfortable air conditioning spread to every corner of the room thanks to the circular flow and wide vertical airflow.



### Individual louver control

Each louver can be set individually by the Touch panel wired remote controller so the user can enjoy the comfort of different directional airflows according to the room layout.

\* UTY-RNRYZ5 Wired remote controller with touch panel and UTY-DCGYZ3 Central remote controller only



### The Human sensor contributes to further energy savings.

Energy saving operation starts automatically by detecting the motion of a person. Two modes of save operation mode and stop mode can be selected.

\* UTY-RNRYZ5 Wired remote controller with touch panel and UTY-DCGYZ3 Central remote controller only



2 modes are available to choose from:

Auto economy mode

The air conditioner switches to operate on reduced power when it detects that the room is unoccupied.

Auto-off mode

The air conditioner stops operating when it detects that the room is unoccupied.

Model: AUXM018GLEH / AUXM024GLEH / AUXM030GLEH



### Specifications

Model name	AUXM018GLEH		AUXM024GLEH		AUXM030GLEH
Power source	Single phase, ~230 V, 50 Hz				
Capacity	Cooling	kW	5.6	7.1	9.0
	Heating		6.3	8.0	10.0
Input power		W	20	25	49
	High		1,050	1,120	1,470
	Med-High		930	1,050	1,160
	Med		900	930	1,070
	Med-Low		870	900	930
	Low		810	870	900
	Quiet		780	780	780
	High		33	35	40
	Med-High		32	33	36
	Med		31	32	34
	Med-Low		30	31	32
	Low		29	30	31
	Quiet		28	28	28
Dimensions (H × W × D)	mm		246 × 840 × 840		
Weight	kg		24.0	24.5	24.5
Connection pipe diameter	Liquid (Flare)		6.35	9.52	9.52
	Gas (Flare)		12.70	15.88	15.88
Drain Hose Diameter (I.D./O.D.)			25/32		
Cassette Grille	Model name	UTG-UKYC-W/UTG-UKYA-B			
	Dimensions (H × W × D)	mm	53 × 950 × 950		
	Weight	kg	6.0		

Note: Specifications are subject to the following conditions:

Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.

Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature of 7°CDB/6°CWB.

Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V].

When AUX\*018GLEH is connected to an outdoor unit other than one of the J-IVL Series, the pipe diameter should be Ø9.52/Ø15.88 mm (Liquid/Gas).

When connecting AUXK036GLEH, AUXK045GLEH, and AUXK054GLEH to an outdoor unit other than the outdoor unit of the J-IVL Series, the gas pipe diameter should be Ø19.05 mm.

\*For more details, please refer to the chapter "Optional parts".

### Optional parts





Human sensor Kit: UTY-SHZC  
Wide Panel: UTG-AKXA-W  
Panel Spacer: UTG-BKXA-W  
Fresh air intake kit: UTZ-VXRA

Air Outlet Shutter Plate: UTR-YDZK  
Insulation kit for high humidity: UTZ-KXRA  
Cassette Grille: UTG-UKYC-W, UTG-UKYA-B  
External power supply unit: UTZ-GXXA, UTZ-GXXC\*

IR Receiver Unit: UTY-LBHD  
WLAN adapter: UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIF1Z1  
Silver Ion Filter: UTD-HFRA  
Remote sensor kit: UTY-XSZXZ1

### Dimensions

(Unit: mm)




## Cassette Large type Circular Flow

DC  
FAN

### Unique circular flow design

This Cassette type air conditioner is equipped with a high performance DC fan motor, a turbo fan, and a louver to propel powerful airflows in all directions.



### Uniform temperature air conditioning


Achieve a comfortable air conditioning spread to every corner of the room by circular flow and wide vertical airflow.



### Individual louver control

Each louver can be set individually by the Touch panel wired remote controller so the user can enjoy the comfort of different directional airflows according to the room layout.

\* UTY-RNRYZ5 Wired remote controller with touch panel and UTY-DCGYZ3 Central remote controller only



2 modes are available to choose from:

Auto economy mode

The air conditioner switches to operate on reduced power when it detects that the room is unoccupied.

Auto-off mode

The air conditioner stops operating when it detects that the room is unoccupied.

### The Human sensor contributes to further energy savings.

Energy saving operation starts automatically by detecting the motion of a person. Two modes of save operation mode and stop mode can be selected.

\* UTY-RNRYZ5 Wired remote controller with touch panel and UTY-DCGYZ3 Central remote controller only

**Model: AUXK018GLEH / AUXK024GLEH / AUXK030GLEH  
AUXK034GLEH / AUXK036GLEH / AUXK045GLEH  
AUXK054GLEH**



### Specifications

Model name	AUXK018GLEH	AUXK024GLEH	AUXK030GLEH	AUXK034GLEH	AUXK036GLEH	AUXK045GLEH	AUXK054GLEH	
Power source	Single phase, ~230 V, 50 Hz							
Capacity	Cooling	kW	5.6	7.1	9.0	10.0	11.2	
	Heating		6.3	8.0	10.0	11.2	12.5	
Input power		W	40	40	47	47	89	
	High		1,420	1,420	1,440	1,440	1,620	
	Med-High		1,360	1,360	1,400	1,400	1,500	
	Med		1,300	1,300	1,340	1,340	1,400	
	Med-Low		1,270	1,270	1,300	1,300	1,400	
	Low		1,200	1,200	1,280	1,280	1,300	
	Quiet		1,150	1,150	1,150	1,150	1,150	
	High		38	38	39	39	44	
	Med-High		37	37	38	38	42	
	Med		36	36	37	37	40	
	Med-Low		35	35	36	36	39	
	Low		34	34	35	35	36	
	Quiet		33	33	33	33	33	
Dimensions (H × W × D)			288 × 840 × 840					
Weight		kg	26.5	26.5	29.5	29.5	29.5	29.5
Connection pipe diameter	Liquid (Flare)		6.35	9.52	9.52	9.52	9.52	9.52
	Gas (Flare)		12.70	15.88	15.88	15.88	15.88	15.88
Drain Hose Diameter (I.D./O.D.)			25/32					
Model name	UTG-UKYC-W/UTG-UKYA-B							
Cassette Grille Dimensions (H × W × D)		mm	53 × 950 × 950					
Weight		kg	6.0					

Note: Specifications are subject to the following conditions:

Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.

Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature of 7°CDB/6°CWB.

Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V].

When AUX\*018GLEH is connected to an outdoor unit other than one of the J-IVL Series, the pipe diameter should be Ø9.52/Ø15.88 mm (Liquid/Gas).

When connecting AUXK036GLEH, AUXK045GLEH, and AUXK054GLEH to an outdoor unit other than the outdoor unit of the J-IVL Series, the gas pipe diameter should be Ø19.05 mm.

\*For more details, please refer to the chapter "Optional parts".

### Optional parts






Human sensor Kit: UTY-SHZXC  
Wide Panel: UTG-AKXA-W  
Panel Spacer: UTG-BKXA-W  
Fresh air intake kit: UTZ-VXRA

Air Outlet Shutter Plate: UTR-YDZK  
Insulation kit for high humidity: UTZ-KXRA  
Cassette Grille: UTG-UKYC-W, UTG-UKYA-B  
External power supply unit: UTZ-GXXA, UTZ-GXXC\*


IR Receiver Unit: UTY-LBHD  
WLAN adapter: UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIF1Z1  
Silver Ion Filter: UTD-HFRA  
Remote sensor kit: UTY-XSZXZ1

### Dimensions

(Unit: mm)



## Cassette One-way Flow type

DC  
FAN

### Compact chassis size

The compact size allows easy installation in a variety of commercial facilities and environments.

- The height of the chassis is less than 200 mm for all models.
- All 4 to 12 kBtu models are less than 1,000 mm wide.
- The depth of the chassis is 570 mm, which fits nicely into a grid type ceiling.

	4	7	9	12	14	18	24	(Unit: mm)
H						198 (43)		
W					785 (950)			1,190 (1,360)
D					570 (620)			570 (620)



### Wide airflow range

A large flap with a wide range of movements, equipped with louvers arranged triangularly, sends air into every corner of the room.



In cooling mode, the left/right airflow reaches every corner of the room without directly touching the human body to provide comfortable air conditioning.



In heating mode, warm air is directed downward toward the floor to warm the feet and lower body, while the head is kept relatively cool.



Note: This is a conceptual drawing. The performance of an air conditioner may vary depending on where it is installed, the size of the room, and its distance from the wall.

### Quiet mode

The low operating noise makes the model ideal for use in hotel rooms.



Model: AUXV004GLEH / AUXV007GLEH / AUXV009GLEH  
AUXV012GLEH / AUXV014GLEH / AUXV018GLEH  
AUXV024GLEH



AUXV004/007/009/012GLEH



AUXV014/018/024GLEH

### Specifications

Model name	AUXV004GLEH	AUXV007GLEH	AUXV009GLEH	AUXV012GLEH	AUXV014GLEH	AUXV018GLEH	AUXV024GLEH	
Power source	Single phase, ~230 V, 50 Hz							
Capacity	Cooling	kW	1.1	2.2	2.8	3.6	4.5	
	Heating		1.3	2.8	3.2	4.0	5.0	
Input power		W	30/30	42/42	42/42	60/60	38/38	
	High		460	550	550	670	720	
	Med-High		440	440	440	520	660	
	Med		420	420	420	480	630	
	Med-Low		400	400	400	450	600	
	Low		380	380	380	410	580	
	Quiet		360	360	360	360	550	
	High		38	42	42	45	44	
	Med-High		37	37	37	41	43	
	Med		36	36	36	39	40	
	Med-Low		35	35	35	38	42	
	Low		33	33	33	36	39	
	Quiet		32	32	32	32	36	
Net Dimensions (H × W × D)	mm	198 × 785 × 570	198 × 785 × 570	198 × 785 × 570	198 × 785 × 570	198 × 1,190 × 570	198 × 1,190 × 570	
Weight	kg	18	19	19	19	26	26	
Connection pipe diameter	Liquid (Flare)	6.35	6.35	6.35	6.35	6.35	9.52	
	Gas (Flare)	9.52	9.52	9.52	12.70	12.70	15.88	
Drain Hose Diameter (I.D./O.D.)					25/32			
Cassette	Model name	UTG-UNYA-W						
Grille	Net Dimensions (H × W × D)	43 × 950 × 620						
	Weight	kg	6.5					

Note: Specifications are subject to the following conditions:

Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature of 7°CDB/6°CWB.


Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V]

### Optional parts \*For more details, please refer to the chapter "Optional parts".

WLAN adapter:	UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIF1Z1
IR Receiver Unit:	UTY-TRHX
Cassette Grille:	UTG-UNYA-W (004-012), UTG-UNYB-W (014-024)
External power supply unit:	UTZ-GXXA, UTZ-GXXC*
Remote sensor kit:	UTY-XSZXZ1


### Flexible Installation

The L-shaped pipe kit allows for more flexible installation.  
Equipped with a built-in drain pump as standard, which enables a maximum pipe height difference of 700 m from the ceiling.



### Dimensions

(Unit: mm)



	AUXV 004 / 007 / 009 / 012 GLEH	AUXV 014 / 018 / 024 GLEH
a	950	1,360
b	920	1,330
c	752	1,152
d	785	1,190

\*The design of the service access depends on the installation method. Refer to the installation manual for more information.

## 3D Flow Cassette

DC FAN




### 3 individually controlled air outlet ports

The Comfortable airflow setting enables the left and right air outlet ports as well as the wide center port to work together to provide a comfortable room environment.


#### Temperature distribution during cooling and heating (when set to Comfortable airflow)



**Testing conditions:** Model AUXS024GLEH running cooling operation with the air volume set to "Hi" to maintain the room temperature at 18°C with the outdoor temperature at 35°C, tested in our 40m<sup>2</sup> environmental test room




**Testing conditions:** Model AUXS024GLEH running heating operation with the air volume set to "Hi" to maintain the room temperature at 30°C with the outdoor temperature at 7°C, tested in our 40m<sup>2</sup> environmental test room



\*1: Announced 2018. In the category of room air conditioners for the home (source: Fujitsu General Limited).

### Individual airflow setting

The individual airflow setting function optimizes the airflow direction to match the room layout.



Adjusts airflows from the side air outlet ports to match the layout and usage of the room to minimize the amount of wasted airflow.

#### Individual control of air outlet ports


Individual airflow can be set using a Wired remote controller with touch panel and Central remote controller\*. The airflow from each air outlet port can be set individually.



\* Feature available only on UTY-RNRYZ5 Wired remote controller with touch panel and UTY-DCGYZ3 Central remote controller

### High energy saving

The structural design to take in a larger volume of air and blow air out more smoothly reduces air blowing loss and achieves class-leading energy-saving performance.



\*: 018 model

Model: AUXS018GLEH / AUXS024GLEH



### Specifications

Model name	AUXS018GLEH		AUXS024GLEH
Power source	Single phase, ~230 V, 50 Hz		
Capacity	Cooling	kW	5.60
	Heating		6.30
Input power		W	20/28
	High		750/870
	Med-High		710/830
	Med	m <sup>3</sup> /h	690/780
	Med-Low		660/740
	Low		630/700
	Quiet		540/540
	High		38/41
	Med-High		36/40
	Med	dB(A)	35/39
	Med-Low		35/37
	Low		33/36
	Quiet		29/29
Net Dimensions (H × W × D)	mm	200 × 1,240 × 500	
Weight	kg	25	
Connection pipe diameter	Liquid (Flare) Gas (Flare)	mm	6.35
			12.70
Drain Hose Diameter (I.D./O.D.)		25/32	
Cassette Grille	Model name	UTG-USYA-W	
	Net Dimensions (H × W × D)	mm	85 × 1,350 × 580
	Weight	kg	11.5

Note: Specifications are subject to the following conditions:  
Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature of 7°CDB/6°CWB.  
Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V]

\*: Applicable to cooling and heating operation




### Optional parts

\*For more details, please refer to the chapter "Optional parts".

WLAN adapter:	UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIF1Z1
IR Receiver Unit:	UTY-TRHX
Cassette Grille:	UTG-USYA-W
External power supply unit:	UTZ-GXXA, UTZ-GXXC*
Remote sensor kit:	UTY-XSZXZ1

### Dimensions

(Unit: mm)




## Low Static Pressure Duct Mini Duct (With drain pump)

DC FAN


### Space saving design

- Fits into a space 198 mm high and 450 mm deep
- 30% smaller than previous-generation models
- Weighs 16 kg, 10% lighter




### Optimum airflow path and low noise operation

The stabilized airflow reduces the noise level significantly.




### 6-speed control\*

Multistep airflow adjustment allows installation in a quiet location.



### Easy to design and maintain for drain

Indoor unit design for easy maintenance. Parts can be replaced from the side of the unit where maintenance is easier.



A drain pump is built into the unit as standard:  
Parts can be accessed and replaced through the side of the unit for easy maintenance.

Model: ARXK004GLGH / ARXK007GLGH / ARXK009GLGH  
ARXK012GLGH / ARXK014GLGH / ARXK018GLGH  
ARXK024GLGH



ARXK004/007/009/012/014GLGH



ARXK018GLGH



ARXK024GLGH

### Specifications

Model name	ARXK004GLGH	ARXK007GLGH	ARXK009GLGH	ARXK012GLGH	ARXK014GLGH	ARXK018GLGH	ARXK024GLGH
Power source	Single phase, ~230 V, 50 Hz						
Capacity	Cooling 1.1 1.3	Heating 2.2 2.8	kW	2.8 3.2 4.0 4.5	3.6 4.0 5.0 5.6	5.6 6.3 7.1 8.0	7.1
Input power	W	26	28	28	35	66	73
Airflow rate	High Med-High Med Med-Low Low Quiet	m³/h	460 440 420 400 370 340	460 440 420 400 370 340	460 440 420 400 370 340	550 520 480 450 410 340	760 660 560 490 410 340
Static pressure range	Pa	0 to 30	0 to 30	0 to 30	0 to 30	0 to 50	0 to 50
Standard static pressure		10 10	10 10	10 10	10 10	15 15	15 15
Sound pressure level	dB(A)	High Med-High Med Med-Low Low Quiet	25 24 23 22 21 20	26 25 25 23 22 21	26 25 24 23 22 21	29 27 26 25 24 22	34 31 28 26 24 22
Net Dimensions (H × W × D)	mm	198 × 700 × 450	198 × 700 × 450	198 × 700 × 450	198 × 700 × 450	198 × 700 × 450	198 × 900 × 450
Weight	kg	14.5	15.5	15.5	16	16	19
Connection pipe diameter	Liquid (Flare) Gas (Flare)	6.35 9.52	6.35 9.52	6.35 9.52	6.35 12.70	6.35 12.70	9.52 15.88
Drain Hose Diameter (I.D./O.D.)	mm	25/32					

Note: Specifications are subject to the following conditions:

Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature of 7°CDB/6°CWB.  
Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V].

### Optional parts

\*For more details, please refer to the chapter "Optional parts".

Remote sensor unit: UTY-XSZX1	External power supply unit: UTZ-GXXA, UTZ-GXXC*
IR receiver unit: UTY-TRHX	Auto Louver Grille Kit: UTD-GXTA-W (004-014)
Silver Ion Filter: UTD-HFTA (004-014) UTD-HFTB (018) UTD-HFTC (024)	UTD-GXTB-W (018) UTD-GXTC-W (024) FG-AC-WIF1Z1 UTY-TFSXJ3, UTY-TFSXZ1 (007-024)
UTD-HFTC (024)	WLAN adapter:




### Auto Louver Grille Kit (Optional)

The slim design of the unit provides comfortable cooling and heating air conditioning over a wide area.  
The optional automatic louver grille, which fits nicely into any interior decor, provides comfortable air conditioning (Optional)




### Dimensions

(Unit: mm)



	ARXK 004-014GLGH	ARXK018GLGH	ARXK024GLGH
a	575	775	975
b	P200×2=400	P200×3=600	P200×4=800
c	752	952	1,152
d	700	900	1,100
e	650	850	1,050
f	P100×6=600	P100×8=800	P100×10=1,000

\*The design of the service access depends on the installation method. Refer to the installation manual for more information.




## Low Static Pressure Duct Slim Duct/Slim Concealed Floor

DC FAN




### Slim design

Slim design allows for installation in a tight ceiling space.





### Air intake

Air intake direction can be selected to match the installation site.



### Flexible installation

Ceiling concealed



### Wide range of static pressures

The use of a DC fan motor makes it possible to adjust the static pressure between 0 and 90 Pa.

The static pressure range can be changed by a remote controller.





Static pressure range  
**0 to 90 Pa**

\*024 model static pressure range is 0 to 50 Pa.

### Filter (Accessory)


ARXD04/007/009/012/014/018 ARXD024



**Model:** ARXD04GALH / ARXD007GLEH / ARXD009GLEH  
ARXD012GLEH / ARXD014GLEH / ARXD018GLEH  
ARXD024GLEH



ARXD04GALH  
ARXD007/009/012/014GLEH



ARXD018GLEH



ARXD024GLEH

**Slim Concealed Floor**



### Specifications

Model name	ARXD04GALH*	ARXD007GLEH	ARXD009GLEH	ARXD012GLEH	ARXD014GLEH	ARXD018GLEH	ARXD024GLEH	
Power source	Single phase, ~230 V, 50 Hz							
Capacity	Cooling	kW	1.1	2.2	2.8	3.6	4.5	
	Heating		1.3	2.8	3.2	4.0	5.0	
Input power		W	40	44	50	54	63	
	High		510	550	600	600	800	
	Med-High		-	480	510	530	680	
	Med		400/470*1	440	460	490	600	
Airflow rate	Med-Low		-	410	420	450	520	
	Low		320/440*1	370	370	410	440	
	Quiet		-	320	320	340	340	
Static pressure range		Pa	0 to 90					
Standard static pressure			25	25	25	25	25	
	High		26	28	29	30	34	
	Med-High		-	26	27	28	31	
	Med		21/25*1	25	25	27	29	
	Med-Low		-	24	24	26	27	
	Low		20/22*1	22	22	24	25	
	Quiet		-	21	21	22	23	
Net Dimensions (H × W × D)	mm	198 × 700 × 620	198 × 700 × 620	198 × 700 × 620	198 × 700 × 620	198 × 700 × 620	198 × 900 × 620	198 × 1,100 × 620
Weight	kg	17	17	17	18	18	22	26
Connection pipe diameter	Liquid (Flare)	6.35	6.35	6.35	6.35	6.35	6.35	9.52
	Gas (Flare)	12.70	9.52	9.52	12.70	12.70	12.70	15.88
Drain Hose Diameter (I.D./O.D.)	mm	25/32						

Note: Specifications are subject to the following conditions:

Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature of 7°CDB/6°CWB.

Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V].


\*1: This value is under cooling operation.

\*: ARXD04GALH cannot be connected to J-IVS/J-IV/J-IVL/VR-IV Series.

### Optional parts


\*For more details, please refer to the chapter "Optional parts".

Remote sensor unit: UTY-XSZXZ1	External power supply unit: UTZ-GXXA, UTZ-GXXC*
IR receiver unit: UTY-YWC (04)	Auto Louver Grille Kit: UTD-GXTA-W (04, 007-014)
	UTD-GTXB-W (018)
WLAN adapter: UTY-TFSXJ3 (007-024)	UTD-GXTC-W (024)
	UTD-HFTA (04, 007-014)
UTY-TFSXZ1 (007-024)	UTD-HFTB (018)
FG-RC-WIF1Z2 (04)	UTD-HFTC (024)
FG-AC-WIF1Z1 (007-024)	




### Dimensions

(Unit: mm)



ARXD04GALH ARXD 007-014GLEH	ARXD018GLEH	ARXD024GLEH
a 574	774	974
b P200×2=400	P200×3=600	P200×4=800
c 734	934	1,134
d 700	900	1,100
e 650	850	1,050
f P100×6=600	P100×8=800	P100×10=1,000

\*The design of the service access depends on the installation method. Refer to the installation manual for more information.




# Low Static Pressure Duct

High Efficiency

DC  
FAN

## Slim & Compact design


The slim and compact design of the indoor unit, with the control box mounted on the side, allows installation in narrow spaces.



## Easy maintenance


Structural improvement has been developed by making the bottom panel in two pieces, front and rear. The internal fan casing is also manufactured in two pieces—upper and lower. The motor and fan can be easily accessed and maintained by removing the rear panel and the lower casing with the main chassis remaining in place.

See below for rear-suction type




## Installation styles


Embedded in Ceiling



Hanging from Ceiling



A drain pipe can be installed on either the left or right side of the unit



## High-efficiency DC fan motor achieves low-energy consumption.

Improved motor efficiency from previous model.



## Wide range of static pressures

Static pressures can be changed in the range of 0 to 150 Pa.

Static pressure range  
**0 to 80 Pa**

Model: ARXP018GLFH / ARXP030GLFH \* Production by order



## Specifications

Model name	ARXP018GLFH		ARXP030GLFH
Power source	Single-phase, ~220V, 50Hz		
Capacity	Cooling	kW	5.6
	Heating		6.3
Input power		W	128
	High		1,540 / 1,440
	Med-High		1,460 / 1,380
	Med		1,380 / 1,320
Airflow rate	Med-Low		1,300 / 1,260
	Low		1,220 / 1,200
	Quiet		1,150 / 1,150
Static pressure range		Pa	0 to 80
Standard static pressure			40
	High		35 / 34
	Med-High		34 / 32
	Med		32 / 31
Sound pressure level	Med-Low		31 / 30
	Low		29 / 29
	Quiet		28 / 28
Net Dimensions (H × W × D)		mm	270 × 1,135 × 700
Weight		kg	40
Connection pipe diameter	Liquid (Flare)		6.35
	Gas (Flare)		9.52
Drain Hose Diameter (I.D./O.D.)		mm	12.70
			25/32

Note: Specifications are subject to the following conditions:

Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.  
Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V].


## Optional parts

\*For more details, please refer to the chapter "Optional parts".


Long-life filter:	UTD-LF25NA	IR receiver unit:	UTY-TRHX
Flange (square):	UTD-SF045T	Drain pump unit:	UTZ-PX1NBA
Flange (round):	UTD-RF204	WLAN adapter:	UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIF1Z1
External power supply unit:	UTZ-GXXA, UTZ-GXXC*	Silver Ion Filter:	UTD-HFND
Remote sensor unit:	UTY-XS2XZ1		

## Dimensions

(Unit: mm)



\*The design of the service access depends on the installation method. Refer to the installation manual for more information.




## Medium Static Pressure Duct

Normal

DC  
FAN

### Slim & Compact design


The slim and compact design of the indoor unit, with the control box mounted on the side, allows installation in narrow spaces.



### Easy maintenance


Structural improvement has been developed by making the bottom panel in two pieces, front and rear. The internal fan casing is also manufactured in two pieces—upper and lower. The motor and fan can be easily accessed and maintained by removing the rear panel and the lower casing with the main chassis remaining in place.

See below for rear-suction type




### Installation styles


Embedded in Ceiling



Hanging from Ceiling



A drain pipe can be installed on either the left or right side of the unit



### High-efficiency DC fan motor achieves low-energy consumption.

Improved motor efficiency from previous model.




### Wide range of static pressures

Static pressures can be changed in the range of 0 to 150 Pa.

Static pressure range  
**0 to 150 Pa**

Model: ARXA024GLEH / ARXA030GLEH / ARXA036GLEH / ARXA045GLEH



### Specifications

Model name	ARXA024GLEH	ARXA030GLEH	ARXA036GLEH	ARXA045GLEH		
Power source	Single phase, ~230 V, 50 Hz					
Capacity	Cooling Heating	kW	7.1 8.0	9.0 10.0	11.2 12.5	12.5 14.0
Input power		W	94	108	194	240
	High Med-High Med Med-Low Low Quiet	m³/h	1,280 1,180 1,090 1,000 920 840	1,410 1,350 1,280 1,240 1,190 1,150	1,840 1,750 1,660 1,600 1,530 1,470	1,970 1,910 1,860 1,780 1,710 1,640
Static pressure range		Pa	0 to 150	0 to 150	0 to 150	0 to 150
Standard static pressure	High Med-High Med Med-Low Low Quiet	Pa	40 29 27 26 24 23	50 33 32 31 30 29	50 37 36 35 34 33	60 41 40 38 37 36
Sound pressure level		dB(A)				
Net Dimensions (H × W × D)		mm	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700	270 × 1,135 × 700
Weight	kg		36	40	40	40
Connection pipe diameter	Liquid (Flare) Gas (Flare)	mm	9.52 15.88	9.52 15.88	9.52 15.88	9.52 15.88
Drain Hose Diameter (I.D./O.D.)						

25/32

Note: Specifications are subject to the following conditions:

Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature of 7°CDB/6°CWB.  
Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V].


### Optional parts

\*For more details, please refer to the chapter "Optional parts".

Long-life filter:	UTD-LF25NA	IR receiver unit: UTY-TRHX
Flange (square):	UTD-SF045T	Drain pump unit: UTY-PX1NBA
Flange (round):	UTD-RF204	WLAN adapter: UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIF1Z1
External power supply unit:	UTZ-GXXA, UTZ-GXXC*	Silver Ion Filter: UTD-HFND
Remote sensor unit:	UTY-XS2XZ1	

### Dimensions

(Unit: mm)



\*The design of the service access depends on the installation method. Refer to the installation manual for more information.

## High Static Pressure Duct

Normal



### Static pressure mode selection

The use of a DC fan motor makes it possible to adjust the static pressure between 0 to 200 Pa (ARXC036) / 250Pa (ARXC045/060) / 300 Pa (ARXC072/090/096)

MAX.  
200 Pa  
(036type)

MAX.  
250 Pa  
(045/060type)

MAX.  
300 Pa

MAX.  
300 Pa



(ARXC036/045/060 type)



(ARXC072/090 type)



(ARXC096 type)

### Easy installation (Compact & Lightweight)

The indoor unit is designed to be compact and light by reducing the basic chassis size and the overall material weight.



(ARXC036/045/060 type)



(ARXC072/090 type)




(ARXC096 type)

(Unit: mm)

### Low noise


**Models:** ARXC036/ARXC045/ARXC060

The corners of the front panel and fan casing of the indoor unit are shaved to reduce air turbulence. The use of a plastic case and fan reduces the noise level generated by the unit.



**ARXC036GTEH:**  
Plastic fan [42 dB(A)]

\* Model: Material  
(Actual noise measurement  
value measured at 100 Pa)



### High-efficiency DC fan motor achieves low energy consumption.

Improved motor efficiency compared to the previous model



(ARXC036/045/060 type)



(ARXC072/090/096 type)

**Model:** ARXC036GTEH / ARXC045GTEH / ARXC060GTEH  
ARXC072GTEH / ARXC090GTEH / ARXC096GTEH



ARXC036/045/060GTEH



ARXC072/090GTEH



ARXC096GTEH

### Specifications

Model name	ARXC036GTEH	ARXC045GTEH	ARXC060GTEH*	ARXC072GTEH*	ARXC090GTEH*	ARXC096GTEH*	
Power source	Single phase, ~230 V, 50 Hz						
Capacity	Cooling kW	11.2 12.5	18.0 20.0	22.4 25.0	25.0 28.0	28.0 31.5	
Input power	W	207	715	730	681	819 838	
Airflow rate	High m³/h	1,990	3,500	3,500	3,900	4,300 4,850	
	Med	1,680	3,000	3,000	3,300	4,000 4,250	
	Low	1,330	2,460	2,460	3,000	3,500 3,600	
Static pressure range	Pa	0 to 200	100 to 250	100 to 250	0 to 300	0 to 300 0 to 300	
Standard static pressure	High	100	100	100	150	150 150	
Sound pressure level	dB(A)	42	49	49	47 48	48 48	
	Med	36	45	45	43 46	46 45	
	Low	32	42	42	40 44	44 42	
Net Dimensions (H × W × D)	mm	400 × 1,050 × 500	400 × 1,050 × 500	400 × 1,050 × 500	450 × 1,587 × 700	450 × 1,587 × 700 550 × 1,587 × 700	
Weight	kg	40	46	46	84	84 105	
Connection pipe diameter	Liquid mm	9.52 (Flare) 15.88 (Flare)	9.52 (Flare) 15.88 (Flare)	9.52 (Flare) 15.88 (Flare)	9.52 (Flare) 19.05 (Flare)	9.52 (Brazing) 22.22 (Brazing)	
Drain Hose Diameter (I.D./O.D.)	mm	25/32					

Note: Specifications are based on the following conditions:

Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.

Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature of 7°CDB/6°CWB.

Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V]

\*: ARXC060/072/090/096G cannot be connected to J-IV/I-IVS Series.

### Optional parts

\*For more details, please refer to the chapter "Optional parts".



Long-life filter: UTD-LF60KA (036/045/060)  
IR receiver unit: UTY-TRHX  
External power supply unit: UTZ-GXXA, UTZ-GXXC\*

WLAN adapter: UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIF1Z1  
Silver Ion Filter: UTD-HFKB (036/045/060)  
Remote sensor unit: UTY-XSZXZ1

### Dimensions



(Unit: mm)

Models: ARXC036/ARXC045/ARXC060



\*The design of the service access depends on the installation method. Refer to the installation manual for more information.

Models: ARXC072/ARXC090/ARXC096



ARXC072 / 090 GTEH	ARXC096 GTEH
a 450	550
b 370	470

\*The design of the service access depends on the installation method. Refer to the installation manual for more information.



## Compact floor

DC  
FAN


### 2-fan and wide airflow

A 2-fan individual vertical airflow cools or warms the entire room comfortably.

#### Cooling




#### Heating





### Flexible and easy installation

The compact and whole-surface suction design provides flexible installation options, including floor-standing, embedded, partially embedded, and wall-mounted installation to match the room layout.



### Quiet operation


6-fan speed control for quiet operation (via 2-wire controller)



\* Remote controller is compatible with the following:  
UTY-RNRYZ5 / UTY-RLRY / UTY-RSRY / UTY-RHRY / UTY-DCGYZ3 / UTY-ALGX1 / UTY-APGX1

### Flexible pipe connection enables draining and piping in 6 directions

The drain hose and pipe can be connected to the unit in the right, left, straight in depth, or downward direction.



**Model:** AGYA004GCGH / AGYA007GCGH / AGYA009GCGH  
AGYA012GCGH / AGYA014GCGH

[external EEV]  
AGYE004GCEH / AGYE007GCEH / AGYE009GCEH  
AGYE012GCEH / AGYE014GCEH



### Specifications

Model name	AGYA004GCGH	AGYA007GCGH	AGYA009GCGH	AGYA012GCGH	AGYA014GCGH	AGYE004GCEH	AGYE007GCEH	AGYE009GCEH	AGYE012GCEH	AGYE014GCEH			
Power source	Single phase, ~230 V, 50 Hz					Single phase, ~230 V, 50 Hz							
Capacity	Cooling	kW	1.1	2.2	2.8	3.6	4.0	1.1	2.2	2.8	3.6	4.0	
	Heating		1.3	2.8	3.2	4.0	4.5	1.3	2.8	3.2	4.0	4.5	
Input power		W	12/14	16	17	22	29	14	16	17	22	29	
	High		380/430	470	500	590	670	380/430	470	500	590	670	
	Med-High		350	420	450	520	590	350	420	450	520	590	
	Med		320	390	400	470	520	320	390	400	470	520	
	Med-Low		310	360	360	420	450	310	360	420	450	450	
	Low		280	330	330	390	390	280	330	330	390	390	
	Quiet		210	270	270	340	340	210	270	270	340	340	
	High		35/36	37	38	42	46	35/36	37	38	42	46	
	Med-High		33	35	36	39	42	33	35	36	39	42	
	Med		31	33	34	37	39	31	33	34	37	39	
	Med-Low		30	31	31	35	36	30	31	31	35	36	
	Low		28	29	29	33	33	28	29	29	33	33	
	Quiet		22	22	22	30	30	22	22	22	30	30	
Net Dimensions (H × W × D)	mm					600 × 740 × 200					600 × 740 × 200		
Weight	kg					15.0	15.0	15.0	15.0	14.5	14.5	14.5	14.5
Connection pipe diameter	Liquid (Flare)	mm					6.35	6.35	6.35	6.35	6.35	6.35	6.35
	Gas (Flare)	mm					9.52	9.52	9.52	9.52	9.52	12.70	12.70
Drain Hose Diameter (I.D./O.D.)	mm					13.8/15.8 to 16.7					13.8/15.8 to 16.7		
EV kit (optional)						-					UTR-EV09XB	UTR-EV14XB	

Note: Specifications are subject to the following conditions:

Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.

Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature of 7°CDB/6°CWB.

Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V]

When connecting AGYA004/007/009GCGH, AGYE004/007/009GCEH to an outdoor unit other than an outdoor unit of the J-IVL Series, the gas pipe diameter should be Ø12.70 mm.

### Optional parts

\*For more details, please refer to the chapter "Optional parts".

Partially concealing kit: UTR-STA



External power supply unit: UTZ-GXXA, UTZ-GXXC\*

WLAN adapter: UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIF1Z1

Silver Ion Filter: UTR-FA03-5

### Dimensions

(Unit: mm)



## Floor/Ceiling

DC  
FAN

### Flexible installation

#### Example of floor standing installation

Floor standing console with the back against the wall




#### Example of ceiling installation

Under ceiling



### Double auto swing

The combination of horizontal and vertical swings enables 3-dimensional control of the airflow direction.




### High-power DC fan motor

- High power
- Wide rotation range
- High-efficiency



### Compact design

Symmetrical, slim and compact design.



Model: ABYA012GTEH / ABYA014GTEH / ABYA018GTEH / ABYA024GTEH



### Specifications

Model name		ABYA012GTEH	ABYA014GTEH	ABYA018GTEH	ABYA024GTEH
Power source		Single phase, ~230 V, 50 Hz			
Capacity	Cooling	kW	3.6	4.5	5.6
	Heating		4.0	5.0	6.3
Input power		W	30	42	74
	High		660	780	1,000
	Med-High		620	740	910
	Med	m³/h	580	690	830
	Med-Low		550	640	750
	Low		520	600	660
	Quiet		490	550	580
	High		36	40	46
	Med-High		34	39	44
	Med	dB(A)	33	38	42
	Med-Low		31	36	40
	Low		29	35	37
	Quiet		28	34	35
Net Dimensions (H × W × D)		mm	199 × 990 × 655	199 × 990 × 655	199 × 990 × 655
Weight		kg	25	26	26
Connection pipe diameter	Liquid (Flare) Gas (Flare)	mm	6.35	6.35	6.35
			12.70	12.70	12.70
Drain Hose Diameter (I.D./O.D.)			25/32		

Note: Specifications are subject to the following conditions:

Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature of 7°CDB/6°CWB.  
Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V]


### Optional parts

\*For more details, please refer to the chapter "Optional parts".

External power supply unit: UTZ-GXXA, UTZ-GXXC\*  
WLAN adapter: UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIF1Z1

### Dimensions

(Unit: mm)




# Ceiling


DC FAN




## Installation



General installation with indoor unit installed on the ceiling




Installation with indoor unit embedded into the ceiling



Wall-mounting brackets are used to mount the indoor unit on the wall. (Locally available)  
This type of installation is used when the ceiling space is insufficient.

## Double auto swing and wide airflow

Auto airflow direction and auto swing




## High-power DC fan motor

- High power
- Wide rotation range
- High-efficiency




## Long airflow

Long airflow provides comfort in every corner of a large room.



## Fresh air intake



## Slim & Compact design



Model: ABYA030GTEH / ABYA036GTEH / ABYA045GTEH / ABYA054GTEH



## Specifications

Model name	ABYA030GTEH		ABYA036GTEH		ABYA045GTEH		ABYA054GTEH	
Power source	Single phase, ~230 V, 50 Hz							
Capacity	Cooling	kW	9.0	11.2	12.5	14.0		
	Heating		10.0	12.5	14.0	16.0		
Input power		W	66	85	131	180		
	High		1,630	1,690	2,010	2,270		
Airflow rate	Med-High		1,520	1,560	1,840	2,070		
	Med		1,420	1,450	1,690	1,860		
	Med-Low		1,320	1,360	1,530	1,660		
	Low		1,220	1,270	1,380	1,470		
	Quiet		1,140	1,170	1,230	1,280		
	High		42	45	48	51		
Sound pressure level	Med-High		40	41	46	49		
	Med		39	39	45	46		
	Med-Low		37	38	41	43		
	Low		35	36	38	40		
	Quiet		33	34	35	36		
Net Dimensions (H × W × D)	mm	240 × 1,660 × 700	240 × 1,660 × 700	240 × 1,660 × 700	240 × 1,660 × 700	240 × 1,660 × 700		
Weight	kg	46	48	48	48	48		
Connection pipe diameter	Liquid (Flare)	9.52	9.52	9.52	9.52	9.52		
	Gas (Flare)	15.88	15.88	15.88	15.88	15.88		
Drain Hose Diameter (I.D./O.D.)	mm	25/32						


Note: Specifications are subject to the following conditions:

Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature of 7°CDB/6°CWB.  
Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V]

## Optional parts


\*For more details, please refer to the chapter "Optional parts".

- Drain pump unit: UTR-DPB24T  
Flange: UTD-RF204  
External power supply unit: UTZ-GXXA, UTZ-GXXC\*  
WLAN adapter: UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIF1Z1



## Dimensions

(Unit: mm)



## Wall-mounted type

DC  
FAN

### Highly-efficiency, compact design

The 004-014 models share the same design. The high-density and large heat exchanger achieves a highly-efficiency and compact design. The compact body blends in well with conference rooms and offices, providing comfortable air conditioning.



### More comfortable airflow

The unique power diffuser provides comfortable air conditioning.

#### Heating

The vertical airflow provides powerful floor-level heating.




#### Cooling

The left/right airflow avoids blowing cool air directly at the occupants in a room.



### Quiet operation & 6-Step fan speed control


The airflow pattern achieves significant noise reduction. Multistep airflow adjustment to suit the environment



### The Human sensor contributes to further energy savings.

Energy saving operation starts automatically by detecting the motion of a person. Two modes of save operation mode and stop mode can be selected.

\*If you want to use the Human sensor control' function, you need an setting device that can set the Human sensor control' function. For example: Wired RC (Touch panel).



**Model:** ASYA004GCGH / ASYA007GCGH / ASYA009GCGH  
 ASYA012GCGH / ASYA014GCGH

[external EEV]  
 ASYE004GCEH / ASYE007GCEH / ASYE009GCEH  
 ASYE012GCEH / ASYE014GCEH



### Specifications

Model name	Single phase, ~230 V, 50 Hz					Single phase, ~230 V, 50 Hz									
	Power source		ASYA004GCGH			ASYA007GCGH		ASYA009GCGH		ASYA012GCGH		ASYA014GCGH			
Capacity	Cooling	Heating	kW	1.1	2.2	2.8	3.6	4.0	1.1	2.2	2.8	3.6	4.0		
Input power			W	12	19	20	25	36	12	19	34	25	36		
	High			450	550	610	690	800	450	550	610	690	800		
	Med-High			430	510	560	610	740	430	510	560	610	740		
	Med			400	470	510	560	680	400	470	510	560	680		
	Med-Low			380	410	440	530	610	380	410	440	530	610		
	Low			360	360	360	470	550	360	360	360	470	550		
	Quiet			310	310	310	330	310	310	310	310	310	330		
	High			31	34	37	40	44	31	35	43	40	44		
	Med-High			30	32	35	37	42	30	32	38	37	42		
	Med			28	30	32	35	40	28	30	34	35	40		
	Med-Low			27	28	29	33	37	27	27	29	33	37		
	Low			26	26	26	30	34	26	24	24	30	34		
	Quiet			22	22	22	24	24	22	22	22	24	24		
Net Dimensions (H × W × D)														268 × 840 × 203	268 × 840 × 203
Weight			kg	8.0	8.5	8.5	8.5	8.5	8.0	8.5	8.5	8.5	8.5		
Connection pipe diameter	Liquid (Flare)	Gas (Flare)	mm	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35		6.35
Drain Hose Diameter (I.D./O.D.)			mm	9.52	9.52	9.52	12.70	12.70	9.52	9.52	9.52	12.70	12.70		13.8/15.8 to 16.7
EV kit (optional)														UTR-EV09XB	UTR-EV14XB

Note: Specifications are subject to the following conditions:

Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.

Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature of 7°CDB/6°CWB.

Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V]

When connecting ASY\*004G\*\*H, ASY\*007G\*\*H, ASY\*009G\*\*H to an outdoor unit other than the outdoor unit of the J-IVL Series, the gas pipe diameter should be Ø12.70 mm.



### Optional parts

\*For more details, please refer to the chapter "Optional parts".

External power supply unit: UTZ-GXXA, UTZ-GXXC\*  
 WLAN adapter: UTY-TFSXZ1, UTY-TFSXJ3, FG-AC-WIF1Z1  
 Silver Ion Filter: UTR-FA16-5  
 Remote sensor kit: UTY-XSZXZ1

### Dimensions



(Unit: mm)



## Wall-mounted type

DC  
FAN


### Powerful & Comfort airflow



### The Human sensor contributes to further energy savings. (ASYA030/034GTEH only)



Energy saving operation starts automatically by detecting the motion of a person. Two modes of save operation mode and stop mode can be selected.

\*If you want to use the Human sensor control' function, you need an setting device that can set the Human sensor control' function. For example: Wired RC (Touch panel).



### 6-step fan speed control for quiet operation

The airflow pattern achieves significant noise reduction. A 6-step sound level setting allows for multiple-step silent operations.



\* Remote controller is compatible with the following:  
UTY-RNRYZ5 / UTY-RLRY / UTY-RSRY / UTY-RHRY / UTY-DCGYZ3 / UTY-ALGXZ1 / UTY-APQXZ1

**Model: ASYA18GBCH / ASYA24GBCH  
ASYA030GTEH / ASYA034GTEH**



ASYA18/24GBCH



ASYA030/034GTEH

### Specifications

Model name	ASYA18GBCH		ASYA24GBCH		ASYA030GTEH		ASYA034GTEH	
Power source	Single phase, ~230 V, 50 Hz		Single phase, ~230 V, 50 Hz		Single phase, ~230 V, 50 Hz		Single phase, ~230 V, 50 Hz	
Capacity	Cooling	kW	5.6	7.1	9.0	10.0	1,620/1,520	1,620/1,520
	Heating		6.3	8.0	10.0	11.2	1,200	1,300
Input power		W	32	60	74	103	1,050	1,120
	High		840	1,100	1,440	1,720	55/54	55/54
	Med-High		-	-	1,200	1,300	49	51
	Med		770	910	940	980	45	47
	Med-Low		-	-	890	890	39	39
	Low		690	730	700	700	33	33
	Quiet		-	-	700	700	700	700
	High		41	48	53	55/54	49	51
	Med-High		-	-	49	51	45	47
	Med		39	43	42	43	39	39
	Med-Low		-	-	35	35	33	33
	Low		-	-	-	-	13.8/15.8 to 16.7	13.8/15.8 to 16.7
	Quiet		-	-	-	-	12/16	12/16
Net Dimensions (H × W × D)	mm	320 × 998 × 238	320 × 998 × 238	340 × 1,150 × 280	340 × 1,150 × 280			
Weight	kg	15	15	18	18			
Connection pipe diameter	Liquid (Flare) Gas (Flare)	mm	6.35	9.52	9.52	9.52	15.88	15.88
Drain Hose Diameter (I.D./O.D.)								

Note: Specifications are subject to the following conditions:

Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.

Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature of 7°CDB/6°CWB.

Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m. Voltage: 230 [V].

When connecting ASYA18GBCH to an outdoor unit other than the outdoor unit of the J-IVL Series, the pipe diameter should be Ø9.52/Ø15.88 mm (Liquid/Gas).

### Optional parts

\*For more details, please refer to the chapter "Optional parts".



External power supply unit: UTZ-GXXA (030/034), UTZ-GXXC\* (030/034)  
WLAN adapter: UTY-TFSXJ3 (030/034), UTY-TFSXZ1 (030/034)  
FG-RC-WIF1Z2 (18/24), FG-AC-WIF1Z1 (030/034)

Silver Ion Filter: UTR-FA13-3  
Remote sensor kit: UTY-XSZZX1



### Dimensions

(Unit: mm)

Models: ASYA18 / ASYA24





Models: ASYA030 / ASYA034



# Residential, Commercial & Light Commercial VENTILATION

## VENTILATION Lineup

- Vn-002 Energy Recovery Ventilator
- Vn-004 DX kit for Air handling applications
  - for VRF Outdoor unit
- Vn-006 DX kit for Air handling applications
  - for Single Split Outdoor Units



## Lineup

Airflow rate (m³/h)	250	350	500	800	1000						
Energy Recovery Ventilator											
Connectable capacity class (kW)	5.0  Control unit UTY-VDGX	6.3  Control unit UTY-VDGX	8.0  Control unit UTY-VDGX	10.0  Control unit UTY-VDGX	12.5  Control unit UTY-VDGX	14.0  Control unit UTY-VDGX	20.0  Control unit UTY-VDGX	25.0  Control unit UTY-VDGX	40.0  Control unit UTY-VDGX	50.0  Control unit UTY-VDGX	
Connectable capacity class (kW)	2.5 - 22.0										
DX kit for Air handling applications for Single Split Outdoor Units											

## Energy Recovery Ventilator



The energy recovery ventilator unit provides energy efficiency for comfort and improved savings.


### Heat exchange ventilation and normal ventilation

#### Heat exchange ventilation

When a room is cooled or heated, the exhausted cooling or heating energy is recovered by heat exchange ventilation.

#### Normal ventilation

Used when the indoor space does not require cooling or heating, i.e., when there is little temperature difference between the indoor and outdoor environments.



A high-efficiency counter-flow heat-exchanging element is used in the setup.


### Energy efficiency and ecology

The use of a counter-flow heat-exchanging element, designed to recover up to 77% of heat from the outgoing air, significantly reduces energy consumption.

The air conditioning load is reduced by approximately 20%, which results in substantial savings in energy cost.

### Comparison of heat-exchanging elements

Air flows in a straight line through a crossflow element. In contrast, air flows for a longer time (a longer distance) through a counter-flow element to achieve more consistent heat-exchanging performance.



### Quiet operation

Significantly lower noise levels are achieved by reducing pressure loss.

**25.5dB**  
(UTZ-BD035C)


### Slim design for easier installation

The use of a counter-flow heat-exchanging element made it possible to design a quieter, slimmer unit.



### Reverse-mountable direct air supply and exhaust system

Simplifies the duct design, due to its straight ducts for air supply and exhaust. Since each unit can be mounted facing opposite directions, only one inspection hole is needed for two units. This makes duct work easier and more flexible.



### Simple remote operation

Easy operation with connected liquid crystal switch

- Power On/Off
- On/Off Timer
- Air volume High/Low
- Clean filter display
- Heat exchange ventilation and normal ventilation



### Model: UTZ-BD025C/UTZ-BD035C/UTZ-BD050C/UTZ-BD080C/UTZ-BD100C




### Specifications

	250 m <sup>3</sup> /h	350 m <sup>3</sup> /h	500 m <sup>3</sup> /h	800 m <sup>3</sup> /h	1000 m <sup>3</sup> /h
Model name	UTZ-BD025C	UTZ-BD035C	UTZ-BD050C	UTZ-BD080C	UTZ-BD100C
Power source	Single phase, -220 to 240 V, 50 Hz				
Heat Exchange Ventilation					
Input power	(Extra high)/High/Low W	128/123/96	190/185/168	289/225/185	418/378/295
Airflow rate	(Extra high)/High/Low m <sup>3</sup> /h	250/25/190	350/350/240	500/500/440	800/800/630
External static pressure	(Extra high)/High/Low Pa	105/95/45	140/60/45	120/60/35	140/110/55
Temperature exchange efficiency	(Extra high)/High/Low %	75/75/77	75/75/78	75/75/76	75/75/79
Energy exchange efficiency cooling	(Extra high)/High/Low %	63/63/65	66/66/71	62/62/64	65/65/68
Energy exchange efficiency heat pump	(Extra high)/High/Low %	70/70/72	69/69/73	67/67/69	71/71/74
Sound pressure level	(Extra high)/High/Low dB*	31.5/30.5/26.5	33.0/31.0/25.5	37.5/35.5/32.5	37.5/37.0/34.5
Normal Ventilation					
Input power	(Extra high)/High/Low W	128/123/96	190/185/168	289/225/185	418/378/295
Airflow rate	(Extra high)/High/Low m <sup>3</sup> /h	250/25/190	350/350/240	500/500/440	800/800/630
External static pressure	(Extra high)/High/Low Pa	105/95/45	140/60/45	120/60/35	140/110/55
Sound pressure level	(Extra high)/High/Low dB*	31.5/30.5/26.5	33.0/31.0/25.5	38.5/38.0/32.5	37.5/37.0/34.5
Dimensions	W × D × H mm	882 × 599 × 270	1,050 × 804 × 317	1,090 × 904 × 317	1,322 × 884 × 388
Weight	kg	29	49	57	71
Outlet duct diameter	mm	150	150	200	250
Operating range	°C	-10 to 40	-10 to 40	-10 to 40	-10 to 40
Maximum humidity	%	85	85	85	85

\* Noise level measured 1.5 m below the center of the unit

### Dimensions

(Unit: mm)



	UTZ-BD025C	UTZ-BD035C	UTZ-BD050C	UTZ-BD080C	UTZ-BD100C
A	810	978	1,018	1,250	1,250
B	599	804	904	884	1,134
C	315	580	640	428	678
D	142	112	132	228	228
E	600	600	600	600	600
F	655	860	960	940	1,190
G	19	19	19	19	19
H	270	317	317	388	388
I	135	159	159	194	194
J	159	182	182	218	218
K	882	1,050	1,090	1,322	1,322
L	414	470	470	612	612
M	95	70	70	85	85
N	Ø164	Ø164	Ø210	Ø258	Ø258
O	Ø144	Ø144	Ø194	Ø242	Ø242


## DX kit

for Air handling applications  
for VRF Outdoor unit



With these kits, air handling units (AHUs) and fan coil units (FCUs) from other manufacturers can be incorporated into Fujitsu General VRF systems, or one AHU can be connected to one Fujitsu General VRF dedicated outdoor unit to control outdoor ventilation and room temperatures.


### Multiple temperature sensors optimally control an Air handling unit and a fan coil unit.



When connected to an Air handling unit, the temperature of supply air is controlled by a discharge air sensor.


When connected to a fan coil unit, the room temperature is controlled by the discharge air sensor.

### Application as part of a VRF system




### Supports a wide range of capacity classes

- Two EEV units can be connected in parallel to large-capacity units of up to 20 HP (50 kW). (UTP-LX180A separation tube required)
- Connectable capacity range: 5 kW to 50 kW




### A variety of control options that meet application requirements

Central control enabled by our VRF controllers or central management controllers



### Central control from external controllers



### Summary of functions

#### Inputs

- On/Off
- Setting temperature
- Capacity demand
- Heating/Cooling operation modes
- Fault indication

#### Outputs

- On/Off indication
- Fan On/Off indication
- Thermostat On/Off indication
- Defrost indication
- Fault indication


#### MODBUS® Control

Can be controlled via a MODBUS®-enabled BMS using an optional interface.

### Installation requirements

- Connectable VRF Series: All VRF Series
- Capacity range of connectable DX kit systems with outdoor units: 50 to 100% of capacity
- Capacity range of connectable DX kit systems with indoor units: 30% or less of capacity
- Max. wire length from a control unit: 10 m
- Max. pipe length between EEV unit and indoor unit: 5 m
- A control unit (IP54 class) and an EEV unit can be installed outdoors.


#### Connectable capacity



### Optional separation tube to connect two EEV units: UTP-LX180A



#### Pipe and wire length



### Control unit: UTY-VDGX

EEV unit: UTP-VX30A/UTP-VX60A/UTP-VX90A



### Specifications

Connectable capacity class	5.0 kW	6.3 kW	8.0 kW	10.0 kW	12.5 kW	14.0 kW	20.0 kW	25.0 kW	40.0 kW	50.0 kW	
Capacity	Cooling kW	5.6	6.3	8.0	10.0	12.5	14.0	22.4	25.0	40.0	50.4
	Heating kW	6.3	7.1	9.0	11.2	14.0	16.0	25.0	28.0	45.0	56.5

Control unit	UTY-VDGX
Power source	V/IØ/Hz
Dimensions (H × W × D)	230/I/50 400 × 400 × 120

EEV unit	UTP-VX30A	UTP-VX60A	UTP-VX90A	UTP-VX90A × 2
Connection pipe diameter (Liquid) Dimensions (H × W × D)	Ø9.53 160 × 220 × 90	Ø12.70 160 × 220 × 90	Ø12.70 160 × 220 × 90	Ø12.70 160 × 220 × 90

Note: Specifications are based on the following conditions.  
Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature of 7°CDB/6°CWB.  
Pipe length: 7.5 m Voltage: 230 [V].

## DX kit


for Air handling applications  
for Single Split Outdoor Units



With this kit, other manufacturers' Air handling units (AHUs) and fan coil units (FCUs) can be incorporated into Fujitsu General Split outdoor units.

### Flexible connectivity

This kit allows connections to third-party equipment. This control unit can also be used in conjunction with Fujitsu General single-split outdoor units, providing a perfect solution when a stand-alone Air handling unit is needed.




### Supports a wide range of capacity classes

Capable of connecting large capacities in the range of 2.5 kW to 22.0 kW (Nominal)



### Mobile devices allow for operation from anywhere

Can be operated and managed remotely using your smartphone or tablet.



### Summary of functions

### Inputs

- On/Off
- Heating/Cooling operation modes
- Capacity demand (analogue 0 to 10 V)
- Status indicator with LED
- Heat exchanger temperature

### Outputs


- Status of Compressor, Defrost, and Errors (Potential free relays)
- Status indicator with LED

### Wireless LAN Control

Wireless LAN control through cloud connectivity enables secure remote monitoring and control from anywhere.

### Easy installation

- Compact DIN rail mountable enclosure for easy installation
- No expansion devise required
- No separate external power supply required



**Model: UTY-XDZX**



### Specifications

R410A models

BTU	Cooling	kW	12	14	18	24	30	36	45	54	60	72	90
Capacity (Nominal)	Cooling	kW	3.5	4.3	5.2	6.8	8.5	9.4	12.1	13.3	15.0	19.0	22.0
	Heating		4.1	5.0	6.0	7.8	10.0	10.8	13.3	15.8	18.0	22.4	27.0

R32 models


BTU	Cooling	kW	09	12	14	18	22	24	30	36	45	54
Capacity (Nominal)	Cooling	kW	2.5	3.5	4.3	5.2	6.0	6.8	8.5	9.4	12.1	13.3
	Heating		3.2	4.1	5.0	6.0	7.0	7.5	10.0	10.8	13.3	15.8

Model name	UTY-XDZX
Power source	V/Ø/Hz
Dimensions (H × W × D)	mm
Weight	g

Note: Specifications are based on the following conditions.  
Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.  
Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.  
Pipe length: 5.0 m Voltage: 230 [V].


# Light Commercial & Commercial, Residential CONTROL SYSTEM & OPTIONAL PARTS

- C-002 Control System Overview
- C-006 Best control solution for each building structure
- C-008 Comparison table of controllers
- C-050 Controller System List
- C-058 Optional Parts Overview
- C-066 Optional parts list
- C-070 Function list



A wide product lineup to meet a variety of needs

We can flexibly meet customer needs through a variety of offerings including wired and wireless individual remote controllers, central remote controllers that simultaneously control multiple indoor units, and a variety of converters that link with other systems.



## CONTROL SYSTEM

### INDIVIDUAL CONTROL

- C-010 Wired remote controller (Design type)
- C-012 Wired remote controller (with touch panel)
- C-014 Wired remote controller / Compact wired remote controller
- C-015 Wired remote controller
- C-016 Simple remote controller
- C-017 Wireless remote controller
- C-018 IR receiver unit

### CONVERTERS/ADAPTERS

- C-020 WLAN adapter
- C-024 Multiple protocol WLAN adapter

### CENTRALIZED CONTROL

- C-025 Home central remote controller
- C-026 Central remote controller
- C-028 Touch panel controller
- C-032 System controller Software / System controller lite Software

### CONVERTERS/ADAPTERS

- C-036 MODBUS® converter for indoor unit
- C-037 MODBUS® interface
- C-038 MODBUS® converter for VRF
- C-039 BACnet® interface
- C-040 BACnet® gateway Software
- C-041 BACnet® gateway Hardware
- C-042 BACnet®/MODBUS® router
- C-043 BACnet®/MODBUS® cloud device
- C-044 KNX® converter for indoor unit / KNX® converter for VRF
- C-045 KNX® interface
- C-046 Network converter for single-split type
- C-047 Network converter for LONWORKSTM
- C-048 External switch controller / Signal amplifier

## Optional parts

- C-060 Silver ion filter
- C-061 Auto louver grille kit
- C-062 Pressure sensor kit
- C-063 External power supply unit  
AIR BEAM radiation air outlet unit
- C-064 Gas sensor kit
- C-074 Separation tube and other piping products



SPLIT



MULTI-SPLIT



VRF J Series



VRF V Series

# Control System Overview

for Split & Multi-split

All indoor units\* are equipped with a wireless or wired remote controller as standard. Additional options are available, such as individual remote controllers and central remote controllers. The easy-to-operate central remote controller makes it simple to control the operation mode, temperature, airflow volume, timer, and other functions of each indoor unit from a single location.

\* Except for some products

## Air Conditioning Individual control

**Wired remote controller**  
A built-in thermo sensor monitors and controls room temperature accurately.

**Wireless remote controller**  
Simple and versatile operations with a choice of 4 different types of timers

**Simple remote controller**  
Compact remote controller with basic functionality

**For Ceiling type**

**For Duct type**


**For Cassette type**

**IR receiver unit**  
This IR receiver unit enables a wireless remote controller to control a duct-type indoor unit.



## Air Conditioning Centralized control

**Home central remote controller for 5 & 6-unit Multi-split type**  
Enables individual and central control.



## Converters/Adapters

For external control via BMS/Home Automation Systems

**MODBUS® converter**  
for indoor units  
UTY-VMSX



**MODBUS® interface**  
for indoor units



**KNX® converter**  
for indoor units  
UTY-VKSX



**KNX® interface**  
for indoor units



**WLAN adapter**



**Network converter**

DC power supply type  
UTY-VTGX

AC power supply type  
UTY-VTGXV

## Online Control (Wireless Control via Smartphone/Tablet)

With the WLAN adapter and the AIRSTAGE Mobile app, you can control the heating and cooling of your home anytime, anywhere.

### WLAN adapter

The dedicated WLAN adapter enables the air conditioner to be operated by smartphone or tablet computer.




**AIRSTAGE**  
Mobile

Download Free  
App Store Google play

### Simple, user-friendly interface design

The designed screen display makes it easier than ever to operate.



# Control System Overview


for VRF

To meet the diverse needs of customers, we offer a variety of control options for our VRF systems, such as individual control, centralized control, and building management system (BMS) options.


## Air Conditioning Individual control

- Wired remote controller (Design type)**  
UTY-RVRY
- Wired remote controller (with touch panel)**  
UTY-RNRYZ5
- Wired remote controller**  
UTY-RLRY
- Compact wired remote controller**  
UTY-RCRYZ1
- Simple remote controller**  
UTY-RSRY  
UTY-RHRY  
Without operation mode
- Wireless Remote Controller**  
UTY-LNVY  
UTY-LNHY
- IR receiver unit**  
UTB-YWC for duct type  
UTY-TRHX for One-way flow cassette Series/  
3D-flow cassette Series/duct type  
UTY-LBHXD for Circular flow cassette Series

## Air Conditioning Centralized control

- System controller Software**  
UTY-APGXZ1/UTY-ALGXZ1 (Lite version)  
  


Up to 1600<sup>\*2</sup> Indoor units

\*1: Echelon® U10 USB Network Interface  
\*2: The Lite version controls up to 400 indoor units.
- Touch panel controller**  
UTY-DTGYZ1  
  



Up to 400 Indoor units
- Central remote controller**  
UTY-DCGYZ3  
  


Up to 100 Indoor units




## Converters/Adapters

For external control via BMS/Home Automation Systems



## Converters/Adapters for system expansion



# Best control solution for each building structure

Fujitsu General provides the best control solutions suitable for various building structures.

## SHOP

Type	Individual control		Centralized control			Integrating control (Interface)		
	Wired remote controller	Central remote controller	Touch panel controller	System controller	Network converter for LONWORKS™	MODBUS® Converter	KNX® converter	
	UTY-RVRY UTY-RNRYZ5 UTY-RLRY UTY-RVNM UTY-RCRYZ1	UTY-DCGYZ3	UTY-DTGYZ1	UTY-APGXZ1 UTY-ALGXZ1	UTY-VLGX	UTY-VMGX	UTY-VKGX	
Automatic control of air conditioning (Schedule timer, Weekly timer, etc.)	●	●	●	●				
Controls limited to staff: Remote controller prohibition, Setting temperature range limitation, etc.		●	●	●	●	●	●	
Group control		●	●	●				
Advanced energy saving: Peak cut, Operation of indoor unit rotation, etc.				●				
Remote monitoring management		●	●	●				
Manage multiple sites		●	●	●				
Monitor energy consumption				●				
Control third-party products				●				
Integrate Fujitsu General air conditioning into BMS					●	●	●	

## HOTEL

Type	Individual control			Centralized control			Integrating control (Interface)		
	Wired remote controller	Simple remote controller	Wireless remote controller	Central remote controller	Touch panel controller	System controller	BACnet® gateway	Network converter for LONWORKS™	MODBUS® converter
	UTY-RVRY UTY-RNRYZ5 UTY-RLRY UTY-RCRYZ1	UTY-RSRY UTY-RHRY	UTY-LNRY UTY-LNHY UTY-LNTY	UTY-DCGYZ3	UTY-DTGYZ1	UTY-APGXZ1 UTY-ALGXZ1	UTY-ABGXZ1 UTY-VBGX	UTY-VLGX	UTY-VMGX
Local control for hotel guests	●	●	●						
Centralized air conditioning control for common areas			●	●	●	●	●	●	●
Limited control for hotel guests			●	●	●	●	●	●	●
Remote monitoring management			●	●	●				
Advanced energy saving: Peak cut, Operation of indoor unit rotation, etc.					●	●			
Monitor energy consumption					●				
Control third-party products					●				
Integrate Fujitsu General air conditioning into BMS						●	●	●	●
Interlock with window contact									●
Interlock with key card									●

## OFFICE

Type	Individual control			Centralized control			Integrating control (Interface)		
	Wired remote controller	Simple remote controller	Wireless remote controller	Central remote controller	Touch panel controller	System controller	BACnet® gateway	Network converter for LONWORKS™	MODBUS® converter
	UTY-RVRY UTY-RNRYZ5 UTY-RLRY UTY-RCRYZ1	UTY-RSRY UTY-RHRY	UTY-LNRY UTY-LNHY UTY-LNTY	UTY-DCGYZ3	UTY-DTGYZ1	UTY-APGXZ1 UTY-ALGXZ1	UTY-ABGXZ1 UTY-VBGX	UTY-VLGX	UTY-VMGX
Local control for office staff	●	●	●	●					
Automatic control of air conditioning (Schedule timer, Weekly timer, etc.)	●		●	●	●	●	●		
Centralized air conditioning control for management					●	●	●	●	●
Controls limited to staff: Remote controller prohibition, Setting temperature range limitation, etc.				●	●	●	●	●	●
Advanced energy saving: Peak cut, Operation of indoor unit rotation, etc.						●	●		
Remote monitoring management					●	●	●		
Electricity charge apportionment						●	●	●	
Monitor energy consumption							●		
Control third-party products							●		
Integrate Fujitsu General air conditioning into BMS							●	●	●
Interlock with door contact									●
Interlock with Human sensor for meeting room					●				●

# Comparison table of controllers

Item																
	Wired remote controller (Design type)	Wired remote controller (with touch panel)	Wired remote controller	Wired remote controller	Compact wired remote controller	Simple Remote Controller	Simple remote controller*1	Wireless remote controller	Wireless remote controller	Wireless remote controller	Home central remote controller (for 5/6-unit multi-split type)	Central remote controller	Touch panel controller	System controller Lite Software	System controller Software	
Model name	UTY-RVRY	UTY-RNRYZ5	UTY-RLRY	UTY-RVNYM	UTY-RCRYZ1	UTY-RSRY		UTY-RHRY	UTY-LNTY	UTY-LNVY	UTY-LNHY	UTY-DMMYM	UTY-DCGYZ3	UTY-DTGYZ1	UTY-ALGX1	UTY-APGX1
Maximum number of controllable remote controller groups	1	1	1	1	1	16		16	16	16	16	1	100	400	400	1600
Maximum number of controllable indoor units	16	16	16	16	1	16		16	16	16	16	8	100	400	400	1600
Maximum number of controllable groups	—	—	—	—	—	—		—	—	—	—	—	50	400	400	1600
Air conditioning control functions	ON/OFF	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Operation mode setting	●	●	●	●	●	●	—	●	●	●	●	●	●	●	●
	Fan speed control	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Room temperature setting	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Setting temperature range limitation	●	●	●	●	●	—	●	—	—	—	—	●	●	●	●
	Test operation	●	●	●	●	●	●	●	●	●	●	●	●	●	—	—
	Vertical louver setting	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Horizontal louver setting	●	●	●	●	●	●	—	—	●	●	—	●	●	●	●
	Individual louver control	●	●	●	—	—	●	—	—	—	—	—	●	*3	—	—
	Group setting	—	—	—	—	—	—	—	—	—	—	—	●	●	●	●
	Remote controller prohibition	—	—	—	—	—	—	—	—	—	—	—	●	●	●	●
	Anti-freeze setting	●	●	—	—	●	—	—	—	—	—	—	●	●	●	●
	Set temperature auto return	●	●	●	●	●	—	—	—	—	—	—	●	●	—	—
	Economy mode setting	●	●	●	●	●	—	—	●	●	●	●	●	●	●	●
	Human sensor control	●	●	—	—	—	—	—	—	—	—	●	●	●	●	●
	Error	●	●	●	●	●	●	●	—	—	—	—	●	●	●	●
	Defrosting	●	●	●	●	●	●	●	—	—	—	—	●	●	●	●
	Current time	●	●	●	●	●	—	—	●	●	●	●	●	●	●	●
	Day of week	●	●	●	●	●	—	—	—	—	—	—	●	●	●	●
	Remote controller prohibition	●	●	●	●	●	●	●	—	—	—	—	●	●	●	●
Displayed items	Address display	●	●	●	●	●	●	●	—	—	—	—	—	●	●	●
	Room temperature	●	●	—	●	●	●	●	—	—	—	—	*4	*4	*4	*4
	Multiple language support	●	●	—	●	—	—	—	—	—	—	●	●	●	●	●
	Setting for daylight saving time	●	●	—	●	—	—	—	—	—	—	●	●	●	●	●
	Name registration	●	●	—	—	—	—	—	—	—	—	—	●	●	●	●
	Backlighting	●	●	—	●	●	●	●	—	●	—	●	●	●	●	—
	2D floor layout/3D building display	—	—	—	—	—	—	—	—	—	—	—	—	—	—	●
	Refrigerant leak detector	—	—	—	—	—	—	—	—	—	—	—	●	●	●	●
	Refrigerant Cycle Monitor	●	●	—	—	—	—	—	—	—	—	—	—	—	—	—
	Logo Display	●	—	—	—	—	—	—	—	—	—	—	—	—	—	—
	Limited Visibility of Settings	●	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Timer	Period	Week	Week	Week	Week	—	—	—	—	—	—	—	Week	Year	Year	Year
	Schedule timer	8	8	4	8	—	—	—	—	—	—	—	4	20	20	144
	ON/OFF, Temp, Low noise mode*, Times per day	—	—	—	—	●(OFF only)	—	—	●	●	●	—	—	—	—	—
	ON/OFF timer	—	●	●	●	●	—	—	●	●	●	—	—	—	—	—
	Sleep timer	—	—	—	—	—	—	—	●	●	●	—	—	—	—	—
	Program timer	—	—	—	—	—	—	—	●	●	●	—	●	—	—	—
	Auto-off timer	●	●	●	●	—	—	—	—	—	—	—	●	●	—	—
	Day off	●	●	●	●	—	—	—	—	—	—	●	●	●	●	●
	Minimum unit of timer setting (minutes)	1 • 10	10 • 30	30	30	—	—	—	5	5	5	5	10	10	10	10
	Remote monitoring management system	—	—	—	—	—	—	—	—	—	—	—	●	●	●	●
Control	Electricity charge apportionment	—	—	—	—	—	—	—	—	—	—	—	○	○	●	●
	Error history	●	●	●	●	—	—	—	—	—	—	—	●	●	●	●
	Emergency stop	—	—	—	—	—	—	—	—	—	—	—	*2	*2	—	—
	Remote monitoring management	—	—	—	—	—	—	—	—	—	—	—	●	●	○	●
	Energy-saving management	—	—	—	—	—	—	—	—	—	—	—	—	—	○	○
	E-mail notification in case of failure	—	—	—	—	—	—	—	—	—	—	—	●	●	●	●
	Key lock	●	Child lock	●	Child lock	●	—	—	—	—	—	●	Child lock	Password setting	Password setting	Password setting
	Low noise mode	—	—	—	—	—	—	—	—	—	—	●	●	●	●	●

\*1 "Operation mode" setting not available.

\*2 Available only for external input control.

\*3 Monitoring sites can be set up.

The main unit side can only be operated to cancel the settings.

\*4 Available only when using Wired remote controller.

\*5 UTY-DCGYZ3 only

●: Supported ○: Optional function —: Unsupported

## Wired remote controller (Design type)

UTY-RVRY



Up to  
16 indoor units  
Up to  
1 group



GOOD DESIGN  
AWARD 2022

### Simple and stylish design that harmonizes with the space

- The new stylish design controller, UTY-RVRY, enables intuitive operation with touch screen. It is compatible with many 2-wired indoor units.




### Harmonizes with the Installation Space

When not in use, the controller is a part of the interior décor. This is achieved by using mirrors, glass, and clear panels, and it appears to be one with the wall. The sleek and stylish design won the 2022 Good Design Award and was selected as a finalist for the 2023 IDEA award.



### Intuitive operation

The touch screen is easily operated by swiping vertically and horizontally, and users can operate the controller without using manuals.



### Status LED Colors

When not in use, the operation mode is indicated through LED lamp colors shown under the controller. The LED lamp can be switched ON and OFF to avoid glare at night.



Blue: Cooling

Red: Heating



Green: Dry

Purple: Auto

### Features: Wired Remote Controller (Design type)

#### Refrigerant cycle monitor

The controller will display specific sensor values of outdoor and indoor units for maintenance and service support.

- \* Display screen example
- \* This function is only supported by split units, using the H-Serial communication protocol! Example: ASYH30KMTB



#### Logo Display

The controller can display hotel logos when not in use. Images are sent via Bluetooth® connection where data is saved in the flash memory built into each controller.

\* Color display available




#### AIRSTAGE Remo Set application (free download)

Set up your new Wired Remote Controller via Bluetooth from your smartphone (or directly at the controller).


##### Features:

- Initial configuration
- Function setting
- Custom logo import
- Copy settings between controllers



#### Initial Settings / Indoor Unit Function

The initial controller settings and indoor unit function settings can be sent from a smartphone by pairing with the controller via Bluetooth. It also can read the setting values of a paired controller, and send a copy of them to one or more additional controllers, significantly reducing installation time.



\*Smartphone : Wired Remote Controller = 1 : 1

#### Specifications

Model name	UTY-RVRY
Power Source	DC12V
Dimensions (H × W × D) (mm)	121.5 × 116 × 26
Weight (g)	225

## Wired remote controller (with touch panel)

UTY-RNRYZS



Up to  
16 indoor units  
Up to  
1 group



### Easy operation due to large high-resolution STN-LCD touch panel screen

- Touch screen LCD
- Built-in daily/weekly timer (ON/OFF, temperature, modes)
- Backlit screen for easy operation in the dark.
- Room temperature display
- Controls up to 16 indoor units
- Supports 12 languages: Chinese, Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, and Turkish
- Nonpolar 2-core type


### High performance and compact size

A single remote controller controls each connected indoor unit and provides a weekly timer function and a variety of energy-saving options.



### Accurate control for comfort

A thermo sensor built into the remote controller monitors room temperature accurately.




### Energy saving controls

#### Custom Auto

- Maintains 2 separate setpoints for heating and cooling operations.
- Automatically switches between heating and cooling modes.

\* Not available for some models




#### Auto-off timer

- While the Auto-off timer is activated, if the set off time is specified as, for example, one hour, the power will automatically turn off one hour after the start of operation.
- A desired time frame can be specified for the Auto-off timer.
- The off-time can be set from 30 to 240 minutes.

#### 2-setting weekly timer

#### Set temperature auto return

#### Setting temperature range limitation




e.g.) Between 17:00 and 24:00 (over time hours), when the 1 hour set off time has elapsed, the system will automatically turn off the indoor unit as it

### Features: Wired Remote Controller (Touch Panel)

#### Refrigerant cycle monitor (Option)

Wired Remote Controller (Touch Panel) will support to display some sensor values for maintenance and service support.


\* This function is only supported by split units, using the H-Serial communication protocol! Example: ASYH30KMTB



### Multi System Control<sup>\*</sup>


#### 1) Lead Lag Operation

Standby Indoor Unit can be selected in lead lag operation. By this, the Indoor units will last longer than operating by nonstop.




#### 2) Back up operation

In case of unexpected Indoor unit error, other Indoor units will start providing back up operation.



#### 3) Lag Operation

In case of unexpected room temperature rise, other Indoor Units will start providing lag operation.



\*1: "Lead Lag Setting" is an easy-to-use function for room temperature control when using multiple indoor units, while reducing the burden placed on each indoor unit.

If you wish to make use of this function, ensure you use indoor units equipped with a "Special Cooling" function.

For Split products with "Special Cooling" function, refer to S-068 to S-071.

If you use indoor units that do not have a "Special Cooling" function, under certain conditions, there is a chance that "Backup operation" may not operate correctly, and the "Lead Lag Setting" function will not give the expected results.

Additionally, for rooms that require strict conditions, such as server rooms, please consider other appropriate measures.

Please note that we will not provide compensation for any damages suffered to your appliances or data as a result of using this function.

For more details, please confirm with your nearest retail store.

### Specifications

Model name	UTY-RNRYZS
Power Source	DC 12 V
Dimensions (H x W x D) (mm)	120 x 120 x 20.4
Weight (g)	220

DC 12 V is supplied by the indoor unit.

## Wired remote controller

UTY-RRLRY



Up to  
16 indoor units  
Up to  
1 group

- ON/OFF/Weekly timer settings
- A built-in thermo sensor monitors and controls room temperature accurately.
- When something goes wrong, an error code is displayed.
- 16 error codes from the most recent one will be kept in the history. (Last 16 error codes can be accessed)
- Nonpolar 2-core type

### High performance and compact size

A single remote controller controls each connected indoor unit and provides a weekly timer function and a variety of energy-saving options.



### Visually intuitive operation

- The operation mode, set temperature, and fan speed are shown prominently on the top screen.
- Each function to be set is indicated by an icon.
- The control guide makes it simple and straightforward to operate a remote controller.



## Compact wired remote controller

UTY-RCRZY1




Up to  
1 indoor units  
Up to  
1 group

- Simple design that matches stylish interiors
- The body of the controller, which is easy to install, is designed to conform to the European standard junction box.
- Can be operated both by wireless and wired remote controller.
- Nonpolar 2-core type


### Large screen and simple display

- Large screen but compact size
- Large, easy-to-read letters are used.
- The controls are simple and easy to understand.



### System overview

#### VRF connection



#### RAC connection



### Specifications

Model name	UTY-RRLRY	UTY-RCRZY1
Power source	12 V DC	12 V DC
Dimensions (H × W × D) (mm)	120 × 120 × 17	86 × 86 × 44
Weight (g)	170	135

12 V DC supplied by an indoor unit

## Wired remote controller

UTY-RVNYM




Up to  
16 indoor units  
Up to  
1 group

### Hi-grade individual control with a wide range of functions.

- 3.7-inch backlit LCD screen.
- Supports energy-saving functions with simple operation.
- Supports 9 languages: English, French, German, Greek, Italian, Portuguese, Russian, Spanish, and Turkish

### Visually intuitive operation

- Each function is displayed as an icon.
- Main functions are indicated by large icons: "Mode," "Set Temp," and "Fan."
- Easy operation with control guide display
- Simple operation with easy 4-way navigation pad



### High performance and compact size

- A single remote controller controls each connected indoor unit and provides a variety of energy-saving options.



## Wired remote controller

UTY-RNNYM




Up to  
16 indoor units  
Up to  
1 group

- Simple operation with Built-in Weekly/Daily Timer.
- Control up to 16 indoor units.
- Up to 2 Wired remote controllers can be connected to a single indoor unit.

### Accurate control for comfort

A thermo sensor built into the remote controller monitors room temperature accurately. The wired remote controller and an optional Remote sensor can be installed in any location to meet any requirement.

#### Examples of sensor changes



The temperature displayed is the set temperature.

### Built-in timer

**Weekly timer:** ON/OFF time can be set to operate twice for each day of the week.  
**Temperature setback timer:** Sets the time to change the temperature setting and the time to hold the setting for each day of the week.  
At "Weekly timer" + "Temperature setback timer" setup

### Specifications

Model name	UTY-RVNYM	UTY-RNNYM
Power source	12 V DC	12 V DC
Dimensions (H × W × D) (mm)	120 × 120 × 21.3	120 × 120 × 18
Weight (g)	220	160

## Simple remote controller

UTY-RSRV / UTY-RHY (without operation mode)



Up to  
16 indoor units  
Up to  
1 group

### Compact remote controller with basic functionality


- Up to 16 indoor units can be controlled with one remote controller.
- Suitable for hotels or offices as it is easily operated with no complex functions.
- Simple design that matches stylish interiors
- Large LCD screen and easy-to-use control buttons
- Backlight: White backlight makes it easy to operate in the dark.
- Nonpolar 2-core type

### Supports a variety of applications


- Vertical louver control:** Adjusts the vertical airflow direction of a duct-type indoor unit with an auto louver or a cassette type installed in a hotel room or a conference room.



- Setting temperature range limitation:** Enables an indoor unit to operate in an energy-saving manner in a small building not equipped with a central remote controller.



- Built-in room temperature sensor:** Monitors and controls room temperature accuracy.



## Wireless remote controller

UTY-LNTY



Up to  
16 indoor units  
Up to  
1 group  
Up to  
4 different daily timers

### Simple and versatile operations with a choice of 4 different types of timers

- Controls up to 16 indoor units.

### Built-in timer

4 timer programs: ON/OFF/Program/Sleep  
Program timer: Sets ON/OFF time once for every 24 hours.  
Sleep timer: Adjusts the set temperature automatically while the sleep timer is on.

### Easy installation and operation

Different codes can be assigned to up to 4 indoor units to prevent a mix-up.  
Wide and precise transmitting range

## Wireless remote controller

UTY-LNVY

NEW



Up to  
16 indoor units  
Up to  
1 group  
Up to  
4 different daily timers

### New stylish design with backlight

- It has adopted a new simple and stylish design.
- The built-in backlight allows the screen to be seen even in dark rooms.

### Built-in timer

4 timer programs: ON/OFF/Program/Sleep  
Program timer: Sets ON/OFF time once for every 24 hours.  
Sleep timer: Adjusts the set temperature automatically while the sleep timer is on.

### Error diagnosis

It can detect the reason for system errors easily.  
When an error is detected, the error code number can be checked using the remote controller display.

### Precise control

The setting temperature can be adjusted precisely depending on the environment as the controller can set the temperature via 0.5 °C\*.

\*Depends on the indoor unit

## Wireless remote controller

UTY-LNHY



Up to  
16 indoor units  
Up to  
1 group  
Up to  
4 different daily timers

### Simple and versatile operations with a choice of 4 different types of timers

- Controls up to 16 indoor units.

### Built-in timer

4 timer programs: ON/OFF/Program/Sleep  
Program timer: Sets ON/OFF time once for every 24 hours.  
Sleep timer: Adjusts the set temperature automatically while the sleep timer is on.

### Easy installation and operation

Different codes can be assigned to up to 4 indoor units to prevent a mix-up.  
Wide and precise transmitting range

#### Specifications

Model name	UTY-RSRV	UTY-RHY	UTY-LNTY
Power source	12 V DC	12 V DC	3.0V (1.5V R03/LR03/AAA x 2)
Dimensions (H × W × D) (mm)	120 × 75 × 19.4	120 × 75 × 19.4	205 × 61 × 17
Weight (g)	120	120	125

12 V DC supplied by an indoor unit


#### Specifications

Model name	UTY-LNVY	UTY-LNHY
Battery	3.0V (1.5V R03/LR03/AAA x 2)	3.0V (1.5V R03/LR03/AAA x 2)
Dimensions (H × W × D) (mm)	181 × 58 × 17	170 × 56 × 19
Weight (g)	116	85

12 V DC supplied by an indoor unit

## IR receiver unit for duct type

UTY-LRHYM / UTY-LBTYM



The wireless remote controller controls duct type indoor units.



## IR receiver unit for Cassette

UTY-LBTYC



Cassette type indoor unit can be controlled with a Wireless remote controller.



## IR receiver unit for ceiling type

UTY-LBTYH



The wireless remote controller controls ceiling type indoor units.



### Specifications

&lt; Wireless Remote Controller &gt;

Model name	UTY-LRHYM	UTY-LBTYM	UTY-LBTYC	UTY-LBTYH
Battery	1.5 V (R03/LR03/AAA)	1.5 V (R03/LR03/AAA)	1.5 V (R03/LR03/AAA)	1.5 V (R03/LR03/AAA)
Dimensions (H × W × D) (mm)	170 × 56 × 19	205 × 61 × 17	205 × 61 × 17	205 × 61 × 17
Weight (g)	85	125	125	125
< IR Reciver Unit >				
Battery	DC5V	DC5V	DC5V	DC5V
Dimensions (H × W × D) (mm)	145 × 90 × 30	145 × 90 × 30	-*	-*
Weight (g)	150	150	140	100

DC 5 V is supplied the indoor unit.

\*It will replace the parts of the indoor unit to be connected.

## IR receiver unit for duct type

UTB-YWC / UTY-TRHX

The wireless remote controller controls duct type\* indoor units.

\*Large airflow duct types do not work with this IR receiver unit.



\*A separate wireless remote control (model: UTY-LNHY) is required.

## IR receiver unit for Cassette

UTY-LBHxD / UTY-TRHX

Cassette type indoor unit can be controlled with a Wireless remote controller.



\*A separate wireless remote control (model: UTY-LNHY or UTY-LNVY) is required.



### Specifications

&lt; Wireless Remote Controller &gt;

Model name	UTB-YWC	UTY-LBHxD	UTY-TRHX
Battery	1.5 V (R03/LR03/AAA)	1.5 V (R03/LR03/AAA)	1.5 V (R03/LR03/AAA)
Dimensions (H × W × D) (mm)	170 × 56 × 19	170 × 56 × 19	170 × 56 × 19
Weight (g)	85	85	85
< IR Reciver Unit >			
Battery	DC5V	DC5V	DC5V
Dimensions (H × W × D) (mm)	145 × 90 × 30	-*	145 × 90 × 30
Weight (g)	150	140	150

DC 5 V is supplied the indoor unit.

\*It will replace the parts of the indoor unit to be connected.

## WLAN adapter

UTY-TFSXH3 / UTY-TFSXJ3

USB type for single split models  
UTY-TFSXH3UTY-TFSXJ3  
(CN connector type)

### AIRSTAGE Mobile

"AIRSTAGE Mobile" is an application software that enables you to manage the Fujitsu General's air conditioner(s) with a mobile device from anywhere.

- Maximum 5 accounts per 1 indoor unit
- Room / Outdoor temperature display
- Can be used for a Single / Multi and VRF indoor units.
- No separate external power supply required
- "AIRSTAGE Mobile" is an application software that enables you to operate the Fujitsu General's air conditioners with a mobile device.



### User Friendly for Everyone

Enjoy easy-to-use centralized operation of air conditioners via a smartphone anytime, anywhere

Up to  
**1** indoor units

Shop Owner



Commercial Building Owner

### Main Functions

- |                           |                               |
|---------------------------|-------------------------------|
| • ON / OFF                | • Weekly timer                |
| • Operation mode          | • Room temperature display    |
| • Fan speed               | • Outdoor temperature display |
| • Louver position         | • Error display               |
| • Set temperature control |                               |

\*Contents of display differ depending on the type of indoor unit.

### New Design!

**Ease of use is pursued to achieve a stylish design.**


The more legible and accessible timer UI enables effortless schedule management.



### Features: AIRSTAGE Mobile

#### Centralized operation for flexible remote management of all air conditioners


AIRSTAGE Mobile is ideal for a wide range of applications, from large residential buildings to smaller commercial spaces such as offices and stores. Anyone who has a smartphone and an adapter can easily manage the system at a low cost.



Increased the Number of Accounts  
Maximum **5** accounts per 1 indoor unit

#### Hierarchical group management


Multiple air conditioners can be combined into a single group for centralized operation. Several groups can also be organized at once. Grouping the air conditioners by building, floor, or room makes it easy for users to monitor their operation status and operate them quickly.



All on/off  
Centralized operation of each group  
Monitor the status of each air conditioner at a glance




Customer AIRSTAGE Mobile



\*One wireless LAN adapter is required per indoor unit.

#### Operate air conditioner and check its operation status just by talking to it

Connecting with a smart speaker allows the user to operate the air conditioner and check its operation status just by talking to it.



\* The new WLAN adapters for AIRSTAGE Mobile are compatible for the indoor units that can connect the following WLAN adapters for FG Lair.

	CN connector type	USB type
for FG Lair	UTY-TFSXZ1	UTY-TFSXF2
for AIRSTAGE Mobile	UTY-TFSXJ3	UTY-TFSXH3

### Specifications


Model name	UTY-TFSXJ3(CN connector type)	UTY-TFSXH3
Dimensions (H × W × D) (mm)	71 × 38 × 15	56.7 × 34 × 9.72
Weight (g)	35	30

**WLAN adapter**


UTY-TFNXZ1 / UTY-TFSXZ1 / UTY-TFSXF2

USB type for single-split models  
UTY-TFSXF2


- This interface provides the most advanced solution for the remote management of an air conditioning system by using smartphones, tablets, and computers.
- No separate external power supply required
- Can be used for a Single / Multi and VRF indoor units.

UTY-TFNXZ1  
(3-wire RC-line type)  
UTY-TFSXZ1  
(CN connector type)Up to  
**1** indoor units**Basic control**


- Turning the units on and off
- Mode control (Heat, Cool, Dry, Auto, Fan)
- Fan speed control
- Louver position (airflow direction setting)
- Timer operation setting (Weekly timer)
- Economy mode setting

**Multiple air conditioning management**

- Manage multiple air conditioning systems in different locations.

**Error alert and e-mail notice**

- E-mail notification alerts
- Air conditioning malfunction alert
- Enables quick service response when errors occur.

**WLAN adapter (USB type)**  
UTY-TFSXF2

A compact USB type is available. No need for specialized installation.  
Easily installed on the indoor unit.

**Specifications**

Model name	UTY-TFNXZ1(3-wire RC-line type)	UTY-TFSXZ1(CN connector type)	UTY-TFSXF2
Dimensions (H × W × D) (mm)	71 × 38 × 15	71 × 38 × 15	56.7 × 34 × 9.72
Weight (g)	35	35	30

**WLAN adapter**


FG-RC-WIF1Z2 / FG-IR-WIF1Z1 / FG-AC-WIF1Z1

FG-RC-WIF1Z2  
(3-wire RC-line type)FG-AC-WIF1Z1  
(CN connector type)FG-IR-WIF1Z1  
(IR type)Up to  
**1** indoor units**AC Cloud Control**


- This interface provides the most advanced solution for the remote management of an air conditioning system by using smartphones, tablets, and computers.
- No separate external power supply required

**Installation example**


[3-wire RC-line type/CN connector type]



[IR type] Connection to wall-mounted type



[IR type] Connects to the product with the optional receiver kit



\*IR receiver required.

**Basic control**

- |   |                            |                                |
|---|----------------------------|--------------------------------|
| • Turning air conditioner on and off          | • Fan speed control        | • Multiple language support    |
| • Mode select (Heat, Cool, Dry, Auto, Fan)    | • Room temperature display | • One single scene is created. |
| • Louver position (airflow direction setting) | • Setting temperature      |                                |

**Advanced control (optional functions)**

- Climate-based operation modes (ECO, Comfort, and Powerful) (to be available in the future)
- Schedule functions (ON/OFF, modes, set temperature, fan speed, louver position)
- Setting temperature range limitation
- Multiple Scenes and Calendars are created.
- Smart Speaker compatibility
- Advanced internet service connections

**Notification and operation history**

- E-mail notification alerts
- Air conditioning malfunction alert
- Connectivity monitoring and alert
- Operation history (to be available in the future)

**Specifications**

Model name	FG-RC-WIF1Z2 (3-wire RC-line type)	FG-AC-WIF1Z1 (CN connector type)	FG-IR-WIF1Z1 (IR type)
Number of controllable groups	1	1	1
Dimensions (H × W × D) (mm)	108 × 70 × 28	81 × 78 × 28	127 × 50 × 17
Weight (g)	80	76	80

## Multiple protocol WLAN adapter

FG-RC-WMP1Z1 / FG-IR-WMP1Z1 / FG-AC-WMP1Z1


**Intesis®**FG-RC-WMP1Z1  
(3-wire RC-line type)

### AC Cloud Control


- Air conditioner control of Home Automation systems via wireless LAN connection.
- No separate external power supply required

#### Installation example

[3-wire RC-line type/CN connector type]



[IR type]



\*IR receiver required for other than wall-mounted type.

Up to  
1 indoor units

#### Specifications

Model name	FG-RC-WMP1Z1 (3-wire RC-line type)	FG-AC-WMP1Z1 (CN connector type)	FG-IR-WMP1Z1 (IR type)
Number of controllable groups	1	1	1
Dimensions (H × W × D) (mm)	70 × 100 × 28	127 × 50 × 17	81 × 78 × 28
Weight (g)	98	80	76


## Multiple protocol LAN adapter

FG-TL-MBS16Z1

**Intesis®**Up to  
16 indoor units

#### Installation example

[VRF type]



\*No separate external power supply required

#### Specifications

Model name	FG-TL-MBS16Z1 (VRF type)
Power supply	9 to 36 V DC, Max.: 140 mA or 24 V AC 50/60 Hz, Max.: 127 mA.*
Input power (W)	1.7
Dimensions (H × W × D) (mm)	90 × 88 × 56
Weight (g)	330

\*24 V DC power supply is recommended.

## Home central remote controller


UTY-DMMYM / UTY-DMMYM1



### For 5-unit and 6-unit multi-split type

- Batched control of up to 6 indoor units For all indoor units connected to the remote controllers, the Home central remote controller sets room temperature, airflow volume, and remote controller prohibition from other remote controllers at once.
- Supports 9 languages: English, French, German, Greek, Italian, Portuguese, Russian, Spanish, and Turkish.
- Large backlit LED screen
- Large, easy-to-see operation panel


#### Example of system configuration



### Home central remote controller

#### Weekly timer

Up to 4 ON/OFF settings can be programmed per day. Two weekly patterns can be set, one for the cooling season and the other for the heating season.



#### Low noise operation

You can choose from 4 low noise levels depending on the installation environment. ON/OFF timing of low noise mode can be set with the timer.


#### 10 °C heat operation

When you leave the house, the air conditioner runs a minimum heating operation to maintain the room temperature at 10°C.

\*Consult your dealer for conditions of use.

#### Economy operation

When you select energy-saving economy mode, the temperature setting for the indoor unit increases (during cooling operation) or decreases (during heating operation) by 1°C and the maximum electric value of the outdoor unit is suppressed.



#### Prohibiting local control, including settings such as child lock

The Home central remote controller is equipped with a lock function to prevent unauthorized operation from the remote controllers of the indoor unit in each room. The Home central remote controller is equipped with a child lock to prevent children from accidentally turning the air conditioner on or off or changing its settings.

#### Specifications

Model name	UTY-DMMYM/UTY-DMMYM1
Power source	12 V DC
Dimensions (H × W × D) (mm)	120 × 120 × 21.3
Weight (g)	220
	12 V DC supplied by an indoor unit

# Central remote controller

UTY-DCGYZ3



**Up to 100 indoor units**  
**Up to 50 groups**


## For tenants in small to midsize commercial premises

- Individual control and monitoring of up to 100 indoor units
- 7.0inch TFT color screen
- Visually intuitive operation
- Room temperature display by indoor unit sensor & remote controller sensor
- 50 Remote Controller Groups Display & remote controller group rename
- Supports 14 languages: Chinese (Simplified/Traditional), Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, Turkish, and Thai (Remote Management only)

## Easy operation

### Air conditioning management by detecting room temperatures of each room

The room temperature detected with indoor unit sensor or remote controller sensor can be displayed. New model can detect the room temperature by indoor units sensors even if wired remote controllers are not connected to the indoor units.



\*Room temperature is displayed only when indoor unit operates.



### 50 Remote Controller Groups Display

The group display and the 50 remote controller groups display can be switched easily.  
Users can choose which display is better, depending on the situation.

#### Group Display



Manage & Monitor  
by each Groups




#### 50 Remote Controller Groups Display



Manage & Monitor  
by 50 Remote Controller Groups


### Remote Controller Groups Rename

The remote controller group names can be changed. Users can know easily where the air conditioning is located by changing the remote controller group names.



## Features: Central Remote Controller


- Easy intuitive operation from the touch panel display.
- All functions can be accessed through the monitoring screen showing a pop-up window for detailed operation.



Individual setting

### Added individual wind direction control

Individual wind direction control has been added.  
Circular Flow cassette / 3D Flow cassette



Circular flow cassette

### Human sensor Compatible

Human sensor setting  
• Auto save  
• Auto on / off  
• Auto off detection time  
• Enable and disable



Human Sensor


## Remote Management

### Remote monitoring / Remote operation

New central remote controller can control your tenant's air conditioner anytime and anywhere.

When the central remote controller manages the indoor units of some tenants, air conditioning of each tenant can be managed separately online.

### Increased the Number of Accounts



Maximum  
**30**  
accounts

## Schedule management


### Annual schedule

- An annual schedule can be arranged for each remote controller group or user-defined group.
- Allows for the programming of special settings for weekends, holidays, and store closings throughout the year.



### Low noise schedule

Low noise operation of outdoor units can be scheduled.



### Automatic return to set temperature

A function that automatically returns the changed temperature to its original value over time.

# Touch panel controller

UTY-DTGYZ1



Up to  
400 indoor units  
Up to  
100 outdoor units  
Up to  
400 groups

- Large 7.5-inch TFT color LCD screen
- Touch screen operation
- Stylish design to fit nicely into any room environment
- Controls up to 400 indoor units.
- Icon or list view can be selected in monitoring mode.
- Supports 7 languages: Chinese, English, French, German, Polish, Russian, and Spanish.
- Mounted with LAN adapter for remote control & operation, external input/output with emergency stop and batch ON/OFF

## Easy operation

- Wide range of simple-to-understand icons
- Operate by pressing the icons on the screen with your finger or a stylus.
- The color on the back identifies the current control operation; blue is for monitoring and green is for operational control.



## Easy maintenance

- The flat touch panel can be easily cleaned.
- Touch panel controller with non-glare coating to prevent finger marks
- Front cover for easy removal.




## Easy installation

- The touch panel controller can be mounted on a wall.
- Flat back surface enables easy installation anywhere on a wall.
- No additional parts or components required for installation




## Controls up to 400 indoor units.



## Features:

### Control & monitoring

- Control and monitor Fujitsu General air conditioners via LAN or internet.
- Users and tenants can manage their assigned equipment from anywhere by computer or tablet.
- When something goes wrong, an error notice is sent by e-mail for prompt troubleshooting.



### Smartphone


Model name	Browser
Nexus 6P (Android 7.1.1)	Google Chrome 5.5
iPhone 7 (iOS 10.1)	Safari 10

### Tablet

Model name	Browser
iPad Pro 9.7 inch (iOS 10.2.1)	Safari 10


## Flexible access permissions can be granted to users at each point level.

The administrator can register multiple users and permit them to access any indoor unit and any functions.



## Additional languages


Supports 7 languages as standard: Chinese, English, French, German, Polish, Russian, and Spanish.  
Create a language database to integrate additional languages into the remote device.  
The added languages will only be displayed on the remote device and cannot be added to the Touch panel controller.



## Electricity charge apportionment (Option: UTY-PTGXA)

- Energy cost can be calculated and allocated to each billing user in proportion to the amount of energy used for air conditioning.

- Apportionment charge/bill calculation
- Tenant (block) setting
- Common facilities apportionment setting
- Rated power consumption allotment
- Individual calculations for cooling and heating
- Electricity meter supported



\* An electricity usage meter can be connected to an external input connector of the Touch panel controller. In that case, the meter cannot be connected to an outdoor unit at the same time.


**Features:****Automatic setting for daylight saving time****Functions provided**

1) Schedule setting for daylight saving time

- It prevents the user from forgetting to set daylight saving time. In addition, it saves time and effort for the user.



**Automatic clock adjustment**

2) Time can be set for all controllers in a batch automatically.

**Outdoor unit low noise operation**

You can choose from 4 low noise levels depending on the installation environment.

ON/OFF timing of low noise mode can be set with the timer.


**Energy-saving controls****Custom Auto**

- Maintains 2 separate setpoints for heating and cooling operations.
- Automatically switches between heating and cooling modes.

\* Not available for some models



Cooling set temp. 28°C, Heating set temp. 18°C

**Refrigerant leak detector**

Refrigerant leakage status is indicated by the management equipment. A pop-up message is displayed to notify the user, and the refrigerant is shut off.



Pop-up highlighting

**FUNCTIONS SUMMARY**

	UTY-DTGYZ1	Monitoring side
<b>Air conditioning control functions</b>		
ON/OFF	●	●
Operation mode setting*		
Fan speed control	●	●
Room temperature setting	●	●
Setting temperature range limitation	●	●
Test operation	●	●
Vertical louver setting	●	●
Horizontal louver setting	●	●
Individual louver control	●* <sup>1</sup>	●
Group setting	●	●
Remote controller prohibition	●	●
Anti-freeze setting	●	●
Set temperature auto return	—	●
Energy-saving controls	—	●
Economy mode setting	●	●
Human sensor control	—	●
<b>Displayed items</b>		
Error	●	●
Defrosting	●	●
Current time	●	●
Day of week	●	●
Remote controller prohibition	●	●
Cooling/heating priority	●	●
Address display	●	●
Room temperature	●* <sup>3</sup>	●* <sup>3</sup>
Multiple language support	●	●
Setting for daylight saving time	●	●
Time zone setting	●	●
Name registration	●	●
Backlighting	●	●
Language setting	7	7+other
Filter sign reset	●	●
Memory operations	●	●
Refrigerant leak detector	●	●

●: Supported ○: Optional function —: Not supported

\*1 Only setting cancellation can be operated.

\*2 Only available for external input control.

\*3 Available only when using a Wired remote controller.

	UTY-DTGYZ1	Monitoring side
<b>Timer</b>		
Schedule timer	Period ON/OFF, Temp, Mode, Times per day	Year 20 20
ON/OFF timer	—	—
Sleep timer	—	—
Program timer	—	—
Auto-off timer	—	●
Day off	●	●
Minimum unit of timer setting (minutes)	10	10
<b>Control</b>		
Remote monitoring management system	●	●
Electricity charge apportionment	○	○
Error history	●	●
Emergency stop	●* <sup>2</sup>	●* <sup>2</sup>
Remote monitoring management	—	●
Energy-saving management	—	—
E-mail notification in case of failure	—	●
Key lock	●	—
Low noise mode	●	●

## System controller

UTY-APGXZ1 Software

Up to  
4 VRF network systems  
Up to  
400 outdoor units  
Up to  
1,600 indoor units



**System controller enables advanced integrated monitoring and control of VRF network systems operating in small to large buildings.**

- Up to 1,600 indoor units and 400 outdoor units on up to 4 VRF network systems can be controlled.
- To accommodate facility management needs, the system controller offers—in addition to precise air conditioning control—remote central control, electricity charge apportionment, schedule management, and energy-saving options for VRF network systems.
- Supports 7 languages: Chinese, English, French, German, Polish, Russian, and Spanish.

## System controller lite

UTY-ALGXZ1 Software

Up to  
1 VRF network systems  
Up to  
100 outdoor units  
Up to  
400 indoor units




**System controller Lite offers a set of standard functions to manage air conditioners operating in a small or midsize building.**

- Up to 400 indoor units and 100 outdoor units on a VRF network system can be controlled.
- In addition to precise air conditioning control, a variety of applications are available as options to offer a wider range of control.
- Supports 7 languages: Chinese, English, French, German, Polish, Russian, and Spanish.

## Visually intuitive operation

**Click & Operate:** The visual representation of the property is shown on the screen from the perspective most suitable for operation (Click & Operate) You can select from among 4 display options: site, building, floor, and list.




## Features:

### Third-party devices connected via MODBUS® can be controlled.

**Standard** for System Controller   **Option** for System controller Lite UTY-PLGXX2

When a MODBUS® adapter (locally available) is connected to a computer, electrical equipment and devices supported by MODBUS® can be monitored and controlled centrally from the computer. The central control can reduce wasted energy throughout an entire building resulting from a failure to turn equipment off during or after work, as well as reduce the need for on-site patrols.



### Wide-ranging operation and data management

**Standard** System controller and System controller Lite

#### Schedule management

- An annual schedule can be arranged for each remote controller group or user-defined group.
- ON/OFF, operation mode, remote controller prohibition, and temperature settings can be programmed for up to 143 times per day at 10-minute intervals and for up to 101 configurations for each remote controller group.
- Settings can be programmed for a period that spans midnight.
- Allows for the programming of special settings for weekends, holidays, and store closings throughout the year.
- Low noise operation of outdoor units can be scheduled.



#### Wide-ranging control of indoor and outdoor units

- The operation status and mode of each indoor unit are displayed.
- Turn on and off each indoor unit and switch its operation mode.
- Setting temperature range limitation
- Low noise setting of outdoor units

#### Remote controller prohibition

Prohibits the operation mode, temperature setting, or ON/OFF of an indoor unit.

#### Error alert and e-mail notice

When something goes wrong, an error message is shown in a popup on a computer display with a chime, and an e-mail notice is sent. Errors of the past one year are logged and can be reviewed.

#### Operation and control history

A history of operation status and control can be maintained and retrieved.

#### Importing and exporting databases

Only an administrator is authorized to import and export registration, layout, and image data.

#### Automatic clock adjustment

Time can be set for all controllers in batch automatically.


## Electricity charge apportionment

**Standard** on System controller  
**Option** System controller Lite UTY-PLGXA2

#### Electricity charge apportionment method

This is a method to calculate monthly energy costs to be allocated to each tenant based on the amount of energy used by their air conditioners. The first step is to determine exactly how much energy is consumed by air conditioners in each tenant space. The second step is to divide the total energy charge billed by an electric power company based on the amount of energy used by each tenant to determine the energy cost to be allocated to each of them. (See figure on right)

The calculation takes into consideration such factors as the number of unused rooms and nighttime electricity rate, which are shown in detail on an energy cost allocation schedule.



**Features:****Remote monitoring management**

**Standard** on System controller  
**Option** System controller Lite UTY-PLGXR2





The System controller can be used on site or remotely over networks for remote central control.

The System controller requires 2 software programs working together: The VRF controller runs on site and communicates with the VRF system;

The VRF explorer, which runs at a remote location, provides a user interface and communicates with the VRF controller.

The VRF controller and the VRF explorer run on a single computer or on different computers connected on a network.

A computer running VRF explorer can centrally control up to 10 VRF system sites having up to 20 buildings each.

**On site central control****Remote central control****Energy-saving management**

**Option** System controller UTY-PEGXZ1  
**Option** System controller Lite UTY-PLGXE2

A variety of energy-saving options can be selected depending on the season, weather, and time of day. Excellent energy-saving operation is performed while keeping users comfortable.



Main screen for energy-saving management

Energy saving graph data: This chart compares the energy consumption for the current month with the previous month and with the same month of the previous year to keep track of the energy-saving performance.

**Indoor unit rotation**

Indoor units can be automatically rotated to operate within a group in accordance with a predetermined annual schedule to reduce power consumption while keeping users comfortable. The operation stoppage rate can be selected for an indoor unit.

**Peak-cut mode**

The system controller monitors the connected power meter and controls the energy to maintain the target power consumption set for each time period by changing the set temperature of the indoor units or turning off the thermostat so as to keep the users comfortable. Indoor units to be controlled can be grouped in many ways, and the control level can be set for each group.

**Capacity saving for outdoor unit**

The upper limit on the capacity of an outdoor unit can be adjusted to reduce power consumption during a hot summer or cold winter by averaging out the power-saving performance of each refrigerant system. The upper limit on capacity can be set at 50% of the rated capacity or more.

**Summary of functions**

Functions	Type	System controller		System controller Lite				
		UTY-APGXZ1	Option UTY-PEGXZ1	UTY-ALGXZ1	Option UTY-PLGXR2	Option UTY-PLGA2	Option UTY-PLGE2	Option UTY-PLGX2
Specifications		Max. number of VRF networks supported	4	—	1	—	—	—
		Max. number of indoor unit and remote controller groups per VRF network	400	—	400	—	—	—
		Max. number of outdoor units per VRF network	100	—	100	—	—	—
		Max. number of outdoor units per System controller	1600	—	400	—	—	—
		Max. number of outdoor units per System controller	400	—	100	—	—	—
Site supervision		Multiple site display	10	—	10	—	—	—
		Number of buildings per site	20	—	—	—	—	—
		Number of floors per site	200	—	—	—	—	—
		Number of floors per building	50	—	—	—	—	—
Error management		3D graphical layout view	●	—	—	—	—	—
		2D graphical layout view	●	—	—	—	—	—
History		List display	●	—	●	—	—	—
		Tree display	●	—	●	—	—	—
		Group display	—	—	—	—	—	—
		Error notification	●	—	●	—	—	—
		Audible alarm	—	—	—	—	—	—
		E-mail notification of errors	—	—	—	—	—	—
		Error history	—	—	—	—	—	—
		Operation history	●	—	●	—	—	—
		Control history	—	—	—	—	—	—
Operation control		ON/OFF	●	—	—	—	—	—
		Operation mode*	—	—	—	—	—	—
		Room temperature	●	—	—	—	—	—
		Fan speed	—	—	—	—	—	—
		Airflow direction	—	—	—	—	—	—
		Economy mode	—	—	—	—	—	—
		Setting temperature range limitation	●	—	●	—	—	—
		Anti-freeze	—	—	—	—	—	—
		Low noise setting of outdoor units	—	—	—	—	—	—
Individual management		Remote controller prohibition	—	—	—	—	—	—
		Setting temperature range limitation	—	—	—	—	—	—
		Filter sign reset	—	—	—	—	—	—
		Memory operations	—	—	—	—	—	—
		Pattern operations	—	—	—	—	—	—
Schedule		Annual Schedule	●	—	—	—	—	—
		Setting for a specific date	—	—	—	—	—	—
		ON/OFF per day	72	—	72	—	—	—
		ON/OFF per week	504	—	504	—	—	—
		Day off	●	—	—	—	—	—
		Minimum unit of timer setting (minutes)	10	—	10	—	—	—
		Weekly schedule for low noise mode	—	—	—	—	—	—
Remote monitoring management		Web Operation	●	—	—	—	—	—
		Remote monitoring	—	—	●	—	—	—
		Remote operation control	—	—	●	—	—	—
		Remote function setting	—	—	—	—	—	—
Electricity charge apportionment		Apportionment charge/bill calculation	—	—	—	—	—	—
		Tenant (block) setting	—	—	—	—	—	—
		Common facilities apportionment setting	●	—	—	—	—	—
		Rated power consumption allotment	—	—	—	—	—	—
		Individual calculations for cooling and heating	—	—	—	—	—	—
		Electricity meter supported	—	—	—	—	—	—
Energy-saving management		Indoor unit rotation	—	—	—	—	—	—
		Peak cut control	—	—	—	—	—	—
		Capacity saving for outdoor unit	—	—	—	—	—	—
		Record of energy-saving operation	—	—	—	—	—	—
		Information on energy saving	—	—	—	—	—	—
		Power consumption monitor	—	—	—	—	—	—
		Electricity meter supported	—	—	—	—	—	—
Control of external devices		Monitor	●	—	—	—	—	—
		Control	—	—	—	—	—	—
		Importing and exporting databases	●	—	—	—	—	—
		Automatic clock adjustment	●	—	—	—	—	—
Others		Multiple language support	7 languages	—	7 languages	—	—	—
		Refrigerant leak detector	●	—	●	—	—	—
		Power shutdown	●	—	●	—	—	—

●: Available -: Not available

**Computer requirements**

The specifications required for the computer are shown in the table below:

	System controller	System controller Lite
Operating system	<ul style="list-style-type: none"> <li>Microsoft® Windows® 7 Home Premium (32-bit or 64-bit) SP1, Windows® 7 Professional (32-bit or 64-bit) SP1</li> <li>Microsoft® Windows® 8.1 (32-bit or 64-bit), Windows® 8.1 Pro (32-bit or 64-bit)</li> <li>Microsoft® Windows® 10 Home (32-bit or 64-bit), Windows® 10 Pro (32-bit or 64-bit)</li> </ul> Supports 7 languages: English, Chinese, French, German, Russian, Spanish, and Polish	
CPU	Intel® Core™ i3 2 GHz or higher	
Memory	<ul style="list-style-type: none"> <li>2 GB or more (for Windows® 7 [32-bit])</li> <li>4 GB or more (for Windows® 7 [64-bit], Windows® 8.1, and Windows® 10)</li> </ul>	
HDD	40 GB or more of free space	
Displayed items	1024 x 768 or higher resolution	
Interfaces	<ul style="list-style-type: none"> <li>Ethernet port (for getting access to the internet using LAN) or a modem (for getting access to the internet via landline)</li> <li>Up to 6 USB ports (Only required for a server computer working as a VRF controller)           <ul style="list-style-type: none"> <li>Maximum of 2 USB ports are required to connect to a White-USB-key/WibuKey</li> <li>Up to 4 USB ports are required to connect to an Echelon® U10 USB network interface</li> </ul> </li> <li>* Maximum number of required USB ports depends on the applicable system configuration.</li> </ul>	<ul style="list-style-type: none"> <li>Ethernet port (for getting access to the internet using LAN) or a modem (for getting access to the internet via landline)</li> <li>Up to 6 USB ports (Only required for a server computer working as a VRF controller)           <ul style="list-style-type: none"> <li>Maximum of 4 USB ports are required to connect to a White-USB-key/WibuKey</li> <li>1 USB port is required for an Echelon® U10 USB Network interface</li> </ul> </li> <li>* The maximum number of required USB ports depends on the applicable system configuration.</li> </ul>
Graphic accelerator	Microsoft® DirectX® 9.0c compatible	
Software	Adobe® Acrobat Reader® 9.0 or later	
	• Echelon® U10 USB Network interface - TP/FT-10 Channel (Model name: 75010R) (Required for each VRF Network)	

**Packing list**

Type	For System controller		For System controller Lite				
	System controller	Option Energy manager	System controller Lite	Remote access	Electricity charge apportionment	Energy saving	Centralized control
Model name	UTY-APGXZ1	UTY-PEGXZ1	UTY-ALGXZ1	UTY-PLGXR2	UTY-PLGA2	UTY-PLGE2	UTY-PLGX2
White-USB-key	1	1	1	1	1	1	1

\*1: Software protection key to be inserted in a USB slot running System controller or System controller Lite.


System controller or System controller Lite may only run on a PC with

## MODBUS® converter for indoor unit

UTY-VMSX




Up to  
1 indoor unit



### Easy Installation

Easy to install with minimal wiring and without the need for a power supply cable to the converter



### Basic control

- Turning the units on and off
- Mode control (Heat, Cool, Dry, Auto, Fan)
- Fan speed control
- Louver position (airflow direction setting)
- Room temperature setting and display
- Economy mode setting
- Error status

### Specifications

Model name	UTY-VMSX
Power supply	12 V DC
Input power (W)	Max. 1.2 W
Dimensions (H × W × D) (mm)	140 × 117 × 43
Weight (g)	200
Maximum number of connectable indoor units per MODBUS® converter	1

### Modbus communication specifications

Transfer mode	RTU mode
Communication speed	9600/19200 bps
Data bit	8
Parity	even/odd/none
Stop bit	1/2 (no parity)
Network	RS485
Maximum cable length	1000 m (3280 ft)

## MODBUS® interface

FG-RC-MBS1Z1 / FG-AC-MBS1Z1 / FG-IR-BMG1Z1

**Intesis**  
BY HHS NETWORKS



FG-RC-MBS1Z1  
(3-wire RC-line type)

**Intesis**  
BY HHS NETWORKS



FG-AC-MBS1Z1  
(CN connector type)

**Intesis**  
BY HHS NETWORKS




FG-IR-BMG1Z1  
(IR type)

MODBUS® interface enables air conditioners to be fully integrated into a MODBUS® network.


- Small, compact, and easy to install on DIN rails.
- No separate external power supply required.
- MODBUS® interface enables central monitoring and control of air conditioners from BMS.

### Installation example



The MODBUS® interface can be used with or without a Wired remote controller.

### [IR type] Connection to wall-mounted type



Wall-mounted type indoor unit

### Specifications

Model name	FG-RC-MBS1Z1 (3-wire RC-line type)	FG-AC-MBS1Z1 (CN connector type)	FG-IR-BMG1Z1 (IR type)
Number of controllable groups	1	1	1
Dimensions (H × W × D) (mm)	93 × 53 × 58	93 × 53 × 58	93 × 60 × 21
Weight (g)	85	85	55

## MODBUS® converter for VRF

UTY-VMGX / FG-TL-MBS16Z1



UTY-VMGX



Up to  
9 units per VRF system  
Up to  
100 outdoor units  
Up to  
128 indoor units



FG-TL-MBS16Z1

Up to  
16 indoor units  
Up to  
16 outdoor units  
Up to  
128 indoor units

### Installation example



### Specifications

Model name	UTY-VMGX	FG-TL-MBS16Z1
Power supply	Single phase ~220 to 240 V 50/60 Hz	9 to 36 V DC, Max.: 140 mA or 24 V AC 50/60 Hz, Max.: 127 mA.*
Input power (W)	Max. 2	1.7
Dimensions (H × W × D) (mm)	54 × 260 × 150	90 × 88 × 56
Weight (g)	1,100	330

\*24 V DC power supply is recommended.

## BACnet® interface


FG-AC-BAC1Z1 / FG-IR-BMG1Z1

FG-AC-BAC1Z1  
(CN connector type)FG-IR-BMG1Z1  
(IR type)


Up to  
1 indoor units

- BACnet® interface connects BMS and a Fujitsu General split/multi-split/VRF system.
- Compatible with BACnet® (ANSI/ASHRAE-135-2012) application-specific controller (B-ASC).
- Compatible with BACnet®/IP over Ethernet.

### Installation example



[IR type] Connection to wall-mounted type



### Specifications

Model name	FG-AC-BAC1Z1 (CN connector type)	FG-IR-BMG1Z1 (IR type)
Number of controllable groups	1	1
Dimensions (H × W × D) (mm)	93 × 53 × 58	93 × 60 × 21
Weight (g)	85	55

12 V DC supplied by an indoor unit

## BACnet® gateway


UTY-ABGXZ1 Software

White-USB-key  
(Software Protection Key)

Bacnet® is a registered trademark of ASHRAE. ASHRAE does not endorse, approve or test products for compliance with ASHRAE standards. Compliance of listed products to the requirements of ASHRAE Standard 135 is the responsibility of Bacnet International (BI). BI is a registered trademark of Bacnet International.

Up to  
4 VRF network systems  
Up to  
400 outdoor units  
Up to  
1,600 indoor units

### Installation example



\*1: U10 USB network interface available from Echelon® Corporation.

### Computer requirements

	UTY-ABGXZ1
Operating system	<ul style="list-style-type: none"> <li>Microsoft® Windows® 7 Home Premium (32-bit or 64-bit) SP1, Windows® 7 Professional (32-bit or 64-bit) SP1</li> <li>Microsoft® Windows® 8.1 (32-bit or 64-bit), Windows® 8.1 Pro (32-bit or 64-bit)</li> <li>Microsoft® Windows® 10 Home (32-bit or 64-bit), Windows® 10 Pro (32-bit or 64-bit)</li> </ul> Supported languages: Chinese, English, French, German, Polish, Russian, and Spanish
CPU	Intel® Core™ i3 2 GHz or higher
Memory	<ul style="list-style-type: none"> <li>2 GB or more (for Windows® 7 [32-bit])</li> <li>4 GB or more (for Windows® 7 [64-bit], Windows® 8.1, and Windows® 10)</li> </ul>
HDD	40 GB or more of free space
Displayed items	1024 × 768 or higher resolution
Interfaces	<ul style="list-style-type: none"> <li>Ethernet port (for getting access to the internet using LAN)</li> <li>Up to 5 USB ports               <ul style="list-style-type: none"> <li>- 1 USB port required to connect to a White-USB-key/WibuKey</li> <li>- Up to 4 USB ports required to connect to an Echelon® U10 USB network interface</li> </ul> </li> </ul> <p>*The maximum number of required USB ports varies depending on the applicable system configuration.</p>
Software	Adobe® Acrobat Reader® 9.0 or later
• Echelon® U10 USB Network interface – TP/FT-10 Channel (Model name: 75010R) (Required for each VRF Network)	
<b>Packing list</b>	
Name and shape	Quantity Application
White-USB-key	1 Includes the software, user's manual, and license for BACnet® gateway.

## BACnet® gateway

UTY-VBGX Hardware




Bacnet® is a registered trademark of ASHRAE. ASHRAE does not endorse, approve or test products for compliance with ASHRAE standards. Compliance of listed products to the requirements of ASHRAE Standard 135 is the responsibility of Bacnet International (BI). BI is a registered trademark of Bacnet International.

Up to  
1 VRF network systems  
Up to  
32 refrigerant systems  
Up to  
128 indoor units

- BACnet® gateway connects BMS and a Fujitsu General VRF system.
- Up to 128 indoor units and 32 refrigerant systems can be connected to a single BACnet® gateway.
- Compatible with BACnet® (ANSI/ASHRAE-135-2012) application-specific controller (B-ASC)
- Compatible with BACnet®/IP over Ethernet.

### Installation example



### Specifications

Model name	UTY-VBGX
Number of controllable indoor units	128
Number of controllable refrigerant systems	32
Number of controllable VRF networks	1
Number of connectable units / one VRF network	4
Power supply	Single phase, 100-240 V, 50/60 Hz
Power consumption (W)	4.6 (max.)
Dimensions (H × W × D) (mm)	59.6 × 270.4 × 176
Weight (g)	1200

**BACnet®/MODBUS® router**


FG-RTR-BAC32Z1 / FG-RTR-MBS32Z1

**Intesis®**  
BY HMS NETWORKSFG-RTR-BAC32Z1  
(BAC net)**Intesis®**  
BY HMS NETWORKSFG-RTR-MBS32Z1  
(MODBUS®)**Routing between BaCnet® MS/TP and BaCnet® IP networks**


- Routing between BaCnet® MS/TP and BaCnet® IP networks
- Routing between MODBUS® RTU and MODBUS® TCP networks

**Installation example**

[BaCnet® type]



[MODBUS® type]


**BACnet®/MODBUS® cloud device**

FG-CLD-BMG4Z1 / FG-CLD-BMG8Z1 / FG-CLD-BMG16Z1 / FG-CLD-BMG32Z1

**Intesis®**  
BY HMS NETWORKS

FG-CLD-BMG4/8/16/32Z1

- The most powerful configuration tool common to all BACnet® gateways provides the system integrators with the power to configure and monitor their systems in an easy and reliable manner.
- A simple, easy-to-use description for the ST Cloud Web and App User Interface, with all widgets customizable to the user's needs, enabling system integrators to easily offer the best user experience to customers who are in control of their BaCnet® or MODBUS® devices.

**Installation example**

\*BMS: Building Management System

**Gateway features**

- BaCnet® IP/MSTP or MODBUS® TCP/RTU connectivity
- Up to 32 devices can be connected to each gateway.
- Up to 12 widgets per device
- Easy device configuration with Intesis MAPS

**Next-generation services**

- Industrial-grade connectivity now for building automation
- Fast and scalable real-time edge connectivity over HMS HubTM
- Full data control and protection
- Secure and remote updates during the application lifetime

**System Features**

- Monitor and control all devices in an intuitive way
- Comes with a native iOS and Android app and a web interface
- Create scenes and interact with multiple concurrent devices
- Calendar that shows the daily planned installation commands
- Notifications keep you updated about system status
- Device sharing and usage permissions management
- Multiple site management from a common dashboard

**Specifications**

Model name	FG-RTR-BAC32Z1 (MS/TP to IP)	FG-RTR-MBS32Z1 (RTU to TCP)
Number of routable devices (max.)	32	32
Power supply	9 to 36 V DC, Max.: 140 mA or 24 V AC 50/60 Hz, Max.: 127 mA	9 to 36 V DC, Max.: 140 mA or 24 V AC 50/60 Hz, Max.: 127 mA
Power consumption (W)	1.7	1.7
Dimensions (H × W × D) (mm)	93 × 53 × 58	93 × 53 × 58
Weight (g)	150	150

**Specifications**


Model name	FG-CLD-BMG4Z1	FG-CLD-BMG8Z1	FG-CLD-BMG16Z1	FG-CLD-BMG32Z1
Number of connectable BaCnet® (IP/MSTP) or MODBUS® (TCP/RTU) devices	4	8	16	32
Power supply	9 to 24 V DC, 50/60Hz			
Power consumption (W)	1.7	1.7	1.7	1.7
Dimensions (H × W × D) (mm)	93 × 53 × 58	93 × 53 × 58	93 × 53 × 58	93 × 53 × 58
Weight (g)	150	150	150	150

**KNX® converter** for indoor unit


UTY-VKSX

Up to  
1 indoor unit**KNX® Converter enables individual control of an indoor unit.**

- The new KNX® converter connects a central or home controller and a Fujitsu General indoor unit.
- Compact and lightweight design

**KNX® converter** for VRF

UTY-VKGX / FG-TL-KNX16Z1

Up to  
100 outdoor units  
Up to  
128 indoor units**Intesis®**  
BY HHS NETWORKSUp to  
16 indoor units  
Up to  
16 outdoor units**Installation example****Specifications**

Model name	UTY-VKSX	UTY-VKGX	FG-TL-KNX16Z1
Power supply	12 V DC	Single phase ~220 to 240 V 50/60 Hz	9 to 36 V DC, Max.: 140 mA or 24 V AC 50/60 Hz, Max.: 127 mA.*
Input power (W)	0.6	1.5	1.6
Dimensions (H × W × D) (mm)	140 × 117 × 43	54 × 260 × 150	90 × 88 × 56
Weight (g)	215	1,200	340

\*24 V DC power supply is recommended.

**KNX® interface**


FG-RC-KNX1Z1 / FG-AC-KNX1Z1 / FG-IR-KNX1Z1

**Intesis®**  
BY HHS NETWORKSFG-RC-KNX1Z1  
(3-wire RC-line type)FG-AC-KNX1Z1  
(CN connector type)FG-IR-KNX1Z1  
(IR type)**The KNX® interface enables air conditioners to be fully integrated into a KNX® network system.**


- Simple installation due to small and compact size.
- No separate external power supply required (only KNX® bus power required)

**Installation example**


[3-wire RC-line type/CN connector type]



[IR type] Connection to wall-mounted type



[IR type] Connection to a product other than wall-mounted type



## Network converter for single-split type


UTY-VTGX / UTY-VTGXV

UTY-VTGX  
DC power supply typeUTY-VGXV  
AC power supply typeUp to  
16 single indoor unitsUp to  
1 groupUp to  
100 Network Converters


- A network converter is required when connecting a single-split system to a VRF network system.
- Compact and lightweight design
- Connectable to both nonpolar 2-core and polar 3-core remote controllers

**Installation example**


- A 1-remote-controller type and a 2-remote-controller type are available.
- Power supply (220 to 240 V AC, 50/60 Hz) is required for the 2-remote-controllers type.



- Both nonpolar 2-core and polar 3-core type Wired remote controllers can be connected.



- Central control can be provided for single-split systems. (Up to 100 network converters can be connected in a VRF network system)

**Specifications**


Model name	UTY-VTGX		UTY-VGXV
Power supply	Polar 3-core 12 V DC	Nonpolar 2-core DC 12 V	Single phase ~220 to 240 V 50/60 Hz
Input power (W)	Max. 1.2 W		Max. 3
Dimensions (H × W × D) (mm)	140 × 117 × 43		54 × 260 × 150
Weight (g)	250		1,100

## Network converter for LONWORKS™

UTY-VLGX



- Connects the VRF network system to a LONWORKS™ open network to manage small and midsized BMS and VRF network system.
- The UTY-VLGX enables centralized monitoring and control of VRF network system from a BMS via a LONWORKS™ interface.
- Up to 128 Indoor units can be connected to one network converter for LONWORKS™

**Installation example****Specifications**

Model name	UTY-VLGX
Power supply	Single phase ~208 to 240 V 50/60 Hz
Power consumption (W)	4.5
Dimensions (H × W × D) (mm)	67 × 288 × 211
Weight (g)	1,500

**Transmission specifications (BMS side)**

Transmission speed	78 kbps
Transceiver	FT-X1 (available from Echelon® Corporation)
Transmission line form	Free topology
Terminal resistor	(converter to be attached at the terminal of a network)

## External switch controller

UTY-TERX


Up to  
1 group

Air conditioner switching can be controlled by connecting this external switch controller to other sensor switches.

- In combination with a commercially available card-key switch or other sensors, this External switch controller enables the control of ON/OFF, room temperature, and fan speed of connected air conditioners as well as master control functions. This makes this product an ideal choice for use in hotel rooms.
- Card key or other sensor switches are locally available.
- The set temperature can be specified at two points each for cooling and heating operations (4 points in total).

### Installation example

Human sensor monitors the movement of a person in a room. When it detects that the person has left the room, it switches the air conditioner to low-capacity mode. When a person returns to the room, the air conditioner returns to the previous operation mode.



Human sensor equipment needs to be purchased separately.  
Human sensor is not mounted on an External switch controller.


## Signal amplifier

UTY-VSGXZ1



- The transmission line can be extended up to 3,600 m using multiple Signal amplifiers.
- Up to 8 Signal amplifiers can be added in a VRF network system.
- A Signal amplifier is required.
  - When the total wiring length of the transmission line exceeds 500 m.
  - When the total number of units on the transmission line exceeds 64.

### Installation example



#### Specifications

Model name	UTY-VSGXZ1	UTY-TERX
Power supply	Single phase ~208 to 240 V 50/60 Hz	6.5 to 16 V DC
Power consumption (W)	4.5	-
Dimensions (H × W × D) (mm)	67 × 288 × 211	140 × 117 × 43
Weight (g)	1,500	250

12 V DC supplied by an indoor unit



# Controller system list (available) for Split/Multi-split

Controller Options/Accessories:



Type	Refrigerant	Indoor unit														Outdoor unit													
		Wall-mounted							Cassette							Duct						Indoor unit						Single phase	
		Designer Range		Standard Range		ECO Range			Compact 4-way flow Range	Circular flow Range	Slim	Medium static pressure (High-Efficiency & Compact)	Medium static pressure (Compact)	Medium static pressure (Standard)	High static pressure		BIG	Floor	Ceiling	Wall-mounted		Compact cassette	Mini duct	Slim duct	5/6-unit multi-split				
	R32	ASEG07/09/ 12/14KGTE	ASEG 07/09/12/14 KETF, KETF-B ASYG 07/09/12/14 KETE, KETE-B	ASEH07/09/ 12/14KGCF, ASYG07/09/ 12/14KMCF, ASYG07/09/ 12/14KGTE	ASEG 07/09/12/14 KETF, KETF-B ASYG 07/09/12/14 KETE, KETE-B	ASEH 07/09/12/14 KETF, KETF-B ASYG 07/09/12/14 KETE, KETE-B	ARXG 09/12/14/18 KLLAP	ARXH 12/14/18 22/24/30/ 36/45/54 KMTAP	ARXG 12/14/18 22/24/30/ 36/45/54 KMLA	ARXG 45/54KHTB			AGEG 09/12/14 KVCA	ABEG 18/22/24/30/ 36/45/54 KRTA	ASEH 05KNCA	ASEG 22KMTE	AUXG 07KVLA	ARXG 07KLLAP	AOEG 36KBTA5										
	R410A																										AOYG 45LBA6		
Controllers	●																												
	●																												
	●																												
	●																												
	●																												
	●																												
Wired remote controller	●																												
	●																												
	●																												
	●																												
	●																												
	●																												
Simple remote controller	●	Nonpolar 2-core type																											
Home central remote controller	●																										● UTY-DMMVM1*3 (KBTAS) UTY-DMMYM1*3 (LBLA6)		
Wireless remote controller	●																										● UTY-LNTY		
IR receiver unit with Wireless remote controller	●	For Duct type																											
	●	For Duct type	For Cassette type	For Ceiling type																							● UTY-LBTYC		

\*There are no optional parts for the KL Series.  
\*1: Available only when the WLAN adapter (UY-TFSXF2) is removed. \*2 Available only when the WLAN adapter (UY-TFSXZ1) is removed.

\*3 Consult your dealer for conditions of use.

## Controller system list (available) for Split/Multi-split

## Controller Options/Accessories:



Type	Refrigerant	Indoor unit																		Indoor unit											
		Wall-mounted										Cassette								Duct				Floor		Ceiling		Multi-split			
		Designer Range		Standard Range			ECO Range			Compact 4-way flow Range		Circular flow Range		Slim	Medium static pressure [High-Efficiency & Comfort]	Medium static pressure [Compact]	Medium static pressure [Standard]	High static pressure		BIG	Floor	Ceiling	Wall-mounted		Compact cassette	Mini duct	Slim duct				
Interface	R32	ASEG07/09/12/14KGTG, ASEH07/09/12/14KGCG, ASYG07/09/12/14KGCF, ASYG07/09/12/14KGTE, KETF, KETF-B ASEG07/09/12/14KGTE, ASYG07/09/12/14KGME, KETE, KETE-B	ASEG07/09/12/14KGTE, ASEH07/09/12/14KGCG, ASYG07/09/12/14KGCF, ASYG07/09/12/14KGTE, KETE, KETE-B	ASEH 07/09/12 ASEG 07/09/12 ASEH 30/36KMTB	ASEH 07/09/12 ASEG 07/09/12 ASEH 07/09/12 ASEG 18/24KMTA	ASEH 07/09/12 ASEG 07/09/12 ASEH 07/09/12 ASEG 18/24KLCA	AUXG 09/12/14/ 18/22/24/30/ 36/45/54 KVLB	AUXG 09/12/14/ 18/22/24/30/ 36/45/54 KVLB	ARXG 09/12/14/18 KLLAP	ARXH 12/14/18/ 22/24/30/ 36/45/54 KMTAP	ARXG 12/14/18/ 22/24/30/ 36/45/54 KMLA	ARXG22KMLB, ARXG 24/30/36/45 KHTAP	ARXG 45/54KHTB						AGEG 09/12/14 KVCA	ABEG 18/22/24/30/ 36/45/54 KRTA	ASEG 05KNCA	ASEG 22KMTB	AUXG 07KVLA	ARXG 07/09/12/14/18 KSLAP	ARXG 07KLLAP						
MODBUS® interface	MODBUS® Converter		● UTY-VMSX					● UTY-VMSX					● UTY-VMSX					● UTY-VMSX		● UTY-VMSX		● UTY-VMSX		● UTY-VMSX		● UTY-VMSX					
		● FG-AC-MBS1Z1					● FG-RC-MBS1Z1 FG-AC-MBS1Z1					● FG-RC-MBS1Z1 FG-AC-MBS1Z1					● FG-RC-MBS1Z1		● FG-AC-MBS1Z1		● FG-AC-MBS1Z1		● FG-AC-MBS1Z1		● FG-RC-MBS1Z1 FG-AC-MBS1Z1						
KNX® interface	KNX® converter		● UTY-VKSX					● UTY-VKSX					● UTY-VKSX					● UTY-VKSX		● UTY-VKSX		● UTY-VKSX		● UTY-VKSX		● UTY-VKSX					
		● FG-AC-KNX1Z1					● FG-RC-KNX1Z1 FG-AC-KNX1Z1					● FG-RC-KNX1Z1 FG-AC-KNX1Z1					● FG-AC-KNX1Z1		● FG-RC-KNX1Z1 FG-AC-KNX1Z1		● FG-AC-KNX1Z1		● FG-AC-KNX1Z1		● FG-RC-KNX1Z1 FG-AC-KNX1Z1						
WLAN adapter			● FG-IR-KNX1Z1					● FG-IR-KNX1Z1+ UTY-LBTYC					● FG-IR-KNX1Z1+ UTY-LBTYM					● FG-IR-KNX1Z1+ UTY-LRHYM		● FG-IR-KNX1Z1+ UTY-LBTYH		● FG-IR-KNX1Z1		● FG-IR-KNX1Z1		● FG-IR-KNX1Z1+ UTY-LBTYM					
			● Accessory (KGTC, KGTF, KETF, KETF-B, KMCG, KMCF) UTY-TFSXH3, UTY-TFSXF2 (KGTE, KETE, KETE-B, KMCE)					● UTY-TFSXH3 UTY-TFSXF2		● Accessory		● UTY-TFSXH3 UTY-TFSXF2		● UTY-TFSXJ3 UTY-TFSXZ1					● UTY-TFNXZ1		● UTY-TFSXJ3 UTY-TFSXZ1		● Accessory		● UTY-TFSXH3 UTY-TFSXF2		● FG-RC-WIF1Z1+ UTY-LBTYM				
External switch controller			● FG-AC-WIF1Z1					● FG-RC-WIF1Z2 FG-AC-WIF1Z1					● FG-RC-WIF1Z2 FG-AC-WIF1Z1					● FG-AC-WIF1Z1		● FG-RC-WIF1Z2 FG-AC-WIF1Z1		● FG-AC-WIF1Z1		● FG-AC-WIF1Z2 FG-AC-WIF1Z1		● FG-AC-WIF1Z1+ UTY-LBTYM					
			● FG-IR-WIF1Z1					● FG-IR-WIF1Z1+ UTY-LBTYC					● FG-IR-WIF1Z1+ UTY-LRHYM					● FG-IR-WIF1Z1		● FG-IR-WIF1Z1+ UTY-LBTYH		● FG-IR-WIF1Z1		● FG-IR-WIF1Z1		● FG-RC-WIF1Z1+ UTY-LBTYM					
Network converter for single-split type			● FG-AC-WMP1Z1					● FG-RC-WMP1Z1 FG-AC-WMP1Z1					● FG-RC-WMP1Z1 FG-AC-WMP1Z1					● FG-AC-WMP1Z1		● FG-RC-WMP1Z1 FG-AC-WMP1Z1		● FG-AC-WMP1Z1		● FG-AC-WMP1Z1		● FG-RC-WMP1Z1 FG-AC-WMP1Z1					
			● FG-IR-WMP1Z1					● FG-IR-WMP1Z1+ UTY-LBTYC					● FG-IR-WMP1Z1+ UTY-LRHYM					● FG-IR-WMP1Z1		● FG-IR-WMP1Z1+ UTY-LBTYH		● FG-IR-WMP1Z1		● FG-IR-WMP1Z1		● FG-IR-WMP1Z1+ UTY-LBTYM					
External switch controller			● UTY-TERX+UTY-TWRXZ2					● UTY-TERX					● UTY-TERX					● UTY-TERX+ UTY-TWRXZ3		● UTY-TERX		● UTY-TERX+ UTY-TWRXZ2		● UTY-TERX		● UTY-TERX					
Network converter for single-split type			● UTY-VTGX+UTY-TWRXZ2 or UTY-VTGXV+UTY-TWRXZ2					● UTY-VTGX UTY-VTGXV					● UTY-VTGX+ UTY-TWRXZ2 or UTY-VTGXV+ UTY-TWRXZ2					● UTY-VTGX UTY-VTGXV		● UTY-VTGX+ UTY-TWRXZ2 or UTY-VTGXV+ UTY-TWRXZ2		● UTY-VTGX UTY-VTGXV		● UTY-VTGX		● UTY-VTGXV					

\*1: Available only when the WLAN adapter (UY-TFSXF2) is removed. \*2: Available only when the WLAN adapter (UTY-TFSX21) is removed.

# Controller system list (available) for VRF

Controller Options:



Type	Refrigerant	Indoor unit																		Indoor unit										
		Cassette						Duct						Duct						Floor		Ceiling/ Floor	Ceiling	Wall-mounted						
		One-way flow	3D flow	Compact		Slim type	Large type	Low static pressure duct			High Efficiency			Low static pressure duct	Medium static pressure	High static pressure	-	External EEV	-	External EEV	-	External EEV	-	External EEV	-	External EEV				
				Grid type/Standard type		Circular flow		Mini (With drain pump)	Slim (With drain pump)	High Efficiency	High Efficiency		High Efficiency	Normal	Normal															
	AUXB 004/005/007/ 009/012/014/ 018HLAH	AUXN 009/012/014 HLAH	ARXD 004/005/007/ 009/012/014/ 018/024 HLAH	ARXP 009/012/014 HLAH	ASYA 004/005/007/ 009/012/014 HCAH	ASYE 004/005/007/ 009/012/014 HCAH																								
	AUXV 004/007/009/ 012/014/018/ 024GLEH	AUXS 018/024 GLEH	AUXB 004/007/009/ 012/014/018/ 024GLEH	AUXM 018/024/030 GLEH	AUXK 018/024/030/ 034/036/045/ 054GLEH	ARXK 004/007/009/ 012/014/018/ 024GLEH	ARXD 007/009/012/ 014/018/024 GLEH	ARXP 018/030 GLFH	ARXA 024/030/ 036/045 GLEH	ARXC 036/045/060/ 072/090/096 GTEH	AGYA 004/005/060/ 009/012/014 GCGH	AGYE 004/007/ 009/012/014 GCEH	ABYA 012/014/ 018/024 GTEH	ABYA 030/036/ 045/054 GTEH	ASYA 004/007/009 GCGH	ASYE 004/007/009 GCEH	ASYA 012/014/GCEH	ASYE 012/014GCEH	ASYA 18/24GBCH	ASYA 030/034GTEH										
Controllers																														
Wired remote controller																														
Simple remote controller																														
Wireless remote controller																														
IR receiver unit																														
Central remote controller																														
Touch panel controller																														
System controller, System controller Lite																														

# Controller system list (available) for VRF

Controller Options:



Type	Refrigerant	Indoor unit																		Indoor unit															
		Cassette						Duct												Indoor unit						Wall-mounted									
		One-way flow	3D flow	Compact		Grid type/Standard type	Slim type	Large type	Low static pressure duct						Duct			Floor			Ceiling/Floor	Ceiling	Wall-mounted												
				High Efficiency	Circular flow	(With drain pump)	Mini	Slim (With drain pump)	High Efficiency	High Efficiency	Low static pressure duct	Medium static pressure	High static pressure	Normal	Normal	Normal	External EEV	-	Ceiling/Floor	Ceiling	-	External EEV	-	External EEV	-	-	-								
	R32			AUXB 004/005/007/ 009/012/014/ 018HLAH	AUXN 009/012/014 HLAH				ARXD 004/005/007/ 009/012/014/ 018/024 HLAH	ARXP 009/012/014 HLAH											ASYA 004/005/007/ 009/012/014 HCAH	ASYE 004/005/007/ 009/012/014 HCAH													
	R410A	AUXV 004/007/009/ 012/014/018/ 024GLEH	AUXS 018/024 GLEH	AUXB 004/007/009/ 012/014/018/ 024GLEH		AUXM 018/024/030 GLEH	AUXK 018/024/030/ 034/036/045/ 054GLEH	ARXK 004/007/009/ 012/014/018/ 024GLEH	ARXD 04GALH	ARXD 007/009/012/ 014/018/024 GLEH	ARXP 018/030 GLEH	ARXA 024/030/ 036/045 GLEH	ARXC 036/045/060/ 072/090/096 GTEH	AGYA 004/007/ 009/012/014 GCGH	AGYE 004/007/ 009/012/014 GCEH	ABYA 012/014/ 018/024 GTEH	ABYA 030/036/ 045/054 GTEH	ASYA 004/007/009 GCEH	ASYE 004/007/009 GCEH	ASYA 012/014/GCEH	ASYE 012/014/GCEH	ASYA 18/24GCH	ASYA 030/034GTEH												
Interfaces	BAControl® gateway		UTY-ABGXZ1, UTY-VBGX																		UTY-ABGXZ1, UTY-VBGX														
			FG-AC-BAC1Z1							FG-AC-BAC1Z1													FG-AC-BAC1Z1								FG-AC-BAC1Z1				
			FG-IR-BMG1Z1+ UTY-TRHX		FG-IR-BMG1Z1		FG-IR-BMG1Z1+ UTY-LBHD		FG-IR-BMG1Z1+ UTY-TRHX	FG-IR-BMG1Z1+ UTB-YWC	FG-IR-BMG1Z1+ UTY-TRHX		FG-IR-BMG1Z1+ UTY-TRHX																						
Network converter for LonWorks™	MODBUS® Converter		UTY-VLGX																		UTY-VLGX														
			UTY-VMSX							UTY-VMSX													UTY-VMSX								UTY-VMSX				
			UTY-VMGX FG-TL-MBS16Z1																				UTY-VMGX FG-TL-MBS16Z1												
MODBUS® interface	3-wire RC-line type		FG-AC-MBS1Z1							FG-RC-MBS1Z1	FG-AC-MBS1Z1																								
			FG-IR-BMG1Z1+ UTY-TRHX		FG-IR-BMG1Z1		FG-IR-BMG1Z1+ UTY-LBHD		FG-IR-BMG1Z1+ UTY-TRHX	FG-IR-BMG1Z1+ UTB-YWC	FG-IR-BMG1Z1+ UTY-TRHX		FG-IR-BMG1Z1+ UTY-TRHX																						
KNX® converter	KNX® interface		UTY-VKSX																		UTY-VKSX														
			UTY-VKGX FG-TL-KNX16Z1																				UTY-VKGX FG-TL-KNX16Z1												
WLAN adapter	3-wire RC-line type		FG-AC-KNX1Z1							FG-RC-KNX1Z1	FG-AC-KNX1Z1									FG-AC-KNX1Z1															
			FG-IR-KNX1Z1+ UTY-TRHX		FG-IR-KNX1Z1		FG-IR-KNX1Z1+ UTY-LBHD		FG-IR-KNX1Z1+ UTY-TRHX	FG-IR-KNX1Z1+ UTB-YWC	FG-IR-KNX1Z1+ UTY-TRHX		FG-IR-KNX1Z1+ UTY-TRHX																						
External switch controller	3-wire RC-line type		UTY-TFSXJ3 UTY-TFSXZ1 (007-024)																				UTY-TFSXJ3 UTY-TFSXZ1								UTY-TFSXJ3 UTY-TFSXZ1				
			FG-AC-WIF1Z1							FG-RC-WIF1Z2	FG-AC-WIF1Z1																								
			FG-IR-WIF1Z1+ UTY-TRHX		FG-IR-WIF1Z1		FG-IR-WIF1Z1+ UTY-LBHD		FG-IR-WIF1Z1+ UTY-TRHX	FG-IR-WIF1Z1+ UTB-YWC	FG-IR-WIF1Z1+ UTY-TRHX		FG-IR-WIF1Z1+ UTY-TRHX																						
External switch controller	3-wire RC-line type		FG-AC-WMP1Z1							FG-RC-WMP1Z1	FG-AC-WMP1Z1																								
			FG-IR-WMP1Z1+ UTY-TRHX		FG-IR-WMP1Z1		FG-IR-WMP1Z1+ UTY-LBHD		FG-IR-WMP1Z1+ UTY-TRHX	FG-IR-WMP1Z1+ UTB-YWC	FG-IR-WMP1Z1+ 																								

# Optional parts Overview

## For Split & Multi-split, VRF

A variety of optional parts are available to enable installation of the selected indoor unit properly according to the environment.

### Optional Parts For Cassette



**Human sensor kit**  
A built-in thermo sensor monitors and controls room temperature accurately.




**Cassette grille**  
A lineup of cassette grilles that match a variety of interiors. A grid ceiling-type cassette grille has been added to the lineup.




**Silver ion filter**  
The Silver ion filter helps to keep indoor air free from viruses, bacteria and molds.\*




**Fresh air intake kit**  
Fresh air can be taken in by a fan connected to an external control unit.




**Insulation kit for high humidity**  
Insulation kit for high humidity is used when the installation location is in a high humidity environment.



**Air outlet shutter plate**  
Airflow directions can be changed to 3 directions using the Air outlet shutter plate depending on the installation location.



**Wide Panel**  
When a cassette type is installed in a narrow space in the ceiling, the wide panel fills in that space.  
Indoor unit 950  
Panel 600 (mm)  
600



**Panel spacer**  
If the ceiling space is tight and the main body protrudes from the ceiling surface, a panel spacer can be used as a decorative trim.  
242 mm  
Panel spacer

### Optional Parts For V-IV



**Pressure sensor kit**  
When installed, the height difference between the outdoor unit and indoor unit can be allowed up to 110 m.



### Optional Parts For R32 VRF products




**Gas Sensor kit**  
Used to ensure standards compliance and safety when R32 VRF products are installed.



**Expansion kit**  
Connect to indoor units to expand the number of inputs and outputs when using multiple safety devices or external input/output functions.


### Optional Parts For Floor



**Half concealed kit**  
Used to half conceal a floor type indoor unit in the wall.



**Silver ion filter**  
The Silver ion filter helps to keep indoor air free from viruses, bacteria and molds.\*




## Optional Parts For Duct & Ceiling



**Auto louver grille kit**  
The optional clean-looking flat Auto louver grille blends into any interior and provides a comfortable airflow.



**Remote sensor unit**  
The remote sensor provides additional convenience.



**Silver ion filter**  
The Silver ion filter helps to keep indoor air free from viruses, bacteria and molds.\*



**Long-life filter**  
Captures grit and dust. Long-life design with consideration of running costs.



**Flange**  
Flanges are used when connecting a medium static pressure duct type and a ceiling type with air intake and exhaust ducts.




**Drain pump unit**  
Drains water that has accumulated during operation.

### Connection Parts



**Communication kit**  
Required for a wall-mounted type when the External connect kit set or a Wired remote controller is connected to the indoor unit.



**External connect kit & set**  
Connect the printed circuit board (PCB) to external devices.



**Connection Units**  
Connection units are available to separate the pipes when connecting multiple indoor units in a Multi-split type or VRF system.



**External power supply unit**  
The External power supply unit protects the increment in the system even if the power supply for some of the indoor units is shut down.



**External input and output PCB**  
For Wall-mounted, Duct, or Cassette type, these parts are required when the external input and output function is used.



**External input and output PCB box & bracket**  
Box and bracket for installing the External input and output PCB.

## Silver Ion Filter

UTR-FA16-5 / UTR-FA13-3 / UTR-FA03-5 / UTD-HFAA / UTD-HFRA / UTD-HFTA / UTD-HFTB / UTD-HFTC / UTD-HFNC / UTD-HFNB / UTD-HFNA / UTD-HFND / UTD-HFKB / UTD-HFKA



For Wall mounted / Floor  
UTR-FA16-5 / UTR-FA13-3  
UTR-FA03-5

For Cassette  
UTD-HFAA / UTD-HFRA


For Duct  
UTD-HFTA / UTD-HFTB  
UTD-HFTC / UTD-HFNC  
UTD-HFNB / UTD-HFNA  
UTD-HFND / UTD-HFKB  
UTD-HFKA

The Silver ion filter helps to keep indoor air free from viruses, bacteria and molds.

(Not a result of experiments in an actual use environment. Silver ion filter inhibits activity or growth of microorganism, but do not prevent infection.)

The silver ion filter inhibits the activities of viruses<sup>\*1</sup>, bacteria<sup>\*2</sup> and molds<sup>\*3</sup> trapped on the filter.

(Only effective when the microorganism is trapped on the filter with dust or droplet)




\*1 [Testing organization] Kitasato Research Center for Environmental Science [Test Report] No. 2020\_0408 [Test virus] Escherichia coli phage Obeta NBRC 20012 (1 type) [Test Method] Based on the antiviral test method for textile products (JIS L 1922)  
[Test results] Inhibited by at least 99% in 24 hours. Not tested to prevent transmission of SARS-CoV-2.

\*2 [Testing organization] Kitasato Research Center for Environmental Science [Test Report] No. 2020\_0409 [Test bacteria] Escherichia coli NBRC 3972 (1 type) [Test Method] Based on the determination of antibacterial activity and efficacy of textile products (JIS L 1902)  
[Test results] The growth of the test bacteria was inhibited by 24 hours testing

\*3 [Testing organization] Kitasato Research Center for Environmental Science [Test Report] No. 2020\_0410 [Test fungi] Aspergillus Niger NBRC 105649 and other fungi (3 types) [Test Method] Based on the test for fungus resistance (JIS Z 2911)  
[Test results] The growth of the fungus was inhibited by 28 days testing

The filter is easily removable\* and hand-washable.

(\*Wall mounted and floor models only)



\*4 Hand-washing or vacuuming by 3 months is recommended. Cleaning frequency varies depending on the environment of use.

### Specifications


Model name	For Wall mounted / Floor					for Cassette									
	UTR-FA16-5	UTR-FA13-3	UTR-FA03-5	UTD-HFAA	UTD-HFRA	UTD-HFTA	UTD-HFTB	UTD-HFTC	UTD-HFNC	UTD-HFNB	UTD-HFNA	UTD-HFND	UTD-HFKB	UTD-HFKA	
Net Dimension (H × W × D)	mm	35 × 210 × 6	50 × 364 × 6	43 × 272 × 6	350 × 125 × 6	550 × 136 × 6	290 × 70 × 6	390 × 70 × 6	290 × 70 × 6	620 × 88 × 6	420 × 88 × 6	620 × 88 × 6	500 × 79 × 6	420 × 125 × 6	620 × 108 × 6
Weight	g	2	2	2	7	23	6	8	10	10	16	12	16	2	20
Quantity		2	2	2	1	1	2	2	3	1	2	2	2	2	2
for Duct															
Net Dimension (H × W × D)	mm	290 × 70 × 6	390 × 70 × 6	290 × 70 × 6	620 × 88 × 6	420 × 88 × 6	620 × 88 × 6	500 × 79 × 6	420 × 125 × 6	620 × 108 × 6	2	8	10	8	2
Weight	g	6	8	10	8	10	16	12	16	2	2	2	2	2	20
Quantity		2	2	3	1	2	2	2	2	2	2	2	2	2	2

## Auto louver grille kit

UTD-GXTA-W / UTD-GXTB-W / UTD-GXTC-W



The optional clean-looking flat Auto louver grille kit blends into any interior and provides a comfortable airflow.




### Flexible Control


- The Auto louver grille of the indoor unit can be operated in conjunction with the remote control of the indoor unit.

- Vertical auto swing**
  - Auto airflow direction and auto swing
  - 4 steps selectable

- Auto-closing louver**  
The louvers will automatically close when the indoor unit stops operating.



### Dimensions



Unit: mm						
Model name	W1	W2	H1	H2	D1	D2
UTD-GXTA-W	683	645				
UTD-GXTB-W	883	845	180	148	9	84
UTD-GXTC-W	1,083	1,045				

### Specifications

Model name	SPLIT & MULTI-SPLIT	UTD-GXTA-W	UTD-GXTB-W	UTD-GXTC-W
Applicable indoor unit		ARYG07/09/12/14KLLTA ARYG07/09/12/14KSLAP ARYG07/09/12/14KLLAP ARYG07/09/10LSLAP	ARXG18KSLAP ARXG18KLLAP	
VRF		ARXD007/009/012/014GLEH ARXK04/007/009/012/014GLGH ARXD004/005/007/009/012/014HLAH ARXP009/012/014HLAH	ARXD018GLEH ARXD018HLAH ARXK018GLGH	ARXD024GLEH ARXD024HLAH ARXK024GLGH
Power supply		Connecting with Control box of indoor unit		
Fixing Auto louver grille		Screwed to Flange or Square duct		
Extension Square duct limit		1.0 m (Max. duct length between indoor unit and Auto louver grille)		
Net Dimensions (H × W × D)	mm	180 × 683 × (84 + 9)	180 × 883 × (84 + 9)	180 × 1,083 × (84 + 9)
Weight	kg (lbs)	2.0 (4.4)	2.5 (5.6)	3.0 (6.7)
Accessories				
Operating range	Cooling	Fitting Flame, etc. 18 to 32 °C		
	% RH	80 % or less		
	Heating	16 to 30 °C		


## Pressure sensor kit

UTY-SPWX




### Design flexibility


The height difference between the outdoor unit and the indoor unit is normally 50 m for the V-IV Series, but can be extended to 110 m by installing the Pressure sensor kit.  
(Can only be connected to the V-IV Series. Also, it can only be connected to outdoor units using outdoor unit software compatible with the product.)



### System overview



### Pressure sensor kit



### Specifications

Model name	UTY-SPWX
Power supply	9 to 16 V DC
Dimensions (H × W × D) (mm)	140 × 117 × 43
Weight (g)	200

## External power supply unit

UTZ-GXXA / UTZ-GXXC / UTZ-GXXD




### The External power supply unit protects the increment in the system even if the power supply for some of the indoor units is shut down.

Connects to the External power supply unit to supply power to the indoor unit from the auxiliary power supply. This allows for continuous operation without system errors. Built-in relays reduce installation time and cost. The UTZ-GXXC and UTZ-GXXD have a built-in relay, which reduces installation time and cost.

### High reliability

- A: Interruption of the main power supply is detected by the power cut-off detection part.
- B: Supplies power for driving the expansion valve of the indoor unit. (12 V or 5 V DC)
- C: Gives notification of the power supply from the External power supply unit.



### Note

- When changing the power supply voltage to 24 V AC, use a power transformer with an insulated structure that complies with the regulations\* of the installation region.
- A powered-off indoor unit driven by the External power supply unit is treated in the same way as an operation-off unit in the electricity charge appointment function. If standby power is generated, the result of the electricity charge appointment may not be zero.

\* UL Class II or IEC 61558 Class III, for example.

### Specifications


Model name	UTZ-GXXA	UTZ-GXXC	UTZ-GXXD
Power supply	24 V AC 50/60 Hz		
Dimensions (H × W × D) (mm)	97 × 200 × 178		
Weight (g)	800		

## AIR BEAM Radiation air outlet unit


\*Production by order  
Contact us for more details.



### Key component



### Cross-section view



Airflow rate (m³/h)	180 (160-215)	270 (240-325)
Grid	600 × 2	600 × 3
AIR BEAM For system ceiling (Integrated type)	KS-180	KS-270

## Gas sensor kit



UTY-SGZY



### Enhanced disaster safety measures

The system is designed to meet the environmental safety requirements specified in the IEC 603352-40 standard for the use of R32 refrigerant. The environment requiring safety measures is determined by the size of the room in relation to the amount of refrigerant required. For example, if the system is designed for maximum pipe length and the refrigerant charge is 6 kg, safety measures are required for rooms of 15 m<sup>2</sup> or less.

**For Example: Total pipe length 120m**



**Shut off valve kit**  
UTP-GX027A, UTP-GX060A

Block the path to prevent refrigerant flow in the event of a refrigerant leakage.



**Gas sensor kit**  
UTY-SGZY

Gas Sensor kit Used to ensure standards compliance and safety when R32 VRF products are installed.




**Expansion kit**  
UTZ-JXXA\*

Used to ensure standards compliance and safety when R32 VRF products are installed.

\*Connection cable (UTY-XWZXZL) is required.

### Conditions requiring safety measures

The graph below will help you determine if a safety design is required when installing R32 VRF products. The amount of refrigerant in a refrigerant system determines the floor area, and if the room to be conditioned by the system is less than that area, a "shut off valve kit" and a "gas sensor kit" must be installed.



### Features: Gas sensor kit


#### Refrigerant leak detector connection pattern

- 1) Corresponds to the case where the classification of air conditioner installation differs from property to property.  
Installation position of "Shut off valve kit"


A Indoor unit 1~4 in one room

B Indoor units 1, 2 and 3, 4, if they are set up in two separate rooms.


C Indoor units 1~4 are installed in different rooms.



- 2) Multiple rooms or areas are air conditioned using ducted airflow paths



- 3) When operating multiple indoor units with a remote control group



### Specifications

Model name	UTY-SGZY
Dimensions (H × W × D) (mm)	80 × 130 × 35
Weight (g)	500

## Optional parts list for Split/Multi-split



Type	Refrigerant	Indoor unit										Indoor unit										Multi-split			
		Wall-mounted					Cassette					Duct					Duct		Floor	Ceiling	Multi-split				
		Designer Range		Standard Range			ECO Range			4-way flow Compact		Circular flow		Slim	Medium static pressure (High-Efficiency & Comfort)	Medium static pressure (Compact)	Medium static pressure (Standard)	High static pressure	Big		4-way flow Compact cassette	Mini duct	Slim duct		
		ASEG07/09/12/14KGTF, ASY07/09/12/14KGTF, ASY07/09/12/14KGTE	ASEG07/09/12/14KETF, KETF-B ASYG07/09/12/14KETE, KETE-B	ASEH07/09/12/14KMCG, ASY07/09/12/14KMCF, ASY07/09/12/14KMC	ASEH07/09/12/14KMCE	ASEG 18/24KMTE	ASEH 30/36KMTB	ASEH 05/07/09/12 KNCA	ASEG 07/09/12 KPCE	ASEH 07/09/12 KLTA	ASEG 18/24KLCA	AUXG 09/12/14/18/22/24 KVLA	AUXG 18/22/24/30/36/45/54 KRLB	ARXG 09/12/14/18 KLLAP	ARXH 12/14/18/22/24/30/36/45/54 KHTAP	ARXG22KMLB, ARXG 24/30/36/45 KMLA	ARXG45/54KHTB	AGEG 09/12/14 KVCA	ABEG 18/22/24/30/36/45/54 KRTA	AUXG07KVLA	ARXG07KSLAP	ARXG07KLLAP			
																						AUYG07/09LVLA	ARYG07/09LSLAP	ARYG07/09LLTA	
Human sensor kit														● UTG-SHZXC											
Remote sensor unit		The remote sensor provides additional convenience.													● UTY-XSZXZ1									● UTY-XSZXZ1	
Cassette grille												● UTG-UFYF-W		● UTG-UKYA-W, UTG-UKYC-W, UTG-UKYA-B								● UTG-UFYF-W (KVLA), UTG-UFYD-W (LVLA)			
Auto louver grille kit														● UTD-GXTA-W (09/12/14) UTD-GXTB-W (18)									● UTD-GXTA-W (07/09/12/14), UTD-GXTB-W (18)		
Silver ion filter			● UTR-FA16-5		● UTR-FA13-3		● UTR-FA16-5		● UTD-HFAA		● UTD-HFRA		● UTD-HFTA (09/12/14) UTD-HFTB (18)	● UTD-HFNC (12/14/18) UTD-HFNH (22/24), UTD-HFNA (30/36/45/54)	● UTD-HFNC (12/14) UTD-HFNH (18/22/24/30) UTD-HFNA (36/45/54)	● UTD-HFND	● UTD-HFKB (45/54)	● UTD-HFKA	● UTR-FA03-5		● UTD-HFAA	● UTD-HFTA (07/09/12/14) UTD-HFTB (18)	● UTD-HFTA (07/09/12/14) UTD-HFTB (18)		
Long-life filter														● UTD-LFDC (12/14/18) UTD-LFDB (22/24), UTD-LFDA (30/36/45/54)	● UTD-LFNC (36/45/54) UTD-LFB (18/22/24/30) UTD-LFNA (12/14)	● UTD-LF25NA	● UTD-LF60KA (45/54)	● UTD-LFKA							
Flange																● UTD-SFO45T UTD-RF204									
Drain pump unit																● UTZ-PX1NBA		● UTZ-PX1NAB		● UTR-DPB24T					
Wide Panel													● UTZ-AKXA-W												
Panel spacer													● UTZ-BKXA-W												
Fresh air intake kit		For Compact cassette For Circular flow cassette										● UTZ-VXAA		● UTZ-VXRA									● UTZ-VXAA		
Air outlet shutter plate		For Compact cassette For Circular flow cassette										● UTR-YDZB		● UTR-YDK									● UTR-YDZB		
Insulation kit for high humidity												● UTZ-KXGC		● UTZ-KXRA									● UTZ-KXGC		
Half concealed kit		Used to half conceal a floor type indoor unit in the wall.															● UTR-STA								
L-type piping kit																		● UTP-FX24A (18/22/24) UTP-FX35A (30/36/45/54)							

# Optional parts list for VRF



Type	Refrigerant	Indoor unit																		V-IV Series			
		Cassette				Duct								Indoor unit									
		One-way flow	3D flow	Compact grid type/ Standard type		Slim type		Large type		Low static pressure duct			Duct			Floor		Floor/Ceiling	Ceiling	Wall-mounted			
				Mini (With drain pump)	Circular flow	High Efficiency	Slim (With drain pump)	High Efficiency	High Efficiency	Low static pressure duct	Medium static pressure	High static pressure	High Efficiency	Normal	Normal	-	external EEV			-	external EEV	-	-
	AUXB 004/005/007/ 009/012/014/ 018HLAH	AUXN 009/012/014/ HLAH	AUXM 018/024GLEH	AUXX 018/024/030/ 034/036/045/ 054GLEH	ARXD 004/005/007/ 009/012/014/ 018/024/ HLAH	ARXP 009/012/014/ HLAH	ARXD 007/009/012/ 014/018/024/ GLEH	ARXP 018/030/ GLEH	ARXA 024/030/ 036/045/ GLEH	ARXC 036/045/060/ GTEH	ARXC 072/090/096/ GTEH	AGYA 004/007/ 009/012/014/ GCEH	AGYE 004/007/ 009/012/014/ GCEH	ABYA 012/014/ 018/024/ GTEH	ASYA 004/005/007/ 009/012/014/ HCAH	ASYE 004/005/007/ 009/012/014/ HCAH	AJY 072/090/108/ 126/144/162/ LADH						
	AUXV 004/007/009/ 012/014/018/ 024GLEH	AUXS 018/024GLEH	AUXB 004/007/009/ 012/014/018/ 024GLEH	AUXM 018/024/030/ GLEH	AUXK 018/024/030/ 034/036/045/ 054GLEH	ARXK 004/007/009/ 012/014/018/ 024GLEH	ARXD 04GALH	ARXD 007/009/012/ 014/018/024/ GLEH	ARXP 018/030/ GLEH	ARXA 024/030/ 036/045/ GLEH	ARXC 036/045/060/ GTEH	ARXC 072/090/096/ GTEH	AGYA 004/007/ 009/012/014/ GCEH	AGYE 004/007/ 009/012/014/ GCEH	ABYA 012/014/ 018/024/ GTEH	ASYA 004/007/009/ 012/014/ GCEH	ASYE 004/007/009/ 012/014/ GCEH	ASYA 030/034GTEH	ASYA 18/24GBCH	ASYA 030/034GTEH	AJY 072/090/108/ 126/144/162/ LADH		
Human sensor kit																							
Remote sensor unit																							
Cassette grille		UTG-UNYA-W (004-012) UTG-UNYB-W (014-024)	UTG-USYA-W	UTG-UFCY-W (004-012) UTG-UNYB-W (014-024)	UTG-UFCY-W (004-012) UTG-UFYH-W (HLAH)	UTG-UFYH-W	UTG-UFYH-W (HLAH)	UTG-UKYC-W (004-012) UTG-UFYH-W (HLAH)	UTG-UKYC-W (004-012) UTG-UFYH-W (HLAH)	UTY-SHZXC	UTY-XSZXZ1	UTY-XSZXZ1	UTY-XSZXZ1										
Auto louver grille kit																							
Silver ion filter																							
Long-life filter																							
Flange																							
Drain Pump Unit																							
Wide Panel																							
Panel spacer																							
Fresh air intake kit*1		For Compact cassette	For Circular flow cassette																				
Air outlet shutter plate		For Compact cassette	For Circular flow cassette																				
Insulation kit for high humidity																							
Half concealed kit																							
External power supply unit		UTZ-GXXA UTZ-GXXC	UTZ-GXXA UTZ-GXXC UTZ-GXXD (HLAH)	UTZ-GXXD		UTZ-GXXA UTZ-GXXC		UTZ-GXXA UTZ-GXXC UTZ-GXXD (HLAH)	UTZ-GXXD									UTZ-GXXA UTZ-GXXC UTZ-GXXD (HLAH)	UTZ-GXXA UTZ-GXXC				
Pressure sensor kit																					UTZ-SPWIX		
Gas sensor kit																					UTY-SGZY (HLAH)		

# Function list for Split/Multi-split



External input and output function/External connect kit/communication kit

Type	Refrigerant	Indoor unit												Indoor unit			Floor	Ceiling	Multi-split				Outdoor unit					
		Wall-mounted				Cassette		Duct				Duct		High static pressure	Bldg	Wall-mounted	Mini duct	Slim duct		Compact cassette	Single split		Simultaneous multi-split					
		Designer Range		Standard Range		ECO Range		Compact 4-way flow	Circular flow	Slim	Medium static pressure (High Efficiency & Comfort)	Medium static pressure (Compact)	Medium static pressure (Standard)								AOEG 36/45/54 KRTA	AOEG 36/45/54 KRTA	AOEG 36/45/54 KRTA	AOEG 36/45/54 KRTA				
Indoor	R32	ASEH07/09/12/14/16/18/20/22/24/26/28/30/32/34/36/38/40/42/44/46/48/50/52/54/56/58/60/62/64/66/68/70/72/74/76/78/80/82/84/86/88/90/92/94/96/98/100/102/104/106/108/110/112/114/116/118/120/122/124/126/128/130/132/134/136/138/140/142/144/146/148/150/152/154/156/158/160/162/164/166/168/170/172/174/176/178/180/182/184/186/188/190/192/194/196/198/200/202/204/206/208/210/212/214/216/218/220/222/224/226/228/230/232/234/236/238/240/242/244/246/248/250/252/254/256/258/260/262/264/266/268/270/272/274/276/278/280/282/284/286/288/290/292/294/296/298/299/300/301/302/303/304/305/306/307/308/309/310/311/312/313/314/315/316/317/318/319/320/321/322/323/324/325/326/327/328/329/330/331/332/333/334/335/336/337/338/339/340/341/342/343/344/345/346/347/348/349/350/351/352/353/354/355/356/357/358/359/360/361/362/363/364/365/366/367/368/369/3610/3611/3612/3613/3614/3615/3616/3617/3618/3619/3620/3621/3622/3623/3624/3625/3626/3627/3628/3629/3630/3631/3632/3633/3634/3635/3636/3637/3638/3639/3640/3641/3642/3643/3644/3645/3646/3647/3648/3649/3650/3651/3652/3653/3654/3655/3656/3657/3658/3659/3660/3661/3662/3663/3664/3665/3666/3667/3668/3669/36610/36611/36612/36613/36614/36615/36616/36617/36618/36619/36620/36621/36622/36623/36624/36625/36626/36627/36628/36629/36630/36631/36632/36633/36634/36635/36636/36637/36638/36639/366310/366311/366312/366313/366314/366315/366316/366317/366318/366319/366320/366321/366322/366323/366324/366325/366326/366327/366328/366329/3663210/3663211/3663212/3663213/3663214/3663215/3663216/3663217/3663218/3663219/3663220/3663221/3663222/3663223/3663224/3663225/3663226/3663227/3663228/3663229/36632210/36632211/36632212/36632213/36632214/36632215/36632216/36632217/36632218/36632219/36632220/36632221/36632222/36632223/36632224/36632225/36632226/36632227/36632228/36632229/366322210/366322211/366322212/366322213/366322214/366322215/366322216/366322217/366322218/366322219/366322220/366322221/366322222/366322223/366322224/366322225/366322226/366322227/366322228/366322229/3663222210/3663222211/3663222212/3663222213/3663222214/3663222215/3663222216/3663222217/3663222218/3663222219/3663222220/3663222221/3663222222/3663222223/3663222224/3663222225/3663222226/3663222227/3663222228/3663222229/36632222210/36632222211/36632222212/36632222213/36632222214/36632222215/36632222216/36632222217/36632222218/36632222219/36632222220/36632222221/36632222222/36632222223/36632222224/36632222225/36632222226/36632222227/36632222228/36632222229/366322222210/366322222211/366322222212/366322222213/366322222214/366322222215/366322222216/366322222217/366322222218/366322222219/366322222220/366322222221/366322222222/366322222223/366322222224/366322222225/366322222226/366322222227/366322222228/366322222229/3663222222210/3663222222211/3663222222212/3663222222213/3663222222214/3663222222215/3663222222216/3663222222217/3663222222218/3663222222219/3663222222220/3663222222221/3663222222222/3663222222223/3663222222224/3663222222225/3663222222226/3663222222227/3663222222228/3663222222229/36632222222210/36632222222211/36632222222212/36632222222213/36632222222214/36632222222215/36632222222216/36632222222217/36632222222218/36632222222219/36632222222220/36632222222221/36632222222222/36632222222223/36632222222224/36632222222225/36632222222226/36632222222227/36632222222228/36632222222229/366322222222210/366322222222211/366322222222212/366322222222213/366322222222214/366322222222215/366322222222216/366322222222217/366322222222218/366322222222219/366322222222220/366322222222221/366322222222222/366322222222223/366322222222224/366322222222225/366322222222226/366322222222227/366322222222228/366322222222229/3663222222222210/3663222222222211/3663222222222212/3663222222222213/3663222222222214/3663222222222215/3663222222222216/3663222222222217/3663222222222218/3663222222222219/3663222222222220/3663222222222221/3663222222222222/3663222222222223/3663222222222224/3663222222222225/3663222222222226/3663222222222227/3663222222222228/3663222222222229/36632222222222210/36632222222222211/36632222222222212/36632222222222213/36632222222222214/36632222222222215/36632222222222216/36632222222222217/36632222222222218/36632222222222219/36632222222222220/36632222222222221/36632222222222222/36632222222222223/36632222222222224/36632222222222225/36632222222222226/36632222222222227/36632222222222228/36632222222222229/366322222222222210/366322222222222211/366322222222222212/366322222222222213/366322222222222214/366322222222222215/366322222222222216/366322222222222217/366322222222222218/366322222222222219/366322222222222220/366322222222222221/366322222222222222/366322222222222223/366322222222222224/366322222222222225/366322222222222226/366322222222222227/366322222222222228/366322222222222229/3663222222222222210/3663222222222222211/3663222222222222212/3663222222222222213/3663222222222222214/3663222222222222215/3663222222222222216/3663222222222222217/3663222222222222218/3663222222222222219/3663222222222222220/366322222222222221/3663222222222222222/366322222222222223/366322222222222224/366322222222222225/366322222222222226/366322222222222227/366322222222222228/366322222222222229/3663222222222222210/3663222222222222211/3663222222222222212/3663222222222222213/3663222222222222214/3663222222222222215/3663222222222222216/3663222222222222217/3663222222222222218/3663222222222222219/3663222222222222220/366322222222222221/3663222222222222222/366322222222222223/366322222222222224/366322222222222225/366322222222222226/366322222222222227/366322222222222228/366322222222222229/3663222222222222210/3663222222222222211/3663222222222222212/3663222222222222213/3663222222222222214/3663222222222222215/3663222222222222216/3663222222222222217/3663222222222222218/3663222222222222219/3663222222222222220/366322222222222221/3663222222222222222/366322222222222223/366322222222222224/366322222222222225/366322222222222226/366322222222222227/366322222222222228/366322222222222229/3663222222222222210/3663222222222222211/3663222222222222212/3663222222222222213/3663222222222222214/3663222222222222215/3663222222222222216/3663222222222222217/366322222222																										

# Function list for VRF



## External input and output function/External connect kit

Type	Refrigerant	Indoor unit										Indoor unit										controller	Other								
		Cassette					Duct					Floor					Wall-mounted					J-VS	J-IVL	J-IV	J-IVS	V-IV	VR-IV	Central remote controller	RB unit		
		One-way flow	3D flow	Compact grid type/Standard type		Slim type/Large type	Low static pressure		Low static pressure	Medium static pressure	High static pressure	-	EEV external	Floor/Ceiling				-	EEV external	-											
				Circular flow			Mini (With drain pump)	Slim (With drain pump)						High Efficiency	Normal	Normal															
input	R32			AUXB 004/005/007/ 009/012/014/ 018HLAH	AUXN 009/012/014			ARXD 004/005/007/ 009/012/014/ 018/024 HLAH	ARXP 009/012/014 HLAH						ASYA 004/005/007/ 009/012/014 HCAH	ASYE 004/005/007/ 009/012/014 HCAH				AJY 040/045/054 KCTAH											
	R410A	AUXV 004/007/009/ 012/014/018/ 024GLEH	AUXS 018/024 GLEH	AUXB 004/007/009/ 012/014/018/ 024GLEH		AUXM 018/024/030 GLEH	AUXK 018/024/030/ 034/036/045/ 054GLEH	ARXK 004/007/009/ 012/014/018/ 024GLEH	ARXD 007/009/012/ 014/018/024 GLEH, ARXD 04GALH	ARXA 024/030/ 036/045 GLEH	ARXC 036/045/060 036/045/060 GLEH	AGYA 004/007/ 009/012/014 GCEH	AGYE 004/007/ 009/012/014 GCEH	ABYA 012/014/018/ 024GTEH	ABVA 030/036/045/ 054GTEH	ASYA 004/007/009/ 012/014 GCH	ASYE 004/007/009/ 012/014 GCEH				ASYA 18/24GBCH	ASYA 030/034/GTEH				AJY 040/045/054 LBDLH, AJY 040/045/054 LELDH	AJY 040/045/054 LCLDH	AJY 072/090/108/ 126/144/162 GALDH	UTY-DGGYZ3	UTP-RX01AH UTP-RX01BH UTP-RX01CH UTP-RX04BH UTP-RX08AH UTP-RX12AH	
output	Operation/Stop	<input checked="" type="checkbox"/> UTY-XWZXZD <input type="checkbox"/> UTY-XWZXZB	<input checked="" type="checkbox"/> UTY-XWZXZD <input type="checkbox"/> UTY-XWZXZB																												
	All On/All Off																										● UTY-XWZXZ7 ○ UTY-XWZXZ8				
	Group stop																										● UTY-XWZXZ6				
	Forced stop	<input checked="" type="checkbox"/> UTY-XWZXZD <input type="checkbox"/> UTY-XWZXZB	<input checked="" type="checkbox"/> UTY-XWZXZD <input type="checkbox"/> UTY-XWZXZB																												
	Emergency stop	<input checked="" type="checkbox"/> UTY-XWZXZD <input type="checkbox"/> UTY-XWZXZB	<input checked="" type="checkbox"/> UTY-XWZXZD <input type="checkbox"/> UTY-XWZXZB																							● UTY-XWZXZ7 ○ UTY-XWZXZ8					
	Forced thermostat off	<input checked="" type="checkbox"/> UTY-XWZXZE <input type="checkbox"/> UTY-XWZXZ7	<input checked="" type="checkbox"/> UTY-XWZXZE <input type="checkbox"/> UTY-XWZXZ7																												
	Low noise mode operation																										● UTY-XWZXZ6				
	Cooling/Heating priority																										● UTY-XWZXZ6 ○ UTY-XWZXZB				
	Outdoor unit operation peak control																										● UTY-XWZXZ6				
	Power usage information from electricity meter																										● UTY-XWZXZF				
audio	Operation status	<input checked="" type="checkbox"/> UTY-XWZXZC	<input checked="" type="checkbox"/> UTY-XWZXZC													<input checked="" type="checkbox"/> UTY-XWZXZ6						○ UTY-XWZXZ6				○ UTY-XWZXZA					
	Error status	<input checked="" type="checkbox"/> UTY-XWZXZC	<input checked="" type="checkbox"/> UTY-XWZXZC													<input checked="" type="checkbox"/> UTY-XWZXZ6						○ UTY-XWZXZ6				○ UTY-XWZXZA					
	Indoor unit fan operation status	<input checked="" type="checkbox"/> UTY-XWZXZC	<input checked="" type="checkbox"/> UTY-XWZXZC																												
	Auxiliary heater output	<input checked="" type="checkbox"/> UTY-XWZXZC	<input checked="" type="checkbox"/> UTY-XWZXZC																												
	Base pan heater																										● UTY-XWZXZ9				
audio	Expansion kit	<input checked="" type="checkbox"/> UTZ-JXXA+ UTY-XWZXZL (HLAH)					<input checked="" type="checkbox"/> UTZ-JXXA+ UTY-XWZXZL (HLAH)					<input checked="" type="checkbox"/> UTZ-JXXA+ UTY-XWZXZL (HLAH)					<input checked="" type="checkbox"/> UTY-XWZXZL (HCAH)					<input checked="" type="checkbox"/> UTY-XWZXZ9					● UTY-XWZXZ9				
	Connection Cable	<input checked="" type="checkbox"/> UTY-XWZXZL																													

\*2: The Touch panel controller has the functions of dry contact and voltage application, but the external connection kit described above is not necessary because the touch panel controller has an external input terminal block.

●: Dry Contact ○: Apply Voltage

## For VRF

Communication system		External connect kit		For indoor unit		For outdoor unit		For RB unit		Central remote controller		For Touch panel controller	
Expansion kit	Connection Cable	UTZ-JXXA	UTY-XWZXZL	UTY-XWZXZD	UTY-XWZXZB	UTY-XWZXZ9	UTY-XWZXZF	UTY-XWZXZ6	UTY-XWZXZB	UTY-XWZXZ7	UTY-XWZXZ8	UTY-XWZXZA	

# Separation tube



## For SPLIT/MULTI-SPLIT/SIMULTANEOUS MULTI-SPLIT

### Separation tube

UTP-SX236A / UTP-SX254A  
For 3-phase simultaneous multi-split



UTP-SX354A  
For 3-phase simultaneous multi-split



UTP-SX272A  
For Simultaneous multi-split Twin/  
Triple/Double Twin


UTP-SX372A  
For Simultaneous multi-split Twin/  
Triple/Double Twin




## for VRF

### Separation tube


UTP-AX054A




UTP-AX090A




UTP-AX180A



UTP-AX567A



UTP-BX090A



UTP-BX180A



UTP-BX567A




UTP-LX180A  
For DX kit




### Header


UTR-H0906L / UTR-H1806L




UTR-H0908L / UTR-H1808L



UTP-J0906A / UTP-J1806A




UTP-J0908A / UTP-J1808A



### Outdoor unit branch kit


UTP-CX567A





UTP-DX567A



UTP-EX060A



UTP-EX096A



## for VRF

### EV kit

Model name ≤ 09: UTR-EV09XB  
Model name ≥ 12: UTR-EV14XB  
for compact wall-mounted type



**NEW** Model name ≤ 09: UTR-EV09XC  
Model name ≤ 12: UTR-EV14XC  
for R32 VRF wall-mounted type



### Shut off valve kit

**NEW** UTP-GX027A  
for R32 VRF indoor unit



**NEW** UTP-GX060A  
for R32 VRF outdoor unit



## RB unit

UTP-RX01AH / UTP-RX01BH /  
UTP-RX01CH  
Single type



UTP-RX04BH  
Multi-split type



UTP-RX08AH  
Multi-split type



UTP-RX12AH  
Multi-split type



## Specifications

### Separation tube

Model name	UTP-AX054A	UTP-AX090A	UTP-AX180A	UTP-AX567A
Total cooling capacity of indoor unit (kW)	19.6 or less	28.0 or less	28.1 to 56.0	56.1 or more

Model name	UTP-BX090A	UTP-BX180A	UTP-BX567A
Total cooling capacity of indoor unit (kW)	28.0 or less	28.1 to 56.0	56.1 or more

### Header

Model name	3-6 Branches	3-8 Branches	UTR-H0906L	UTR-H1806L
Total cooling capacity of indoor unit (kW)	28.0 or less	28.1 to 56.0	UTR-H0908L	UTR-H1808L

Model name	3-6 Branches	3-8 Branches	UTP-J0906A	UTP-J1806A
Total cooling capacity of indoor unit (kW)	28.0 or less	28.1 to 56.0	UTP-J0908A	UTP-J1808A

### Outdoor unit branch kit

Model name	UTP-CX567A (for V-IV)	UTP-DX567A (for VR-IV)
Number of outdoor units	2 outdoor units	1
	3 outdoor units	2

### EV kit

Model name	UTR-EV09XB	UTR-EV14XB	UTR-EV09XC	UTR-EV14XC
Application model	ASYE004GCEH ASYE007GCEH ASYE009GCEH	AGYE004GCEH AGYE007GCEH AGYE009GCEH	ASYE012GCEH ASYE014GCEH	AGYE012GCEH AGYE014GCEH ASYE009CAH ASYE012CAH ASYE014CAH

### RB unit

Type	Single type			Multi-split type		
Model name	UTP-RX01AH	UTP-RX01BH	UTP-RX01CH	UTP-RX04BH	UTP-RX08AH	UTP-RX12AH

Power source	V/Ø/Hz	230/1/50
Input power	W	17 24 31 96 136 204

Number of branches	1	1	1	4	8	12
Maximum capacity of connectable indoor units (Q)	kW	Q ≤ 8.0	Q ≤ 18.0	Q ≤ 28.0	Q ≤ 56.1*	Q ≤ 72.0

Maximum capacity of connectable indoor units per branch (Q)	kW	Q ≤ 8.0	Q ≤ 18.0	Q ≤ 28.0	Q ≤ 8.0	Q ≤ 8.0
Maximum Connectable Indoor Units per Branch	3 8	8	8	7	7	7

Dimensions (H × W × D)	mm	198 × 298 × 268	260 × 658 × 428	298 × 660 × 618	298 × 990 × 618
------------------------	----	-----------------	-----------------	-----------------	-----------------


\*1: When two RB units are connected in series (8 branches in total), the maximum capacity of the connectable indoor units is up to 56.0 kW.

### Shut off valve kit

Model name	UTP-GX027A	UTP-GX060A
Power source	230/1/50	230/1/50
Input power	W	24
Number of branches		1
Maximum number of connectable Expansion kit		4
Maximum capacity of connectable indoor units (Q)	kW	Q ≤ 8.0
Maximum capacity of Connectable Indoor Units per		

# Residential AIR TO WATER

- W-002 AIR TO WATER Overview
- W-004 AIR TO WATER Lineup
- W-006 Benefits
- W-008 Home Heating & Domestic Hot Water Supply
- W-010 High-Efficiency Technology
- W-012 Split Type
  - Comfort Series
  - Super High Power Series
  - High Power Series
- W-018 Split DHW Integrated Type
  - Comfort Series
  - Super High Power Series
  - High Power Series
- W-024 Control Overview
- W-026 Comfort Control
- W-028 System Configuration
- W-030 Case Studies
- W-032 Simple installation
  - Easy Installation & Maintenance
- W-034 Installation requirements
- W-035 AIR TO WATER Optional Parts



AIR TO WATER  
Residential



FUJITSU GENERAL LIMITED

# AIR TO WATER Overview

## Solutions that meet a variety of needs


Water heated by Air to water using clean energy is delivered reliably and comfortably throughout the house, including the living room.



## Heat Pump System Framework

Heat is absorbed from the atmosphere by expanding the refrigerant.

Higher-temperature heat is generated by compressing the refrigerant, and the indoor unit transfers that heat to the water.






## Our Goal

### Decarbonisation

European Commission is committed to decarbonisation and has a national target of "Net Zero" carbon emissions by 2050.

We need to reduce carbon emissions with green technology products and increase carbon absorption by working to extend nature.




Fujitsu General's ATW system will provide the best solutions that are friendly to the environment and people with products conscious of decarbonisation.

## The Choice of ATW


### Optimized refrigerant cycle operation

Super High Power and High Power Series deliver high performance and efficiency with twin sensors and hot water heating technology.

#### Split Type




#### Split DHW Integrated Type



### What is a heat pump?


A heat pump extracts heat energy from the atmosphere. It requires only 1 kW of electricity to generate 3 to 5 kW of thermal energy.



### Primary energy usage reduced substantially

Proportion of primary energy converted into heating energy is 100%

#### Primary Energy Consumption\*



\* The amount of electricity loss varies according to the power plant. Typical energy efficiency of a power plant: 36%

## AIR TO WATER Lineup



Type	Split Type			Split DHW Integrated Type		
	Comfort Series	Super High Power Series	High Power Series	Comfort Series	Super High Power Series	High Power Series
Hydraulic unit						
Outdoor unit						
Capacity range	5/6 kW 8 kW 10 kW	16 kW 15/17 kW	11/14 kW 11/16 kW	5/6 kW 8 kW 10 kW	16 kW 15/17 kW	11/14 kW 11/16 kW
System outline	<ul style="list-style-type: none"> <li>Supplies 55°C hot water even when the outdoor temperature is -10°C.</li> <li>Heating and DHW supply in one system.*</li> <li>Equipped with additional electric heater for backup</li> <li>Up to two independent control circuits.*</li> <li>Cooling operation is possible.*</li> <li>Operating range is -20 to 35°C.</li> <li>Can be used with a variety of heating systems, including underfloor heating and radiators.*</li> </ul>	<ul style="list-style-type: none"> <li>Supplies 60°C hot water even when the outdoor temperature is -20°C.</li> <li>Supplies 55°C hot water even when the outdoor temperature is -22°C.</li> <li>Can be used with a variety of heating systems, including underfloor heating and radiators.*</li> <li>Heating and DHW supply in one system.*</li> <li>Up to two independent control circuits.*</li> <li>Cascade connection is possible for up to three systems.*</li> <li>Equipped with additional electric heater for backup</li> <li>Up to two independent control circuits.*</li> <li>Cooling operation is possible.*</li> <li>Operating range is -25 to 35°C.</li> </ul>	<ul style="list-style-type: none"> <li>Supplies 60°C hot water even when the outdoor temperature is -10°C.</li> <li>Heating and DHW supply in one system.</li> <li>Equipped with additional electric heater for backup</li> <li>Up to two independent control circuits.*</li> <li>Cooling operation is possible.*</li> <li>Operating range is -20 to 35°C.</li> <li>Can be used with a variety of heating systems, including underfloor heating and radiators.*</li> </ul>	<ul style="list-style-type: none"> <li>Supplies 60°C hot water even when the outdoor temperature is -20°C.</li> <li>Supplies 55°C hot water even when the outdoor temperature is -22°C.</li> <li>Can be used with a variety of heating systems, including underfloor heating and radiators.*</li> <li>Space saving heating and DHW supply in a single Hydraulic unit</li> <li>Equipped with additional electric heater for backup</li> <li>Up to two independent control circuits.*</li> <li>Cooling operation is possible.*</li> <li>Operating range is -25 to 35°C.</li> </ul>	<ul style="list-style-type: none"> <li>Supplies 60°C hot water even when the outdoor temperature is -20°C.</li> <li>Can be used with a variety of heating systems, including underfloor heating and radiators.*</li> <li>Space saving heating and DHW supply in a single Hydraulic unit</li> <li>Up to two independent control circuits.*</li> <li>Cooling operation is possible.*</li> <li>Operating range is -25 to 35°C.</li> </ul>	
Power source	Single phase, ~230 V, 50 Hz	Single phase, ~230 V, 50 Hz	3-phase, ~400 V, 50 Hz	Single phase, ~230 V, 50 Hz	3-phase, ~400 V, 50 Hz	Single phase, ~230 V, 50 Hz
5 kW	WSYA050ML3 WOYA060KLT				WGYA050ML3 WOYA060KLT	
6 kW	WSYA080ML3 WOYA060KLT				WGYA080ML3 WOYA060KLT	
8 kW	WSYA080ML3 WOYA080KLT				WGYA080ML3 WOYA080KLT	
10 kW	WSYA100ML3 WOYA100KLT				WGYA100ML3 WOYA100KLT	
11 kW				WSYG140DG6 WOYG112LHT	WSYK160DG9 WOYK112LCTA	
14 kW				WSYG140DG6 WOYG140LCTA	WSYK160DG9 WOYK140LCTA	
15 kW			WSYK170DJ9 WOYK150LJL			WGKY170DJ9 WOYK150LJL
16 kW		WSYG160DJ6 WOYG160LJL		WSYG160DG9 WOYG160LCTA		WGYG160DJ6 WOYG160LJL
17 kW			WSYK170DJ9 WOYK170LJL			WGKY170DJ9 WOYK170LJL
Approval						


\* Please refer to page W-038 and W-039 for optional parts information.

# Benefits

## Less CO<sub>2</sub> Emissions

Air to water is an environmentally friendly system that emits substantially less carbon dioxide than conventional gas and hydrocarbon combustion systems.

### Average annual CO<sub>2</sub> emissions



## Clean and Healthy


As an Air to water system does not use a burner to heat water, it does not produce NOx or other harmful substances.



## Low Running Cost

High-efficiency heat pump technology keeps the running cost of an Air to water system.

### Average annual running cost



\*The running cost may vary depending on a system's installation, geographical location, and operating conditions.



## Easy Installation and Maintenance

All components are built into a compact outdoor unit or a Hydraulic unit.

- No chimney sweep
- No pollution
- Low maintenance cost

**Well-designed Hydraulic unit**  
The sophisticated arrangement of Hydraulic units makes piping and maintenance work easy.

## Energy Efficiency Standards Product labels



## The Ecodesign Directive Lot 1 Regulation 813/2013

The Ecodesign directive defines a regulatory framework for improving the environmental performance of energy-related products (ErP) through design.

Since September 26, 2015, the Ecodesign Directive has applied to space heaters, including heat pumps and fossil fuel fired boilers, combination heaters for space and hot water heating, water heaters, and water storage tanks.

All of these products must meet minimum requirements for energy efficiency<sup>\*1</sup> and maximum sound power level. The minimum energy efficiency class were raised on September 26, 2017, and the maximum sound levels were lowered on September 26, 2018.

<sup>\*1</sup>: Energy efficiency is expressed in terms of seasonal space heating efficiencies ( $\eta_s$ ). The value is based upon the Seasonal Coefficient of Performance (SCOP).

## The Energy Labelling Directive (EU) No. 811/2013

Energy label is intended to enable consumers to make direct comparisons of energy use and product features. All labels should indicate the product identifier, efficiency class, sound power level, and heat output. Heat generators are rated A+++ to D. There are two different product labels. One for space heaters and one for combination heaters.

### EHPA Quality Label



Fujitsu General's Air to water<sup>\*2</sup> has acquired the EHPA Quality Label<sup>\*3</sup> through testing in accordance with the International Standards EN14511 and EN17025. The EHPA Quality Label<sup>\*3</sup> is a label that shows the end-consumer a quality heat pump unit on the market.

<sup>\*2</sup>: 3-phase High Power Series only  
<sup>\*3</sup>: Learn more about the validity of the mark at [www.ehpa.org/quality/quality-label/](http://www.ehpa.org/quality/quality-label/)

### SG ready Label



SG ready is a label issued to heat pumps and their control technologies that meet the requirements set by BWP<sup>\*4</sup>, and technologies that conform to their standards can be integrated into a smart grid. SG ready labeled heat pumps receive signals from the power grid and PV systems with regard to energy and renewable energy sources such as wind, solar, and water. All of Fujitsu General's new heat pump series are SG ready compatible.

<sup>\*4</sup>: BWP: Bundesverband Wärmepumpe e. V. (Federal German Heat Pump Association)

### The CEN Heat Pump KEYMARK




The Heat Pump KEYMARK is a full certificate supporting the quality of heat pumps in the European market. The Heat Pump KEYMARK is a voluntary, independent, European certification mark (ISO Type 5 Certification) for all heat pumps, combination heat pumps, and hot water heaters (as covered by Ecodesign, EU Regulation 813/2013 and 814/2013). Fujitsu General's Air to water<sup>\*5</sup> has acquired the KEYMARK certificate<sup>\*6</sup>.

<sup>\*5</sup>: R32 refrigerant comfort model only

<sup>\*6</sup>: Learn more about the validity of the mark at [www.heatpumpkeymark.com/about/](http://heatpumpkeymark.com/about/)

# Home Heating & Domestic Hot Water Supply

A wide range of products to suit regional characteristics, family structures, and usage patterns. We provide a variety of products to meet the needs of customers from the heating-centered High Power Series to the reasonably priced Compact Series.



**Water flow temperature  
60°C**

Super High Power Series  
High Power Series

## High water flow temperature

The temperature of water flow can be maintained at 60°C without using a backup heater, even when the outdoor temperature drops to -20°C.

## Floor heating and domestic hot water supply

Outdoor units and hydraulic indoor units can be installed flexibly and easily. Hydraulic units installed inside the house prevent the circulating water from freezing. More units can be cascaded together to provide a greater heating capacity with greater flexibility.\*1

\*1: High Power Series only

REFRIGERANT  
**R32**



## Adopting R32 refrigerant

R32 refrigerant is an environmentally friendly refrigerant with a significantly lower Global Warming Potential (GWP) than conventional refrigerants.




## + DHW tank

A DHW tank (optional) can be connected to supply hot water.

## + Boiler

By combining with an existing boiler, powerful heating can be achieved even at low outdoor temperature.

\* Please refer to page W-038 and W-039 for optional parts information.




Stylish space saving solution with built-in DHW tank



## Built-in DHW tank saves a great deal of space.

Existing boilers can be replaced easily. A higher heating capacity can be achieved with the flexibility to cascade more units.



## Smart control

To meet the diverse needs of customers, we offer a variety of control options, such as individual control and remote control options.

# High-Efficiency Technology



## Twin-Rotary Compressor




For Outdoor unit

### Twin-Rotary Compressor with Linear Control Injection Port

The compressor achieves a high condensing temperature without overheating the discharge gas temperature due to the Linear control injection process used during compression. This makes the condensing temperature higher than in a normal circuit. Higher water temperatures can be achieved by controlling the injection volume according to usage conditions.



## High-durability coaxial heat exchanger



For Hydraulic unit

### Stainless steel buffer tank

Heat exchange amount is 25% higher than the previous model. Energy-saving performance has also been improved.

- Anti-corrosion protection
- No flow switch required
- Anti-freeze protection not required

### Class A Pump

Energy-saving pump with the ability to adjust the flow rate and pressure to a constant level



## SPLIT TYPE Comfort Series



### High water flow temperature

The temperature of water flow is up to 55°C without a backup heater. Hot water supply temperature can be maintained even at -10°C outdoor temperature.

\* If you want to raise the temperature of the water supply to above the maximum temperature, use a backup heater to supplement the primary heater.




### High COP

Heat pumps of ATW Systems work more efficiently and consume less energy than conventional heating systems.



\*Temperature application: Heating temp. 35°C



### Outdoor unit technology



**DC Fan Motor**  
High-performance, high-efficiency small DC fan motor mounted



**DC Twin-Rotary Compressor**  
High-efficiency DC twin-rotary compressor



**DC Inverter**  
DC inverter provides smooth water temperature control.

**Hydraulic unit:**  
**WSYA050ML3 / WSYA080ML3 /**  
**WSYA100ML3**  
**Outdoor unit:**  
**WOYA060KLT / WOYA080KLT /**  
**WOYA100KLT**



### Specifications

Model Name	Hydraulic unit	WSYA050ML3	WSYA080ML3	WSYA080ML3	WSYA100ML3
Capacity Range	Outdoor unit	WOYA060KLT	WOYA060KLT	WOYA080KLT	WOYA100KLT
7°C/35°C floor heating *1	Heating capacity kW	4.50	5.50	7.50	9.50
	Input power kW	0.949	1.18	1.69	2.11
	COP	4.74	4.65	4.43	4.50
2°C/35°C floor heating *1	Heating capacity kW	4.50	5.30	6.30	9.30
	Input power kW	1.33	1.65	1.96	3.08
	COP	3.39	3.22	3.21	3.02
-7°C/35°C floor heating*1	Heating capacity kW	4.40	5.00	5.70	8.90
	Input power kW	1.59	1.90	2.13	3.36
	COP	2.76	2.63	2.68	2.65
-7°C/55°C Radiator*1	Heating capacity kW	3.90	4.25	5.30	8.00
	Input power kW	2.11	2.25	2.79	4.10
	COP	1.85	1.89	1.90	1.95

### Space heating characteristics\*2

Temperature application °C	55	35	55	35	55	35	55	35
Energy efficiency class	A++	A+++	A++	A+++	A++	A+++	A++	A+++
Rated heat output ( $P_{rated}$ ) kW	5	5	5	6	6	7	8	9
Seasonal space heating energy efficiency ( $\eta_s$ ) %	125	175	125	175	128	177	130	178
Annual energy consumption kWh	3,035	2,322	3,411	2,594	3,903	2,982	5,083	3,875
Sound power level*3 dB(A)	40	-	40	-	40	-	40	-
Hydraulic unit	57	-	57	-	60	-	62	-
Outdoor unit								

### Hydraulic unit specifications

Power source		Single phase, ~230 V, 50 Hz			
Dimensions H × W × D	mm	847 × 450 × 493	847 × 450 × 493	847 × 450 × 493	847 × 450 × 493
Weight (Net) kg	47	47	47	47	47
Water circulation Min./Max. L/min	7.6/22.0	8.5/22.0	10.0/22.0	13.2/30.0	
Buffer tank capacity L	16	16	16	16	
Expansion vessel capacity L	8	8	8	8	
Water flow temperature range °C	55	55	55	55	
Water pipe connection diameter Flow/Return mm	Ø25.4/Ø25.4	Ø25.4/Ø25.4	Ø25.4/Ø25.4	Ø25.4/Ø25.4	
Backup heater Capacity kW	3.0	3.0	3.0	3.0	

### Outdoor unit specifications

Power source		Single phase, ~230 V, 50 Hz			
Current Max. A	13.0	13.0	18.0	19.0	
Dimensions H × W × D mm	632 × 799 × 290	632 × 799 × 290	716 × 820 × 315	998 × 940 × 320	
Weight (Net) kg	39	39	42	62	
Refrigerant Type (Global Warming Potential)	R32 (675)	R32 (675)	R32 (675)	R32 (675)	
Charge kg	0.97	0.97	1.02	1.63	
Additional refrigerant charge g/m	25	25	25	20	
Connection pipe Diameter Liquid mm	6.35	6.35	6.35	9.52	
Length Gas mm	12.70	12.70	12.70	15.88	
Length (Pre-charge) m	3/30	3/30	3/30	3/30	
Height difference Max. m	15	15	15	20	
Operating range Heating °C	-20 to 35	-20 to 35	-20 to 35	-20 to 35	

\*1: Heating capacity, input power, and COP are measured using the EN14511 standard. Actual usage environments, such as the operating modes of the heating equipment, room temperature, and controller settings, may cause differences in values between those listed in the catalog and the actual performance characteristics.


\*2: Information about ErP can be downloaded from our website at [www.fujitsu-general.com/global/support/downloads/search/](http://www.fujitsu-general.com/global/support/downloads/search/)

\*3: The sound power level values are based on EN12102 standard measurements under EN14825 standard conditions.


### Dimensions

(Unit: mm)


#### Outdoor unit: WOYA060KLT




#### WOYA080KLT



#### WOYA100KLT



#### Hydraulic unit: WSYA050ML3/WSYA080ML3/WSYA100ML3



## Split Type


Super High Power Series



### High water flow temperature

The temperature of water flow can be maintained at 60°C without using a backup heater, even when the outdoor temperature drops to -20°C. The system can supply 55°C water without a backup heater at an outdoor temperature of -22°C.

\* If you want to raise the temperature of the water supply to above the maximum temperature, use a backup heater to supplement the primary heater.




### High COP

Heat pumps of ATW Systems work more efficiently and consume less energy than conventional heating systems.

Energy efficiency class

**A<sup>++</sup>**



### Operating range extended to -25°C

Operating range improved down to -25°C outdoor temperature



**Hydraulic unit:**  
WSYG160DJ6 / [3-phase] WSYK170DJ9  
**Outdoor unit:**  
WOYG160LJL  
[3-phase] WOYK150LJL / WOYK170LJL



Hydraulic unit  
Single phase/  
3-phase



Outdoor unit  
Single phase 16 kW  
3-phase 15/17 kW

### Specifications

Model Name	Hydraulic unit	WSYG160DJ6	WSYK170DJ9	WSYK170DJ9
Capacity range	Outdoor unit	WOYG160LJL	WOYK150LJL	WOYK170LJL
7°C/35°C floor heating * <sup>1</sup>	Heating capacity kW	16.00	15.00	17.00
	Input power kW	3.86	3.46	4.10
	COP	4.15	4.33	4.15
2°C/35°C floor heating * <sup>1</sup>	Heating capacity kW	13.30	13.20	13.50
	Input power kW	4.25	4.06	4.27
	COP	3.13	3.25	3.16
-7°C/35°C floor heating* <sup>1</sup>	Heating capacity kW	14.50	13.20	15.00
	Input power kW	5.27	4.55	5.32
	COP	2.75	2.90	2.82
-7°C/55°C Radiator* <sup>1</sup>	Heating capacity kW	10.90	13.20	14.20
	Input power kW	5.89	6.77	7.40
	COP	1.85	1.95	1.92
<b>Space heating characteristics*<sup>2</sup></b>				
Temperature application °C	55	35	55	35
Energy efficiency class	A++	A++	A++	A++
Rated heat output ( $P_{rated}$ ) kW	14	16	17	17
Seasonal space heating energy efficiency ( $\eta_s$ ) %	125	163	130	164
Annual energy consumption kWh	8,757	8,014	9,915	8,606
Sound power level dB(A)	45	45	45	45
Hydraulic unit specifications				
Power source		Single phase, ~230 V, 50 Hz		3-phase, ~400 V, 50 Hz
Dimensions H × W × D mm	805 × 450 × 471			805 × 450 × 471
Weight (Net) kg	52.5			52.5
Water circulation Min./Max. L/min	26.4/57.8		24.0/54.2	27.3/61.4
Buffer tank capacity L	22			22
Expansion vessel capacity L	10			10
Water flow temperature range °C	60		60	60
Water pipe connection diameter Flow/Return mm	Ø25.4/Ø25.4			Ø25.4/Ø25.4
Backup heater Capacity kW	6.0 (3.0 kW × 2 pcs.)			9.0 (3.0 kW × 3 pcs.)
<b>Outdoor unit specifications</b>				
Power source		Single phase, ~230 V, 50 Hz		3-phase, ~400 V, 50 Hz
Current Max. A	28.0		14.0	14.0
Dimensions H × W × D mm	1,428 × 1,080 × 480		1,428 × 1,080 × 480	1,428 × 1,080 × 480
Weight (Net) kg	137		138	138
Refrigerant Type (Global Warming Potential)		R410A (2,088)		
Charge kg	3.80		3.80	3.80
Additional refrigerant charge g/m	50		50	50
Connection pipe Diameter Liquid mm	Ø9.52		Ø9.52	Ø9.52
	Gas mm	Ø15.88	Ø15.88	Ø15.88
Length Min./Max. m	5/30		5/30	5/30
Length (Pre-charge) m	15		15	15
Height difference Max. m		25/15 (Outdoor unit: Upper/Lower)		
Operating range Heating °C	-25 to 35		-25 to 35	-25 to 35

\*1: Heating capacity, input power, and COP are measured using the EN14511 standard. Actual usage environments, such as the operating modes of the heating equipment, room temperature, and controller settings, may cause differences in values between those listed in the catalog and the actual performance characteristics.


\*2: Information about ErP can be downloaded from our website at [www.fujitsu-general.com/global/support/downloads/search/](http://www.fujitsu-general.com/global/support/downloads/search/)

### Dimensions


(Unit: mm)

#### Outdoor unit:

Single phase: WOYG160LJL  
3-phase: WOYK150LJL / WOYK170LJL



**Hydraulic unit:**  
Single phase: WSYG160DJ6  
3-phase: WSYK170DJ9



## Split Type High Power Series



### High water flow temperature

The temperature of water flow can be maintained at 60°C without using a backup heater, even when the outdoor temperature drops to -20°C.

\* If you want to raise the temperature of the water supply to above the maximum temperature, use a backup heater to supplement the primary heater.




### High COP

Heat pumps of ATW Systems work more efficiently and consume less energy than conventional heating systems.

Energy efficiency class



\*Temperature application: Heating temp. 35°C



**Hydraulic unit:**  
**WSYG140DG6 / [3-phase] WSYK160DG9**  
**Outdoor unit:**  
**WOYG112LHT / WOYG140LCTA**  
**[3-phase] WOYK112LCTA / WOYK140LCTA /**  
**WOYK160LCTA**



### Specifications

Model Name	Hydraulic unit	WSYG140DG6	WSYG140DG6	WSYK160DG9	WSYK160DG9	WSYK160DG9	
Capacity range	Outdoor unit	WOYG112LHT	WOYG140LCTA	WOYK112LCTA	WOYK140LCTA	WOYK160LCTA	
7°C/35°C floor heating *1	Heating capacity kW	10.80	13.50	10.80	13.50	15.17	
	Input power kW	2.54	3.23	2.51	3.20	3.70	
	COP	4.25	4.18	4.30	4.22	4.10	
2°C/35°C floor heating *1	Heating capacity kW	10.77	12.00	10.77	13.00	13.50	
	Input power kW	3.44	3.87	3.40	4.15	4.34	
	COP	3.13	3.10	3.17	3.13	3.11	
-7°C/35°C floor heating*1	Heating capacity kW	10.38	11.54	10.38	12.20	13.50	
	Input power kW	2.40	2.27	2.43	2.38	2.50	
	COP	4.32	5.08	4.28	5.13	5.40	
-7°C/55°C Radiator*1	Heating capacity kW	7.57	9.20	9.27	10.10	11.00	
	Input power kW	4.57	5.08	5.09	5.65	6.29	
	COP	1.66	1.81	1.82	1.79	1.75	
<b>Space heating characteristics*2</b>							
Temperature application °C	55	35	55	35	55	35	
Energy efficiency class	A+	A++	A+	A+	A++	A+	
Rated heat output ( $P_{rated}$ ) kW	9	11	11	13	9	11	
Seasonal space heating energy efficiency ( $\eta_s$ ) %	112	151	113	148	112	154	
Annual energy consumption kWh	6,704	6,062	8,041	6,824	6,669	5,930	
Sound power level dB(A)	46	46	46	46	46	46	
Hydraulic unit specifications							
Power source	Single phase, ~230 V, 50 Hz						
Dimensions H x W x D mm	800 x 450 x 457						
Weight (Net) kg	42						
Water circulation Min./Max. L/min	19.5/39.0	24.4/48.7	19.5/39.0	24.4/48.7	27.4/54.8		
Buffer tank capacity L	16						
Expansion vessel capacity L	8						
Water flow temperature range °C	60						
Water pipe connection diameter Flow/Return mm	Ø25.4/Ø25.4						
Backup heater Capacity kW	6.0 (3.0 kW x 2 pcs.)						
Outdoor unit specifications							
Power source	Single phase, ~230 V, 50 Hz						
Current Max. A	22.0	25.0	9.0	9.5	10.5		
Dimensions H x W x D mm	1,290 x 900 x 330						
Weight (Net) kg	92						
Refrigerant Type (Global Warming Potential)	R410A (2,088)						
Additional refrigerant charge Charge kg	2.50						
Connection pipe Diameter Liquid mm	Ø9.52						
	Gas	Ø15.88					
Length Min./Max. m	5/20						
Length (Pre-charge) m	15						
Height difference Max. m	15						
Operating range Heating °C	-25 to 35						

\*1: Heating capacity, input power, and COP are measured using the EN14511 standard. Actual usage environments, such as the operating modes of the heating equipment, room temperature, and controller settings, may cause differences in values between those listed in the catalog and the actual performance characteristics.


\*2: Information about ErP can be downloaded from our website at [www.fujitsu-general.com/global/support/downloads/search/](http://www.fujitsu-general.com/global/support/downloads/search/)

### Dimensions

(Unit: mm)

**Outdoor unit:**  
Single phase: WOYG112LHT/WOYG140LCTA

3-phase: WOYK112LCTA/WOYK140LCTA/WOYK160LCTA



**Hydraulic unit:**  
Single phase: WSYG140DG6  
3-phase: WSYK160DG9

# Split DHW Integrated Type

Comfort Series



## High water flow temperature

The temperature of water flow is up to 55°C without a backup heater. Hot water supply temperature can be maintained even at -10°C outdoor temperature.

\* If you want to raise the temperature of the water supply to above the maximum temperature, use a backup heater to supplement the primary heater.




## High COP

Heat pumps of ATW Systems work more efficiently and consume less energy than conventional heating systems.



\*Temperature application: Heating temp. 35°C



## Outdoor unit technology



- DC Fan Motor**  
High-performance, high-efficiency small DC fan motor mounted
- DC Twin-Rotary Compressor**  
High-efficiency DC twin-rotary compressor
- DC Inverter**  
DC inverter provides smooth water temperature control.

**Hydraulic unit:**  
**WGYA050ML3 / WGYA080ML3 /**  
**WGYA100ML3**  
**Outdoor unit:**  
**WOYA060KLT / WOYA080KLT /**  
**WOYA100KLT**



## Specifications

Model Name	Hydraulic unit Outdoor unit	WGYA050ML3 WOYA060KLT	WGYA080ML3 WOYA060KLT	WGYA080ML3 WOYA080KLT	WGYA100ML3 WOYA100KLT
<b>Capacity range</b>		5	6	8	10
7°C/35°C floor heating * <sup>1</sup>	Heating capacity Input power COP	kW 0.949 4.74	kW 4.50 4.65 4.43	kW 5.50 1.18 2.11	kW 7.50 1.69 4.50
2°C/35°C floor heating * <sup>1</sup>	Heating capacity Input power COP	kW 1.33 3.39	kW 4.50 5.30 6.30	kW 1.65 3.22 9.30	kW 1.96 3.08 3.08
-7°C/35°C floor heating * <sup>1</sup>	Heating capacity Input power COP	kW 1.59 2.76	kW 4.40 5.00 5.70	kW 1.90 2.63 8.90	kW 2.13 2.68 3.36
-7°C/55°C Radiator * <sup>1</sup>	Heating capacity Input power COP	kW 2.11 1.85	kW 3.90 4.25 5.30	kW 2.25 2.79 8.00	kW 1.89 1.90 4.10
<b>Space heating characteristics *<sup>2</sup></b>					
Temperature application	°C	55 35	55 35	55 35	55 35
Energy efficiency class		A++ A+++	A++ A+++	A++ A+++	A++ A+++
Rated heat output ( $P_{rated}$ )	kW	5 5	5 6	6 7	7 8
Seasonal space heating energy efficiency ( $\eta_s$ )	%	125 175	125 175	128 177	130 178
Annual energy consumption	kWh	3,035 2,322	3,411 2,594	3,903 2,982	5,083 3,875
Sound power level * <sup>3</sup>	Hydraulic unit Outdoor unit	dB(A) 57	dB(A) 40	dB(A) 60	dB(A) 62
<b>Domestic hot water characteristics *<sup>2</sup></b>					
Load profile		L	L	L	L
Energy efficiency class		A+	A+	A+	A+
Energy efficiency (qwh)	%	130	130	130	130
Annual electricity consumption	kWh	793	793	793	793
<b>Hydraulic unit specifications</b>					
Power source					Single phase, ~230 V, 50 Hz
Dimensions H × W × D	mm	1,863 × 648 × 700	1,863 × 648 × 700	1,863 × 648 × 700	1,863 × 648 × 700
Weight (Net)	kg	145	145	145	145
Water circulation	Min./Max. L/min.	7.6/22.0	8.5/22.0	10.0/22.0	13.2/30.0
DHW capacity	L	190	190	190	190
Electrical heater capacity	Heating kW	3.0	3.0	3.0	3.0
Buffer tank capacity	L	16	16	16	16
Expansion vessel capacity	L	8	8	8	8
Water flow temperature range	Max. °C	55	55	55	55
Water pipe connection diameter	Flow/Return mm	Ø25.4/Ø25.4	Ø25.4/Ø25.4	Ø25.4/Ø25.4	Ø25.4/Ø25.4
Hot water pipe connection diameter	mm	Ø19.05	Ø19.05	Ø19.05	Ø19.05
<b>Outdoor unit specifications</b>					
Power source					Single phase, ~230 V, 50 Hz
Current	Max. A	13.0	13.0	18.0	19.0
Dimensions H × W × D	mm	632 × 799 × 290	632 × 799 × 290	716 × 820 × 315	998 × 940 × 320
Weight (Net)	kg	39	39	42	62
Refrigerant	Type (Global Warming Potential) R32 (675)	R32 (675)	R32 (675)	R32 (675)	R32 (675)
Additional refrigerant charge	Charge kg	0.97	0.97	1.02	1.63
Connection pipe	Liquid Diameter mm	6.35	6.35	6.35	9.52
	Gas Length m	12.70	12.70	12.70	15.88
	Min./Max. m	3/30	3/30	3/30	3/30
	Length (Pre-charge) m	15	15	15	20
	Height difference m	20	20	20	20
Operating range	Heating °C	-20 to 35	-20 to 35	-20 to 35	-20 to 35

\*1: Heating capacity, input power, and COP are measured using the EN14511 standard. Actual usage environments, such as the operating modes of the heating equipment, room temperature, and controller settings, may cause differences in values between those listed in the catalog and the actual performance characteristics.


\*2: Information about ErP can be downloaded from our website at [www.fujitsu-general.com/global/support/downloads/search/](http://www.fujitsu-general.com/global/support/downloads/search/)

\*3: The sound power level values are based on EN12102 standard measurements under EN14825 standard conditions.

## Dimensions

(Unit: mm)

**Outdoor unit:**  
WOYA060KLT



**Hydraulic unit:**  
WGYA050ML3/WGYA080ML3/WGYA100ML3



## Split DHW Integrated Type


Super High Power Series



### High water flow temperature

The temperature of water flow can be maintained at 60°C without using a backup heater, even when the outdoor temperature drops to -20°C. The system can supply 55°C water without a backup heater at an outdoor temperature of -22°C.

\* If you want to raise the temperature of the water supply to above the maximum temperature, use a backup heater to supplement the primary heater.




Super High Power Series

### High COP

Heat pumps of ATW Systems work more efficiently and consume less energy than conventional heating systems.

Energy efficiency class

A<sup>++</sup>



### Operating range extended to -25°C

Operating range improved down to -25°C outdoor temperature



**Hydraulic unit:**  
WGYG160DJ6 / [3-phase] WGYK170DJ9  
**Outdoor unit:**  
WOYG160LJL  
[3-phase] WOYK150LJL / WOYK170LJL



### Specifications

Model Name	Hydraulic unit	WGYG160DJ6	WGYK170DJ9	WGYK170DJ9
Capacity range	Outdoor unit	WOYG160LJL	WOYK150LJL	WOYK170LJL
7°C/35°C floor heating *1	Heating capacity kW	16.00	15.00	17.00
	Input power kW	3.86	3.46	4.10
	COP	4.15	4.33	4.15
2°C/35°C floor heating *1	Heating capacity kW	13.30	13.20	13.50
	Input power kW	4.25	4.06	4.27
	COP	3.13	3.25	3.16
-7°C/35°C floor heating*1	Heating capacity kW	14.50	13.20	15.00
	Input power kW	5.27	4.55	5.32
	COP	2.75	2.90	2.82
-7°C/55°C Radiator*1	Heating capacity kW	10.90	13.20	14.20
	Input power kW	5.89	6.77	7.40
	COP	1.85	1.95	1.92

### Space heating characteristics\*2

Temperature application	°C	55	35	55	35	55	35
Energy efficiency class		A <sup>++</sup>					
Rated heat output ( $P_{rated}$ )	kW	14	16	16	17	17	18
Seasonal space heating energy efficiency ( $\eta_s$ )	%	125	163	130	164	130	161
Annual energy consumption	kWh	8,757	8,014	9,915	8,606	10,232	9,059
Sound power level	Hydraulic unit	45	45	45	45	45	45
	Outdoor unit	67	66	67	66	67	68

### Domestic hot water characteristics\*2

Load profile	L
Energy efficiency class	A
Energy efficiency (ηwh)	109
Annual electricity consumption	kWh

### Hydraulic unit specifications

Power source	Single phase, ~230 V, 50 Hz	3-phase, ~400 V, 50 Hz
Dimensions H × W × D	mm	1,841 × 648 × 698
Weight (Net)	kg	166
Water circulation	Min./Max. L/min	26.4/57.8
DHW capacity	L	190
Electrical heater capacity	Heating kW	6.0 (3.0 kW × 2 pcs.)
Buffer tank capacity	L	22
Expansion vessel capacity	L	12
Water flow temperature range	Max. °C	60
Water pipe connection diameter	Flow/Return mm	Ø25.4/Ø25.4
Hot water pipe connection diameter	mm	Ø19.05

### Outdoor unit specifications

Power source	Single phase, ~230 V, 50 Hz	3-phase, ~400 V, 50 Hz
Current	Max. A	28.0
Dimensions H × W × D	mm	1,428 × 1,080 × 480
Weight (Net)	kg	137
Refrigerant	Type (Global Warming Potential)	R410A (2,088)
	Charge kg	3.80
Additional refrigerant charge	g/m	50
Connection pipe	Liquid mm	Ø9.52
	Gas Ø15.88	Ø9.52
	Length Min./Max. m	5/30
	Length (Pre-charge) m	15
Operating range	Max. °C	25/15 (Outdoor unit: Upper/Lower)
	Heating -25 to 35	25/15 (Outdoor unit: Upper/Lower)

\*1: Heating capacity, input power, and COP are measured using the EN14511 standard. Actual usage environments, such as the operating modes of the heating equipment, room temperature, and controller settings, may cause differences in values between those listed in the catalog and the actual performance characteristics.


\*2: Information about ErP can be downloaded from our website at [www.fujitsu-general.com/global/support/downloads/search/](http://www.fujitsu-general.com/global/support/downloads/search/)

### Dimensions


(Unit: mm)

#### Outdoor unit:

Single phase: WOYG160LJL  
3-phase: WOYK150LJL/WOYK170LJL



**Hydraulic unit:**  
Single phase: WGYG160DJ6  
3-phase: WGYK170DJ9



## Split DHW Integrated Type

High Power Series



### High water flow temperature

The temperature of water flow can be maintained at 60°C without using a backup heater, even when the outdoor temperature drops to -20°C.

\* If you want to raise the temperature of the water supply to above the maximum temperature, use a backup heater to supplement the primary heater.




### High COP

Heat pumps of ATW Systems work more efficiently and consume less energy than conventional heating systems.

Energy efficiency class




\*Temperature application: Heating temp. 35°C



### Optimized refrigerant cycle operation

The High Power Series deliver high performance and efficiency with twin sensors and hot water heating technology.



**Hydraulic unit:**  
**WGYG140DG6 / [3-phase] WGYK160DG9**  
**Outdoor unit:**  
**WOYG112LHT / WOYG140LCTA**  
**[3-phase] WOYK112LCTA / WOYK140LCTA /**  
**WOYK160LCTA**



### Specifications

Model Name	Hydraulic unit Outdoor unit	WGYG140DG6 WOYG112LHT	WGYG140DG6 WOYG140LCTA	WGYK160DG9 WOYK112LCTA	WGYK160DG9 WOYK140LCTA	WGYK160DG9 WOYK160LCTA
<b>Capacity range</b>		11	14	11	14	16
7°C/35°C floor heating * <sup>1</sup>	Heating capacity kW	10.80	13.50	10.80	13.50	15.17
	Input power kW	2.54	3.23	2.51	3.20	3.70
	COP	4.25	4.18	4.30	4.22	4.10
2°C/35°C floor heating * <sup>1</sup>	Heating capacity kW	10.77	12.00	10.77	13.00	13.50
	Input power kW	3.44	3.87	3.40	4.15	4.34
	COP	3.13	3.10	3.17	3.13	3.11
-7°C/35°C floor heating * <sup>1</sup>	Heating capacity kW	10.38	11.54	10.38	12.20	13.50
	Input power kW	4.32	5.08	4.28	5.13	5.40
	COP	2.40	2.27	2.43	2.38	2.50
-7°C/55°C Radiator* <sup>1</sup>	Heating capacity kW	7.57	9.20	9.27	10.10	11.00
	Input power kW	4.57	5.08	5.09	5.65	6.29
	COP	1.66	1.81	1.82	1.79	1.75

### Space heating characteristics\*<sup>2</sup>

Temperature application	°C	55	35	55	35	55	35	55	35	55	35
Energy efficiency class		A+	A++	A+	A+	A+	A++	A+	A++	A+	A+
Rated heat output ( $P_{rated}$ )	kW	9	11	11	13	9	11	11	13	13	14
Seasonal space heating energy efficiency ( $\eta_s$ )	%	112	151	113	148	112	154	117	150	117	149
Annual energy consumption	kWh	6,704	6,062	8,041	6,824	6,669	5,930	7,803	6,738	9,062	7,408

Sound power level	Hydraulic unit	46	46	46	46	46	46	46	46	46	46
	Outdoor unit	68	69	69	68	70	68	71			

### Domestic hot water characteristics\*<sup>2</sup>

Load profile	L
Energy efficiency class	A
Energy efficiency( $n_{ab}$ )	%
Annual electricity consumption	kWh

Hydraulic unit specifications	
Power source	Single phase, ~230 V, 50 Hz
Dimensions H × W × D	1,840 × 648 × 698
Weight (Net)	kg
	152
Water circulation	Min./Max. L/min
	19.5/39.0 24.4/28.7
DHW capacity	L
	190
Electrical heater capacity	Heating kW
	6.0 (3.0 kW × 2 pcs.)
Buffer tank capacity	L
	16
Expansion vessel capacity	L
	12
Water flow temperature range	Max. °C
	60
Water pipe connection diameter	Flow/Return mm
	Ø25.4/Ø25.4
Hot water pipe connection diameter	mm
	Ø19.05

### Outdoor unit specifications

Power source	Single phase, ~230 V, 50 Hz	3-phase, ~400 V, 50 Hz
Current	Max. A	22.0 25.0
Dimensions H × W × D	mm	1,290 × 900 × 330

Weight (Net)	kg	92	99
Refrigerant	Type (Global Warming Potential)	R410A (2,088)	
	Charge kg	2.50	
Additional refrigerant charge	g/m	50	
Connection pipe	Diameter Liquid mm	Ø9.52	
	Gas mm	Ø15.88	
	Length Min./Max. m	5/20	
	Length (Pre-charge) m	15	
Operating range	Height difference Max. m	15	
	Heating °C	-25 to 35	

\*1: Heating capacity, input power, and COP are measured using the EN14511 standard. Actual usage environments, such as the operating modes of the heating equipment, room temperature, and controller settings, may cause differences in values between those listed in the catalog and the actual performance characteristics.


\*2: Information about ErP can be downloaded from our website at [www.fujitsu-general.com/global/support/downloads/search/](http://www.fujitsu-general.com/global/support/downloads/search/)

### Dimensions

(Unit: mm)

**Outdoor unit:**  
Single phase: WOYG112LHT/WOYG140LCTA

3-phase: WOYK112LCTA/WOYK140LCTA/WOYK160LCTA



# Comfort Control

The high-grade heating controller automatically adjusts the flow temperature according to the climate conditions to maintain the room and domestic hot water temperatures at the desired levels.

## Hydraulic unit Controller

### 4 Heating modes

#### 1. Automatic mode

Enables automatic switching between Comfort mode and Reduce mode according to time program

#### 2. Reduce mode

Maintains water temperature at a lower level

#### 3. Comfort mode

Maintains water temperature at a comfortable level

#### 4. Protection mode


Activates frost protection in standby operation



## Useful Features


### Automatic heating curve control

Automatic temperature regulation according to heating curve (depending on heating terminal and outdoor temperature)



The heating curve will shift to adjust the room temperature setting.

Can be fine-adjusted when it is too warm or too cold.



### Quick recovery from defrosting

Maintains room temperature by boost start operation during defrosting.


### Auto changeover

When cooling mode is selected, the system automatically switches between cooling and heating modes depending on the outdoor temperature to serve as an all-season air conditioner.

### 2-zone independent control

2-zone independent control (For example, the individual control of 2 underfloor heating zones or the combination of 1 underfloor heating zone and 1 radiator zone)\*1


\*1: Optional parts required



### 2-stage low-noise mode

The outdoor unit can be switched to quiet mode, depending on the installation environment.

\*Effective only for High Power Series



### Backup heater operation

Backup heater maintains a comfortable room temperature even when the outside temperature is low. The backup heater is intelligently controlled as a safety backup for very cold days and nights, and only operates when really needed.

## Energy Saving

### Time program

- The timer is easy to set.
- You can select the heating mode in conjunction with various times of the day.

### Day-weekly timer

- Allows up to 3 settings per day.
- Allows individual settings for each day of the week.

### Holiday timer

- Allows up to 8 settings.
- While you are away from home for an extended period during winter, the system prevents your room or house from freezing.

### Peak cut Function<sup>\*2</sup>

Sets the peak current value to reduce power consumption.

Mode	Ratio to reduce power consumption
1	100%
2	75%
3	50%
4	Almost 0%

\* Please refer to page W-038 and W-039 for optional parts information.



## Safety Features


### Anti-Legionella function

Prevents the growth of Legionella bacteria in the DHW tank to supply safe and clean hot water at all times.




### Anti-freeze function

When the outside temperature drops below a specified level, the compressor will self-activate and water will also be automatically circulated to prevent freezing.




### Emergency operation

If an outdoor unit fails to operate, a built-in backup heater or an external boiler is activated to supply an uninterrupted supply of hot water to the house.



### Error and Maintenance Alarm


Enables quick error-handling services and maintenance



# Simple installation

## Presetting configurations

A controller installed makes it easy to configure the system without having to set each component or unit individually.





8 simple patterns for system presetting  
(Pair of heating: 12 patterns)

Configuration (Parameter 5700)	Installation type
Presetting 1	1 heating circuit
Presetting 2	2 heating circuits
Presetting 3	1 heating circuit with boiler backup
Presetting 4	2 heating circuits with boiler backup
Presetting 5	1/2 heating circuit with buffer control
Presetting 6	1/2 heating circuit with buffer control and boiler backup
Presetting 7	Cascade connection Primary
Presetting 8	Cascade connection A
Presetting 9	Cascade connection B/C


- DHW & solar control auto detection
- Cascade connection only available in High Power models.

## Controller with a large liquid crystal display and buttons for easy function setting



# Easy Installation & Maintenance


- All hydraulic safety and control components are built in with no additional selection required.
- Lifting bars for installation free of difficulty or risk
- Easy access for maintenance
- Refrigerant pump down operation



The outdoor temperatures can be simulated in the range of -50°C to +50°C.



## Concrete floor drying

Allows the concrete surrounding the hot-water pipes to dry more quickly, shortening the construction period for underfloor heating installations.



## Maintenance Support

### Diagnostics functions for troubleshooting





# Installation requirements

## Installation of equipment & electrical wiring



### Split type Hydraulic unit

- The Hydraulic unit is hung on the wall.
- Weight  $\leq 88$  kg (including water)
- Space for maintenance needs to be taken into consideration.




### Split DHW Integrated Type Hydraulic Unit

- Floor standing
- Weight  $\leq 393$  kg (including water)
- Space for maintenance needs to be taken into consideration.




## Piping and Wiring Split type

Series	Capacity range (kW)	Pipe diameter (Liquid/Gas) (mm)	H1 (m)	H2 (m)	L (m)		
R32 Comfort	5	6.35/12.70	+20	-20	3-30		
	6						
	8						
	10	9.52/15.88					
High Power	11	9.52/15.88			5-20		
	14						
	16						
Super High Power	15	9.52/15.88	+15	-25	5-30		
	16						
	17						




# System Configuration

## Split Type




## Split DHW Integrated Type




# Case Studies

## Split Type



**2-emitter simultaneous heating  
(Individual control)**  
Underfloor heating + Radiator



**Boiler connected to heating  
(Boiler + Heating)**




**2-emitter simultaneous heating &  
domestic hot water supply (Cascade)**




\*The hydraulic layouts shown are mainly representation. Please check with local dealer for actual hydraulic connections.

## Split DHW Integrated Type


**Single heating & domestic hot water supply**  
Radiator + domestic hot water supply



**2-emitter simultaneous heating  
(Individual control) & domestic hot water supply**  
Radiator + domestic hot water supply



**Boiler connected to heating (Boiler + Heating)  
and domestic hot water supply**



\*The hydraulic layouts shown are mainly representation. Please check with local dealer for actual hydraulic connections.

# Control Overview

To meet the diverse needs of customers, we offer a variety of control options, such as individual control and remote control options.



## Individual Control

- Wireless room thermostat (option)  
UTW-C58XA
- Wired room thermostat (option)  
UTW-C55XA
- Wired remote controller (option)  
UTW-C74TXF<sup>\*1</sup>  
UTW-C74HXF<sup>\*1</sup>



## Service & Maintenance Tool

- Service tool (option)
- Web server (option)  
UTW-KW1XD  
UTW-KW4XD
- OR
- LPB clip (option)  
UTW-KL1XD

<sup>\*3</sup>: UTW-KW1XD or UTW-KW4XD is required for the connection.  
<sup>\*4</sup>: UTW-KL1XD is required for the connection.



## Adapters for external devices

- Web server (option)  
UTW-KW1XD  
UTW-KW4XD
  - MODBUS® clip (option)  
UTW-KMBX<sup>\*2</sup>
- \* Please refer to page W-038 and W-039 for system compatibility information.



Super High Power Series  
Hydraulic unit

## Hydraulic unit Controller

- Easy-to-set operation modes**
  - Selecting the heating mode and domestic hot water (DHW) operation
- Large liquid crystal display**
  - Shows operation status
  - Shows error messages
  - Messages in plain text
- Navigation and setting**
  - Select from heating menu
  - Setting Time program



HMI kit (option)  
UTW-KHMXE  
Supports multiple languages

# Optional Parts Overview

Various optional parts are available to use ATW according to needs and environments.

## for Locally units



### Second circuit Kit

It can supply hot water at different temperatures to each two types of heating equipment, such as radiators and underfloor heating.



UTW-KZDXE<sup>\*1</sup>



UTW-KZDXE<sup>\*1</sup>



UTW-KZSXJ



UTW-KZDXJ

### Boiler connection kit

It can build hybrid systems using both boilers and heat pumps. Boiler and heat pumps are switched according to outside air temperature.



UTW-KBSXD



UTW-KBDXD



UTW-KBSXJ

<sup>\*1</sup>The UTW-KREXD (Regulation extension kit) is not included but is required for connection.



## for DHW



### DHW kit

UTW-KDWXD (External)

Required to connect locally purchased DHW tanks to air to water.



### DHW tank

200 Liters: UTW-T20AXH / UTW-T20BXH

300 Liters: UTW-T30AXH / UTW-T30BXH

The BXH series is a more efficient tank than the AXH series.



### DHW expansion kit

The expansion vessel(18L) for connection to DHW water piping.

UTW-KDEXE

UTW-KDEXL

## for Outdoor unit



### Drain pan

UTW-KDPXB

It is used to collect and drain condensation water generated by outdoor units.



### External connect kit

UTY-XWZXZ2 / UTY-XWZXZ3

The signal input (low noise mode, peak cut) and signal output (compressor operation, base pan heater control) for outdoor units are possible externally.

## for Hydraulic unit



### Circulating pump

UTW-PHFXG

The high-output pump for replacement of the standard pump in the hydraulic unit. It can be used in properties with longer and more complex water piping.

### Cascade master/slave kit

Up to 3 hydraulic units can be connected for large-capacity use. It is need to install a primary kit in one unit and a secondary kit in one or two other units.



Cascade master kit  
(incl. LPB clip)



Cascade slave kit  
(incl. LPB clip)

### Cooling kit

Required when using ATW also for cooling operation. It is used to prevent condensation occurring in the indoor unit.



UTW-KCLXD




UTW-KCLXL



### Electrical backup heater relay

UTW-KBHXL

It allows the backup heater for heating at 3 kW as standard can be used at 6 kW.



## Optional Parts List

Product Name	Model Name	Split Type												Split DHW Integrated Type												
		Super High Power			High Power				R32 Comfort					Super High Power			High Power				R32 Comfort					
		10	30	10	11	14	11	14	16	5	6	8	10	10	30	16	15	17	11	14	11	14	16	5	6	8
HMI kit		UTW-KHMXE	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3
Remote controller		UTW-C74TXF	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3
		UTW-C74HXF	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3	●*3
Room thermostat		UTW-C55XA	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
		UTW-C58XA	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4
Outdoor sensor transmitter		UTW-MOSXD	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4	●*4
RF modules for BSB-Port		UTW-MRCXD	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Web server		UTW-KW1XD	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5
		UTW-KW4XD	—	—	—	●*5	●*5	●*5	●*5	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
LPB clip		UTW-KL1XD	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
MODBUS® clip		UTW-KMBXJ	—	—	—	●*6	●*6	●*6	●*6	●*6	—	—	—	—	—	—	—	●*6	●*6	●*6	●*6	—	—	—	—	—
Service tool (incl. OCI700 Adapter)		UTW-KSTXD	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7	●*7
Service tool software		UTW-KPSXD	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8	●*8
External connect kit		UTY-XWZXZ2	—	—	—	●	●	●	●	●	—	—	—	—	—	—	—	●	●	●	●	●	—	—	—	—
		UTY-XWZXZ3	●	●	●	—	—	—	—	—	—	—	—	—	●	●	●	●	—	—	—	—	—	—	—	●
Electrical backup heater relay		UTW-KBHXL	—	—	—	—	—	—	—	—	●	●	●	●	●	—	—	—	—	—	—	—	●	●	●	

\*1: The UTW-KREXD (Regulation extension kit) is not included but is required for connection.

\*2: Split DHW integrated type supplies DHW without the DHW kit and DHW tank.

\*3: Includes 21 languages with no need to prepare an RC for Eastern Europe separately.  
EU/TYE has a built-in grammar checker.

C74TXF has a built-in room temperature sensor.

\*4: UUTW-MRCXD (RF modules) is required for the connection.

\*4: U1W-MRCXD (RF modules) is required for the connection.  
\*5: The connection of U1W-KW4XD for simultaneous control of multiple ATW units is only possible for cascade systems.

\*5: The connection of UTW-KW4XD for simultaneous control of multiple UTW units is only possible for cascade systems.

\*6: Additional Spare parts 9708302034 (Analogue interface PCB) and 109696 (connection wire) are required.


\*7: UTW-KL1XD (LPB clip) is required for the connection.

\*8: UTW-KW1XD or UTW-KW4XD (Web server) is required for the connection.

●: Available -: Not Available

# SUPPORT

- Sp-002 VRF Support
- Sp-004 HVAC system design Support Tool
- Sp-006 Air To Water Support Tool
- Sp-008 Quick Service & Maintenance
- Sp-010 Service monitoring tool
- Sp-012 Service Tool
- Sp-013 Web monitoring tool




Service & Support Website  
[www.fujitsu-general.com/global/support/](http://www.fujitsu-general.com/global/support/)

Our knowledgeable sales and service representatives assist you, from product selection to installation and maintenance.

Category	Information material	Tool
Product training	●	Mobile technician
Product information seeking	● ● ● ● ●	Service tool and Web monitoring tool
Technical information seeking	● ●	CFD simulation
Model selection	●	Air To Water proposer
Design	● ● ●	Design simulator (Room air conditioner, Packaged air conditioner, and VRF)
Verification		Air To Water Package label creator
Installation	●	Service manual
After-sales service		Installation manuals
		3D CAD (Revit) data
		2D CAD data
		Certification data
		Design & Technical manuals
		Operation manuals
		Promotional movies
		Brochures
		Product news
		Product technical training material
Product sales training material		Product training material

# VRF Support

Fujitsu General provides engineers and consultants with a wide range of product and technical information. In addition, we conduct research on new products and support design activities. We provide a wide range of support services from design to installation to maintain high quality.




## Technical information

We provide equipment selection software that facilitates the design of air conditioning systems by providing performance data for the units and estimation for model selection.

### Features

- Design & Technical manuals
- Model selection & estimation
- Certification data
- 2D/3D CAD data




2D/3D CAD data

## Technical support

Technical support is offered at every stage, from design through to installation, to assist in optimizing air conditioning solutions.

### Features

- CFD simulation
- Guidelines
- Commissioning support



CFD simulation

## Product information

Information on new models is provided in the form of documents and movies in a timely manner for release, readily downloadable from the private section of our website. Contact your Fujitsu General representative for access information.

### Features


- Product news
- Brochures & manuals
- Promotional movies

The screenshot shows the 'Downloads' section for 'AIRSTAGE™ Variable Refrigerant Flow (VRF) Systems'. It includes links for 'Product Catalogues' (AIRSTAGE VRF Catalogue 2023 [PDF, 39 MB] and Control System & Optional Units 2023 [PDF, 27 MB]), 'Document Download' (with a note to search downloadable documents), and 'Document Type' (Operation manual, Installation manual, etc.).

<https://www.fujitsu-general.com/eu/support/downloads/vrf/>



Commissioning support



Fujitsu General regularly provides professional product, technical and service training at its training facilities worldwide. These research facilities also support the development of human resources with advanced technical skills.

### Features

- Designing VRF systems
- On-site training for control systems


- 1 Head office training center in Japan
- 2 Training center in China
- 3 Asia training center in Singapore
- 4 Europe training center in the United Kingdom
- 5 Europe training center in Germany
- 6 America training center in the United States
- 7 Middle East training center in the UAE
- 8 Oceania training center in Australia

# HVAC system design Support tool

Put the charts and pens away and design your projects on a computer using the Design simulator. Everything from selecting indoor and outdoor units, allocating controls and optional parts through to designing the piping and wiring systems is made easier using the program's built-in features.

Once the project design is complete, the Export function makes it easy to generate material lists, product specifications, and refrigerant calculations, and more. You can also export in Word, Excel, and Acrobat formats, as well as group CAD data related to your project.

## Design simulator



### Automatically create model selection information

- The required performance, type, and temperature conditions for each indoor unit are entered and then dragged and dropped onto the outdoor unit to automatically set each unit.
- Creates piping and wiring diagrams automatically to facilitate branching, grouping, and option settings.
- The additional refrigerant charging is automatically calculated when the pipe length is entered.
- Easy configuration of remote controller groups, central controller, and converters.
- The equipment list including the equipment information is created automatically.



### Outputs in the format that matches the application

You can export your project information in a number of industry standard file formats.

- Word format (rtf) (doc)
- Excel format (csv)
- Acrobat format (pdf)
- 2D CAD data (DXF)



### Update your Design simulator

The database can be updated easily online with the AutoUpdate function using FTP.



## BIM

Building information modeling



### BIM files of Fujitsu General's products are available on BIMobject®

Fujitsu General is releasing BIM files of our products on the BIMobject® website [BIMobject.com](http://BIMobject.com).

#### Outline of BIMobject®

BIMobject® is a game changer for the construction industry, offering development, maintenance, and syndication of objects on the world's largest BIM platform.

**bimobject®**  
[www.bimobject.com/en](http://www.bimobject.com/en)



### About BIM files

- BIM files can be viewed in Autodesk Revit® 2018 version or later.
- In each BIM file, the location of the connectors for the refrigerant and drain pipe is different.
- Each BIM file includes several family types.
- A catalog and specification sheet is available in Revit file format for each product.

**R**  
RFA (Revit data)  
A data format available for BIM-designed projects

**Data content**

- Shape (Size)
- Drain direction
- Pipe direction
- Power supply location
- It contains information about the above specifications.



**A**  
DWG  
a standard data format used for Autodesk products



Intermediate data commonly available in CAD products





\*To learn more about how to use BIM files, refer to the instructional video on each product page. [youtu.be/wfL-hwFQ7dM](https://youtu.be/wfL-hwFQ7dM)


# Air To Water (ATW) Support tool

Fujitsu General's software for ATW automatically creates a combination of ATW equipment by simply providing a few parameters.

Supports multiple languages with an automatic update function.




## Air To Water proposer



### Selecting models with detailed technical information

- Simply enter the region where the equipment will be installed, the required heating capacity, the method of heating and other factors, and the software will select the appropriate equipment automatically.

\* From now on, the name will be changed to the new name above.  
The current name is WATERSTAGE Proposer.



The selected unit can be modified after reviewing the overall system configuration.  
The images and the list of devices are displayed at the same time, helping to avoid mistakes in device selection.


## Air To Water Package label creator

### Download Energy labels and Fiches from our website

ErP documents such as Energy labels, Product fiches, Package labels, Package lists, Information sheets, and EC Declarations can be searched for and downloaded from our website.

We will also provide an online service in the future so that installers can easily create various package labels and package fiches for different models.

\* From now on, the name will be changed to the new name above.  
The current name is WATERSTAGE Package label creator.



# Quick service & maintenance

In the unlikely event that a problem should occur with the unit or system, a wide variety of support tools are available to assist with prompt service and maintenance anytime, anywhere, including error code displays on the product, service tools to check the detailed status of the entire system, and remote monitoring tools using the internet.



## Easy maintenance & monitoring

### Designed for easy maintenance

The operating status of the air conditioner and detailed trouble conditions are displayed on the 7-segment indicator lamp on the outdoor unit printed circuit board (PCB) and on the screen of the remote controller. Check the status of the unit quickly for a prompt response.


- Display the operation mode at the time.
- Discharge temperature and pressure
- Compressor operation status
- "Address/Type/Number" of the outdoor unit
- Error code



### Error diagnosis by Service tool


Connect Service tool to check the status details of units, from single split to VRF, on a computer screen. Check the errors quickly for prompt countermeasures.

- Operating status/control
- Monitoring operating conditions
- Monitoring sensor data
- Indicating trend graphs
- Error history
- Indicating refrigerant circuit diagrams (for VRF)



### Remote monitoring

VRF system operating status and trouble status details can be monitored remotely at any time via the internet. Prompt coordination is available with service personnel.



## Mobile troubleshooting App for iOS and Android™ devices

We will release an App for troubleshooting tools for iPhone, iPod touch and other Apple devices, and Android products for Fujitsu General air conditioners (Room air conditioner/Packaged air conditioners VRF and ATW, "AIRSTAGE Mobile", and R32 calculation of allowable refrigerant capacity)

Use Error Code Check, Troubleshooting, and Sensor Check to understand the status of your air conditioner.

The mobile app interface includes sections for 'LED Flash Count', 'Indoor Unit LED' (showing a 6x6 grid of numbers 1-6), 'Thermistor Value Conversion' (for indoor and outdoor units), 'Indoor Unit HEX Temperature', 'Discharge Pressure', 'Resistor', 'Voltage', and a 'Clear' button. It also features QR codes for download from the App Store and Google Play.

## Service monitoring tool

for Single split, Multi-split & Air to water




- A quick overview of the temperature sensor readings and the electronic expansion valves (EEVs), fans, compressors and other control components
- It is not always easy to read the temperature sensor and know the status of the control components. So let the Service monitoring tool judge them.
- Visualizes protected operations
- Troubleshoots intermittent problems effectively
- Provides proof of normal operation to customers during periodical maintenance

The software interface includes tabs for 'Actual operating conditions', 'Graphs', and 'Operational histories'. The 'Actual operating conditions' tab shows a table of sensor values and a graph of temperature over time. The 'Graphs' tab shows multiple line graphs of various parameters. The 'Operational histories' tab shows a table of historical data.

	UTY-ASSX
Dimensions (H × W × D) (mm)	60 × 160 × 160
Weight (g)	500

# **AIRSTAGE Service Monitor Tool**




## Improved work efficiency

AIRSTAGE Service Monitor Tool can diagnose the cause of the error for a wide range of products. It makes maintenance or service support faster and can also reduce the number of visits and maintenance costs.

## Bluetooth communication

AIRSTAGE Service Monitor Tool can diagnose by the smart device\*1 and reduce the working time compared with diagnosis by PC.  
No need to connect a PC makes diagnosis easier even in narrow spaces.



\*1 Android only.  
You need to install the "AIRSTAGE Service Monitor Tool" app on your smart device.

**Compact and  
lightweight design**

New model is easy to carry by compact and lightweight design. The service personnel can visit the maintenance site with small luggage.



## New application with simple design

New application for smart devices has been released. The stylish design makes the application easy to use for everyone.



## Refrigerant cycle diagram display

The operating status can be displayed with a simple, clear diagram<sup>\*2</sup> on the smart device. It reduces the time for diagnosis and makes diagnosis easier. It can complement abundant experience and advanced knowledge of refrigerant cycle. This shortens the training time for service personnel.

\*2 list and graph displays are also available



\*The values in the pictures are examples.

## Specifications

UTY-ASSXZ1	
Dimensions (H x W x D) (mm)	20 x 35 x 60 (adapter)
Communication cable (cm)	60
Weight (g)	25 (adapter)
Communication method	Bluetooth 5.3
Max. communication distance (m)	10*3
Compatible device	Android8.0 or above

\*3 Depends on the environment

## Function List

		UTY-ASSXZ1	UTY-ASSX
Product specification	Installation		Outdoor unit PCB
	Communication	Bluetooth	Wired
Support product type	Split	●	●
	Multi-split	●	●
	ATW	●	●
	VRV	—	—
Function	Product distinction	●	●
	Signal-type distinction	●	●
	Operating status display	List	●
		Graph	●
		Refrigerant cycle diagram	—
	Adapter firmware update	●	—
	Adapter status monitoring	●	—
	Input and output of history data	●	●

# Service tool

UTY-ASGXZ1

## Extensive monitoring and analysis functions that make installation and maintenance easier


- The operation status of the system can be monitored and analyzed to detect any malfunctions.
- Data on the operation status of the system can be stored on a computer to allow for remote access.
- Up to 400 indoor units in a single VRF network system can be controlled and monitored for a large building or hotel.
- This software can be connected to any point of transmission line with a USB adapter (locally available).

\* Saved data can be displayed offline. Note that the data saved by the following software applications cannot be displayed.

- UTR-YSTB/UTR-YSTC (Service tool)
- UTR-YMSA (Web monitoring tool)

## Automatic operation check for refrigeration cycles

Once installed, the Service tool automatically checks for refrigeration cycles. The self-diagnosis function determines whether each sensor value is normal, which reduces the need for manual checks. The result of a diagnosis can be provided in a report.



## Remote technical support and maintenance

On-site check screen can be shared between on-site staff and a service technician in a remote location. When a service technician visits the site for troubleshooting, the system's operation status can be shared in real time with a remote service center for assistance. On-site staff can have an online chat with a remote service center to get further assistance.

## Trend charts

Previous-generation application could display only 3 sets of data from sensors. However, the current generation of the service tool displays multiple charts simultaneously so that refrigeration cycles can be monitored and checked in greater detail.

### Computer requirements

UTY-ASGXZ1	
Operating system	<ul style="list-style-type: none"> <li>Microsoft® Windows® 7 Professional (32-bit or 64-bit) SP1</li> <li>Microsoft® Windows® 8.1 Pro (32-bit or 64-bit)</li> <li>Microsoft® Windows® 10 Pro (32-bit or 64-bit)</li> </ul>
CPU	1 GHz or higher
Memory	<ul style="list-style-type: none"> <li>1 GB or more (for Windows® 7 [32-bit], Windows® 8.1 [32-bit], and Windows® 10 [32-bit])</li> <li>2 GB or more (for Windows® 7 [64-bit], Windows® 8.1 [64-bit], and Windows® 10 [64-bit])</li> </ul>
HDD	40 GB or more of free space
Screen resolution	1366 × 768 pixels or higher
Interface	<ul style="list-style-type: none"> <li>USB port for U10 USB Network interface and software protection key</li> </ul>
Software	Internet Explorer® 11 or Microsoft Edge

### Packing list

Name	Quantity	Application
White-USB-key (Software protection key)	1	Software protection key to be connected to a USB port on a Service tool-installed computer. This software runs only on a computer with WibuKey.

• Computer requirements

• Echelon® U10 USB Network Interface - TP/FT-10 Channel (Model name: 75010R) (Required for each VRF Network)

# Web monitoring tool


UTY-AMGXZ1

## Features

- Troubleshooting is performed by monitoring each air conditioning unit remotely during a periodical system check.
- An error notification is automatically transmitted to several locations via the internet\*1.
- Requires either a dedicated internet connection or landline to operate.
- The occurrence of an error can be confirmed through an error alert and equipment status information obtained from a remote location.
- Monitoring data can be downloaded in a remote location. These data can be accessed and displayed even when the service tool is in offline mode.
- Can be viewed on the monitoring computer's Web browser without installing any special software.

\*1: Internet e-mail access required.


## Web Monitoring System



## Supporting up to 4 VRF network systems

Up to 4 USB adapters can be connected to a computer, enabling the monitoring of up to 1,600 indoor units.

Suitable for use in a large building or hotel.



### Computer requirements

UTY-AMGXZ1	
Operating system	<ul style="list-style-type: none"> <li>Microsoft® Windows® 7 Professional (32-bit or 64-bit) SP1</li> <li>Microsoft® Windows® 8.1 Pro (32-bit or 64-bit)</li> <li>Microsoft® Windows® 10 Pro (32-bit or 64-bit)</li> </ul>
CPU	1 GHz or higher
Memory	<ul style="list-style-type: none"> <li>1 GB or more (for Windows® 7 [32-bit], Windows® 8.1 [32-bit], and Windows® 10 [32-bit])</li> <li>2 GB or more (for Windows® 7 [64-bit], Windows® 8.1 [64-bit], and Windows® 10 [64-bit])</li> </ul>
HDD	40 GB or more of free space
Screen resolution	1366 × 768 pixels or higher
Interface	<ul style="list-style-type: none"> <li>USB ports (one for U10 USB Network interface and up to 4 ports for software protection keys)</li> <li>Interface for remote connection: <ul style="list-style-type: none"> <li>- Landline: Modem is required.</li> <li>- Internet using LAN: Ethernet port is required.</li> </ul> </li> </ul>
Software	Internet Explorer® 11 or Microsoft Edge

### Packing list

Name	Quantity	Application
White-USB-key (Software protection key)	1	Software protection key to be connected to a USB port on a Service tool-installed computer. This software runs only on a computer with WibuKey.

• Computer requirements

• Echelon® U10 USB Network Interface - TP/FT-10 Channel (Model name: 75010R) (Required for each VRF Network)